

DTIC FILE COPY

2

AD-A187 665

# NAVAL POSTGRADUATE SCHOOL

## Monterey, California



DTIC  
ELECTE  
NOV 19 1987  
S D

# THESIS

SEARCH AND RESCUE AND ENFORCEMENT OF LAWS AND  
TREATIES INTELLIGENCE SYSTEM

by

Jon D. Allen  
and  
Heidi R. Lang

September 1987

Thesis Advisor:

Barry A. Frew

Approved for public release; distribution is unlimited

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

## REPORT DOCUMENTATION PAGE

1a REPORT SECURITY CLASSIFICATION Unclassified			1b RESTRICTIVE MARKINGS	
2a SECURITY CLASSIFICATION AUTHORITY			3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; Distribution is Unlimited	
2b DECLASSIFICATION/DOWNGRADING SCHEDULE				
4 PERFORMING ORGANIZATION REPORT NUMBER(S)			5 MONITORING ORGANIZATION REPORT NUMBER(S)	
6a NAME OF PERFORMING ORGANIZATION Naval Postgraduate School	6b OFFICE SYMBOL (if applicable) Code 54	7a NAME OF MONITORING ORGANIZATION Naval Postgraduate School		
6c ADDRESS (City, State, and ZIP Code) Monterey, California 93943-5000		7b ADDRESS (City, State, and ZIP Code) Monterey, California 93943-5000		
8a NAME OF FUNDING/SPONSORING ORGANIZATION	8b OFFICE SYMBOL (if applicable)	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c ADDRESS (City, State, and ZIP Code)		10 SOURCE OF FUNDING NUMBERS		
		PROGRAM ELEMENT NO	PROJECT NO	TASK NO
		WORK UNIT ACCESSION NO		
11 TITLE (Include Security Classification) SEARCH AND RESCUE AND ENFORCEMENT OF LAWS AND TREATIES INTELLIGENCE SYSTEM (u)				
12 PERSONAL AUTHOR(S) Allen, Jon D. and Lang, Heidi R.				
13a TYPE OF REPORT Master's Thesis	13b TIME COVERED FROM _____ TO _____	14 DATE OF REPORT (Year, Month, Day) 1987 September	15 PAGE COUNT 430	
16 SUPPLEMENTARY NOTATION				
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	Database, Coast Guard, Law Enforcement & Search Rescue, SAR, Intelligence	
19 ABSTRACT (Continue on reverse if necessary and identify by block number) In recent years, the political climate surrounding drug interdiction has brought the focus of Coast Guard missions into emphasizing the prosecution of law enforcement cases. Many law enforcement cases are pursuant to a specific search and rescue case and traditionally, the Coast Guard has segregated its information regarding vessels into separate systems for each of these areas. The existence of separate repositories for vessel data has resulted in duplication of information, lack of consistency, and the inability to integrate information between systems. The purpose of this thesis is to propose, design, impliment a prototype law enforcement/search and rescue database system to provide a single repository for law enforcement and search and rescue vessel data. The prototype will be developed at Coast Guard Group Monterey.				
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> OTIC USERS			21 ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a NAME OF RESPONSIBLE INDIVIDUAL Prof. Barry A. Frew			22b TELEPHONE (Include Area Code) (408) 646-2924	22c OFFICE SYMBOL Code 54Fw

DD FORM 1473, 84 MAR

83 APR edition may be used until exhausted  
All other editions are obsoleteSECURITY CLASSIFICATION OF THIS PAGE  
UNCLASSIFIED

Approved for public release; distribution is unlimited.

Search and Rescue and Enforcement of Laws and Treaties  
Intelligence System

by

Jon D. Allen  
Lieutenant, United States Coast Guard  
B.S., United States Coast Guard Academy, 1979

and

Heidi R. Lang  
Lieutenant, United States Navy  
B.S., State University of New York at Buffalo, 1979

Submitted in partial fulfillment of the  
requirements for the degree of

MASTER OF SCIENCE IN INFORMATION SYSTEMS

from the

NAVAL POSTGRADUATE SCHOOL  
September 1987


Authors:


  
Jon D. Allen


  
Heidi R. Lang

Approved by:

  
Barry A. Frew, Thesis Advisor

  
Vincent Y. Lum, Second Reader

  
Willis R. Greer, Chairman,  
Department of Administrative Science

  
James M. Fremgen,  
Acting Dean of Information and Policy Sciences

## ABSTRACT

In recent years, the political climate surrounding drug interdiction has brought the focus of Coast Guard missions into emphasizing the prosecution of law enforcement cases. Many law enforcement cases are pursuant to a specific search and rescue case and traditionally, the Coast Guard has segregated its information regarding vessels into separate systems for each of these areas. The existence of separate repositories for vessel data has resulted in duplication of information, lack of consistency, and the inability to integrate information between systems. The purpose of this thesis is to propose, design, and implement a prototype law enforcement/search and rescue database system to provide a single repository for law enforcement and search and rescue vessel data. The prototype will be developed at Coast Guard Group Monterey.



A-1



## TABLE OF CONTENTS

I.	INTRODUCTION .....	11
A.	COAST GUARD GROUP MONTEREY .....	11
	1. Overview .....	11
	2. Search and Rescue (SAR) .....	11
	3. Law Enforcement .....	13
B.	STATUTORY AUTHORITY .....	14
C.	THESIS BACKGROUND .....	15
D.	GOALS AND OBJECTIVES .....	16
E.	METHODOLOGY .....	17
F.	SYSTEM REQUIREMENTS .....	18
G.	SYSTEM OVERVIEW .....	18
II.	SARELTIS FEASIBILITY .....	20
A.	POLITICAL FEASIBILITY .....	20
B.	ECONOMIC FEASIBILITY .....	21
	1. Existing Method .....	22
	2. Proposed System .....	22
	3. Existing Method Analysis .....	23
	4. Proposed Method Analysis: .....	25
	5. Proposed versus Existing Method Cost Comparisons: .....	29
III.	TECHNICAL FEASIBILITY .....	30
A.	LAW ENFORCEMENT INFORMATION SYSTEM .....	30
B.	SEARCH AND RESCUE INTELLIGENCE INFORMATION SYSTEM .....	31
C.	INADEQUACIES OF REQUEST FOR THE SARELTIS PROTOTYPE .....	31
D.	PROPOSED LANGUAGE ENVIRONMENT .....	32

IV.	USERS GUIDE .....	33
A.	INTRODUCTION .....	33
B.	SYSTEM STARTUP PROCEDURES .....	34
1.	Machine Configuration Requirements .....	34
2.	Initial Program Loading .....	34
C.	SARELTIS SECURITY .....	36
D.	SARELTIS OPERATIONS .....	37
1.	Menu System Overview .....	37
2.	Starting SARELTIS .....	37
3.	SARELTIS Menu Options .....	37
E.	EXITING SARELTIS .....	46
F.	SARELTIS MAINTENANCE .....	46
V.	CONCLUSIONS AND RECOMMENDATIONS .....	48
A.	SARELTIS RESULTS .....	48
B.	CONCLUSIONS .....	48
C.	SUGGESTIONS FOR FURTHER RESEARCH .....	49
APPENDIX A:	LOGICAL MODELS .....	50
APPENDIX B:	SYSTEM REPORTS .....	62
APPENDIX C:	SARELTIS PHYSICAL STRUCTURE .....	109
APPENDIX D:	MODULE FUNCTIONAL DESCRIPTIONS .....	228
APPENDIX E:	SOURCE CODE FOR ANCILLARY PROGRAM MODULES .....	244
APPENDIX F:	SARSYS SOURCE CODE .....	251
APPENDIX G:	SENTRY SOURCE CODE .....	255
APPENDIX H:	MODIFY SOURCE CODE .....	302
APPENDIX I:	SREPORTS SOURCE CODE .....	329
APPENDIX J:	INTRPTS SOURCE CODE .....	332

APPENDIX K: BRDRPTS SOURCE CODE .....	346
APPENDIX L: SARRPTS SOURCE CODE .....	361
APPENDIX M: VSLRPTS SOURCE CODE .....	383
APPENDIX N: PRSRPTS SOURCE CODE .....	390
APPENDIX O: SQUERY SOURCE CODE .....	397
APPENDIX P: SUTILITY SOURCE CODE .....	420
LIST OF REFERENCES .....	425
BIBLIOGRAPHY .....	426
INITIAL DISTRIBUTION LIST .....	428

## LIST OF TABLES

1. GROUP MONTEREY SAR STATISTICS .....	13
2. GROUP MONTEREY BOARDING STATISTICS .....	14
3. FIGURE - PROGRAM CORRESPONDENCE .....	108

## LIST OF FIGURES

1.1	Group Monterey Organization .....	12
4.1	SARELTIS Master Menu .....	38
4.2	SARELTIS Input Menu .....	39
4.3	SARELTIS Modify Menu .....	39
4.4	SARELTIS Query Menu .....	40
4.5	Vessel Query Search Chain .....	41
4.6	Personnel Query Search Chain .....	42
4.7	SARELTIS Reports Main Menu .....	43
4.8	SARELTIS Intelligence Reports Menu .....	43
4.9	SARELTIS Boarding Reports Menu .....	44
4.10	SARELTIS SAR Reports Menu .....	44
4.11	SARELTIS Vessel Reports Menu .....	45
4.12	SARELTIS Personnel Reports Menu .....	45
4.13	SARELTIS Utilities Menu .....	46
A.1	Existing SAR System - Level 0 .....	51
A.2	Existing SAR System - Level 1 .....	52
A.3	Existing ELT System - Level 0 .....	53
A.4	Existing ELT System - Level 1 .....	54
A.5	Proposed SAR System - Level 0 .....	55
A.6	Proposed SAR System - Level 1 .....	56
A.7	SAR System SARELTIS Automation Boundary .....	57
A.8	Proposed ELT System - Level 0 .....	58
A.9	Proposed ELT System - Level 1 .....	59
A.10	ELT System SARELTIS Automation Boundary .....	60
A.11	Bachman Diagram of Proposed System .....	61
B.1	Boarding Listing .....	63
B.2	Major Grid Area Boarding Frequency .....	64
B.3	Minor Grid Area Boarding Frequency .....	66

B.4	Vessel Boarding History .....	68
B.5	Courtesy Motorboat Examination Summary .....	69
B.6	SAR and Boarding Day/Night Summary .....	70
B.7	EPIC Code Statistical Analysis .....	71
B.8	Summary of EPIC Codes Assigned .....	72
B.9	Immediate Distress Statistics .....	73
B.10	Vessel Intelligence Remarks Summary .....	74
B.11	Operator Listing .....	75
B.12	Operators of Vessels Summary .....	76
B.13	Operator Query Report .....	77
B.14	Owners Listing .....	77
B.15	Owners of Vessels Summary .....	78
B.16	Owner Query Report .....	79
B.17	Personnel Intelligence Listing .....	80
B.18	Personnel Query Report .....	81
B.19	Personnel Intelligence Report .....	81
B.20	SAR Listing .....	82
B.21	SAR Months and Years Frequency Statistics .....	83
B.22	SAR Day of Week Frequency Statistics .....	84
B.23	Major Grid Area SAR Frequency .....	85
B.24	Minor Grid Area SAR Frequency .....	87
B.46	Vessel Query SAR History .....	89
B.26	Small Boat Operations Area SAR Frequency .....	90
B.27	SAR Unit Time Summary .....	91
B.47	Small Boat Operations Area Boarding Frequency .....	92
B.29	Stolen Vessel Listing .....	93
B.30	Boarding Unsafe Condition Summary .....	94
B.31	Violation Summary by Vessel Construction Type .....	95
B.32	Violation Summary by Engine Compartment Type .....	95
B.33	Vessel Listing .....	96
B.34	Violation Summary by Fuel Compartment Type .....	97
B.35	Violation Summary by Hull Material Type .....	98
B.36	Query Vessel Intelligence History .....	98

B.37	Boarding Violation Summary .....	99
B.38	Violation Summary by Vessel Length .....	100
B.39	Violation Summary by Vessel Propulsion Type .....	101
B.40	Vessel Operators Summary Listing .....	102
B.41	Vessel Owners Summary Listing .....	103
B.42	Query Vessel Information Listing .....	104
B.43	Violation Summary by Vessel Type .....	105
B.44	Violation Summary by Vessel Use .....	106
B.45	Violation Summary by Vessel Year .....	107
C.1	SARELTIS Menu Hierarchy Chart .....	110
C.2	Input Menu Hierarchy Chart .....	111
C.3	Modify Menu Hierarchy Chart .....	112
C.4	Query Menu Hierarchy Chart .....	113
C.5	Reports Master Menu Hierarchy Chart .....	114
C.6	Intelligence Reports Menu Hierarchy Chart .....	115
C.7	Boarding Reports Menu Hierarchy Chart .....	116
C.8	SAR Reports Menu Hierarchy Chart .....	117
C.9	Vessel Reports Menu Hierarchy Chart .....	118
C.10	Personnel Reports Menu Hierarchy Chart .....	119
C.11	Utilities Menu Hierarchy Chart .....	120

## **I. INTRODUCTION**

### **A. COAST GUARD GROUP MONTEREY**

#### **1. Overview**

Coast Guard Group Monterey is the southernmost of three Groups in the Twelfth Coast Guard District. The Group is the primary Coast Guard interface with other federal, state, and local agencies and the general public in its area of responsibility. Group Monterey serves 175 miles of California coastline out to 60 nautical miles from Point Ano Nuevo (north of Santa Cruz) south to Point Sal (north of Santa Maria). Within this geographic area, the Group is tasked as the Search and Rescue Mission Coordinator.

The primary missions of Group Monterey include law enforcement, search and rescue, marine environmental protection, and boating safety. To fulfill these missions, the Group is staffed with over 100 men and women who operate and maintain a variety of law enforcement and rescue resources. The specific organizational structure and manning is outlined in Figure 1.1.

#### **2. Search and Rescue (SAR)**

Coast Guard Group Monterey has been an active SAR Mission Coordinator during the past eight years. From 1979 to 1983, there were over 1641 SAR cases. More detailed SAR statistics have been maintained since 1984 and are summarized for the period October 1, 1983 - April 1, 1987 in Table 1.1.

Group Monterey has the following Coast Guard units available for SAR response:

- CG-41367 (41 foot utility boat)
- CG-41369 (41 foot utility boat)
- CG-44346 (44 foot motor lifeboat)
- CG-195003 (19 foot utility boat)
- Point Barrow (82 foot patrol boat)
- Point Heyer (82 foot patrol boat)
- Cape Wash (95 foot patrol boat)

Coast Guard and military aviation organizations and units supporting Group Monterey's SAR mission include:

- Coast Guard Air Station Sacramento






Figure 1.1 Group Monterey Organization.

- Coast Guard Air Station San Francisco
- Fort Ord MAST Helicopters
- Fort Hunter Liggett MAST Helicopters

Group Monterey, in addition to its Coast Guard and military SAR resources, has received SAR assistance from the following:

- Coast Guard Auxiliary vessels and aircraft
- Santa Cruz Harbor Master
- Moss Landing Boat Works
- California Fish and Game
- San Luis Obispo Harbor Master
- Morro Bay Harbor Master
- California Highway Patrol
- Various county sheriff departments
- Pacific Grove Marine Rescue
- Numerous local police units

**TABLE 1**  
**GROUP MONTEREY SAR STATISTICS**

FY	Cases	Lives Lost	Lives Saved	Persons Assisted	Value of Property Lost	Value of Property Assisted
84	378	21	62	731	\$ 2,033K	\$ 111,473K
85	324	19	48	604	\$ 1,403K	\$ 7,492K
86	471	20	82	852	\$ 616K	\$ 10,217K
87	217	17	33	372	\$ 122K	\$ 5,276K

### **3. Law Enforcement**

Group Monterey is mandated by law to conduct boardings of recreational, commercial, and passenger vessels to ensure compliance with applicable federal laws, regulations, and standards. The FY86 boarding statistics for Group Monterey are summarized in Table 2.

Agencies that assist or work in cooperation with Coast Guard Group Monterey include:

- Monterey County Sheriff's Department

- Monterey Police Department
- Monterey County District Attorney
- California Highway Patrol
- United States Customs Service (USCS)
- Bureau of Alcohol, Tobacco, and Firearms (ATF)
- Drug Enforcement Administration (DEA)
- California Department of Motor Vehicles
- Santa Cruz County Narcotics Enforcement Team
- United States Border Patrol
- Narcotic Detection Dogs (DELTA IX)
- Fort Ord Federal Police
- Santa Cruz Harbor Master
- Pacific Grove Police Department
- Morro Bay Police Department

**TABLE 2**  
**GROUP MONTEREY BOARDING STATISTICS**

Total Boardings.....	444
Written Notices Issued. ....	181
Written Warnings Issued.....	105
Safety Boardings Conducted. ....	158

## **B. STATUTORY AUTHORITY**

The statutory authority that governs the operations of Coast Guard Group Monterey can be divided into two separate classifications. One area of responsibility and authority involves laws relating to navigation and merchant shipping. Laws that relate to customs and revenue, immigration, quarantine, protection of fish and game that fall within the jurisdiction of other federal agencies, but which require the unique authority and marine facilities of the Coast Guard for effective enforcement comprise the second legal category. Specific statutory authority which delineates and amplifies Coast Guard responsibilities and jurisdiction include the following:

1. 14 USC 2. This statute outlines the specific duties and responsibilities of the Coast Guard and gives the Coast Guard authority to enforce or assist in the enforcement of all applicable federal laws.
2. 14 USC 89. This statute grants specific law enforcement authority to the Coast Guard. It gives the Coast Guard the authority to make "inquiries, examinations, inspections, searches, seizures, and arrests on the high seas and waters over which the United States has jurisdiction for prevention, detection, and suppression of violations of laws of the United States".
3. 14 USC 141. This statute gives the Coast Guard the authority to assist or be assisted by any federal agency, state, territory, or possession of the United States in the enforcement of applicable laws.
4. 14 USC 143 / 19 USC 1401(i). These statutes grant customs law enforcement authority to the Coast Guard.
5. 19 USC 1581. This statute grants authority to the Coast Guard, when enforcing customs laws, to seize any vessel, merchandise, or arrest any person in violation of these laws.
6. Port and Waterways Safety Act of 1970 (33 USC 1221). This act increases the supervision of vessel and port operations and mandates that all vessels operating in navigable waters of the United States comply with all applicable standards and requirements for vessel construction, equipment, manning, operational procedures, and safe handling of hazardous cargos.
7. Federal Boat Safety Act of 1971 (46 USC 1451). This act improves recreational safe boating and facilities by prescribing specific requirements and standards for boats and equipment.
8. Executive Order 11735 on Oil Pollution (August 3, 1973). This order directs the Coast Guard to receive notice of discharges of oil or hazardous substances, to establish procedures to prevent and contain discharges, to inspect vessels containing oil and hazardous substances and to board and arrest persons in violation of applicable laws.
9. Executive Order 11727 on Drug Enforcement (July 6, 1973). This order establishes a Drug Enforcement Administration within the Department of Justice and directs that each federal department and agency shall assist in the enforcement of laws involving narcotics and dangerous drugs.

### **C. THESIS BACKGROUND**

As demonstrated throughout Coast Guard history and mandated by statute, the Coast Guard must be able to rapidly respond to any Search & Rescue crisis or Law Enforcement scenario. Additional and timely information in these crises and scenarios can make the difference between lives-saved and lives-lost, or violators apprehended and violators that escape prosecution. All too often, this information is maintained in filing cabinets --- virtually inaccessible when decisions must be made within minutes.

Coast Guard units, such as Group Monterey, must respond to situations where they have little or no information. To find out that a certain vessel owner/operator has a history of violations or is considered armed and dangerous can assist Coast Guard boarding officers in better preparing for what could be a life-threatening situation. Additionally, during SAR cases, it can be critical to know a vessel's description to facilitate its identification by land-based units, air resources, or Coast Guard vessels dispatched to search for the vessel in distress.

In order to respond to the need for automated information support, the Search and Rescue and Enforcement of Laws and Treaties Intelligence System (SARELTIS) was designed and implemented. Coast Guard Group Monterey served as the test bed for determining information needs and systems analysis. The system is able to not only respond to real-time SAR and Law Enforcement cases, but is also robust enough to allow users to analyze the data collected to form their own local intelligence information base. The system's standard reports can provide limited decision-making support for Coast Guard resource allocation and scheduling.

#### **D. GOALS AND OBJECTIVES**

The goals and objectives of SARELTIS are twofold: first, to provide a real-time query capability and second, to provide historical management reports that can aid in resource allocation, scheduling, and distribution. The following functions/products will be performed/ prepared by SARELTIS:

- a. Interactive Query
  - \* Vessel Searches
  - \* Personnel Searches
- b. Intelligence Reporting
  - \* El Paso Intelligence Center (EPIC) Intelligence Summary
  - \* Vessel Profiles for Violation Analysis
  - \* Personnel Intelligence Summary
- c. Boarding Historical Reports
  - \* Violation/Unsafe Condition Analysis
  - \* Courtesy Motorboat Examination (CME) Analysis
  - \* Geographic Area Analysis
- d. SAR Historical Reports
  - \* Immediate SAR Case Analysis
  - \* Geographic Area Analysis

- \* SAR Unit Operational Time Utilization Summary
- \* Days/Months/Years SAR Case Analysis
- e. Vessel Historical Reports
  - \* Vessel Summary
- f. Personnel Historical Reports
  - \* Vessel Owners Summary
  - \* Vessel Operators Summary

## E. METHODOLOGY

Two prototypes were developed as a precursor to SARELTIS. Functionally, the first prototype concentrated on the Law Enforcement information requirements on a limited scale while the second prototype concentrated on SAR. After proving the technical feasibility of the SARELTIS concept, a feasibility study was prepared and is included as Chapter II. The two prototypes will be discussed in Chapter III.

The logical design structure necessary to fulfill the information requirements to fully implement SARELTIS is presented in the data flow diagrams of Appendix A. These dataflow diagrams depict the complete analysis of the SAR and Law Enforcement functions and processes of Coast Guard Group Monterey, and were developed through extensive interviews with Group personnel. Additionally, these diagrams show the automation boundary of SARELTIS, which is a graphic representation of precisely where SARELTIS will fit into these mission areas. Once this automation boundary was identified, the logical entities and their relationships within this boundary were determined and represented by the Bachman diagram found in Appendix A.

The physical design process for the SARELTIS prototype involved the conversion of the logical model into a language-specific database structure and an identification of the modules required to implement the required functions of the application. To perform this conversion, all of the currently used source documents were identified. A survey was prepared containing all of the data elements present on these forms and was distributed to representative groups of users at Group Monterey. These users identified the degree to which the data elements were necessary for the performance of their duties. From the results of this survey, the data elements required within the SARELTIS database were identified. These data elements were then grouped within the previously defined entities of the Bachman diagram and became the basis for the SARELTIS physical database structure.

At the completion of physical database structure implementation, the specific functions that were required to operate upon this structure were identified, including the generation of all required and anticipated user and management reports. These functions were then divided into implementable modules, coded, and tested. Upon completion of testing, modules with related functionality were combined and the sub-menu code required to invoke each application was developed. Finally, the main menu, security, and utility modules were constructed and the entire system was integrated. The module functional descriptions are provided in Appendix D and the menu hierarchy charts are included in Appendix C.

The User's Guide, located in Chapter IV, provides the user with a step-by-step guide to the SARELTIS menu-based system. The various reports generated by SARELTIS are displayed in Appendix B.

## **F. SYSTEM REQUIREMENTS**

To operate SARELTIS, the following hardware is required:

- \* IBM® PC-XT, PC-AT, or compatible microcomputer
- \* DOS®, Version 2.0 or higher
- \* A hard disk and one double-sided, double-density 5.25 floppy disk drive
- \* 384K of main memory (system processing is greatly enhanced if 640K or 1M of main memory is available)
- \* Color or monochrome monitor
- \* Printer, with normal or large carriage

SARELTIS was developed utilizing the R:base 5000® Database Management System, written by MicroRim, Inc., of Bellevue, Washington.

## **G. SYSTEM OVERVIEW**

SARELTIS is an interactive, user-friendly, menu-driven system. A series of screens displaying various menus provide the user with a functional man-machine interface.

The overall system design is based upon one relational database accessed by eleven functionally separate application modules. Application modules are comprised of functionally distinct programs. These program functions are listed in Chapter IV, the User's Guide, with each module's function explained in detail in Appendix D.

All system reports are designed to be printed on a normal (small) width carriage printer. The forty five reports prepared by the system were designed to assist the

Commanding Officer or Operations Officer to make better resource and planning decisions.

The R:base 5000 language is easily accessible for the advanced user and can be used to build other applications, reports, forms, searches, and displays of SARELTIS information not covered in the original implementation.



## **II. SARELTIS FEASIBILITY**

A feasibility study is a compressed, capsule version of the entire systems analysis and design process. As part of the feasibility process, the existing system is examined, a high level model of the proposed system is developed, and the overall feasibility of the project is evaluated. This chapter will examine the economic and the political feasibilities of SARELTIS. The technical feasibility will be addressed in Chapter III (discussion of the prototypes).

### **A. POLITICAL FEASIBILITY**

Due to recent Congressional pressures and unfavorable publicity concerning the Coast Guard's zealous boarding practices in unwarranted situations, attention has been focused on the lack of available information provided to boarding officers prior to the boarding of a vessel. Boarding officers must comply with the provisions of Title 14 of the U.S. Code, Section 89, concerning their use of force necessary to compel public and commercial boaters to comply with U.S. laws and boarding directions. However, without adequate information or intelligence prior to boarding, the degree of initial force necessary to ensure this compliance is difficult if not impossible to predetermine. Therefore, any means of providing this intelligence information would be strongly welcomed at all levels of the Coast Guard.

Coast Guard Group Monterey was contacted in early June 1986 to determine their willingness to serve as a test site for the implementation of a prototype intelligence system. Their response was overwhelming and highly supportive. Following the initial positive reaction of Group Monterey, both the Twelfth Coast Guard District and Coast Guard Pacific Area intelligence offices were approached in December 1986 concerning the proposal and the results of the first prototype. They also displayed a high degree of enthusiasm for the effort. In April 1987, RADM W. Merlin, the Coast Guard's senior management responsible for all computer applications, expressed an interest in the project and promised additional hardware support.

It is obvious from the above that the concept of providing automated intelligence and information is supported at all levels of the Coast Guard --- from local operational personnel to top management of the entire organization. This kind of multi-level organizational support has shown that the SARELTIS project is politically feasible.

## B. ECONOMIC FEASIBILITY

Economic feasibility is demonstrated if it can be shown that the benefits of a system outweigh its costs. Before making any cost/benefit study, it is important to list the assumptions that were used so that the reader may see what constraints were imposed on the analysis and where the costs and benefits were derived from. The following is a list of assumptions used in formulating the cost/benefit analysis:

- a. Management information research on Search and Rescue (SAR) cases provided monthly.
- b. Management information research on Enforcement of Laws and Treaties (ELT) cases provided weekly.
- c. SAR management information research performed by Group Monterey's Officer-of-the-Day (paygrade E-6).
- d. L/E management information research performed by Group Monterey's ELT Specialist (paygrade E-5).
- e. Specific ELT case research performed by Group Monterey's Officer-of-the-Day (OOD).
- f. Specific SAR case research performed by Group Monterey's Officer-of-the-Day (OOD).
- g. Assume 2,000 man-hours per year.
- h. Development of SARELTIS performed by two lieutenants (paygrade O-3).
- i. All costs and benefits were evaluated based on the Coast Guard's Annual Standard Personnel Costs [Ref. 1]. The pertinent costing data is as follows:
  - 1) paygrade E-5 --- \$18,500 (\$9.25 / hour)
  - 2) paygrade E-6 --- \$22,300 (\$11.15 / hour)
  - 3) paygrade O-3 --- \$33,900 (\$16.95 / hour)
- j. The annual SAR case load is 386 (Table 1).
- k. The annual ELT case load is 444 (Table 2).
- l. The annual SAR and ELT case loads will remain relatively constant over the expected life of the project.
- m. SARELTIS has an expected 5 year project life.
- n. Approximately three years of historical SAR and ELT case data will be entered upon system implementation.

In order to better understand how the actual computations contained in this section were derived, a synopsis of both the existing and proposed systems will be discussed below.

## **1. Existing Method**

ELT and SAR case load research is currently not conducted due to the amount of time necessary to perform the research and the inaccessibility of the information. It has been estimated by Coast Guard Group Monterey OOD's that such research would take a minimum of 1.5 to 2.0 hours to search through their existing records to locate any available pertinent information if the information could be found at all.

Management information research on ELT cases is performed by the Group's ELT Specialist (paygrade E-5) who must manually compile statistics on a weekly basis. He estimates that it takes a minimum of 1 man-day to perform the required research and the preparation of subsequent required reports.

Management information research on SAR cases is performed by the Group's OOD (paygrade E-6) who must manually compile statistics on a monthly basis. It is estimated that this research takes a minimum of 3 man-days to perform the research and to prepare the required reports.

## **2. Proposed System**

ELT and SAR specific case research will be handled through customized database query program modules. It is estimated each query would take an average of 3 minutes to enter the search criteria and perform the actual search.

Management information research on ELT cases would be done through the use of customized reports where users can define specific timeframes, vessels, violations, or personnel to analyze or search. It is estimated that it would take approximately 30 minutes to perform a series of reports relating to ELT information.

Management information research on SAR cases would be done through the use of customized reports where users can define specific timeframes, vessels, or personnel to analyze or search. It is estimated that it would take approximately 30 minutes to perform a series of reports relating to SAR information.

### 3. Existing Method Analysis

#### Recurring Costs:

##### SAR Case Load Research:

Filling out required SAR case documentation:

2 hours x \$11.15 (paygrade E-6) \$22.30

Annual SAR case load 386

---

\$8,607.80

Retrieving specific SAR case data:

1.5 hours x \$11.15 (paygrade E-6) \$16.73

Annual SAR case load 386

---

\$6,457.78

---

Total SAR Case Load Research:

---

\$15,065.58

##### ELT Case Load Research:

Filling out required ELT case documentation:

1 hour x \$11.15 (paygrade E-6) \$11.15

Annual ELT case load 444

---

\$4,950.60

Retrieving specific ELT case data:

1.5 hours x \$11.15 (paygrade E-6) \$16.73

Annual ELT case load 444

---

\$7,428.12

---

Total ELT Case Load Research:

---

\$12,378.72

SAR Management Information Research:

Researching SAR documentation:

4 man-days x \$11.15/hour x 8 hours \$356.80

(paygrade E-6)

Monthly Research 12

---

Total SAR Management Information Research \$4,281.60

ELT Managment Information Research:

Researching ELT documentation:

1 man-day x \$9.25 x 8 hours \$74.00

(paygrade E-5)

Weekly Research 52

---

Total ELT Management Information Research \$3,848.00

Total Existing Method Costs (Recurring):

Total SAR Case Load Research: \$15,065.58

Total ELT Case Load Research: \$12,378.72

Total SAR Management Information Research \$4,281.60

Total ELT Management Information Research \$3,848.00

---

---

Total Recurring Costs: \$35,573.90

#### 4. Proposed Method Analysis:

##### Non-Recurring Costs:

First Prototype Development (using R:base 4000):	
250 man-hours x \$16.95 (paygrade O-3)	\$4,237.50
Second Prototype Development (using ReQuest):	
200 man-hours x \$16.95 (paygrade O-3)	\$3,390.00
SARELTIS Development (using R:base 5000):	
2000 man-hours x \$16.95 (paygrade O-3)	\$33,900.00
SARELTIS Initial Historical SAR Data Loading:	
.25 hours x \$11.15 (paygrade E-6)	\$2.79
386 cases x 3 years	1,158
	<hr/>
	\$3,230.82
SARELTIS Initial Historical ELT Data Loading:	
.25 hours x \$11.15 (paygrade E-6)	\$2.79
444 cases x 3 years	1332
	<hr/>
	\$3,716.28
Hardware / Software Costs:	
IBM PC-XT compatible computer and printer	\$2,000.00
R:base 5000 software	\$400.00
	<hr/>
	\$2,400.00
	<hr/>
Total Non-Recurring Costs:	\$50,874.60

Recurring Costs:

SAR Case Load Research:

Filling out required SAR case documentation:

2 hours x \$11.15 (paygrade E-6) \$22.30

Annual SAR case load 386

---

\$8,607.80

Loading SARELTIS with SAR case data:

.25 hours x \$11.15 (paygrade E-6) \$2.79

Annual SAR case load 386

---

\$1,076.94

Retrieving specific SAR case data:

.05 hours x \$11.15 (paygrade E-6) \$0.56

Annual SAR case load 386

---

\$216.16

Total SAR Case Load Research:

---

\$9,900.90

ELT Case Load Research:

Filling out required ELT case documentation:

1 hour x \$11.15 (paygrade E-6)	\$11.15
Annual ELT case load	444
	<hr/>
	\$4,950.60

Loading SARELTIS with ELT case data:

.25 hours x \$11.15 (paygrade E-6)	\$2.79
Annual ELT case load	444
	<hr/>
	\$1,238.76

Retrieving specific ELT case data:

.05 hours x \$11.15 (paygrade E-6)	\$0.56
Annual ELT case load	444
	<hr/>
	\$248.64

Total ELT Case Load Research:

	<hr/>
	<hr/>
	\$6,438.00



**SAR Management Information Research:**

**Researching SAR documentation:**

.5 hours x \$11.15 (paygrade E-6) \$5.58

Weekly Research 12

---

**Total SAR Management Information Research \$66.96**

**ELT Managment Information Research:**

**Researching ELT documentation:**

.5 hours x \$11.15 (paygrade E-6) \$5.58

Weekly Research 12

---

**Total ELT Management Information Research \$66.96**

**System Manager Data Validation:**

100 hours x \$11.15 (paygrade E-6) \$1,115.00

**Hardware Corrective Maintenance: \$500.00**

**Software Corrective Maintenance: \$500.00**

**Total Recurring Costs: \$18,587.82**

### 5. Proposed versus Existing Method Cost Comparisons:

Total Existing Non-Recurring Costs	\$0.00
Total Proposed Non-Recurring Costs	\$50,874.60
	<hr/>
Additional Non-Recurring Costs	\$50,874.60
Total Existing Recurring Costs	\$35,573.90
Total Proposed Recurring Costs	\$18,587.82
	<hr/>
Total Recurring Savings	\$16,986.08
Payback Period [Ref. 2: p. 319]:	
First Year Costs	\$50,874.60
First Year Benefits	\$16,986.08
Payback Period	= Costs / Benefits
	= \$50,874.60 / \$16,986.08
	= 2.99 years
Internal Rate of Return (IRR):	
Estimated First Year Costs	\$50,874.60
Estimated First Year Benefits	\$16,986.08
Estimated Second Year Benefits	\$16,986.08
Estimated Third Year Benefits	\$16,986.08
Estimated Fourth Year Benefits	\$16,986.08
Estimated Fifth Year Benefits	\$16,986.08
Calculated IRR [Ref. 2: p. 320-322]:	19.93%

### III. TECHNICAL FEASIBILITY

Can the system be implemented using current technology [Ref. 2: p. 274]? This is the question that must be answered to determine and evaluate the technical feasibility of a project. For the SARELTIS project, the issue of current technology was approached from two different perspectives. First, was the concept of a historical database system that could provide on-line query information and complex management reports an implementable concept within the scope of a thesis project? And second, was this concept implementable within the constraints of the Coast Guard standard database language, ReQuest®? During the last year, two limited scale prototypes were developed by the authors to answer these two questions of project technical feasibility.

#### A. LAW ENFORCEMENT INFORMATION SYSTEM

Concept implementability was the question that was addressed by the design of the Coast Guard Law Enforcement Information System, the first prototype. This prototype was programmed on the Coast Guard Standard Terminal System using the relational database system R:base 4000®, and provided historical information on vessels, operators, and vessel boardings. It was designed to facilitate the retrieval of "intelligence-type" information to better prepare boarding officers and boarding petty officers prior to stepping onto a vessel. It also provided statistical information of the locations, times, dates, and the types of vessels that were boarded.

The logical design of this prototype included the entities of an operator, a vessel, and a boarding. To implement this logical design, additional relations were added as required to provide the necessary intersection mechanisms, rules, forms, reports and editing constraints. All restrictions concerning the legal values of attributes and interrelational constraints are stated and controlled through the use of the R:base 4000 rules feature. Menu chaining was used to provide a user friendly system, and menus and programs were written in and controlled through the use of the R:base 4000 command language. The R:base 4000 environment proved to be very capable of supporting this limited scale application.

This prototype was successfully demonstrated in December 1986. The prototype demonstrated the capability of complex nautical chart searching algorithms for use in

making key management decisions for "high incident areas" and "high incident times" and the capability of searching the database for vessels of interest within a given search criteria.

Therefore, through the use of the Law Enforcement Information System prototype, the question of concept implementability was successfully satisfied.

## **B. SEARCH AND RESCUE INTELLIGENCE INFORMATION SYSTEM**

Since all Coast Guard "production" database management system implementations are required to use the Coast Guard standard database language, ReQuest, another limited scale prototype was developed to assess the feasibility of application development within the constraints imposed by Coast Guard directives. The development and testing of this prototype, the Search and Rescue (SAR) Intelligence Information System, occurred during June 1987.

The Search and Rescue Intelligence Information System was programmed on the Coast Guard Standard Terminal System using the language ReQuest, and provided historical information on vessels, owners, and vessel search and rescue cases. It was designed to facilitate the retrieval of detailed vessel and owner historical information to better enable the SAR case personnel to conduct the SAR mission.

The entities of an owner, a vessel, and a SAR case were represented within the logical structure of this prototype. The physical structure included an intersection record to link the owner and vessel entities. All attribute and interrelational constraints were specified and controlled through the attribute descriptions. Forms and reports were created and stored as individual files, independent of the database structure. Menus were very limited as ReQuest does not allow menu chaining beyond the top level. Reports were also very limited due to the restrictions imposed by ReQuest concerning multiple relation searching and reporting. The system was designed to replicate the functionality of the first prototype as much as possible, however, the ReQuest environment did not allow this parallelism.

## **C. INADEQUACIES OF REQUEST FOR THE SARELTIS PROTOTYPE**

Numerous problems were encountered during the development of the second prototype that were directly attributable to the use of the language ReQuest. This language is very limited in scope and inflexible in nature. It does not support any type of command language for program or menu construction. To successfully utilize an application developed within this environment, the user must be very knowledgeable

and fully understand both the language and the application. Unlike more flexible programming environments, the details of the language and the underlying structure of the application cannot be made transparent to the user. Additionally, the true strengths of a relational system, namely the ability to join and search multiple tables for reports or ad-hoc queries, is absent in this language. Reports are limited to the use of two tables at most, with certain restrictions, and information requested by ad-hoc queries may only come from a single predefined table. Any tables that result from a relational operation, such as a join, cannot then be searched by an adhoc query. Therefore, to provide the desired searching functionality within the SARELTIS prototype, the physical implementation would have to consist of a single relation, and would be subject to all the anomalies inherent in a first normal form relational database [Ref. 3: p. 286-290]. Speed is also a major problem. To accomplish even the simplest tasks required a great deal of waiting time on the part of the user. Finally, the security system provided by the language did not function properly. As a result of these constraints imposed by the ReQuest language, it was determined that a different environment would have to be used to successfully implement the SARELTIS prototype.

#### **D. PROPOSED LANGUAGE ENVIRONMENT**

Since ReQuest was determined to be infeasible as a language environment for the SARELTIS project, the additional languages available for the Coast Guard Standard Terminal System were examined to determine if any were suitable. At present, the only additional language available for the standard terminal and the CTOS operating system is the R:base 5000 relational database environment. As this is an updated and enhanced version of the language used for the first prototype, it was determined that R:base 5000 would be used for the SARELTIS project. Unfortunately, the R:base 5000 environment was not available locally for the Coast Guard Standard Terminal System. The language was, however, available for the IBM DOS operating system. Therefore, the decision was made to develop the SARELTIS prototype utilizing the R:base 5000 environment within the IBM DOS operating system. This decision allowed the development of a fully capable product that could ultimately be converted for use on the Coast Guard Standard Terminal System, and established full technical feasibility for the SARELTIS prototype.

## IV. USERS GUIDE

### A. INTRODUCTION

The following user's guide is written assuming that its intended user will be utilizing an IBM PC-XT or an IBM compatible computer with a 5.25 inch floppy disk drive, a minimum of 640K internal memory, a hard disk (minimum 10M Bytes), a printer with a normal size carriage, and using the DOS operating system. If a different hardware configuration is used, the user should refer to the owner's manual to see how to load R:base 5000 and to determine if the configuration will support the database system and SARELTIS.

SARELTIS was designed to assist Coast Guard Group Monterey in automating historical information and intelligence retrieval. To this end, SARELTIS provides comprehensive input and modify programs to assist the user in easily entering information and correcting/updating existing information in the system. Additionally, a realtime query module allows users to access system database records quickly and easily in order to provide the most current intelligence and historical information in a timeframe that can be used in operational missions.

This user's guide is an attempt to direct users through the major portions of SARELTIS. A recent thesis by LCDR J. M. Graham [Ref. 4] provided some of the framework and content of this section. Due to the actual size of the SARELTIS program and the desire to keep the user's guide short and easy to understand, the technical inner workings of each program will not be discussed. Users desiring to know more information should consult the R:base 5000 technical manuals or contact one of the authors for additional clarification. The following topics will be addressed to assist the user with SARELTIS operations:

- System Startup Procedures
- Security
- Operations
- Exiting
- Maintenance

## **B. SYSTEM STARTUP PROCEDURES**

### **1. Machine Configuration Requirements**

Due to the size of SARELTIS (over 800K in database structure and over 500K in application program modules), the user must ensure that the machine is properly initialized with a CONFIG.SYS file which contains the following:

- \* Buffers = 5
- \* Files = 20

If this file does not exist or does not contain the information listed above, the user will need to build or modify the CONFIG.SYS file accordingly. The user should consult the DOS Manual for the specific procedure necessary to create or alter a CONFIG.SYS file. Once the CONFIG.SYS file has been properly created/modified, the computer should be reset/booted to allow this new machine configuration to be installed. To reset the system, the user presses the following three keys simultaneously: <CTRL> <ALT> <DEL>. After the machine has been reset, the computer will ask the user for the current date and current time. It is very important that the user enter the correct time and date into the system as the system time and date are used by many application program modules. After each date and time entry, the user should press the <ENTER> key.

### **2. Initial Program Loading**

If all has proceeded satisfactorily from the above section, the screen should display the following system prompt indicating that you are working from the hard disk: "C:>".

Use the DOS MKDIR (make directory) command to create a directory to store the R:base 5000 programs by typing "MKDIR C:\R5K" at the system prompt. Next, use the DOS CHDIR (change directory) command to change the working directory to the newly created R:base 5000 directory by typing "CHDIR C:\R5K" at the system prompt. At this point you are ready to load the R:base 5000 software if it is not already been installed. To load the R:base 5000 software [Ref. 5: p. 1.3 - 1.6], do the following:

1. Insert one of the R:base 5000 disks into floppy drive a.
2. Copy all files from the disk to the newly created R:base 5000 directory by entering "COPY \*.\*".
3. When all of the files have been copied from the floppy disk to the R:base 5000 directory on your hard disk, remove the floppy disk from the floppy drive.

4. Repeat steps 2 through 4 until all R:base 5000 floppy disks have been copied to your hard disk.

After you have loaded the R:base 5000 database software, you are now ready to load the SARELTIS application. SARELTIS has been designed to operate from its own directory (DBDIR) which the user must create. To create another directory, use the DOS MKDIR command and type "MKDIR C:\DBDIR". Next, you must copy the SARELTIS database and its application and ancillary programs to the DBDIR directory.

The SARELTIS database is stored on 4 diskettes labeled:

- SARELTIS 1
- SARELTIS 2
- SARELTIS 3
- SARELTIS 4

The application programs are stored on 2 diskettes labeled:

- SARELTIS APPLICATIONS 1
- SARELTIS APPLICATIONS 2

The source code for the applications programs are stored on 2 diskettes labeled:

- SARELTIS APPLICATIONS SOURCE CODE 1
- SARELTIS APPLICATIONS SOURCE CODE 2

The application program source code disks are provided for maintenance purposes only. The ancillary programs are stored on 1 diskette labeled SARELTIS ANCILLARY PROGRAMS. To load SARELTIS, do the following:

1. Insert SARELTIS 1 into the A: floppy drive.
2. Type the following DOS command: "RESTORE a: \DBDIR ". You will be prompted by the system to load SARELTIS 2, 3, and 4.
3. Insert SARELTIS APPLICATIONS 1 into the A: floppy drive.
4. Type the following DOS command: "RESTORE a: \DBDIR ". You will be prompted by the system to load SARELTIS APPLICATIONS 2.
5. Insert the SARELTIS ANCILLARY PROGRAMS floppy disk into the A: floppy drive.
6. Type the following DOS command: "COPY a:\*.\*\*".

You have now loaded the SARELTIS database and its application programs and are now ready to start the program. To start SARELTIS, enter the following at the system prompt: "SARSYS". This will automatically take you to a security module that will ask for a user name and password. The default user name is "SYSOP" and the



default user password is "SARSYS". If you wish to protect the system, see the next section on security.

### C. SARELTIS SECURITY

One of SARELTIS' ancillary programs is called "STARTUP.BIN". This program is a compiled/binary program which prints the initial SARELTIS title screen and provides the security module to gain access to the system. As discussed in the previous section, the system has a default user name and password. These can be changed very easily by the user (it is recommended that the user become somewhat familiar with R:base 5000 and SARELTIS before changing the security). Using a text editor or a word processor in the non-document mode, open the ancillary program "STARTUP.PRG". Approximately halfway through the program, you will find the following command:

"if username eq "SYSOP" and userpass eq "SARSYS" then"

By changing "SYSOP" to another user name and altering "SARSYS" to another password, you can protect your own system. Once you have changed the user name and password, ensure that you write it down and store it in a safe place. To activate the new security password, you must recompile "STARTUP.PRG". To recompile STARTUP.PRG, do the following:

1. At the system prompt, type "RCOMPILE" to run the R:base 5000 program compiler. The system will then display the RCOMPILE menu listing eight possible options.
2. Select the option to "Convert an ASCII command file to a binary command file" by entering a "1". The cursor should highlight the "(1)" next to the desired menu option.
3. Press the <ENTER> key to execute the menu option.
4. The system will ask you to enter the name of the ASCII command file to convert. Enter "STARTUP.PRG" and press the <ENTER> key.
5. RCOMPILE will then respond asking for the name of the backup file. Since we do not need a backup of this file, press the <ENTER> key.
6. The system will then ask for the name of the binary command file that you wish to create. In the space provided, enter "STARTUP.BIN" and press the <ENTER> key. The system will now re-compile the program. At the completion of the compilation, RCOMPILE will return you to its menu screen. Enter an "8" and press <ENTER> to exit from the RCOMPILE program.

You have now changed the security on the system and the new user name and password have been activated. To ensure that the system is fully secure, remove the

"STARTUP.PRG" file by typing the following DOS command: "ERASE STARTUP.PRG". This will prevent any unauthorized users from discovering the new security password by merely typing out the "STARTUP.PRG" file. If you wish to alter the security password after this point, you must copy the "STARTUP.PRG" file to the hard disk from the SARELTIS APPLICATIONS SOURCE floppy disk.

## **D. SARELTIS OPERATIONS**

### **1. Menu System Overview**

The man-machine interface for SARELTIS is a series of menus. Beginning with the SARELTIS Master Menu (Figure 4.1), the user can branch to a desired function. Each menu allows the user to return to the previous menu. All menu selections are grouped by functional area to provide the user with a more efficient operating environment. Examples of the remaining menu screens are presented in Figures 4.2 through 4.4 and Figures 4.7 through 4.13. Detailed functional descriptions of each menu option can be reviewed by examining Appendix D.

### **2. Starting SARELTIS**

To start SARELTIS and to get to the main menu screen requires the user to type "SARSYS" at the system prompt and pressing the <ENTER> key. As described in the security section above, the user must supply the correct user name and password in order to gain access to the system. Once the proper user name and password are entered, the system is automatically initialized and the SARELTIS Master Menu appears. The user is free to select any option by either moving the cursor up/down (using the arrow keys on the numeric pad) or by typing the actual number of the option desired to be executed. Once a selection is made, pressing the <ENTER> key will execute the option. The user will then be presented with another menu screen or an actual function will be performed. Short descriptions of each menu option are presented in the following section.

### **3. SARELTIS Menu Options**

#### ***a. SARELTIS Master Menu (Figure 4.1)***

Selecting option (1), INPUT INFORMATION, displays the SARELTIS INPUT MENU (Figure 4.2). Option (2) calls the SARELTIS MODIFY MENU (Figure 4.3). The real-time query menu, QUERY INFORMATION MENU (Figure 4.4), is displayed upon selection of choice (3). The REPORTS MAIN MENU (Figure 4.7) is called when option (4) is chosen. Option (5) provides the user with the UTILITIES MENU (Figure 4.13). User-designed queries or reports may be

constructed by selecting option (6), AD HOC QUERIES, which returns the user to the R:base 5000 command prompt "R>". To exit SARELTIS, the user selects option (7), EXIT SARELTIS.

SARELTIS MASTER MENU	
(1)	INPUT INFORMATION
(2)	MODIFY INFORMATION
(3)	QUERY INFORMATION
(4)	REPORTS
(5)	UTILITIES
(6)	AD HOC QUERIES
(7)	EXIT SARELTIS

Figure 4.1 SARELTIS Master Menu.

***b. Input Information Menu (Figure 4.2)***

The user is provided with eight options to enter data into SARELTIS. The user has the choice of entering SAR information alone by selecting option(1) or entering SAR information with boarding information by choosing option (2). Option (3) allows the user to enter in multiple SAR units. Entering in boarding information alone is performed by choosing option (4). Selecting option (5) will allow the user to enter in additional vessel owners. Vessel intelligence and personnel intelligence are entered into the system by selecting options (6) or (7). To return to the SARELTIS MASTER MENU, the user selects option (8).

***c. SARELTIS Modify Menu (Figure 4.3)***

SARELTIS data can be modified using one of the nine available options. Option (1) allows the user to update historical SAR information. By selecting option (2), existing boarding information can be modified. Vessel information may be changed by selected option (3). Demographic data maintained on vessel owners and operators can be altered by choosing option (4). If the user desires to change the name of an owner or an operator and this individual is both an owner and an operator, the name must be changed in both places. Information regarding Group Monterey SAR

#### SARELTIS INPUT MENU

- (1) INPUT SAR INFORMATION (NO BOARDING)
- (2) INPUT SAR INFORMATION WITH BOARDING
- (3) INPUT MULTIPLE SAR UNITS
- (4) INPUT BOARDING INFORMATION
- (5) INPUT MULTIPLE VESSEL OWNERS
- (6) INPUT VESSEL INTELLIGENCE
- (7) INPUT PERSONNEL INTELLIGENCE
- (8) RETURN TO MASTER MENU

Figure 4.2 SARELTIS Input Menu.

units can be changed by selecting option (5). Options (6) and (7) allow the user to manipulate vessel and personnel intelligence information. The vessel HIN may be changed by selecting option (8) if it was previously entered incorrectly. To return to the MASTER MENU, the user selects option (9).

#### SARELTIS MODIFY MENU

- (1) MODIFY SAR INFORMATION
- (2) MODIFY BOARDING INFORMATION
- (3) MODIFY VESSEL INFORMATION
- (4) MODIFY OWNER/OPERATOR INFORMATION
- (5) MODIFY SAR UNIT INFORMATION
- (6) MODIFY VESSEL INTELLIGENCE
- (7) MODIFY PERSONNEL INTELLIGENCE
- (8) MODIFY VESSEL HIN
- (9) RETURN TO MAIN MENU

Figure 4.3 SARELTIS Modify Menu.

**d. SARELTIS Query Menu (Figure 4.4)**

The real-time query capability of SARELTIS is executed through the invocation of this menu. By selecting Option (1), the user can perform a vessel query based on vessel Hull Identification Number (HIN), vessel name, vessel number, or vessel official number. The query module will search the entire vessel table attempting to find potential matches to the user's selection criteria. Figure 4.5 shows the chaining of searches through the database when selecting the vessel query option. Similarly, the user can search through the database using a person's last name and first name by choosing option (2). The query program will find all potential matches and ask the user to select the correct individual to perform an intelligence/history check. Figure 4.6 shows the chaining of searches through the database for the personnel query option. To return to the SARELTIS MASTER MENU, the user selects option (3).

SARELTIS QUERY MENU	
(1)	VESSEL QUERY
(2)	PERSONNEL QUERY
(3)	RETURN TO MAIN MENU

Figure 4.4 SARELTIS Query Menu.

**e. SARELTIS Reports Main Menu (Figure 4.7)**

Reports in SARELTIS are broken down into mission/functional area groups that can be selected from the Reports Main Menu. This menu calls other sub-menus which represent the available choices within the specific mission/functional area. Selecting option (1) will allow the user to display the INTELLIGENCE REPORTS MENU (Figure 4.8). Option (2) will invoke the BOARDING REPORTS MENU (Figure 4.9). The SAR REPORTS MENU (Figure 4.10) is executed by choosing option (3). Option (4) will call the VESSEL REPORTS MENU (Figure 4.11). By selecting option (5), the user will see the available choices from the PERSONNEL REPORTS MENU (Figure 4.12). Detailed descriptions of each report function can be found in Appendix D. To return to the MASTER MENU, the user selects option (6).




Figure 4.5 Vessel Query Search Chain.




Figure 4.6 Personnel Query Search Chain.




Figure 4.7 SARELTIS Reports Main Menu.




Figure 4.8 SARELTIS Intelligence Reports Menu.

*f. SARELTIS Utilities Menu (Figure 4.13)*

From the Utilities Menu, the user can initialize SARELTIS by selecting option (1). This program is automatically invoked at the start of any SARELTIS session and is also executed upon exiting the system. Option (2) will pack or compress the database to more efficiently use the existing limited hard disk space. It is recommended that the user perform a pack of the database at least once per month. Prior to executing a pack of the database, the user should make a backup copy of the SARELTIS database in the event that an unanticipated error should occur during the packing process. Option (3) will display the procedures for backing up the database. In order to backup the database, the user must exit from SARELTIS (via option (7) on the MASTER MENU) and execute a DOS BATCH File located on the hard disk



#### **SARELTIS BOARDING REPORTS MENU**

- (1) VIOLATION/UNSAFE CONDITION FREQUENCY
- (2) BOARDINGS SUMMARY LISTING
- (3) CME DECALS: ANALYSIS OF VESSELS BOARDED
- (4) LARGE SCALE AREA BOARDING LOCATION ANALYSIS
- (5) SMALL SCALE AND COASTLINE AREA BOARDING LOCATION ANALYSIS
- (6) SMALL BOAT OPERATIONS AREA BOARDING LOCATION ANALYSIS
- (7) TIME OF DAY BOARDING CASE ANALYSIS
- (8) RETURN TO REPORTS MENU

Figure 4.9 SARELTIS Boarding Reports Menu.

#### **SARELTIS SAR REPORTS MENU**

- (1) ANALYSIS OF IMMEDIATE DISTRESS SAR CASES
- (2) SMALL SCALE AND COASTLINE AREA SAR CASE LOCATION ANALYSIS
- (3) LARGE SCALE AREA SAR CASE LOCATION ANALYSIS
- (4) SMALL BOAT OPERATIONS AREA SAR CASE LOCATION ANALYSIS
- (5) SAR TABLE SUMMARY LISTING
- (6) SAR UNIT TIME EXPENDED DURING SAR CASES
- (7) DAY OF THE WEEK, MONTH, AND YEAR ANALYSIS
- (8) SAR CASE ANALYSIS: DAYTIME/NIGHTTIME FREQUENCY
- (9) RETURN TO REPORTS MENU

Figure 4.10 SARELTIS SAR Reports Menu.

called "BACKDBMS.BAT". Since this backup will take a minimum of six floppy disks, the user should ensure that at least six floppy disks have been formatted prior to executing this program. To format a floppy disk, type the command "PATH UTIL"

#### SARELTIS VESSEL REPORTS MENU

- (1) VESSEL SUMMARY LISTING
- (2) VESSEL --- OWNERS OF SPECIFIED VESSELS
- (3) VESSEL --- OPERATORS OF SPECIFIED VESSELS
- (4) RETURN TO REPORTS MENU

Figure 4.11 SARELTIS Vessel Reports Menu.

#### SARELTIS PERSONNEL REPORTS MENU

- (1) OWNERS OF VESSELS SUMMARY LISTING
- (2) OWNER --- VESSELS WHICH ARE OWNED BY SPECIFIED OWNERS
- (3) OPERATORS OF VESSELS SUMMARY LISTING
- (4) OPERATORS --- VESSELS WHICH ARE OPERATED BY SPECIFIED OPERATORS
- (5) RETURN TO REPORTS MENU

Figure 4.12 SARELTIS Personnel Reports Menu.

at the system prompt "C:>", then type "FORMAT A:" at the next system prompt "C:>". The system will prompt the user to insert the disks to be formatted into floppy drive A: and will indicate when the process has been completed. After ensuring that the user has prepared enough formatted floppy disks, the user is ready to execute the batch file. The user should type "BACKDBMS" at the system prompt "C:>" and press the <ENTER> key to execute the program. Follow the system prompts to remove and insert floppy disks. When the database has been backed up the program will automatically return the user to SARELTIS. In the unlikely event that the database has "crashed" (e.g. nothing seems to work as advertised), the user may recover the database from the last back-up. Similar to the back up process, option (4) details the specific procedures in order to recover the database. Basically, the user must exit SARELTIS and at the system prompt type "RESTDBMS" and press the

<ENTER> key. This executes the DOS BATCH File "RESTDBMS.BAT". The user should follow any instructions that the computer displays on the screen. When the database has been fully recovered, the program will automatically return the user to the SARELTIS system.




Figure 4.13 SARELTIS Utilities Menu.

#### **E. EXITING SARELTIS**

To exit SARELTIS and return to the computer's operating system, select option (7) from the SARELTIS Main Menu. This will automatically close all open files and remove any temporary relations/tables and variables that have been created during the operation of the system. The user should not exit the system by merely turning the computer off. Data could be lost or incorrectly entered upon losing system power. Once SARELTIS has completed closing all files and removing temporary tables and variables, it will return the user to the system prompt: "C:>". Once the system prompt is displayed and the computer is no longer needed, the power may safely be turned off without danger to the SARELTIS database.

#### **F. SARELTIS MAINTENANCE**

Maintenance to the SARELTIS application programs should not be undertaken by the casual user. Before performing any alterations to the source code, the user should invest considerable time and effort in understanding the proper techniques of software programming and documentation.

Due to the high degree of interdependencies between the program modules, the user must be aware that a seemingly minor alteration could have far-reaching unseen

effects. The system may appear to operate correctly, but in reality, the data being stored, modified, or printed could be inaccurate or even lost.

Users desiring to modify the source code should have a thorough knowledge of relational database structures, structured programming techniques, and the R:base 5000 command language. Prior to making any changes the user should ensure that the database is backed up and that copies of the applications programs have been made in the event that the modifications do not function properly. Above all, the user should NEVER attempt to make modifications to the source code without outside expert consultation and assistance.

Due to the size and complexity of SARELTIS, the authors recognize that errors will be discovered. This will require that the source code or database structure will need to be modified. A knowledgeable user can use the source code listings found in Appendices E through P to assist in the understanding and modification of the program modules.

## **V. CONCLUSIONS AND RECOMMENDATIONS**

### **A. SARELTIS RESULTS**

SARELTIS was originally conceived to merely replace Group Monterey's corporate knowledge base and provide access to historical information to assist boarding officers and Search and Rescue Coordinators. What has evolved is a system with far more capabilities than originally designed. The concept of providing only summarized frequency data was transformed to providing the capability to perform limited decision support functions. The system still produces the required standard statistical reports but also provides vessel profiles of potential violators. These profiles examine individual violation codes and search the historical boarding information to determine by violation the vessel type, use, hull material, propulsion, engine compartment type, fuel compartment, length, and year of construction of vessels found in violation of the specific code.

The system also provides SAR and ELT planning by examining "high incident times" and "high incident areas". By reviewing SAR historical information, SAR Coordinators can better plan for crew augmentation or additional floating or land resources. Additionally, by examining where SAR cases and ELT missions have occurred, Group Monterey can better plan where to strategically locate or send their floating units.

As discussed in Chapter II, the Coast Guard has been brought under scrutiny for potential harassment of the boating public by repetitively boarding the same vessel during a very small time interval. SARELTIS will provide the means to ascertain whether a particular vessel has been boarded in the operational area, when the vessel was last boarded, and what violations, if any, were discovered.

One of the most important aspects of SARELTIS is the capability of providing real-time information and intelligence to boarding officers and SAR Coordinators. With timely information, boarding officers can better understand and recognize potential dangerous situations prior to going on board a vessel.

### **B. CONCLUSIONS**

This thesis was the first step toward providing better and more timely information to Coast Guard operational units. Although SARELTIS has not been put

## APPENDIX A

### LOGICAL MODELS

A Data Flow Diagram (DFD) is a method to graphically represent the logical functions of a system. Through the use of this very simple modeling technique, the analyst and user can examine the functions and interfaces of the existing system and easily define the components required within the proposed new system. These diagrams serve to summarize the processes and the flow of data within the logical model of the current methodology and to depict the functions of the proposed system independent of physical implementation details.

Within the diagrams, processes or activities are depicted as uniquely identified circles, and the flow of data is represented by arrows. Rectangles indicate a source or destination for some type of information or product. The number included within a process circle uniquely identifies that process and serves as a means for indicating the subprocesses of a higher level process. Higher level processes have single digit numbers, while a subprocess number consists of the parent number(s) and the subprocess number. This numbering convention allows the subfunctions of a higher level function to be easily identified. [Ref. 2: p. 282].

A second tool that is very useful for the logical modeling of a database system is the Bachman diagram. This diagram depicts the entities that are present within the system, represented as boxes, and their interrelationships, which are depicted by arrows between the entities. Representing the logical structure of the proposed database, this diagram sets a foundation for the development of the physical database structure [Ref. 3: p. 39].

Within this appendix, the existing search and rescue and law enforcement system processes are depicted by Figures A.1 through A.4, the proposed new systems as Figures A.5 through A.10, and the combined database logical structure as Figure A.11.

into production at Group Monterey, it will be implemented there in September 1987. It is anticipated that its use will stimulate further interest in the SARELTIS concept and create other needs not previously identified nor programmed in the first version.

### **C. SUGGESTIONS FOR FURTHER RESEARCH**

This thesis successfully analyzed, designed, and implemented an automated intelligence system to assist small Coast Guard units similar to Group Monterey. The robustness of the system has been demonstrated in its preparation of over 45 standard reports for use by the small unit to assist in recordkeeping, intelligence reporting, and resource planning. Although not originally conceived, a limited decision support capability was built into the system. This seems to be one of the potential areas for further research. The reports designed in SARELTIS are by no means complete. It is envisioned that with the proper tools the SARELTIS database could be used as the basis for a comprehensive decision support system.

Another area of potential research that was beyond the scope of this thesis was the interfacing to a central database. By telecommunicating the data collected by the system to a Coast Guard district office or area office, the SARELTIS concept can be transported to a larger geographic area. Terminals could be connected via MODEM to this online database to provide the most up-to-date information possible.

Data entry into the system could also be improved. If SARELTIS could automatically receive intelligence information from local or federal law enforcement agencies, this would eliminate the necessity to manually enter the information via the computer keyboard. Additionally, if an optical mark boarding form was used by boarding officers, manual data entry could also be reduced with the aid of an optical mark reader.




Figure A.1 Existing SAR System - Level 0.






Figure A.2 Existing SAR System - Level 1.




Figure A.3 Existing ELT System - Level 0.




Figure A.4 Existing ELT System - Level 1.




Figure A.5 Proposed SAR System - Level 0.




Figure A.6 Proposed SAR System - Level 1.




Figure A.7 SAR System SARELTIS Automation Boundary.





Figure A.8 Proposed ELT System - Level 0.








Figure A.10 ELT System SARELTIS Automation Boundary.




Figure A.11 Bachman Diagram of Proposed System.

## **APPENDIX B**

### **SYSTEM REPORTS**

To assist Coast Guard Group Monterey with operations, planning and report generation, the SARELTIS prototype provides numerous hard copy reports. Procedures utilized to generate these reports are discussed in Chapter IV, the System User's Guide. Examples of all reports produced by the prototype are displayed in this appendix as Figures B.1 through B.45. Table 3 provides a reference for the correspondence between the figures included in this appendix and the report names called within the program listing.

US Coast Guard Group Monterey  
Vessel Boarding Summary Listing  
For the Period: 01/01/1980 - 01/01/1988  
=====

Date: 08/15/1987  
Page: 1

Vessel	HIN														
-----															
111111111111	01/15/1980	mon	5:00:00a	bm3	smith										
mry-001	37.00 N	121.52 W	CG Group Monterey		11	36268									
	Monterey Bay	Monterey	Monterey	CA											
WPNS- 3 POB-	8 ADLT-	6 CHLD-	2 OWST-1	S/R:	6:00:00a	S/S:	7:00:00p								
	V54	V55	V56	V57	V58	V59	V60	V61	V62	V63	V64	V65	V66	V67	V68
	x	-	x	-	x	-	x	-	x	-	x	-	x	-	x
	U69	U70	U71	U72	U73	U74	U75	U76	U77	U78	U79				
	-	-	-	x	-	x	-	x	-	x	-				
owner/operator was abusive towards boarding officer															
-----															
222222222222	02/25/1981	fri	7:30:00p	bm2	adams										
mry-002	36.29 N	122.46 W	CG Group Monterey		11	36268									
	Monterey Bay	Monterey	Monterey	CA											
WPNS- 1 POB-	12 ADLT-	12 CHLD-	0 OWST-1	S/R:	6:00:00a	S/S:	7:00:00p								
	V54	V55	V56	V57	V58	V59	V60	V61	V62	V63	V64	V65	V66	V67	V68
	x	x	x	x	x	-	-	-	-	-	-	-	-	-	x
	U69	U70	U71	U72	U73	U74	U75	U76	U77	U78	U79				
	-	-	-	-	-	-	-	x	-	x	-				
-----															
333333333333	03/18/1983	mon	12:00:00p	bm2	adams										
mry-003	36.28 N	123.06 W	CG Group Monterey		11	36268									
	Monterey Bay	Monterey	Monterey	CA											
WPNS- 1 POB-	12 ADLT-	12 CHLD-	0 OWST-1	S/R:	6:00:00a	S/S:	7:00:00p								
	V54	V55	V56	V57	V58	V59	V60	V61	V62	V63	V64	V65	V66	V67	V68
	x	x	-	x	x	-	-	x	x	-	-	x	x	-	x
	U69	U70	U71	U72	U73	U74	U75	U76	U77	U78	U79				
	x	-	-	x	x	-	-	x	-	-	-				
belligerent operator															
-----															

Figure B.1 Boarding Listing.

US Coast Guard Group Monterey  
Boarding Location Frequency  
For Major Grid Areas  
During Period 01/01/1980 - 01/01/1988  
=====

Total Boardings - 8

Date - 08/15/1987

Page - 1

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total Boardings
A	37.30	37.00	122.30	123.00	0	0.00 %
B	37.30	37.00	122.00	122.30	0	0.00 %
C	37.00	36.30	123.00	123.30	0	0.00 %
D	37.00	36.30	122.30	123.00	0	0.00 %
E	37.00	36.30	122.00	122.30	0	0.00 %
F	37.00	36.30	121.30	122.00	1	12.50 %
G	36.30	36.00	123.00	123.30	1	12.50 %
H	36.30	36.00	122.30	123.00	2	25.00 %
I	36.30	36.00	122.00	122.30	1	12.50 %
J	36.30	36.00	121.30	122.00	0	0.00 %
K	36.00	35.30	122.30	123.00	0	0.00 %
L	36.00	35.30	122.00	122.30	0	0.00 %
M	36.00	35.30	121.30	122.00	0	0.00 %
N	36.00	35.30	121.00	121.30	0	0.00 %
O	35.30	35.00	122.30	123.00	0	0.00 %
P	35.30	35.00	122.00	122.30	1	12.50 %
Q	35.30	35.00	121.30	122.00	0	0.00 %
R	35.30	35.00	121.00	121.30	1	12.50 %
S	35.30	35.00	120.30	121.00	0	0.00 %

Figure B.2 Major Grid Area Boarding Frequency.

Date - 08/15/1987

Page - 2

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total Boardings
T	35.00	34.30	122.00	122.30	0	0.00 %
U	35.00	34.30	121.30	122.00	0	0.00 %
V	35.00	34.30	121.00	121.30	0	0.00 %
W	35.00	34.30	120.30	121.00	0	0.00 %
X	34.30	34.00	121.30	122.00	0	0.00 %
Y	34.30	34.00	121.00	121.30	0	0.00 %

Total Boardings In Major Grid Areas.....	7	87.50 %
Total Boardings Outside Grid Area.....	1	12.50 %
Total Boardings.....	8	

Figure B.2 Major Grid Area Boarding Frequency. (cont'd.)

US Coast Guard Group Monterey  
Boarding Location Frequency  
For Minor Grid Areas (Coastline)  
During Period 01/01/1981 - 01/01/1988  
=====

Total Boardings - 7

Date - 08/15/1987

Page - 1

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total Boardings
01	37.10	37.05	122.20	122.25	0	0.00 %
02	37.10	37.05	122.15	122.20	0	0.00 %
03	37.05	37.00	122.20	122.25	0	0.00 %
04	37.05	37.00	122.15	122.20	0	0.00 %
05	37.05	37.00	122.10	122.15	0	0.00 %
06	37.00	36.55	122.15	122.20	0	0.00 %
07	37.00	36.55	122.10	122.15	0	0.00 %
08	37.00	36.55	122.05	122.10	0	0.00 %
09	37.00	36.55	122.00	122.05	0	0.00 %
10	37.00	36.55	121.55	122.00	0	0.00 %
11	37.00	36.55	121.50	121.55	0	0.00 %
12	36.55	36.50	122.00	122.05	0	0.00 %
13	36.55	36.50	121.55	122.00	0	0.00 %
14	36.55	36.50	121.50	121.55	0	0.00 %
15	36.55	36.50	121.45	121.50	0	0.00 %
16	36.50	36.45	122.00	122.05	0	0.00 %
17	36.50	36.45	121.55	122.00	0	0.00 %
18	36.50	36.45	121.50	121.55	0	0.00 %
19	36.50	36.45	121.45	121.50	0	0.00 %

Figure B.3 Minor Grid Area Boarding Frequency.

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total Boardings
20	36.45	36.40	122.00	122.05	0	0.00 %
21	36.45	36.40	121.55	122.00	0	0.00 %
22	36.45	36.40	121.50	121.55	0	0.00 %
23	36.45	36.40	121.45	121.50	0	0.00 %
24	36.40	36.35	122.00	122.05	0	0.00 %
25	36.40	36.35	121.55	122.00	0	0.00 %
26	36.40	36.35	121.50	121.55	1	14.29 %
27	36.40	36.35	121.45	121.50	0	0.00 %
28	36.35	36.30	121.55	122.05	0	0.00 %
29	36.30	36.25	121.53	122.05	0	0.00 %
30	36.25	36.20	121.52	122.05	0	0.00 %
31	36.20	36.15	121.50	122.05	0	0.00 %
32	36.15	36.00	121.30	122.00	0	0.00 %
33	36.00	35.40	121.15	121.45	0	0.00 %
34	35.40	35.20	120.45	121.30	1	14.29 %
35	35.20	35.00	120.35	121.10	0	0.00 %
36	35.00	34.40	120.35	121.00	0	0.00 %
37	34.40	34.27	120.28	121.00	0	0.00 %

Total Boardings in Minor Grid/Coastline Areas.....	2	28.57 %
Total Boardings Outside Minor Grid Areas.....	5	71.43 %
Total Boardings.....	7	

Figure B.3 Minor Grid Area Boarding Frequency. (cont'd.)



# US Coast Guard Group Monterey Boarding History

Date-08/15/1987

Page- 1

DATE	TIME	BONO	VESSEL HIN	BOLAT	BOLONG	POB
01/15/1980	5:00:00a	mry-001	111111111111	37.00N	121.52W	8
	V54 V55 V56 V57	V58 V59	V60 V61 V62 V63	V64 V65	V66 V67	V68
	x x x	x x x	x x x	x x x	x x x	x
	U69 U70 U71 U72 U73	U74 U75	U76 U77 U78	NOVIOLS	WEAPONS	ALCOHOL
	x x x	x x x	x x x		3	x

owner/operator was abusive towards boarding officer

BOARDING OFFICER - smith

bm3

DATE	TIME	BONO	VESSEL HIN	BOLAT	BOLONG	POB
04/17/1985	2:30:00p	mry-008	111111111111	36.38N	121.52W	0
	V54 V55 V56 V57	V58 V59	V60 V61 V62 V63	V64 V65	V66 V67	V68
	x x x	x x x	x x x	x x x	x x x	x
	U69 U70 U71 U72 U73	U74 U75	U76 U77 U78	NOVIOLS	WEAPONS	ALCOHOL
	x x x	x x x	x x x		2	x

owner/operator was uncooperative and abusive towards boarding officer

BOARDING OFFICER - adams

bm2

Figure B.4 Vessel Boarding History.

US Coast Guard Group Monterey  
 Courtesy Motorboat Examinations (CME's)  
 During the Period: 01/01/1980 - 01/01/1988  
 =====

Date: 08/15/1987

Page: 1

<u>CME Issue Year</u>	<u>Occurrences</u>	<u>Percentage Total CME's</u>	<u>Percentage Total Boardings</u>
prior to 1970 .....	0	0.00 %	0.00 %
1971 - 1975 .....	0	0.00 %	0.00 %
1976 - 1979 .....	0	0.00 %	0.00 %
1980 - 1981 .....	0	0.00 %	0.00 %
1982 - 1983 .....	2	50.00 %	15.38 %
1984 - 1985 .....	2	50.00 %	15.38 %
1986 - 1987 .....	0	0.00 %	0.00 %
1988 - 1989 .....	0	0.00 %	0.00 %
after 1990 .....	0	0.00 %	0.00 %
-----			
Total CME's .....	4		30.76 %
Total Boardings .....	8		

Figure B.5 Courtesy Motorboat Examination Summary.

US Coast Guard Group Monterey  
 Nighttime / Daytime Operations  
 For the Period: 01/01/1980 - 01/01/1988  
 =====

Date: 08/15/1987

Page: 1

SAR Cases:	Occurrences	Percentage Total SAR Cases
	-----	-----
Daytime .....	5	41.67 %
Nighttime .....	7	58.33 %
	=====	
Total SAR Cases .....	12	
Boardings:		
Daytime .....	4	50.00 %
Nighttime .....	4	50.00 %
	=====	
Total Boardings .....	8	

Figure B.6 SAR and Boarding Day/Night Summary.

US Coast Guard Group Monterey  
 EPIC Code Statistical Analysis  
 For Information Collected  
 During the Period: 01/01/1980 - 01/01/1988  
 =====

Date: 08/15/1987

Page: 1

EPIC Lookout Category	EPIC Code Description	Occurrences	Percentage Total EPIC Category
1	In the course of normal operations be on lookout for vessel described, determine course and speed; and notify requesting agency. Do not maintain surveillance. Take no action that would make subject vessel aware of interest.	3	42.86 %
2	In the course of normal operations be on lookout for vessel described, determine course and speed; notify requesting agency. Maintain remote surveillance pending instructions. Take no action that would make subject vessel aware of surveillance.	0	0.00 %
3	In the course of normal operations be on lookout for vessel described. If sighted notify requesting agency, board vessel, and, if evidence supports, seize vessel and arrest persons on board.	3	42.86 %
4	Conduct harbor check for vessel. If found, maintain remote surveillance, notify requesting agency and await further instructions.	1	14.29 %

Figure B.7 EPIC Code Statistical Analysis.

Date: 08/15/1987

Page: 2

EPIC Category	EPIC Code Description	Occurrences	Percentage Total EPIC Category
5	Conduct harbor check, board vessel if located and if evidence supports, seize vessel, arrest persons on board and report to requesting agency.	0	0.00 %
6	Conduct search for vessel in most appropriate area based on information in paragraph 4 of lookout message. If located, notify requesting agency, board vessel, and if evidence supports, seize vessel and arrest persons on board.	0	0.00 %
Total EPIC Occurrences .....		7	

Figure B.7 EPIC Code Statistical Analysis. (cont'd.)

US Coast Guard Group Monterey  
Vessel Intelligence  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* EPIC Code Summary \*\*\*  
=====

Date: 08/15/1987

Page: 1

Vessel Name	Intelligence Date	EPIC CODE
miss alfa	03/01/1983	1
miss alfa	05/05/1985	1
miss cocaine	05/20/1986	1
constance	01/09/1986	3
miss barbs	02/05/1986	3
miss cocaine	06/01/1985	3
miss cannibis	05/18/1985	4

Figure B.8 Summary of EPIC Codes Assigned.

US Coast Guard Group Monterey  
 Immediate Distress Statistics  
 During Period: 01/01/1980 - 01/01/1988  
 =====

Date: 08/15/1987

Page: 1

	Occurrences -----	Percentage Total SAR Cases -----
Non-immediate SAR Cases .....	4	33.33 %
Immediate Distress SAR Cases .....	8	66.67 %
-----		
Total SAR Cases .....	12	

Figure B.9 Immediate Distress Statistics.

US Coast Guard Group Monterey  
Vessel Intelligence  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Intelligence Remarks \*\*\*  
=====

Date: 08/15/1987

Page: 1

Vessel Name	Date of Intelligence	Remarks
constance	01/09/1986	seen in panama carrying a large load of marijuana on the stern
miss alfa	03/01/1983	suspected of smuggling illegal firearms
miss alfa	05/05/1985	vessel seen in Cartegena, Columbia taking on a load of marijuana
miss barbs	02/05/1986	vessel stolen in 01/86 in san francisco, ca suspected of being used in major drug operations
miss cannibis	05/18/1985	vessel stolen in san diego, ca on 04/14/1985
miss cocaine	06/01/1985	vessel suspected of hauling illegal contraband and child pornography armed and dangerous

Figure B.10 Vessel Intelligence Remarks Summary.

US Coast Guard Group Monterey  
 Operator Table Dump  
 For DOB's: 01/01/1920 - 01/01/1945  
 Last Names Beginning - a Ending - z  
 =====

Date: 08/15/1987

Page: 1


allen		, david	g.	
benson		, richard	q.	
cranston		, ralph	s.	
fairbanks		, doug	i.	

Figure B.11 Operator Listing.



US Coast Guard Group Monterey  
Operators of Vessels Summary

Date: 08/15/1987  
Page: 1

Vessel Operator	Operator Address / Telno	Vessel Name / HIN
allen david g. [REDACTED]	[REDACTED]	miss foxtrot 666666666666
allen david g. [REDACTED]	[REDACTED]	miss alfa 111111111111
benson richard q. [REDACTED]	[REDACTED]	unk 222222222222
cranston ralph s. [REDACTED]	[REDACTED]	miss charlie 333333333333
flinstone fred f. [REDACTED]	[REDACTED]	miss alfa 111111111111
flintstone fred f. [REDACTED]	[REDACTED]	miss kilo 999999999999
public john q. [REDACTED]	[REDACTED]	miss cocaine 777777777777
simmons richard d. [REDACTED]	[REDACTED]	miss charlie 333333333333
simmons richard d. [REDACTED]	[REDACTED]	miss echo 555555555555
simpson greg t. [REDACTED]	[REDACTED]	miss delta 444444444444

Figure B.12 Operators of Vessels Summary.

US Coast Guard Group Monterey  
Operator Query Summary Report  
=====

Date: 01/01 1980

Last Name: flinstone  
First Name: fred  
Initial: f




Figure B.13 Operator Query Report.

US Coast Guard Group Monterey  
Owners Table Dump  
For DOB's: 01/01/1940 - 01/01/1960  
Last Names Beginning - a Ending - z  
=====

Date: 08/15/1987

Page: 1

allen		, david		g.
edwards		, george		w.
flintstone		, fred		f.
harris		, sam		k.
williams		, scott		i.



Figure B.14 Owners Listing.

US Coast Guard Group Monterey  
 Owners of Vessels Summary  
 =====

Date: 08/15/1987  
 Page: 1

Vessel Owner	Owner Address / Telno	Vessel Name / HIN
allen david g. [REDACTED]	[REDACTED]	miss alfa 111111111111
benson richard q. [REDACTED]	[REDACTED]	unk 222222222222
cranston ralph s. [REDACTED]	[REDACTED]	miss charlie 333333333333
edwards george w. [REDACTED]	[REDACTED]	miss delta 444444444444
flintstone fred f. [REDACTED]	[REDACTED]	miss kilo 999999999999
harris sam k. [REDACTED]	[REDACTED]	miss foxtrot 666666666666
harris sam k. [REDACTED]	[REDACTED]	miss alfa 111111111111
public john q. [REDACTED]	[REDACTED]	miss cocaine 777777777777
rivera edward w. [REDACTED]	[REDACTED]	unk 222222222222
simmons richard d. [REDACTED]	[REDACTED]	miss echo 555555555555

Figure B.15 Owners of Vessels Summary.

US Coast Guard Group Monterey  
Owner Query Summary Report  
=====

Date: 08/15/1987

Last Name: harris  
First Name: sam  
Initial: k



Figure B.16 Owner Query Report.

US Coast Guard Group Monterey  
 Personnel Intelligence Summary Listing  
 For the Period: 01/01/1980 - 01/01/1988  
 =====

Date: 08/15/1987  
 Page: 1

Last Name	First Name	MI	DOB	Date of Intelligence
allen	david	g.	[REDACTED]	08/08/1984
	suspected of illegal narcotics smuggling considered armed and dangerous			
allen	david	g.	[REDACTED]	03/04/1983
	suspected of being involved in arms smuggling ring considered armed and dangerous			
harris	sam	-	[REDACTED]	02/03/1983
	suspected of possession of stolen vessels			
public	john	g.	[REDACTED]	07/15/1986
	suspected of illegal drug trafficking			
rivera	edward	a.	[REDACTED]	04/06/1986
	suspected of being involved in illegal arms smuggling			
rivera	fernando	w.	[REDACTED]	04/08/1985
	suspected of illegal narcotics smuggling			
rivera	pablo	f.	[REDACTED]	04/06/1986
	armed and dangerous fugitive from prosecution contact FBI upon detention			

Figure B.17 Personnel Intelligence Listing.

US Coast Guard Group Monterey  
Personnel Query Summary Report  
=====

Date: 08/15/1987

Last Name: public  
First Name: John  
Middle Initial: q





Figure B.18 Personnel Query Report.

US Coast Guard Group Monterey  
Personnel Intelligence Information  
=====

Date: 08/15/1987  
Page: 1

DATE OF INTEL	LAST NAME	FIRST NAME	MI	DOB
07/15/1986	public	John	q	
suspected of illegal drug trafficking				

-----

Figure B.19 Personnel Intelligence Report.

US Coast Guard Group Monterey  
Vessel SAR Case Summary Listing  
For the Period: 01/01/1980 - 01/01/1988  
=====

Date: 08/15/1987  
Page: 1

Vessel HIN						
111111111111	01/15/1980	mon	5:00:00a	37.00 N	121.52 W	
FLDR-mry-001	IMMED-y	NOD-taking on water		S/R-	6:00:00a	
UCN-00000001	OFFSHORE-	2 POB-	8	S/S-	7:00:00p	
MUCN-	SEAS-	3 SWLS-	2 WIND DIR-180 SPD-	15	VISDIST-10	
222222222222	02/25/1981	fri	7:30:00p	36.29 N	122.46 W	
FLDR-mry-002	IMMED-n	NOD-mast broke		S/R-	6:00:00a	
UCN-00000002	OFFSHORE-	3 POB-	12	S/S-	7:00:00p	
MUCN-	SEAS-	7 SWLS-	5 WIND DIR-120 SPD-	12	VISDIST- 5	
333333333333	03/18/1983	mon	12:00:00p	36.28 N	123.06 W	
FLDR-mry-003	IMMED-n	NOD-engine stopped		S/R-	6:00:00a	
UCN-00000003	OFFSHORE-	4 POB-	12	S/S-	7:00:00p	
MUCN-	SEAS-	6 SWLS-	8 WIND DIR-270 SPD-	15	VISDIST-10	
444444444444	04/21/1984	fri	10:00:00p	35.20 N	122.15 W	
FLDR-mry-004	IMMED-n	NOD-broken mast		S/R-	6:00:00a	
UCN-00000004	OFFSHORE-	6 POB-	8	S/S-	7:00:00p	
MUCN-	SEAS-	12 SWLS-	15 WIND DIR-220 SPD-	25	VISDIST- 8	
555555555555	05/22/1985	sat	11:12:00p	36.28 N	122.35 W	
FLDR-mry-005	IMMED-y	NOD-taking on water		S/R-	6:00:00a	
UCN-00000005	OFFSHORE-	1 POB-	4	S/S-	7:00:00p	
MUCN-	SEAS-	6 SWLS-	10 WIND DIR-260 SPD-	15	VISDIST- 1	
333333333333	06/15/1985	sat	11:00:00p	36.37 N	121.56 W	
FLDR-mry-010	IMMED-y	NOD-man overboard in surf		S/R-	5:00:00a	
UCN-00000010	OFFSHORE-	1 POB-	5	S/S-	7:30:00p	
MUCN-	SEAS-	2 SWLS-	4 WIND DIR-300 SPD-	5	VISDIST-10	
666666666666	04/16/1986	fri	2:00:00a	36.36 N	121.59 W	
FLDR-mry-012	IMMED-y	NOD-vessel on fire		S/R-	6:00:00a	
UCN-00000012	OFFSHORE-	1 POB-	5	S/S-	7:00:00p	
MUCN-	SEAS-	2 SWLS-	3 WIND DIR-280 SPD-	3	VISDIST-15	
666666666666	06/13/1986	sat	1:00:00p	36.28 N	122.15 W	
FLDR-mry-006	IMMED-y	NOD-fire on board		S/R-	6:00:00a	
UCN-00000006	OFFSHORE-	6 POB-	4	S/S-	7:00:00p	
MUCN-	SEAS-	3 SWLS-	5 WIND DIR-330 SPD-	15	VISDIST-10	

Figure B.20 SAR Listing.

US Coast Guard Group Monterey  
SAR Case Frequency Statistics  
For Months and Years  
01/01/1980 - 12/30/1986  
=====

Date: 08/15/1987  
Page: 1

Month	Total Number SAR Cases	Percentage Total SAR Cases
January .....	1	9.09%
February .....	1	9.09%
March .....	1	9.09%
April .....	2	18.18%
May .....	1	9.09%
June .....	3	27.27%
July .....	1	9.09%
August .....	1	9.09%
September .....	0	0.00%
October .....	0	0.00%
November .....	0	0.00%
December .....	0	0.00%

Year	Total Number SAR Cases
1980 .....	1
1981 .....	1
1982 .....	0
1983 .....	1
1984 .....	2
1985 .....	2
1986 .....	4

Total SAR Cases ..... 11

Figure B.21 SAR Months and Years Frequency Statistics.



US Coast Guard Group Monterey  
SAR Case Day of the Week Frequency  
=====

Date: 08/15/1987  
Page: 1

<u>Day of the Week</u>	<u>SAR Occurrences</u>	<u>Percentage Total SAR Cases</u>
Monday .....	2	16.67 %
Tuesday .....	0	0.00 %
Wednesday .....	0	0.00 %
Thursday .....	0	0.00 %
Friday .....	5	41.67 %
Saturday .....	5	41.67 %
Sunday .....	0	0.00 %

---

Total SAR Cases Evaluated.....	12
-----------------------------------	----

Figure B.22 SAR Day of Week Frequency Statistics.

US Coast Guard Group Monterey  
SAR Case Location Frequency  
For Major Grid Areas  
During Period 01/01/1980 - 01/01/1988  
=====

Total SAR Cases - 12

Date - 08/15/1987

Page - 1

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total SAR Cases
A	37.30	37.00	122.30	123.00	0	0.00 %
B	37.30	37.00	122.00	122.30	0	0.00 %
C	37.00	36.30	123.00	123.30	0	0.00 %
D	37.00	36.30	122.30	123.00	0	0.00 %
E	37.00	36.30	122.00	122.30	0	0.00 %
F	37.00	36.30	121.30	122.00	4	33.33 %
G	36.30	36.00	123.00	123.30	1	8.33 %
H	36.30	36.00	122.30	123.00	2	16.67 %
I	36.30	36.00	122.00	122.30	2	16.67 %
J	36.30	36.00	121.30	122.00	0	0.00 %
K	36.00	35.30	122.30	123.00	0	0.00 %
L	36.00	35.30	122.00	122.30	0	0.00 %
M	36.00	35.30	121.30	122.00	0	0.00 %
N	36.00	35.30	121.00	121.30	0	0.00 %
O	35.30	35.00	122.30	123.00	0	0.00 %
P	35.30	35.00	122.00	122.30	1	8.33 %
Q	35.30	35.00	121.30	122.00	0	0.00 %
R	35.30	35.00	121.00	121.30	1	8.33 %

Figure B.23 Major Grid Area SAR Frequency.

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total SAR Cases
S	35.30	35.00	120.30	121.00	0	0.00 %
T	35.00	34.30	122.00	122.30	0	0.00 %
U	35.00	34.30	121.30	122.00	0	0.00 %
V	35.00	34.30	121.00	121.30	0	0.00 %
W	35.00	34.30	120.30	121.00	0	0.00 %
X	34.30	34.00	121.30	122.00	0	0.00 %
Y	34.30	34.00	121.00	121.30	0	0.00 %

Total SAR Cases in Major Grid Areas.....	11	91.67 %
Total SAR Cases Outside Grid Areas.....	1	8.33 %
Total SAR Cases.....	12	

Figure B.23 Major Grid Area SAR Frequency. (cont'd.)

US Coast Guard Group Monterey  
SAR Case Location Frequency  
For Minor Grid Areas (Coastline)  
During Period 01/01/1980 - 01/01/1988  
=====

Total SAR Cases - 12

Date - 08/15/1987

Page - 1

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total SAR Cases
01	37.10	37.05	122.20	122.25	0	0.00 %
02	37.10	37.05	122.15	122.20	0	0.00 %
03	37.05	37.00	122.20	122.25	0	0.00 %
04	37.05	37.00	122.15	122.20	0	0.00 %
05	37.05	37.00	122.10	122.15	0	0.00 %
06	37.00	36.55	122.15	122.20	0	0.00 %
07	37.00	36.55	122.10	122.15	0	0.00 %
08	37.00	36.55	122.05	122.10	0	0.00 %
09	37.00	36.55	122.00	122.05	0	0.00 %
10	37.00	36.55	121.55	122.00	0	0.00 %
11	37.00	36.55	121.50	121.55	0	0.00 %
12	36.55	36.50	122.00	122.05	0	0.00 %
13	36.55	36.50	121.55	122.00	0	0.00 %
14	36.55	36.50	121.50	121.55	0	0.00 %
15	36.55	36.50	121.45	121.50	0	0.00 %
16	36.50	36.45	122.00	122.05	0	0.00 %
17	36.50	36.45	121.55	122.00	0	0.00 %
18	36.50	36.45	121.50	121.55	1	8.33 %
19	36.50	36.45	121.45	121.50	0	0.00 %

Figure B.24 Minor Grid Area SAR Frequency.

Grid Area Designation	North Boundary	South Boundary	East Boundary	West Boundary	Total Occurrences	Percentage Total SAR Cases
20	36.45	36.40	122.00	122.05	0	0.00 %
21	36.45	36.40	121.55	122.00	0	0.00 %
22	36.45	36.40	121.50	121.55	0	0.00 %
23	36.45	36.40	121.45	121.50	0	0.00 %
24	36.40	36.35	122.00	122.05	0	0.00 %
25	36.40	36.35	121.55	122.00	3	25.00 %
26	36.40	36.35	121.50	121.55	0	0.00 %
27	36.40	36.35	121.45	121.50	0	0.00 %
28	36.35	36.30	121.55	122.05	0	0.00 %
29	36.30	36.25	121.53	122.05	0	0.00 %
30	36.25	36.20	121.52	122.05	0	0.00 %
31	36.20	36.15	121.50	122.05	0	0.00 %
32	36.15	36.00	121.30	122.00	0	0.00 %
33	36.00	35.40	121.15	121.45	0	0.00 %
34	35.40	35.20	120.45	121.30	1	8.33 %
35	35.20	35.00	120.35	121.10	0	0.00 %
36	35.00	34.40	120.35	121.00	0	0.00 %
37	34.40	34.27	120.28	121.00	0	0.00 %

Total SAR Cases in Minor Grid/Coastline Areas.....	5	41.67 %
Total SAR Cases Outside Grid Areas.....	7	58.33 %
Total SAR Cases.....	12	

Figure B.24 Minor Grid Area SAR Frequency. (cont'd.)

# US Coast Guard Group Monterey Vessel SAR History

Date-08/15/1987  
Page- 1

SARDATE	SARTIME	FOLDERNO	VESSEL HIN	UCN	MUCN	POB
01/15/1980	5:00:00a	mry-001	111111111111	00000001		8
	NOD - taking on water			IMMED? - y		
	LAT - 37.00N	LONG - 121.52W		DISTOFF(NM) - 2		
-----						
06/15/1986	11:35:00p	mry-011	111111111111	00000011		4
	NOD - engine stopped			IMMED? - n		
	LAT - 36.39N	LONG - 121.56W		DISTOFF(NM) - 1		
-----						
08/01/1986	2:00:00p	mry-008	111111111111	00000008	00000002	6
	NOD - vessel on fire			IMMED? - y		
	LAT - 36.47N	LONG - 121.52W		DISTOFF(NM) - 2		
-----						

Figure B.46 Vessel Query SAR History.

US Coast Guard Group Monterey  
SAR Case Location Frequency  
For Small Boat OPS Area  
During the Period: 01/01/1980 - 01/01/1988  
=====

Total SAR Cases - 12

Date: 08/15/1987

Page: 1

Area -----	Occurrences -----	Percentage Total SAR Cases -----
Inside Small Boat OPS Area .....	7	58.33 %
Outside Small Boat OPS Area .....	5	41.67 %

-----  
\*\*\* NOTE \*\*\*

The Small Boat OPS Area is defined as the area bounded by  
the following coordinates:

South Boundary -----	North Boundary -----	East Boundary -----	West Boundary -----
36-10 N	36-18 N	121-40 W	122-20 W
36-18	36-37	121-40	122-25
36-37	36-48	121-40	122-30
36-48	36-53	121-40	122-35
36-53	36-57	121-40	122-40
36-57	37-00	121-40	122-45
37-00	37-05	121-40	122-45
37-05	37-10	121-40	122-30

Figure B.26 Small Boat Operations Area SAR Frequency.

US Coast Guard Group Monterey  
 SAR Case Times Summary (in hours)  
 For the Period: 01/01/1980 - 01/01/1988  
 =====

Date: 08/15/1987

Page: 1

Number of Cases Examined -----		Total Unit Time Expended -----	Average Unit Time Expended -----	Maximum Time Expended -----	Minimun Time Expended -----
15	Total Time Expended .....	111.8	7.5	14.5	2.2
15	Total Time to Being on Scene ....	22.7	1.5	3.5	0.6
14	Total Time to Being Alongside Distressed Vessel .	34.7	2.5	11.1	0.8
14	Total Time in Searching for Distressed Vessel .	13.3	0.9	9.3	0.0
11	Total Time in Towing Distressed Vessel .	40.8	3.7	7.5	1.1

Figure B.27 SAR Unit Time Summary.



US Coast Guard Group Monterey  
Boarding Location Frequency  
For Small Boat OPS Area  
During the Period: 01/01/1980 - 01/01/1988  
=====

Total Boardings - 8

Date: 08/15/1987

Page: 1

Area -----	Occurrences -----	Percentage Total Boardings -----
Inside Small Boat OPS Area .....	3	37.50 %
Outside Small Boat OPS Area .....	5	62.50 %

-----  
\*\*\* NOTE \*\*\*

The Small Boat OPS Area is defined as the area bounded by  
the following coordinates:

South Boundary -----	North Boundary -----	East Boundary -----	West Boundary -----
36-10 N	36-18 N	121-40 W	122-20 W
36-18	36-37	121-40	122-25
36-37	36-48	121-40	122-30
36-48	36-53	121-40	122-35
36-53	36-57	121-40	122-40
36-57	37-00	121-40	122-45
37-00	37-05	121-40	122-45
37-05	37-10	121-40	122-30

Figure B.47 Small Boat Operations Area Boarding Frequency.

US Coast Guard Group Monterey  
Vessel Intelligence  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Stolen Vessel List \*\*\*  
=====

Date: 08/15/1987

Page: 1

Vessel Name	Date of Intelligence
miss barbs	02/05/1986
miss cannibis	05/18/1985
miss cocaine	06/01/1985
miss cocaine	05/20/1986
miss everyday	08/08/1985
miss mariposa	05/06/1986

Figure B.29 Stolen Vessel Listing.

US Coast Guard Group Monterey  
Boarding Unsafe Condition Summary  
For the Period: 01/01/1980 - 01/01/1988  
=====

Total Boardings - 8

Date: 08/15/1987

Page: 1

Unsafe Condition -----	Occurrences -----	Percentage of Total Boardings -----
Unsafe Conditions ---		
Terminated Use .....	3	37.50 %
Corrected on the Spot .....	0	0.00 %
Overloaded .....	2	25.00 %
Accumulation of Fuel in Bilges .....	3	37.50 %
Fuel Leak --- Engine or Fuel System .....	2	25.00 %
Manifestly Unsafe Voyage ..	3	37.50 %
Hazardous Bars (13th District) .....	1	12.50 %
Alcohol Condition .....	6	75.00 %
Other .....	1	12.50 %
-----		
Total Unsafe Conditions ...	21	
=====		
Warning Issued .....	4	50.00 %
No Violation Found .....	0	0.00 %

Figure B.30 Boarding Unsafe Condition Summary.

US Coast Guard Group Monterey  
Demographics for Violation --- 54  
Numbering  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Vessel Construction Type \*\*\*  
=====

Date: 08/15/1987

Page: 1

Construction Type	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
open	2	28.57 %	25.00 %
closed	5	71.43 %	62.50 %
unknown	0	0.00 %	0.00 %

Total Occurrences.	7	87.50 %
Total Boardings...	8	

Figure B.31 Violation Summary by Vessel Construction Type.

US Coast Guard Group Monterey  
Demographics for Violation --- 54  
Numbering  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Vessel Engine Compartment Type \*\*\*  
=====

Date: 08/15/1987

Page: 1

Engine Compartment Type	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
open	3	42.86 %	37.50 %
closed	4	57.14 %	50.00 %
unknown	0	0.00 %	0.00 %

Total Occurrences.	7	87.50 %
Total Boardings...	8	

Figure B.32 Violation Summary by Engine Compartment Type.

**US Coast Guard Group Monterey  
Vessel Summary Listing**  
=====

Date: 08/15/1987  
Page: 1

Vessel											
HIN											
111111111111	TYP-1	USE-2	MK-criscraft	MD-supra	YR-1981	TNS- 12					
miss alfa	LEN-	65(ft)	3(in)	VALUE-	\$75,000.00						
11111111	CONST-2	ENG-2	FUEL-1	HULL-3	PROP-2						
-	COLORS: CB-blu DK-brn HL-red TR-wht					SL-unk	SL#-				
34f56	CME-n	YR-	MSTS--	S/S-	H/P-120						
catalina, ca	MRKS-										
-----											
333333333333	TYP-2	USE-1	MK-bayliner	MD-supra	YR-1980	TNS- 12					
miss charlie	LEN-	84(ft)	7(in)	VALUE-	\$45,000.00						
33333333	CONST-2	ENG-2	FUEL-2	HULL-4	PROP-3						
3333333333	COLORS: CB-red DK-blu HL-brn TR-wht					SL-unk	SL#-				
ki3we	CME--	YR-	MSTS-0	S/S-	H/P-170						
monterey, ca	MRKS-										
-----											
777777777777	TYP-1	USE-1	MK-trawler	MD-	YR-1967	TNS- 17					
miss cocaine	LEN-	85(ft)	4(in)	VALUE-	\$25,000.00						
77777777	CONST-2	ENG-2	FUEL-2	HULL-3	PROP-3						
	COLORS: CB-wht DK-wht HL-wht TR-wht					SL-unk	SL#-				
	CME-n	YR-	MSTS-0	S/S-	H/P-250						
moss landing, ca	MRKS-										
-----											
444444444444	TYP-3	USE-2	MK-express	MD-37	YR-1983	TNS- 8					
miss delta	LEN-	37(ft)	4(in)	VALUE-	\$42,000.00						
44444444	CONST-1	ENG-1	FUEL-1	HULL-1	PROP-1						
4444444444	COLORS: CB-wht DK-brn HL-blu TR-wht					SL-brn	SL#-12				
	CME-n	YR-	MSTS-2	S/S-	H/P-40						
moss landing, ca	MRKS-										
-----											
555555555555	TYP-1	USE-2	MK-boston	MD-whaler	YR-1984	TNS- 1					
miss echo	LEN-	23(ft)	3(in)	VALUE-	\$6,000.00						
55555555	CONST-1	ENG-1	FUEL-1	HULL-2	PROP-1						
5555555555	COLORS: CB-unk DK-unk HL-wht TR-blu					SL-unk	SL#-				
	CME--	YR-	MSTS-0	S/S-	H/P-80						
las vegas, nv	MRKS-										

Figure B.33 Vessel Listing.

US Coast Guard Group Monterey  
 Demographics for Violation --- 54  
 Numbering  
 For the Period: 01/01/1980 - 01/01/1988  
 \*\*\* Vessel Fuel Compartment Type \*\*\*  
 =====

Date: 08/15/1987

Page: 1

Fuel Compartment Type	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
-----	-----	-----	-----
open	4	57.14 %	50.00 %
closed	3	42.86 %	37.50 %
unknown	0	0.00 %	0.00 %

-----	-----	-----
Total Occurrences.	7	87.50 %
Total Boardings...	8	

Figure B.34 Violation Summary by Fuel Compartment Type.

US Coast Guard Group Monterey  
Demographics for Violation --- 54  
Numbering  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Vessel Hull Material Type \*\*\*  
=====

Date: 08/15/1987

Page: 1

Hull Material Type	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
-----	-----	-----	-----
wood	1	14.29 %	12.50 %
aluminum	1	14.29 %	12.50 %
steel	3	42.86 %	37.50 %
fiberglass	2	28.57 %	25.00 %
rubber, vinyl	0	0.00 %	0.00 %
cement	0	0.00 %	0.00 %
other	0	0.00 %	0.00 %
unknown	0	0.00 %	0.00 %
-----			
Total Occurrences.	7		87.50 %
Total Boardings...	8		

Figure B.35 Violation Summary by Hull Material Type.

US Coast Guard Group Monterey  
Vessel Intelligence Information  
=====

Date: 08/15/1987  
Page: 1

DATE OF INTEL	VESSEL NAME	EPIC CODE	STOLEN ?
03/01/1983	miss alfa	1	n
suspected of smuggling illegal firearms			

DATE OF INTEL	VESSEL NAME	EPIC CODE	STOLEN ?
05/05/1985	miss alfa	1	n
vessel seen in Cartegena, Columbia taking on a load of marijuana			

Figure B.36 Query Vessel Intelligence History.

US Coast Guard Group Monterey  
Boarding Violation Statistical Summary  
For Period 01/01/1980 - 01/01/1988  
=====

Total Boardings - 8

Date - 08/15/1987

Page - 1

----- Violation -----	Occurrences	Percentage of Total Boardings
-----	-----	-----
Numbering.....	7	87.50 %
Certificate.....	5	62.50 %
Personal Flotation Device...	6	75.00 %
Sound Producing Device.....	5	62.50 %
Bell.....	6	75.00 %
Fire Extinguisher.....	1	12.50 %
Flame Control.....	2	25.00 %
Ventilation.....	2	25.00 %
Navigation Anchor Lights....	3	37.50 %
Negligent Operations.....	1	12.50 %
Failure To Terminate.....	2	25.00 %
Pollution Placard Not Posted	2	25.00 %
Marine Sanitation Devices...	3	37.50 %
Visual Distress Signals.....	3	37.50 %
Document Official Numbers...	7	87.50 %
-----		
Total Violations.....	55	

Figure B.37 Boarding Violation Summary.



US Coast Guard Group Monterey  
Demographics for Violation --- 54  
Numbering  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Vessel Length Profile \*\*\*  
=====

Date: 08/15/1987

Page: 1

Vessel Length (feet)	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
-----	-----	-----	-----
less than 20 .....	0	0.00 %	0.00 %
20 - 29 .....	1	14.29 %	12.50 %
30 - 39 .....	1	14.29 %	12.50 %
40 - 49 .....	1	14.29 %	12.50 %
50 - 59 .....	0	0.00 %	0.00 %
60 - 69 .....	1	14.29 %	12.50 %
70 - 79 .....	0	0.00 %	0.00 %
80 - 89 .....	2	28.57 %	25.00 %
90 - 99 .....	1	14.29 %	12.50 %
100 or greater .....	0	0.00 %	0.00 %
-----			
Total Occurrences.....	7		87.50 %
Total Boardings.....	8		

Figure B.38 Violation Summary by Vessel Length.

US Coast Guard Group Monterey  
 Demographics for Violation --- 54  
 Numbering  
 For the Period: 01/01/1980 - 01/01/1988  
 \*\*\* Vessel Propulsion Type \*\*\*  
 =====

Date: 08/15/1987

Page: 1

Propulsion Type	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
-----	-----	-----	-----
outboard	3	42.86 %	37.50 %
inboard gas	1	14.29 %	12.50 %
inboard diesel	3	42.86 %	37.50 %
inbrd/outbrd	0	0.00 %	0.00 %
jet propelled	0	0.00 %	0.00 %
sail only	0	0.00 %	0.00 %
manual	0	0.00 %	0.00 %
other	0	0.00 %	0.00 %
unknown	0	0.00 %	0.00 %
-----			
Total Occurrences.	7		87.50 %
Total Boardings...	8		

Figure B.39 Violation Summary by Vessel Propulsion Type.

**US Coast Guard Group Monterey  
Vessel Operators Summary Listing**  
=====

Date: 08/15/1987

Page: 1


Vessel Name / HIN	Vessel Operator	Operator Address / Telno
miss alfa 111111111111	flinstone fred f.	
miss alfa 111111111111	allen david g.	
miss charlie 333333333333	simmons richard d.	
miss charlie 333333333333	cranston ralph s.	
miss cocaine 777777777777	public john g.	
miss delta 444444444444	simpson greg t.	
miss echo 555555555555	simmons richard d.	
miss foxtrot 666666666666	williams scott j.	
miss foxtrot 666666666666	allen david g.	
miss kilo 999999999999	flintstone fred f.	

Figure B.40 Vessel Operators Summary Listing.

**US Coast Guard Group Monterey  
Vessel Owners Summary Listing**  
=====

Date: 08/15/1987  
Page: 1


Vessel Name / HIN	Vessel Owner	Owner Address / Telno
miss alfa 111111111111	allen david q.	
miss alfa 111111111111	harris sam k.	
miss charlie 333333333333	cranston ralph s.	
miss cocaine 777777777777	public john q.	
miss delta 444444444444	edwards george w.	
miss echo 555555555555	simmons richard d.	
miss foxtrot 666666666666	harris sam k.	
miss foxtrot 666666666666	williams scott j.	
miss kilo 999999999999	flintstone fred f.	
unk 222222222222	benson richard q.	

Figure B.41 Vessel Owners Summary Listing.

# US Coast Guard Group Monterey Vessel Query Information

NAME - miss alfa	USE - pleasure
HIN - 111111111111	TYPE - open m/b
NO - 11111111	PROPULSION - inboard gas
OFF. NO -	HULL MATERIAL - steel
MAKE - criscraft	ENGINE COMPARTMENT - closed
MODEL - supra	FUEL COMPARTMENT - open
YEAR - 1981	CONSTRUCTION - closed
TONS - 12	SUPERSTRUCTURE DESC -
LEN (ft) - 65	MASTS -
LEN (in) - 3	
HORSEPOWER - 120	COLORS:
HOMEPORT - catalina, ca	HULL - red
CALL SIGN - 34f56	TRIM - wht
VALUE - \$75,000.00	CABIN - blu
CME DECAL - n	DECK - brn
YEAR -	SAIL - unk
	SAIL NUMBER -
UNUSUAL MARKINGS -	

Figure B.42 Query Vessel Information Listing.

US Coast Guard Group Monterey  
Demographics for Violation --- 54  
Numbering  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Vessel Type Profile \*\*\*  
=====

Date: 08/15/1987

Page: 1

Vessel Type	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
open m/b	3	42.86 %	37.50 %
closed m/b	2	28.57 %	25.00 %
sail	2	28.57 %	25.00 %
rowboat	0	0.00 %	0.00 %
canoe/kayak	0	0.00 %	0.00 %
houseboat	0	0.00 %	0.00 %
inflatable	0	0.00 %	0.00 %
other	0	0.00 %	0.00 %
unknown	0	0.00 %	0.00 %
-----			
Total Occurrences....	7		87.50 %
Total Boardings.....	8		

Figure B.43 Violation Summary by Vessel Type.

US Coast Guard Group Monterey  
 Demographics for Violation --- 54  
 Numbering  
 For the Period: 01/01/1980 - 01/01/1988  
 \*\*\* Vessel Use Profile \*\*\*  
 =====

Date: 08/15/1987

Page: 1

Vessel Use	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
commercial	3	42.86 %	37.50 %
pleasure	4	57.14 %	50.00 %
passenger	0	0.00 %	0.00 %
unknown	0	0.00 %	0.00 %
<hr/>			
Total Occurrences.	7		87.50 %
Total Boardings...	8		

Figure B.44 Violation Summary by Vessel Use.

US Coast Guard Group Monterey  
Demographics for Violation --- 54  
Numbering  
For the Period: 01/01/1980 - 01/01/1988  
\*\*\* Vessel Year Profile \*\*\*  
=====

Date: 08/15/1987

Page: 1

Vessel Years	Occurrences	Percentage Total Violation-54	Percentage Total Boardings
-----	-----	-----	-----
earlier than 1960 .....	1	14.29 %	12.50 %
1960 - 1964 .....	0	0.00 %	0.00 %
1965 - 1969 .....	1	14.29 %	12.50 %
1970 - 1974 .....	0	0.00 %	0.00 %
1975 - 1979 .....	0	0.00 %	0.00 %
1980 - 1984 .....	5	71.43 %	62.50 %
1985 - 1989 .....	0	0.00 %	0.00 %
1990 - 1994 .....	0	0.00 %	0.00 %
1995 - 1999 .....	0	0.00 %	0.00 %
2000 or later .....	0	0.00 %	0.00 %
-----			
Total Occurrences.....	7		0.00 %
Total Boardings.....	8		

Figure B.45 Violation Summary by Vessel Year.



**TABLE 3**  
**FIGURE - PROGRAM CORRESPONDENCE**

FIGURE NUMBER	REPORT NAME
B.1	boarding
B.2	bomajor
B.3	bominor
B.4	boqprn
B.5	cmerpt
B.6	daynight
B.7	epicrpt
B.8	epicsum
B.9	immedsar
B.10	intelsum
B.11	operator
B.12	opervsls
B.13	opqprn
B.14	owners
B.15	ownvsls
B.16	owqprn
B.17	perintel
B.18	perqprn
B.19	pintqprn
B.20	sar
B.21	sardates
B.22	sardays
B.23	sarmajor
B.24	sarminor
B.46	sarqprn
B.26	sarsmbt
B.27	sartimes
B.28	smboatrpt
B.29	stolesum
B.30	unsfreq
B.31	vconstmo
B.32	vengmo
B.33	vessel
B.34	vfuelmo
B.35	vhullmo
B.36	vintqprn
B.37	violfreq
B.38	vlenftmo
B.39	vpropmo
B.40	vsloper
B.41	vslowner
B.42	vslqprn
B.43	vtypemo
B.44	vusemo
B.45	vyearmo

## **APPENDIX C**

### **SARELTIS PHYSICAL STRUCTURE**

The physical structure of SARELTIS is presented in this appendix through various types of database documentation. This documentation includes the following:

- Menu Hierarchy Charts (Figure C.1 through Figure C.11)
- A listing of all current Tables
- A listing of all current Report Formats
- A listing of all current Entry/Edit Forms
- Database Table Compositions
- A listing of Reports and Associated Tables
- A listing of Database Attributes sorted by Attribute Name
- A listing of Database Attributes sorted by Input Source
- A listing of Database Attributes sorted by Program Where Used
- A listing of Variables sorted by Variable Name
- A listing of Variables sorted by Program Where Used
- A listing of the Data Entry / Edit Rules




Figure C.1 SARELTIS Menu Hierarchy Chart.




Figure C.2 Input Menu Hierarchy Chart.




Figure C.3 Modify Menu Hierarchy Chart.




Figure C.4 Query Menu Hierarchy Chart.




Figure C.5 Reports Master Menu Hierarchy Chart.




Figure C.6 Intelligence Reports Menu Hierarchy Chart.






Figure C.7 Boarding Reports Menu Hierarchy Chart.




Figure C.8 SAR Reports Menu Hierarchy Chart.




Figure C.9 Vessel Reports Menu Hierarchy Chart.




Figure C.10 Personnel Reports Menu Hierarchy Chart.




Figure C.11 Utilities Menu Hierarchy Chart.

**US COAST GUARD GROUP MONTEREY**  
**SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES**  
**INTELLIGENCE SYSTEM (SARELTIS) DATABASE**

*Tables*

BOARDING	BOATPROP	BOATTYPE	BOATUSE
COLORS	CONSTR	COURSES	DATADICT
DAYS	DISTRICT	ENGCOMP	EPIC
FORMS	FUELCOMP	HULLMAT	MAJAREA
MINAREA	NATIONS	OPERATOR	OPOWN
OPVSL	OWNERS	OWVSL	PERINTEL
RULES	REPORTS	SAR	SARUNITS
STATES	STATUS	VARDICT	VESSEL
VIOLS	VSLINTEL		

*Reports*

BOARDING	BOMAJOR	BOMINOR	BOOPRN
CMERPT	DATADICT	DAYNIGHT	EPICRPT
EPICSUM	IMMEDSAR	INTELSUM	OPERATOR
OPERVSL	OPOPRN	OWNERS	OWNVSL
OWQPRN	PERINTEL	PEROPRN	PINTOPRN
SAR	SARDATES	SARDAYS	SARMAJOR
SARMINOR	SAROPRN	SARSBMT	SARTIMES
SMBOATRP	STOLESUM	UNSFREQ	VARDICT
VCONSTMO	VENGMO	VESSEL	VFUELMO
VHULLMO	VINTOPRN	VIOLFREQ	VLENFTMO
VPROPMO	VSLOPER	VSLOWNER	VSLQPRN
VTYPEMO	VUSEMO	VYEARMO	

*Forms*

BOMOD1	BOMOD2	BOMOD3	BRDOQUERY
CG4100A1	CG4100A2	CG4100A3	CG4100A4
CG4100A5	CG4100A6	CG4100A7	CG4100A8
CG4100A9	DATADICT	HINQUERY	MAJAREA
MINAREA	OPERM0D1	OPERM0D2	OPOQUERY
OWNOQUERY	OWNRMOD1	OWNRMOD2	OWOPFORM
PEROQUER1	PEROQUER2	PINTFORM	PINTOQUER
SARFORM1	SARFORM2	SARFORM3	SARFORM4
SARFORM5	SARFORM6	SARFORM7	SARFORM8
SARFORM9	SARMOD	SAROQUERY	SBDFORM1
SUNITMOD	VARDICT	VHINFORM	VINTFORM
VINTOQUER	VIOLS	VSLMOD1	VSLMOD2
VSLQUERY			

### Composition of Database Tables

Table: datadict  
Read Password: NO  
Modify Password: YES

#### Column definitions

#	Name	Type	Length	Key
1	attname	TEXT	8 characters	yes
2	relname	TEXT	8 characters	yes
3	type	TEXT	7 characters	
4	length	TEXT	3 characters	
5	attdesc	TEXT	40 characters	
6	source	TEXT	15 characters	

Table: operator  
Read Password: NO  
Modify Password: NO

#### Column definitions

#	Name	Type	Length	Key
1	oplname	TEXT	20 characters	yes
2	opfname	TEXT	15 characters	yes
3	opmi	TEXT	1 characters	
4	opaddr	TEXT	25 characters	
5	opcity	TEXT	18 characters	
6	opstate	TEXT	2 characters	
7	opzip	TEXT	9 characters	
8	optelno	TEXT	12 characters	
9	opdob	DATE	1 value(s)	yes
10	opcouse	TEXT	1 characters	
11	opid	INTEGER	1 value(s)	yes

Table: opvsl  
Read Password: NO  
Modify Password: NO

#### Column definitions

#	Name	Type	Length	Key
1	vhinoper	TEXT	12 characters	yes
2	idoper	INTEGER	1 value(s)	yes

Table: owners  
Read Password: NO  
Modify Password: NO

#### Column definitions

#	Name	Type	Length	Key
1	ownlname	TEXT	20 characters	yes
2	ownfname	TEXT	15 characters	yes
3	ownmi	TEXT	1 characters	
4	ownaddr	TEXT	25 characters	
5	owncity	TEXT	18 characters	
6	ownstate	TEXT	2 characters	
7	ownzip	TEXT	9 characters	
8	owntelno	TEXT	12 characters	
9	owndob	DATE	1 value(s)	yes
10	ownid	INTEGER	1 value(s)	yes

Table: owvsl  
 Read Password: NO  
 Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	vhinown	TEXT	12 characters	yes
2	idowner	INTEGER	1 value(s)	yes

Table: perintel  
 Read Password: NO  
 Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	intlname	TEXT	20 characters	yes
2	incdob	DATE	1 value(s)	yes
3	pintrem1	TEXT	70 characters	
4	pintrem2	TEXT	70 characters	
5	pintrem3	TEXT	70 characters	
6	pintdate	DATE	1 value(s)	
7	intfname	TEXT	15 characters	
8	intmi	TEXT	1 characters	

Table: sar  
 Read Password: NO  
 Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	folderno	TEXT	7 characters	yes
2	uch	TEXT	8 characters	yes
3	mucn	TEXT	8 characters	
4	sardate	DATE	1 value(s)	yes
5	sarday	TEXT	3 characters	
6	sartime	TIME	1 value(s)	
7	ssunrise	TIME	1 value(s)	
8	ssunset	TIME	1 value(s)	
9	sarnod	TEXT	25 characters	
10	sarpob	INTEGER	1 value(s)	
11	sarvhin	TEXT	12 characters	yes
12	sarlat	REAL	1 value(s)	
13	sarlong	REAL	1 value(s)	
14	offshore	INTEGER	1 value(s)	
15	immedsar	TEXT	1 characters	
16	winddir	INTEGER	1 value(s)	

Column definitions

#	Name	Type	Length	Key
17	windspd	INTEGER	1 value(s)	
18	visdist	INTEGER	1 value(s)	
19	clouds	INTEGER	1 value(s)	
20	ceiling	INTEGER	1 value(s)	
21	seas	INTEGER	1 value(s)	
22	swells	INTEGER	1 value(s)	



Table: vslintel  
 Read Password: NO  
 Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	intvname	TEXT	17 characters	yes
2	intdate	DATE	1 value(s)	
3	epiccode	TEXT	1 characters	
4	stolen	TEXT	1 characters	
5	vremark1	TEXT	70 characters	
6	vremark2	TEXT	70 characters	
7	vremark3	TEXT	70 characters	

Table: vessel  
 Read Password: NO  
 Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	vslno	TEXT	8 characters	
2	vslname	TEXT	17 characters	yes
3	vslhin	TEXT	12 characters	yes
4	vslmake	TEXT	10 characters	
5	vslmodel	TEXT	10 characters	
6	vslyear	TEXT	4 characters	
7	vsltons	INTEGER	1 value(s)	
8	vslenft	INTEGER	1 value(s)	
9	vslenin	INTEGER	1 value(s)	
10	vslhp	TEXT	3 characters	
11	vsluse	TEXT	2 characters	
12	vsltype	TEXT	2 characters	
13	vslprop	TEXT	1 characters	
14	vslhull	TEXT	1 characters	
15	vsleng	TEXT	1 characters	
16	vslfuel	TEXT	1 characters	

Column definitions

#	Name	Type	Length	Key
17	vslconst	TEXT	1 characters	
18	cmedecal	TEXT	1 characters	
19	cmeyear	TEXT	4 characters	
20	vslloffno	TEXT	10 characters	
21	homeport	TEXT	25 characters	
22	vslcall	TEXT	12 characters	
23	vslvalue	DOLLAR	1 value(s)	
24	vslsuper	TEXT	12 characters	
25	vslmasts	TEXT	1 characters	
26	sailno	TEXT	8 characters	
27	hlcolor	TEXT	3 characters	
28	trcolor	TEXT	3 characters	
29	slcolor	TEXT	3 characters	
30	cbcolor	TEXT	3 characters	
31	dkcolor	TEXT	3 characters	
32	vslmarks	TEXT	40 characters	

Table: boarding  
 Read Password: NO  
 Modify Password: NO

Column definitions				
#	Name	Type	Length	Key
1	bodate	DATE	1 value(s)	
2	botime	TIME	1 value(s)	
3	bono	TEXT	7 characters	yes
4	vslpob	INTEGER	1 value(s)	
5	adultpfd	INTEGER	1 value(s)	
6	childpfd	INTEGER	1 value(s)	
7	owstatus	TEXT	1 characters	
8	obsbody	TEXT	15 characters	
9	obscount	TEXT	15 characters	
10	obscity	TEXT	13 characters	
11	obsstate	TEXT	2 characters	
12	obslat	REAL	1 value(s)	
13	obslong	REAL	1 value(s)	
14	viol54	TEXT	1 characters	
15	viol55	TEXT	1 characters	
16	viol56	TEXT	1 characters	

Column definitions				
#	Name	Type	Length	Key
17	viol57	TEXT	1 characters	
18	viol58	TEXT	1 characters	
19	viol59	TEXT	1 characters	
20	viol60	TEXT	1 characters	
21	viol61	TEXT	1 characters	
22	viol62	TEXT	1 characters	
23	viol63	TEXT	1 characters	
24	viol64	TEXT	1 characters	
25	viol65	TEXT	1 characters	
26	viol66	TEXT	1 characters	
27	viol67	TEXT	1 characters	
28	viol68	TEXT	1 characters	
29	uns69	TEXT	1 characters	
30	uns70	TEXT	1 characters	
31	uns71	TEXT	1 characters	
32	uns72	TEXT	1 characters	

Column definitions				
#	Name	Type	Length	Key
33	uns73	TEXT	1 characters	
34	uns74	TEXT	1 characters	
35	uns75	TEXT	1 characters	
36	uns76	TEXT	1 characters	
37	uns77	TEXT	1 characters	
38	uns78	TEXT	1 characters	
39	uns79	TEXT	1 characters	
40	borem1	TEXT	70 characters	
41	borem2	TEXT	70 characters	
42	borem3	TEXT	70 characters	
43	boname	TEXT	25 characters	
44	borate	TEXT	5 characters	
45	bounit	TEXT	25 characters	
46	bodist	TEXT	2 characters	
47	boopfacc	TEXT	5 characters	
48	boday	TEXT	3 characters	

Column definitions				
#	Name	Type	Length	Key
49	bsunrise	TIME	1 value(s)	
50	bsunset	TIME	1 value(s)	
51	bovhin	TEXT	12 characters	yes
52	weapons	INTEGER	1 value(s)	

Table: forms  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	fname	TEXT	8 characters	yes
2	fdata	TEXT	80 characters	

Table: reports  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	rname	TEXT	8 characters	yes
2	rdata	TEXT	132 characters	

Table: states  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	abbrev	TEXT	2 characters	yes

Table: colors  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	shade	TEXT	3 characters	yes
2	clrdesc	TEXT	20 characters	

Table: days  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	dayabbr	TEXT	3 characters	yes

Table: constr  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	constype	TEXT	1 characters	yes
2	consdesc	TEXT	10 characters	

Table: engcomp  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	ecomptyp	TEXT	1 characters	yes
2	ecompdcs	TEXT	10 characters	

Table: fuelcomp  
Read Password: NO  
Modify Password: YES

Column definitions			
#	Name	Type	Length
1	fcomptyp	TEXT	1 characters
2	fcompdes	TEXT	10 characters

Key  
yes

Table: hullmat  
Read Password: NO  
Modify Password: YES

Column definitions			
#	Name	Type	Length
1	hmattype	TEXT	1 characters
2	hmatdesc	TEXT	15 characters

Key  
yes

Table: boattype  
Read Password: NO  
Modify Password: YES

Column definitions			
#	Name	Type	Length
1	vtype	TEXT	2 characters
2	vtypedes	TEXT	15 characters

Key  
yes

Table: boatuse  
Read Password: NO  
Modify Password: YES

Column definitions			
#	Name	Type	Length
1	vuse	TEXT	2 characters
2	vusedesc	TEXT	15 characters

Key  
yes

Table: boatprop  
Read Password: NO  
Modify Password: YES

Column definitions			
#	Name	Type	Length
1	proptype	TEXT	1 characters
2	propdesc	TEXT	15 characters

Key  
yes

Table: status  
Read Password: NO  
Modify Password: YES

Column definitions			
#	Name	Type	Length
1	ostattyp	TEXT	1 characters
2	ostatdes	TEXT	30 characters

Key  
yes

Table: courses  
 Read Password: NO  
 Modify Password: YES

Column definitions				
#	Name	Type	Length	Key
1	coursestp	TEXT	1 characters	yes
2	coursede	TEXT	15 characters	

Table: majarea  
 Read Password: NO  
 Modify Password: YES

Column definitions				
#	Name	Type	Length	Key
1	majgrid	TEXT	2 characters	yes
2	majnorth	REAL	1 value(s)	
3	majsouth	REAL	1 value(s)	
4	majeast	REAL	1 value(s)	
5	majwest	REAL	1 value(s)	

Table: nations  
 Read Password: NO  
 Modify Password: YES

Column definitions				
#	Name	Type	Length	Key
1	symbol	TEXT	2 characters	yes
2	registry	TEXT	30 characters	

Table: minarea  
 Read Password: NO  
 Modify Password: YES

Column definitions				
#	Name	Type	Length	Key
1	mingrid	TEXT	2 characters	yes
2	minnorth	REAL	1 value(s)	
3	minsouth	REAL	1 value(s)	
4	mineast	REAL	1 value(s)	
5	minwest	REAL	1 value(s)	

Table: epic  
 Read Password: NO  
 Modify Password: YES

Column definitions				
#	Name	Type	Length	Key
1	epicno	TEXT	1 characters	yes
2	epicdsc1	TEXT	70 characters	
3	epicdsc2	TEXT	70 characters	
4	epicdsc3	TEXT	70 characters	
5	epicdsc4	TEXT	70 characters	

Table: rules  
 Read Password: NO  
 Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	numrule	INTEGER	1 value(s)	
2	and/or	TEXT	4 characters	
3	colname1	TEXT	8 characters	
4	table1	TEXT	8 characters	
5	boolean	TEXT	4 characters	
6	colname2	TEXT	8 characters	
7	table2	TEXT	8 characters	
8	rulvalue	TEXT	40 characters	

Table: district  
 Read Password: NO  
 Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	distno	TEXT	2 characters	
2	distdesc	TEXT	35 characters	

Table: sarunits  
 Read Password: NO  
 Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	foldno	TEXT	7 characters	yes
2	unitname	TEXT	25 characters	
3	uwtime	TIME	1 value(s)	
4	uodate	DATE	1 value(s)	
5	oseta	TIME	1 value(s)	
6	etadate	DATE	1 value(s)	
7	ostime	TIME	1 value(s)	
8	osdate	DATE	1 value(s)	
9	alangtime	TIME	1 value(s)	
10	alangdate	DATE	1 value(s)	
11	towtime	TIME	1 value(s)	
12	towdate	DATE	1 value(s)	
13	dvmooored	TIME	1 value(s)	
14	dvmdate	DATE	1 value(s)	
15	sutmoor	TIME	1 value(s)	
16	sutdate	DATE	1 value(s)	

Table: viols  
 Read Password: NO  
 Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	violno	TEXT	2 characters	
2	violdesc	TEXT	40 characters	

Table: opown  
Read Password: NO  
Modify Password: NO

Column definitions

#	Name	Type	Length	Key
1	ownno	INTEGER	1 value(s)	
2	opno	INTEGER	1 value(s)	

Table: vardict  
Read Password: NO  
Modify Password: YES

Column definitions

#	Name	Type	Length	Key
1	varname	TEXT	8 characters	yes
2	vartype	TEXT	8 characters	
3	varuse	TEXT	12 characters	yes
4	vardesc	TEXT	25 characters	

# *Report Format and Associated Table*

REPORT NAME	ASSOCIATED TABLE
BOARDING	BOSUM
BOMAJOR	POSITFRQ
BOMINOR	POSITFRQ
BOOPRN	BOHIS
CMERPT	TEMP
DATADICT	DATADICT
DAYNIGHT	TEMP
EPICRPT	EPICTMP
EPICSUM	EPICSUM
IMMEDSAR	TEMP
INTELSUM	INTELSUM
OPERATOR	OPSUM2
OPERSVLS	OPERSVLS
OPOPRN	TEMP
OWNERS	OWNSUM2
OWNVSL	OWNVSL
OWOPRN	TEMP
PERINTEL	PERSUM
PEROPRN	TEMP
PINTQPRN	PERINT
SAR	SARSUM
SARDATES	SARSTAT
SARDAYS	TEMP
SARMAJOR	POSITFRQ
SARMINOR	POSITFRQ
SAROPRN	SARHIS
SARSMBT	TEMP
SARTIMES	TEMP
SMBOATRP	TEMP
STOLESUM	STOLESUM
UNSFREQ	TEMP
VARDICT	VARDICT
VCONSTMO	SUMMARY3
VENGMO	SUMMARY4
VESSEL	VLSUM
VFUELMO	SUMMARY5
VHULLMO	SUMMARY6
VINTOPRN	VSLINT
VIOLFREQ	TEMP
VLENFTMO	TEMP
VPROPMO	SUMMARY7
VSLOPER	OPERSVLS
VSLOWNER	OWNVSL
VSLOPRN	TEMP
VTYPEMO	SUMMARY1
VUSEMO	SUMMARY2
VYEARMO	TEMP



*Database Attributes Sorted by Attribute Name*

AttName	RelName	Type	Len	Attribute Description
abbrev	states	text	2	state abbreviation
adultpfd	boarding	integer		number of adult pfd's on board
	bosum			
alngdate	sartime3	date		date alongside distressed vessel
	sartime4			
	sarunits			
alngtime	sartime3	time		alongside time of sar unit
	sartime4			
	sarunits			
and/or	rules	text	4	and/or conjunction in editing rules
attdesc	datadict	text	40	attribute description
attname	datadict	text	8	data dictionary attribute name
bodate	boarding	date		date of boarding
	bohis			
	bosum			
	violsum			
boday	boarding	text	3	boarding day of week
	bosum			
bodist	boarding	text	2	boarding officer district
	bosum			
boname	boarding	text	25	boarding officer name
	bohis			
	bosum			
bono	boarding	text	7	boarding report number
	bohis			
	bosum			
	bovslsum			
	frqchart			
	violsum			
	vslmo			
boolean	rules	text	4	boolean conjunction used in edit rule
boopfac	boarding	text	5	boarding unit operating facility code
	bosum			
borate	boarding	text	5	boarding officer rank/rate
	bohis			
	bosum			
borem1	boarding	text	70	boarding officer remarks
	bohis			
	bosum			
borem2	boarding	text	70	boarding officer remarks
	bohis			
	bosum			
borem3	boarding	text	70	boarding officer remarks
	bohis			
	bosum			
botime	boarding	time		time of boarding
	bohis			
	bosum			
	bosum			
bounit	boarding	text	25	boarding officer unit
	bosum			
bovhin	boarding	text	12	vessel hull identification number
	bohis			
	bosum			
	bovslsum			
	violsum			
bsunrise	boarding	time		time of sunrise
	bosum			
bsunset	boarding	time		time of sunset
	bosum			

AttName	RelName	Type	Len	Attribute Description
cbcolor	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	3	vessel cabin color
ceiling	sar sarsum	integer		on scene ceiling in feet
childpfd	boarding bosum	integer		number of child pfd's on board
clouds	sar sarsum	integer		on scene cloud coverage in tenths
clrdesc	colors	text	20	color abbreviation description
cmedecal	bovslsum opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	1	y or n for cme decal displayed
cmeyear	bovslsum opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	4	year of cme decal displayed
colname1	rules	text	8	column name used in editing rule
colname2	rules	text	8	column used in editing rule
consdesc	constr	text	10	vessel construction code description
constdes	summary3	text	10	vessel construction code description
constype	constr	text	1	vessel construction code
counter	summary1	integer		vessel type counter
coursede	courses	text	15	course description
coursetp	courses	text	1	course type code
dayabbr	days	text	3	day abbreviation
descprop	summary6	text	15	vessel propulsion description
distdesc	district	text	35	district number description
distno	district	text	2	district number code
dkcolor	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	3	vessel deck color
dvmdate	sartime5 sarunits	date		date distressed vessel moored
dvmmoored	sartime5 sarunits	time		time distressed vessel moored
ecnumber	epictmp	integer		count of total epic codes
ecomptes	engcomp	text	10	vessel engine compartment description
ecomptyp	engcomp	text	1	vessel engine compartment code
ecpct	epictmp	real		individual epic code percentage
engdesc	summary4	text	10	vessel engine compartment description

AttName	RelName	Type	Len	Attribute Description
epiccode	epicsum epictmpl vslint vslintel	text	1	epic code
epicdsc1	epic epictmp epictmp2	text	70	description of epic code
epicdsc2	epic epictmp epictmp2	text	70	epic code description
epicdsc3	epic epictmp epictmp2	text	70	epic code description
epicdsc4	epic epictmp epictmp2	text	70	epic code description
epicno	epic epictmp epictmp2	text	1	epic code number
etadate	sarunits	date		date of estimated arrival
fcompdes	fuelcomp	text	10	vessel fuel compartment description
fcomptyp	fuelcomp	text	1	vessel fuel compartment code
fdata	forms	text	80	forms data
fname	forms	text	8	form name
folderno	sar	text	7	sar folder number
	sarhis sarsum sarsum1			
foldno	sartime1 sartime2 sartime3 sartime4 sartime5 sarunits	text	7	sar folder number
freqcnt	positfrq positfrq	integer		major grid counter
fueldesc	summary5	text	10	vessel fuel compartment description
gridpct	positfrq	real		major grid percentage
hlcolor	positfrq opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	3	vessel hull color
hmatdesc	hullmat	text	15	vessel hull material description
hmattype	hullmat	text	1	vessel hull material code
homeport	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	25	vessel homeport
hulldesc	summary6	text	15	vessel hull material description
idoper	opvsl opvsls1 opvsls2 pvsljoin vslsopr	integer		operator identification number (system)

AttName	RelName	Type	Len	Attribute Description
idowner	ownvsls1 ownvsls2 owvsl vslsown wvsljoin	integer		owner identification number (system)
inmedsar	sar sarhis sarsum sarsum	text	1	y or n vessel in immediate danger
intdate	epicsum epictmpl stolesum vslint vslintel	date		date intelligence received/entered
intdob	perint perintel persum	date		date of birth of person
intfname	perint perintel persum	text	15	first name of person
intlname	perint perintel persum	text	20	last name of person
intmi	perint perintel persum	text	1	middle initial of person
intvdate	intelsum	date		date intelligence received/entered
intvname	epicsum intelsum stolesum vslint vslintel	text	17	vessel name
length	datadict	text	3	data dictionary attribute length
majeast	majarea	real		eastern bound of major grid
majgrid	positfrq majarea	text	2	designation of major grid area
majnorth	positfrq majarea	real		northern bound of major grid
majsouth	positfrq majarea	real		southern bound of major grid
majwest	positfrq majarea	real		western bound of major area
mineast	positfrq minarea	real		eastern bound of minor grid
mingrid	positfrq minarea	text	2	designation of minor grid area
minnorth	positfrq minarea	real		northern bound of minor grid
minsouth	positfrq minarea	real		southern bound of minor grid
minwest	positfrq minarea	real		western bound of minor grid
mucn	sar sarhis sarsum	text	8	multi-unit case number
numconst	summary3	integer		vessel construction counter
numeng	summary4	integer		vessel engine compartment counter
numfuel	summary5	integer		vessel fuel compartment counter
numhull	summary6	integer		vessel hull material counter
numprop	summary7	integer		vessel propulsion counter
numrule	rules	integer		number of input editing rule
numuse	summary2	integer		vessel use counter

AttName	RelName	Type	Len	Attribute Description
obsbody	boarding	text	15	body of water that boarding occurred
obscity	bosum boarding	text	13	city that boarding occurred
obscount	bosum boarding	text	15	county that boarding occurred
obslat	bosum boarding	real	2.3	latitude where boarding occurred
obslong	bhis bosum boarding	real	3.3	longitude where boarding occurred
obsstate	bhis bosum boarding	text	2	coded state abbrev that boarding occurs
offshore	bosum sar	integer		distance in nm offshore
opaddr	sarhis sarsum operator	text	25	operator street address
opcity	opervsls opsum1 opsum2 opvsls1 opvsls2 operator	text	18	operator city address
opcourse	opervsls opsum1 opsum2 opvsls1 opvsls2 operator	text	1	coded operator courses
opdob	opsum1 opsum2 opvsls1 opvsls2 operator	date		operator date of birth
opfname	opervsls opsum1 opsum2 opvsls1 opvsls2 operator	text	15	operator first name
opid	opervsls opsum1 opsum2 opvsls1 opvsls2 operator	integer		operator identification number (system)
oplname	opsum1 opsum2 opvsls1 opvsls2 operator	text	20	operator last name
opmi	opervsls opsum1 opsum2 opvsls1 opvsls2 operator	text	1	operator middle initial
opno	opsum1 opsum2 opvsls1 opvsls2 opown	integer		operator identification number (system)

AttName	RelName	Type	Len	Attribute Description
opstate	operator opervsls opsum1 opsum2 opvsls1 opvsls2	text	2	coded operator state abbrev.
optelno	operator opervsls opsum1 opsum2 opvsls1 opvsls2	text	12	operator telephone number
opzip	operator opervsls opsum1 opsum2 opvsls1 opvsls2	text	9	operator zip code address
osdate	sartime1 sartime4 sarunits	date		date on-scene
oseta	sarunits	time		on scene eta of sar unit
ostatdes	status	text	30	owner status description
ostattyp	status	text	1	owner status code
ostime	sartime1 sartime4 sarunits	time		on scene time of sar unit
ownaddr	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	25	owner street address
owncity	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	18	owner city address
owndob	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	date		owner date of birth
ownfname	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	15	owner first name
ownid	owners ownsum1 ownsum2 ownvsls1 ownvsls2	integer		owner identification number (system)
ownlname	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	20	owner last name

AttName	RelName	Type	Len	Attribute Description
ownmi	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	1	owner middle initial
ownno	opown	integer		owner identification number (system)
ownstate	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	2	coded owner state abbreviation address
owntelno	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	12	owner telephone number
ownzip	owners ownsum1 ownsum2 ownvsls ownvsls1 ownvsls2	text	9	owner zip code address
owstatus	boarding bosum	text	1	coded owner status at time of boarding
pctincr	sarstat	real		percentage increase in sar cases
pintdate	perint perinte persum	date		date intelligence received/entered
pintrem1	perint perintel persum	text	70	intelligence remarks on person
pintrem2	perint perintel persum	text	70	intelligence remarks on person
pintrem3	perint perintel persum	text	70	intelligence remarks on person
propdesc	boatprop	text	15	vessel propulsion description
proptype	boatprop	text	1	vessel propulsion code
rdata	reports	text	132	report data
registry	nations	text	30	nation description
relname	datadict	text	8	data dictionary relation name
rname	reports	text	8	report name
rulvalue	rules	text	40	edit error message
sailno	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	8	sail number of vessel
sardate	sar sarhis sarsum sarsum1	date		date of sar
sarday	sar sarsum sarsum1	text	3	sar day of week abbreviated
sarlat	sar sarhis sarsum	real	2.3	latitude position of sar

AttName	RelName	Type	Len	Attribute Description
sarlong	sar sarhis sarsum	real	3.3	longitude position of sar
sarnod	sar sarhis sarsum	text	25	sar nature of distress
sarnum	sarstat	integer		number of sar cases
sarpob	sar sarhis sarsum	integer		number of personnel onboard
sartime	sar sarhis sarsum	time		time sar report received
sarvhin	sar sarhis sarsum	text	12	vessel hull identification number
saryear	sarstat	text	4	year of sar case
seas	sar sarsum	integer		on scene sea height in feet
shade	colors	text	3	color abbreviation
slcolor	opvsls2 ownvsls2 pvs1join vessel vslsum vslsum1 vslsum2 wvsljoin	text	3	vessel sail color
source	datadict	text	15	source document
ssunrise	sar sarsum	time		time of sunrise
ssunset	sar sarsum	time		time of sunset
stolen	epicsum stolesum vslint vslintel	text	1	y or n for vessel stolen
sutdate	sartime2 sarunits	date		date sar unit moored/ returned
sutmoor	sartime2 sarunits	time		time sar unit moored
swells	sar sarsum	integer		on scene swell height in feet
symbol	nations	text	2	nation abbreviation
table1	rules	text	8	table used in editing rule
table2	rules	text	8	table used in editing rule
tmp	temp	text	2	attribute/relation for report printing
towdate	sartime5 sarunits	date		date distressed vessel in tow
towtime	sartime5 sarunits	time		time distressed vessel in tow
trcolor	opvsls2 ownvsls2 pvs1join vessel vslsum vslsum1 vslsum2 wvsljoin	text	3	vessel trim color
type	datadict	text	7	data dictionary attribute type
typedesc	summary1	text	15	vessel type description
uch	sar sarhis sarsum	text	8	unit case number



AttName	RelName	Type	Len	Attribute Description
unitname	sarunits	text	25	sar unit name
uns69	boarding	text	1	'X' if vessel terminated
	bohis			
	bosum			
	frqchart			
	violsum			
uns70	boarding	text	1	'X' if condition corrected on the spot
	bohis			
	bosum			
	frqchart			
	violsum			
uns71	boarding	text	1	'X' if vessel overloaded
	bohis			
	bosum			
	frqchart			
uns72	boarding	text	1	'X' if fuel in bilges
	bohis			
	bosum			
	frqchart			
	violsum			
uns73	boarding	text	1	'X' if fuel leak
	bohis			
	bosum			
	frqchart			
	violsum			
uns74	boarding	text	1	'X' if manifestly unsafe voyage
	bohis			
	bosum			
	frqchart			
	violsum			
uns75	boarding	text	1	'X' if hazardous bars (13th district)
	bohis			
	bosum			
	frqchart			
	violsum			
uns76	boarding	text	1	'X' if operator alcohol condition
	bohis			
	bosum			
	frqchart			
	violsum			
uns77	boarding	text	1	'X' if other unsafe condition
	bohis			
	bosum			
	frqchart			
	violsum			
uns78	boarding	text	1	'X' if warning issued
	bohis			
	bosum			
	frqchart			
	violsum			
uns79	boarding	text	1	'X' if no violations
	bohis			
	bosum			
	frqchart			
	violsum			
usedesc	summary2	text	15	vessel use description
uupdate	sartime1	date		sar unit underway date
	sartime2			
	sartime3			
	sarunits			
uwttime	sartime1	time		underway time of sar unit
	sartime2			
	sartime3			
	sarunits			

AttName	RelName	Type	Len	Attribute Description
vardesc	vardict	text	25	attribute represented or how used
varname	vardict	text	8	name of variable
vartype	vardict	text	8	type of variable
varusel	vardict	text	12	where the variable is used
vhinoper	opvsl	text	12	vessel hull identification
	opvsls1			
	opvsls2			
	pvs1join			
	vslsopr			
vhinown	ownvsls1	text	12	vessel hull identification number
	ownvsls2			
	owvsl			
	vslsown			
	wvsljoin			
viol54	boarding	text	1	'X' if numbering violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol55	boarding	text	1	'X' if certificate violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol56	boarding	text	1	'X' if pfd violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol57	boarding	text	1	'X' if sound producing device violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol58	boarding	text	1	'X' if bell violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol59	boarding	text	1	'X' if fire extinguisher violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol60	boarding	text	1	'X' if flame control violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol61	boarding	text	1	'X' if ventilation violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol62	boarding	text	1	'X' if navigation/anchor lts. violation
	bohis			
	bosum			
	frqchart			
	violsum			
viol63	boarding	text	1	'X' if negligent operation violation
	bohis			
	bosum			
	frqchart			
	violsum			

AttName	RelName	Type	Len	Attribute Description
viol64	boarding bohis bosum frqchart violsum	text	1	'X' if failure to terminate violation
viol65	boarding bohis bosum frqchart violsum	text	1	'X' if pollution placard not posted
viol66	boarding bohis bosum frqchart violsum	text	1	'X' if marine sanitation device violtn.
viol67	boarding bohis bosum frqchart violsum	text	1	'X' if visual distress signal violation
viol68	boarding bohis bosum frqchart violsum	text	1	'X' if document/official no. violation
violdesc	viols	text	40	violation description
violno	viols	text	2	violation number
visdist	sar	integer		visibility distance
vremark1	sarsum intelsum vslint vslintel	text	70	vessel intelligence remarks
vremark2	intelsum vslint vslintel	text	70	vessel intelligence remarks
vremark3	intelsum vslint vslintel	text	70	vessel intelligence remarks
vslcall	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	12	vessel call sign
vslconst	opvsls2 ownvsls2 pvsljoin summary3 vessel violsum vslmo vslsum vslsum1 vslsum2 wvsljoin	text	1	coded vessel construction type

AttName	RelName	Type	Len	Attribute Description
vsleng	opvsls2 ownvsls2 pvsljoin summary4 vessel violsum vslmo vslsum vslsum1 vslsum2 wvsljoin	text	1	coded vessel engine compartment type
vslfuel	opvsls2 ownvsls2 pvsljoin summary5 vessel violsum vslmo vslsum vslsum1 vslsum2 wvsljoin	text	1	coded vessel fuel compartment type
vslhin	bovslsum opervsls opvsls2 ownvsls ownvsls2 pvsljoin vessel violsum vslsum vslsum1 vslsum2 wvsljoin	text	12	vessel hull identification number
vslhp	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	3	vessel horsepower
vslhull	opvsls2 ownvsls2 pvsljoin summary6 vessel violsum vslmo vslsum vslsum1 vslsum2 wvsljoin	text	1	coded vessel hull material
vsllefft	opvsls2 ownvsls2 pvsljoin vessel violsum vslmo vslsum vslsum1 vslsum2 wvsljoin	integer		vessel length in feet

AttName	RelName	Type	Len	Attribute Description
vslilenin	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	integer		vessel length inches
vslmake	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	10	vessel make
vslmarks	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	40	vessel unusual markings
vslmasts	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	1	number of masts on vessel
vslmodel	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	10	vessel model
vslname	opervsls opvsls2 ownvsls ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	17	vessel name
vslno	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	8	vessel number
vslloffno	opvsls2 ownvsls2 pvsljoin vessel vslsum vslsum1 vslsum2 wvsljoin	text	10	vessel official number (main beam no.)

AttName	RelName	Type	Len	Attribute Description
vslpob	boarding	integer		number of personnel on board vessel
	bohis			
	bosum			
vslprop	opvsls2	text	1	coded vessel propulsion method
	ownvsls2			
	pvslljoin			
	summary6			
	vessel			
	violsum			
	vslmo			
	vslsum			
	vslsum1			
	vslsum2			
	wvsljoin			
vslsuper	opvsls2	text	12	vessel superstructure
	ownvsls2			
	pvslljoin			
	vessel			
	vslsum			
	vslsum1			
	vslsum2			
	wvsljoin			
vsltons	opvsls2	integer		vessel net tonnage
	ownvsls2			
	pvslljoin			
	vessel			
	violsum			
	vslsum			
	vslsum1			
	vslsum2			
	wvsljoin			
vsltype	opvsls2	text	2	coded vessel type
	ownvsls2			
	pvslljoin			
	summary1			
	vessel			
	violsum			
	vslmo			
	vslsum			
	vslsum1			
	vslsum2			
	wvsljoin			
vsluse	opvsls2	text	2	coded vessel use
	ownvsls2			
	pvslljoin			
	summary2			
	vessel			
	violsum			
	vslmo			
	vslsum			
	vslsum1			
	vslsum2			
	wvsljoin			
vslvalue	opvsls2	dollar		vessel value
	ownvsls2			
	pvslljoin			
	vessel			
	vslsum			
	vslsum1			
	vslsum2			
	wvsljoin			

AttName	RelName	Type	Len	Attribute Description
vslyear	opvsls2 ownvsls2 pvs1join vessel violsum vslmo vslsum vslsum1 vslsum2 wvsljoin	text	4	vessel model year
vtype	boattype	text	2	vessel type code
vtypedes	boattype	text	15	vessel type description
vuse	boatuse	text	2	vessel use code
vusedesc	boatuse	text	15	vessel use description
weapons	boarding bohis bosum violsum	integer		number of weapons on board
winddir	sar sarsum	integer		wind direction
windspd	sar sarsum	integer		wind speed

*Database Attributes Sorted by Input Source*

Source	AttName	RelName	Type	Len
-----	-----	-----	-----	----
4100	adultpfd	boarding	integer	
	bodate	boarding	date	
	boday	boarding	text	3
	bodist	boarding	text	2
	boname	boarding	text	25
	bono	boarding	text	7
	boopfac	boarding	text	5
	borate	boarding	text	5
	borem1	boarding	text	70
	borem2	boarding	text	70
	borem3	boarding	text	70
	botime	boarding	time	
	bounit	boarding	text	25
	bovhin	boarding	text	12
	bsunrise	boarding	time	
	bsunset	boarding	time	
	childpfd	boarding	integer	
	cmedecal	vessel	text	1
	cmeyear	vessel	text	4
	obsbody	boarding	text	15
	obscity	boarding	text	13
	obscount	boarding	text	15
	obslat	boarding	real	2.3
	obslong	boarding	real	3.3
	obsstate	boarding	text	2
	opaddr	operator	text	25
	opcity	operator	text	18
	opcouse	operator	text	1
	opdob	operator	date	
	opfname	operator	text	15
	oplname	operator	text	20
	opmi	operator	text	1
	opstate	operator	text	2
	optelno	operator	text	12
	opzip	operator	text	9
	ownaddr	owners	text	25
	owncity	owners	text	18
	owndob	owners	date	
	ownfname	owners	text	15
	ownlname	owners	text	20
	ownmi	owners	text	1
	ownstate	owners	text	2
	owntelno	owners	text	12
	ownzip	owners	text	9
	owstatus	boarding	text	1
	uns69	boarding	text	1
	uns70	boarding	text	1
	uns71	boarding	text	1
	uns72	boarding	text	1
	uns73	boarding	text	1
	uns74	boarding	text	1
	uns75	boarding	text	1
	uns76	boarding	text	1
	uns77	boarding	text	1
	uns78	boarding	text	1
	uns79	boarding	text	1
	vhinoper	opvsl	text	12
	vhinown	owvsl	text	12
	viol54	boarding	text	1
	viol55	boarding	text	1
	viol56	boarding	text	1
	viol57	boarding	text	1
	viol58	boarding	text	1
	viol59	boarding	text	1
	viol60	boarding	text	1



Source	AttName	RelName	Type	Len
-----	-----	-----	-----	---
4100	viol61	boarding	text	1
	viol62	boarding	text	1
	viol63	boarding	text	1
	viol64	boarding	text	1
	viol65	boarding	text	1
	viol66	boarding	text	1
	viol67	boarding	text	1
	viol68	boarding	text	1
	vsiconst	vessel	text	1
	vsileng	vessel	text	1
	vsifuel	vessel	text	1
	vsilhin	vessel	text	12
	vsilhp	vessel	text	3
	vsilhull	vessel	text	1
	vsllenft	vessel	integer	
	vsllenin	vessel	integer	
	vsImake	vessel	text	10
	vsImodel	vessel	text	10
	vsIname	vessel	text	17
	vsIno	vessel	text	8
	vsIpob	boarding	integer	
	vsIprop	vessel	text	1
	vsItons	vessel	integer	
	vsItype	vessel	text	2
	vsIuse	vessel	text	2
	vsIyear	vessel	text	4
designer	weapons	boarding	integer	
	abbrev	states	text	2
	and/or	rules	text	4
	attdesc	datadict	text	40
	attname	datadict	text	8
	boolean	rules	text	4
	clrdesc	colors	text	20
	colname1	rules	text	8
	colname2	rules	text	8
	consdesc	constr	text	10
	constype	constr	text	1
	coursede	courses	text	15
	coursetp	courses	text	1
	dayabbr	days	text	3
	distdesc	district	text	35
	distno	district	text	2
	ecomptes	engcomp	text	10
	ecomptyp	engcomp	text	1
	epicdsc1	epic	text	70
	epicdsc2	epic	text	70
	epicdsc3	epic	text	70
	epicdsc4	epic	text	70
	epicno	epic	text	1
	fcompdes	fuelcomp	text	10
	fcomptyp	fuelcomp	text	1
	fdata	forms	text	80
	fname	forms	text	8
	hmatdesc	hullmat	text	15
	hmattyp	hullmat	text	1
	length	datadict	text	3
	majeast	majarea	real	
	majgrid	majarea	text	2
	majnorth	majarea	real	
	majsouth	majarea	real	
	majwest	majarea	real	
	mineast	minarea	real	
	mingrid	minarea	text	2
	minnorth	minarea	real	
	minsouth	minarea	real	

Source	AttName	RelName	Type	Len
-----	-----	-----	-----	---
designer	minwest	minarea	real	
	numrule	rules	integer	
	ostatdes	status	text	30
	oscattp	status	text	1
	propdesc	boatprop	text	15
	proptype	boatprop	text	1
	rdata	reports	text	132
	registry	nations	text	30
	relname	datadict	text	8
	rname	reports	text	8
	rulvalue	rules	text	40
	shade	colors	text	3
	source	datadict	text	15
	symbol	nations	text	2
	table1	rules	text	8
	table2	rules	text	8
	type	datadict	text	7
	vardesc	vardict	text	25
	varname	vardict	text	8
	vartype	vardict	text	8
	varusel	vardict	text	12
	violdesc	viols	text	40
	violno	viols	text	2
	vtype	boatttype	text	2
	vtypedes	boatttype	text	15
	vuse	boatuse	text	2
	vusedesc	boatuse	text	15
numerous	epiccode	vslintel	text	1
	intdate	vslintel	date	
	intdob	perintel	date	
	intfname	perintel	text	15
	intlname	perintel	text	20
	intmi	perintel	text	1
	intvname	vslintel	text	17
	pintdate	perintel	date	
	pintrem1	perintel	text	70
	pintrem2	perintel	text	70
	pintrem3	perintel	text	70
	stolen	vslintel	text	1
	vremark1	vslintel	text	70
	vremark2	vslintel	text	70
	vremark3	vslintel	text	70
ood	ssunrise	sar	time	
	ssunset	sar	time	
sar fold	alngdate	sarunits	date	
	alngtime	sarunits	time	
	cbcolor	vessel	text	3
	ceiling	sar	integer	
	clouds	sar	integer	
	dkcolor	vessel	text	3
	dvmdate	sarunits	date	
	dvmoored	sarunits	time	
	etadate	sarunits	date	
	folderno	sar	text	7
	foldno	sarunits	text	7
	hlcolor	vessel	text	3
	homeport	vessel	text	25
	immedsar	sar	text	1
	mucn	sar	text	8
	offshore	sar	integer	
	osdate	sarunits	date	
	oseta	sarunits	time	
	ostime	sarunits	time	
	sailno	vessel	text	8
	sardate	sar	date	

Source	AttName	RelName	Type	Len
-----	-----	-----	-----	---
sar fold	sarday	sar	text	3
	sarlat	sar	real	2.3
	sarlong	sar	real	3.3
	sarnod	sar	text	25
	sarpob	sar	integer	
	sartime	sar	time	
	sarvhin	sar	text	12
	seas	sar	integer	
	slcolor	vessel	text	3
	sutdate	sarunits	date	
	sutmoor	sarunits	time	
	swells	sar	integer	
	towdate	sarunits	date	
	towtime	sarunits	time	
	trcolor	vessel	text	3
	ucn	sar	text	8
	unitname	sarunits	text	25
	uwnate	sarunits	date	
	uwtime	sarunits	time	
	visdist	sar	integer	
	vslcall	vessel	text	12
	vslmarks	vessel	text	40
	vslmasts	vessel	text	1
	vsloffno	vessel	text	10
	vsisuper	vessel	text	12
	vslvalue	vessel	dollar	
	winddir	sar	integer	
	windspd	sar	integer	
system	idoper	opvsl	integer	
	idowner	owvsl	integer	
	opid	operator	integer	
	opno	opown	integer	
	ownid	owners	integer	
	ownno	opown	integer	

*Database Attributes Sorted by Where Used*

<u>Used In</u>	<u>AttName</u>	<u>RelName</u>	<u>Type</u>	<u>Len</u>
boarding	adultpfd	bosum	integer	
	bodate	bosum	date	
	boday	bosum	text	3
	bodist	bosum	text	2
	boname	bosum	text	25
	bono	bosum	text	7
	boopfac	bosum	text	5
	borate	bosum	text	5
	borem1	bosum	text	70
	borem2	bosum	text	70
	borem3	bosum	text	70
	botime	bosum	text	
	bounit	bosum	text	25
	bovhin	bosum	text	12
	bsunrise	bosum	time	
	bsunset	bosum	time	
	childpfd	bosum	integer	
	obsbody	bosum	text	15
	obscity	bosum	text	13
	obscount	bosum	text	15
	obslat	bosum	real	2.3
	obslong	bosum	real	3.3
	obsstate	bosum	text	2
	owstatus	bosum	text	1
	uns69	bosum	text	1
	uns70	bosum	text	1
	uns72	bosum	text	1
	uns73	bosum	text	1
	uns74	bosum	text	1
	uns75	bosum	text	1
	uns76	bosum	text	1
	uns77	bosum	text	1
	uns78	bosum	text	1
	uns79	bosum	text	1
	viol54	bosum	text	1
	viol55	bosum	text	1
	viol56	bosum	text	1
	viol57	bosum	text	1
	viol58	bosum	text	1
	viol59	bosum	text	1
	viol60	bosum	text	1
	viol61	bosum	text	1
	viol62	bosum	text	1
	viol63	bosum	text	1
	viol64	bosum	text	1
	viol65	bosum	text	1
	viol66	bosum	text	1
	viol67	bosum	text	1
	viol68	bosum	text	1
	vslpob	bosum	integer	
bomajor	weapons	bosum	integer	
	bono	bosum	text	7
	frecnt	positfrq	integer	
	gridpct	positfrq	real	
	majeast	positfrq	real	3.3
	majgrid	positfrq	text	2
	majnorth	positfrq	real	2.3
	majsouth	positfrq	real	2.3
	majwest	positfrq	real	3.3
	obslat	bosum	real	2.3
bominor	obslong	bosum	real	3.3
	bono	bosum	text	7
	frecnt	positfrq	integer	
	gridpct	positfrq	real	
	mineast	positfrq	real	3.3

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
bominor	mingrid	positfrq	text	2
	minnorth	positfrq	real	2.3
	minsouth	positfrq	real	2.3
	minwest	positfrq	real	3.3
	obslat	bosum	real	2.3
cmerpt	obslong	bosum	real	3.3
	bono	bosum	text	7
	bono	bovslsum	text	7
	bovhin	bosum	text	12
	bovhin	bovslsum	text	12
	cmedecal	bovslsum	text	1
	cmedecal	vslsum	text	1
	cmeyear	bovslsum	text	4
	cmeyear	vslsum	text	4
	tmp	temp	text	2
	vslhin	bovslsum	text	12
	vslhin	vslsum	text	12
daynight	bodate	bosum	date	
	botime	bosum	time	
	bsunrise	bosum	time	
	bsunset	bosum	time	
	sardate	sarsum	date	
	sartime	sarsum	time	
	ssunrise	sarsum	time	
	ssunset	sarsum	time	
	tmp	temp	text	2
	ecnumber	epictmp	integer	
	ecpct	epictmp	real	
epicdump	epiccode	epicsum	text	1
	epiccode	epictmp1	text	1
	epicdsc1	epictmp	text	70
	epicdsc1	epictmp2	text	70
	epicdsc2	epictmp	text	70
	epicdsc2	epictmp2	text	70
	epicdsc3	epictmp	text	70
	epicdsc3	epictmp2	text	70
	epicdsc4	epictmp	text	70
	epicdsc4	epictmp2	text	70
	epicno	epictmp	text	1
	epicno	epictmp2	text	1
	intdate	epicsum	date	
	intdate	epictmp1	date	
	intdate	stolesum	date	
	intvdate	intelsum	date	
	intvname	epicsum	text	17
	intvname	intelsum	text	17
	intvname	stolesum	text	17
	stolen	epicsum	text	1
	stolen	stolesum	text	1
	vremark1	intelsum	text	70
	vremark2	intelsum	text	70
	vremark3	intelsum	text	70
immedsar	folderno	sarsum	text	7
	immedsar	sarsum	real	1
	sardate	sarsum	date	
intelrpt	tmp	temp	text	2
	bodate	bosum	date	
	bodate	violsum	date	
	bono	bosum	text	7
	bono	violsum	text	7
	bono	vslmo	text	7
	bovhin	bosum	text	12
	bovhin	violsum	text	12
	constdes	summary3	text	10
	counter	summary1	integer	

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
intelrpt	descprop	summary6	text	15
	engdesc	summary4	text	10
	fueldesc	summary5	text	10
	hulldesc	summary6	text	15
	numconst	summary3	integer	
	numeng	summary4	integer	
	numfuel	summary5	integer	
	numhull	summary6	integer	
	numprop	summary7	integer	
	numuse	summary2	integer	
	tmp	temp	text	2
	typedesc	summary1	text	15
	uns69	bosum	text	1
	uns69	violsum	text	1
	uns70	bosum	text	1
	uns70	violsum	text	1
	uns71	bosum	text	1
	uns72	bosum	text	1
	uns72	violsum	text	1
	uns73	bosum	text	1
	uns73	violsum	text	1
	uns74	bosum	text	1
	uns74	violsum	text	1
	uns75	bosum	text	1
	uns75	violsum	text	1
	uns76	bosum	text	1
	uns76	violsum	text	1
	uns77	bosum	text	1
	uns77	violsum	text	1
	uns78	bosum	text	1
	uns78	violsum	text	1
	uns79	bosum	text	1
	uns79	violsum	text	1
	usedesc	summary2	text	15
	viol54	bosum	text	1
	viol54	violsum	text	1
	viol55	bosum	text	1
	viol55	violsum	text	1
	viol56	bosum	text	1
	viol56	violsum	text	1
	viol57	bosum	text	1
	viol57	violsum	text	1
	viol58	bosum	text	1
	viol58	violsum	text	1
	viol59	bosum	text	1
	viol59	violsum	text	1
	viol60	bosum	text	1
	viol60	violsum	text	1
	viol61	bosum	text	1
	viol61	violsum	text	1
	viol62	bosum	text	1
	viol62	violsum	text	1
	viol63	bosum	text	1
	viol63	violsum	text	1
	viol64	bosum	text	1
	viol64	violsum	text	1
	viol65	bosum	text	1
	viol65	violsum	text	1
	viol66	bosum	text	1
	viol66	violsum	text	1
	viol67	bosum	text	1
	viol67	violsum	text	1
	viol68	bosum	text	1
	viol68	violsum	text	1
	vsiconst	summary3	text	2

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
intelrpt	vslconst	violsum	text	1
	vslconst	vslmo	text	1
	vslconst	vslsum	text	1
	vsleng	summary4	text	1
	vsleng	violsum	text	1
	vsleng	vslmo	text	1
	vsleng	vslsum	text	1
	vslfuel	summary5	text	1
	vslfuel	violsum	text	1
	vslfuel	vslmo	text	1
	vslfuel	vslsum	text	1
	vslhin	violsum	text	12
	vslhin	vslsum	text	12
	vslhull	summary6	text	1
	vslhull	violsum	text	1
	vslhull	vslmo	text	1
	vslhull	vslsum	text	1
	vslilenft	violsum	integer	
	vslilenft	vslmo	integer	
	vslilenft	vslsum	integer	
	vslprop	summary6	text	1
	vslprop	violsum	text	1
	vslprop	vslmo	text	1
	vslprop	vslsum	text	1
	vsltons	violsum	integer	
	vsltons	vslsum	integer	
	vsltype	summary1	text	2
	vsltype	violsum	text	2
	vsltype	vslmo	text	2
	vsltype	vslsum	text	2
	vsluse	summary2	text	2
	vsluse	violsum	text	2
	vsluse	vslmo	text	2
	vsluse	vslsum	text	2
	vslyear	violsum	text	4
	vslyear	vslmo	text	4
	vslyear	vslsum	text	4
	weapons	bosum	integer	
	weapons	violsum	integer	
operator	opaddr	opsum1	text	25
	opaddr	opsum2	text	25
	opcity	opsum1	text	18
	opcity	opsum2	text	18
	opcouse	opsum1	text	1
	opcouse	opsum2	text	1
	opdob	opsum1	date	
	opdob	opsum2	date	
	opfname	opsum1	text	15
	opfname	opsum2	text	15
	opid	opsum1	integer	
	opid	opsum2	integer	
	oplname	opsum1	text	20
	oplname	opsum2	text	20
	opmi	opsum1	text	1
	opmi	opsum2	text	1
	opstate	opsum1	text	2
	opstate	opsum2	text	2
	optelno	opsum1	text	12
	optelno	opsum2	text	12
	opzip	opsum1	text	9
	opzip	opsum2	text	9

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
opervsls	cbcolor	opvsls2	text	3
	cmedecal	opvsls2	text	1
	cmeyear	opvsls2	text	4
	dkcolor	opvsls2	text	3
	hlcolor	opvsls2	text	3
	homeport	opvsls2	text	25
	idoper	opvsls1	integer	
	idoper	opvsls2	integer	
	opaddr	opervsls	text	25
	opaddr	opvsls1	text	25
	opaddr	opvsls2	text	25
	opcity	opervsls	text	18
	opcity	opvsls1	text	18
	opcity	opvsls2	text	18
	opcouse	opvsls1	text	1
	opcouse	opvsls2	text	1
	opdob	opervsls	date	
	opdob	opvsls1	date	
	opdob	opvsls2	date	
	opfname	opervsls	text	15
	opfname	opvsls1	text	15
	opfname	opvsls2	text	15
	opid	opvsls1	integer	
	opid	opvsls2	integer	
	oplname	opervsls	text	20
	oplname	opvsls1	text	20
	oplname	opvsls2	text	20
	opmi	opervsls	text	1
	opmi	opvsls1	text	1
	opmi	opvsls2	text	1
	opstate	opervsls	text	2
	opstate	opvsls1	text	2
	opstate	opvsls2	text	2
	optelno	opervsls	text	12
	optelno	opvsls1	text	12
	optelno	opvsls2	text	12
	opzip	opervsls	text	9
	opzip	opvsls1	text	9
	opzip	opvsls2	text	9
	sailno	opvsls2	text	8
	slcolor	opvsls2	text	3
	trcolor	opvsls2	text	3
	vhinoper	opvsls1	text	12
	vhinoper	opvsls2	text	12
	vslcall	opvsls2	text	12
	vslconst	opvsls2	text	1
	vsleng	opvsls2	text	1
	vslfuel	opvsls2	text	1
	vslhin	opervsls	text	12
	vslhin	opvsls2	text	12
	vslhp	opvsls2	text	3
	vslhull	opvsls2	text	1
	vsllefft	opvsls2	integer	
	vsllefft	opvsls2	integer	
	vslmake	opvsls2	text	10
	vslmarks	opvsls2	text	40
	vslmasts	opvsls2	text	1
	vslmodel	opvsls2	text	10
	vslname	opervsls	text	17
	vslname	opvsls2	text	17
	vslno	opvsls2	text	8
	vslloffno	opvsls2	text	10
	vslprop	opvsls2	text	1
	vslsuper	opvsls2	text	12
	vsltons	opvsls2	integer	



Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
opervsls	vsltype	opvsls2	text	2
	vsluse	opvsls2	text	2
	vslvalue	opvsls2	dollar	
owners	vslyear	opvsls2	text	4
	ownaddr	ownsum1	text	25
	ownaddr	ownsum2	text	25
	owncity	ownsum1	text	18
	owncity	ownsum2	text	18
	owndob	ownsum1	date	
	owndob	ownsum2	date	
	ownfname	ownsum1	text	15
	ownfname	ownsum2	text	15
	ownid	ownsum1	integer	
	ownid	ownsum2	integer	
	ownlname	ownsum1	text	20
	ownlname	ownsum2	text	20
	ownmi	ownsum1	text	1
	ownmi	ownsum2	text	1
	ownstate	ownsum1	text	2
	ownstate	ownsum2	text	2
	owntelno	ownsum1	text	12
	owntelno	ownsum2	text	12
	ownzip	ownsum1	text	9
	ownzip	ownsum2	text	9
ownervsl	cbcolor	ownvsls2	text	3
	cmedecal	ownvsls2	text	1
	cmeyear	ownvsls2	text	4
	dkcolor	ownvsls2	text	3
	hlcolor	ownvsls2	text	3
	homeport	ownvsls2	text	25
	idowner	ownvsls1	integer	
	idowner	ownvsls2	integer	
	ownaddr	ownvsls	text	25
	ownaddr	ownvsls1	text	25
	ownaddr	ownvsls2	text	25
	owncity	ownvsls	text	18
	owncity	ownvsls1	text	18
	owncity	ownvsls2	text	18
	owndob	ownvsls	date	
	owndob	ownvsls1	date	
	owndob	ownvsls2	date	
	ownfname	ownvsls	text	15
	ownfname	ownvsls1	text	15
	ownfname	ownvsls2	text	15
	ownid	ownvsls1	integer	
	ownid	ownvsls2	integer	
	ownlname	ownvsls	text	20
	ownlname	ownvsls1	text	20
	ownlname	ownvsls2	text	20
	ownmi	ownvsls	text	1
	ownmi	ownvsls1	text	1
	ownmi	ownvsls2	text	1
	ownstate	ownvsls	text	2
	ownstate	ownvsls1	text	2
	ownstate	ownvsls2	text	2
	owntelno	ownvsls	text	12
	owntelno	ownvsls1	text	12
	owntelno	ownvsls2	text	12
	ownzip	ownvsls	text	9
	ownzip	ownvsls1	text	9
	ownzip	ownvsls2	text	9
	sailno	ownvsls2	text	8
	slcolor	ownvsls2	text	3
	trcolor	ownvsls2	text	3
	vhinown	ownvsls1	text	12

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
	vhinown	ownvsls2	text	12
	vslcall	ownvsls2	text	12
	vslconst	ownvsls2	text	1
	vsleng	ownvsls2	text	1
	vslfuel	ownvsls2	text	1
	vslhin	ownvsls	text	12
	vslhin	ownvsls2	text	12
	vslhp	ownvsls2	text	3
	vslhull	ownvsls2	text	1
	vsllefft	ownvsls2	integer	
	vsllefft	ownvsls2	integer	
	vslmake	ownvsls2	text	10
	vslmarks	ownvsls2	text	40
	vslmasts	ownvsls2	text	1
	vslmodel	ownvsls2	text	10
	vslname	ownvsls	text	17
	vslname	ownvsls2	text	17
	vslno	ownvsls2	text	8
	vslloffno	ownvsls2	text	10
	vslprop	ownvsls2	text	1
	vslsuper	ownvsls2	text	12
	vsltons	ownvsls2	integer	
	vsltype	ownvsls2	text	2
	vsluse	ownvsls2	text	2
	vslvalue	ownvsls2	dollar	
	vslyear	ownvsls2	text	4
perintel	intdob	persum	date	
	intfname	persum	text	15
	intlname	persum	text	20
	intmi	persum	text	1
	pintdate	persum	date	
	pintrem1	persum	text	70
	pintrem2	persum	text	70
	pintrem3	persum	text	70
quer_per	bodate	bohis	date	
	boname	bohis	text	25
	bono	bohis	text	7
	borate	bohis	text	5
	borem1	bohis	text	70
	borem2	bohis	text	70
	borem3	bohis	text	70
	botime	bohis	time	
	bovhin	bohis	text	12
	cbcolor	pvsjjoin	text	3
	cbcolor	wvsjjoin	text	3
	cmedecal	pvsjjoin	text	1
	cmedecal	wvsjjoin	text	1
	cmeyear	pvsjjoin	text	4
	cmeyear	wvsjjoin	text	4
	dkcolor	pvsjjoin	text	3
	dkcolor	wvsjjoin	text	3
	epiccode	vslint	text	1
	folderno	sarhis	text	7
	hlcolor	pvsjjoin	text	3
	hlcolor	wvsjjoin	text	3
	homeport	pvsjjoin	text	25
	homeport	wvsjjoin	text	25
	idoper	pvsjjoin	integer	
	idoper	vslsopr	integer	
	idowner	vslsown	integer	
	idowner	wvsjjoin	integer	
	immedsar	sarhis	text	1
	intdate	vslint	date	
	intdob	perint	date	
	intfname	perint	text	15

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	-----
quer_per	intlname	perint	text	20
	intml	perint	text	1
	intvname	vslint	text	17
	mucn	sarhis	text	8
	obslat	bohis	real	2.3
	obslong	bohis	real	3.3
	offshore	sarhis	integer	
	pintdate	perint	date	
	pintrem1	perint	text	70
	pintrem2	perint	text	70
	pintrem3	perint	text	70
	sailno	pvslljoin	text	8
	sailno	wvsljoin	text	8
	sardate	sarhis	date	
	sarlat	sarhis	real	2.3
	sarlong	sarhis	real	3.3
	sarnod	sarhis	text	25
	sarpob	sarhis	integer	
	sartime	sarhis	time	
	sarvhin	sarhis	text	12
	slcolor	pvslljoin	text	3
	slcolor	wvsljoin	text	3
	stolen	vslint	text	1
	tmp	temp	text	2
	trcolor	pvslljoin	text	3
	trcolor	wvsljoin	text	3
	ucn	sarhis	text	8
	uns69	bohis	text	1
	uns70	bohis	text	1
	uns71	bohis	text	1
	uns72	bohis	text	1
	uns73	bohis	text	1
	uns74	bohis	text	1
	uns75	bohis	text	1
	uns76	bohis	text	1
	uns77	bohis	text	1
	uns78	bohis	text	1
	uns79	bohis	text	1
	vhinoper	pvslljoin	text	12
	vhinoper	vslsopr	text	12
	vhinown	vslsown	text	12
	vhinown	wvsljoin	text	12
	viol54	bohis	text	1
	viol55	bohis	text	1
	viol56	bohis	text	1
	viol57	bohis	text	1
	viol58	bohis	text	1
	viol59	bohis	text	1
	viol60	bohis	text	1
	viol61	bohis	text	1
	viol62	bohis	text	1
	viol63	bohis	text	1
	viol64	bohis	text	1
	viol65	bohis	text	1
	viol66	bohis	text	1
	viol67	bohis	text	1
	viol68	bohis	text	1
	vremark1	vslint	text	70
	vremark2	vslint	text	70
	vremark3	vslint	text	70
	vslcall	pvslljoin	text	12
	vslcall	wvsljoin	text	12
	vslconst	pvslljoin	text	1
	vslconst	wvsljoin	text	1
	vsleng	pvslljoin	text	1

Used In	AttName	RelName	Type	Len
quer_per	vsleng	wvsljoin	text	1
	vslfuel	pvslljoin	text	1
	vslfuel	wvsljoin	text	1
	vslhin	pvslljoin	text	12
	vslhin	wvsljoin	text	12
	vslhp	pvslljoin	text	3
	vslhp	wvsljoin	text	3
	vslhull	pvslljoin	text	1
	vslhull	wvsljoin	text	1
	vsllefft	pvslljoin	integer	
	vsllefft	wvsljoin	integer	
	vsllefft	pvslljoin	integer	
	vsllefft	wvsljoin	integer	
	vslmake	pvslljoin	text	10
	vslmake	wvsljoin	text	10
	vslmarks	pvslljoin	text	40
	vslmarks	wvsljoin	text	40
	vslmasts	pvslljoin	text	1
	vslmasts	wvsljoin	text	1
	vslmodel	pvslljoin	text	10
	vslmodel	wvsljoin	text	10
	vslname	pvslljoin	text	17
	vslname	wvsljoin	text	17
	vslno	pvslljoin	text	8
	vslno	wvsljoin	text	8
	vslloffno	pvslljoin	text	10
	vslloffno	wvsljoin	text	10
	vslpob	bohis	integer	
	vslprop	pvslljoin	text	1
	vslprop	wvsljoin	text	1
	vslsuper	pvslljoin	text	12
	vslsuper	wvsljoin	text	12
	vsltons	pvslljoin	integer	
	vsltons	wvsljoin	integer	
	vsltype	pvslljoin	text	2
	vsltype	wvsljoin	text	2
	vsluse	pvslljoin	text	2
	vsluse	wvsljoin	text	2
	vslvalue	pvslljoin	dollar	
	vslvalue	wvsljoin	dollar	
	vslyear	pvslljoin	text	4
	vslyear	wvsljoin	text	4
quer_vsl	weapons	bohis	integer	
	bodate	bohis	date	
	boname	bohis	text	25
	bono	bohis	text	7
	borate	bohis	text	5
	borem1	bohis	text	70
	borem2	bohis	text	70
	borem3	bohis	text	70
	botime	bohis	time	
	bovhin	bohis	text	12
	epiccode	vslint	text	1
	folderno	sarhis	text	7
	immedsar	sarhis	text	1
	intdate	vslint	date	
	intdob	perint	date	
	intfname	perint	text	15
	intlname	perint	text	20
	intmi	perint	text	1
	intvname	vslint	text	17
	mucn	sarhis	text	8
	obslat	bohis	real	2.3
	obslong	bohis	real	3.3
	offshore	sarhis	integer	

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
quer_vsl	pintdate	perint	date	
	pintrem1	perint	text	70
	pintrem2	perint	text	70
	pintrem3	perint	text	70
	sardate	sarhis	date	
	sarlat	sarhis	real	2.3
	sarlong	sarhis	real	3.3
	sarnod	sarhis	text	25
	sarpob	sarhis	integer	
	sartime	sarhis	time	
	sarvhin	sarhis	text	12
	stolen	vslint	text	1
	tmp	temp	text	2
	ucn	sarhis	text	8
	uns69	bohis	text	1
	uns70	bohis	text	1
	uns71	bohis	text	1
	uns72	bohis	text	1
	uns73	bohis	text	1
	uns74	bohis	text	1
	uns75	bohis	text	1
	uns76	bohis	text	1
	uns77	bohis	text	1
	uns78	bohis	text	1
	uns79	bohis	text	1
	viol54	bohis	text	1
	viol55	bohis	text	1
	viol56	bohis	text	1
	viol57	bohis	text	1
	viol58	bohis	text	1
	viol59	bohis	text	1
	viol60	bohis	text	1
	viol61	bohis	text	1
	viol62	bohis	text	1
	viol63	bohis	text	1
	viol64	bohis	text	1
	viol65	bohis	text	1
	viol66	bohis	text	1
	viol67	bohis	text	1
	viol68	bohis	text	1
	vremark1	vslint	text	70
	vremark2	vslint	text	70
	vremark3	vslint	text	70
	vslpob	bohis	integer	
sardump	weapons	bohis	integer	
	ceiling	sarsum	integer	
	clouds	sarsum	integer	
	folderno	sarsum	text	7
	immedsar	sarsum	text	1
	mucn	sarsum	text	8
	offshore	sarsum	integer	
	sardate	sarsum	date	
	sarday	sarsum	text	3
	sarlat	sarsum	real	2.3
	sarlong	sarsum	real	3.3
	sarnod	sarsum	text	25
	sarpob	sarsum	integer	
	sartime	sarsum	time	
	sarvhin	sarsum	text	12
	seas	sarsum	integer	
	ssunrise	sarsum	time	
	ssunset	sarsum	time	
	swells	sarsum	integer	
	ucn	sarsum	text	8
	visdist	sarsum	integer	

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	---
sardump	winddir	sarsum	integer	
	windspd	sarsum	integer	
sarday	folderno	sarsum	text	7
	folderno	sarsum1	text	7
	pctincr	sarstat	real	
	sardate	sarsum	date	
	sardate	sarsum1	date	
	sarday	sarsum	text	3
	sarday	sarsum1	text	3
	sarsum	sarstat	integer	
	saryear	sarstat	text	4
	tmp	temp	text	2
sarmajor	folderno	sarsum	text	7
	frecnt	positfrq	integer	
	gridpct	positfrq	real	
	majeast	positfrq	real	3.3
	majgrid	positfrq	text	2
	majnorth	positfrq	real	2.3
	majsouth	positfrq	real	2.3
	majwest	positfrq	real	3.3
	sarlat	sarsum	real	2.3
	sarlong	sarsum	real	3.3
sarminor	folderno	sarsum	text	7
	frecnt	positfrq	integer	
	gridpct	positfrq	real	
	mineast	positfrq	real	3.3
	mingrid	positfrq	text	2
	minnorth	positfrq	real	2.3
	minwest	positfrq	real	3.3
	sarlat	sarsum	real	2.3
	sarlong	sarsum	real	3.3
sarsmbt	folderno	sarsum	text	7
	sarlat	sarsum	real	2.3
	sarlong	sarsum	real	3.3
	tmp	temp	text	2
sartimes	alngdate	sartime3	date	
	alngdate	sartime4	date	
	alngtime	sartime3	time	
	alngtime	sartime4	time	
	dvmdate	sartime5	date	
	dvmooored	sartime5	time	
	foldno	sartime1	text	7
	foldno	sartime2	text	7
	foldno	sartime3	text	7
	foldno	sartime4	text	7
	foldno	sartime5	text	7
	osdate	sartime1	date	
	osdate	sartime4	date	
	ostime	sartime1	time	
	ostime	sartime4	time	
	sutdate	sartime2	date	
	sutmoor	sartime2	time	
	tmp	temp	text	2
	towdate	sartime5	date	
	towtime	sartime5	time	
	uwdate	sartime1	date	
	uwdate	sartime2	date	
	uwdate	sartime3	date	
	uwtime	sartime1	time	
	uwtime	sartime2	time	
	uwtime	sartime3	time	
smboatrp	bono	bosum	text	7
	obslat	bosum	real	2.3
	obslong	bosum	real	3.3
	tmp	temp	text	2

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	-----
vessel	cbcolor	vs1sum	text	3
	cbcolor	vs1sum1	text	3
	cbcolor	vs1sum2	text	3
	cmedecal	vs1sum	text	1
	cmedecal	vs1sum1	text	1
	cmedecal	vs1sum2	text	1
	cmeyear	vs1sum	text	4
	cmeyear	vs1sum1	text	4
	cmeyear	vs1sum2	text	4
	dkcolor	vs1sum	text	3
	dkcolor	vs1sum1	text	3
	dkcolor	vs1sum2	text	3
	hlcolor	vs1sum	text	3
	hlcolor	vs1sum1	text	3
	hlcolor	vs1sum2	text	3
	homeport	vs1sum	text	25
	homeport	vs1sum1	text	25
	homeport	vs1sum2	text	25
	sailno	vs1sum	text	8
	sailno	vs1sum1	text	8
	sailno	vs1sum?	text	8
	slcolor	vs1sum	text	3
	slcolor	vs1sum1	text	3
	slcolor	vs1sum2	text	3
	trcolor	vs1sum	text	3
	trcolor	vs1sum1	text	3
	trcolor	vs1sum2	text	3
	vs1call	vs1sum	text	12
	vs1call	vs1sum1	text	12
	vs1call	vs1sum2	text	12
	vs1const	vs1sum	text	1
	vs1const	vs1sum1	text	1
	vs1const	vs1sum2	text	1
	vs1eng	vs1sum	text	1
	vs1eng	vs1sum1	text	1
	vs1eng	vs1sum2	text	1
	vs1fuel	vs1sum	text	1
	vs1fuel	vs1sum1	text	1
	vs1fuel	vs1sum2	text	1
	vs1hin	vs1sum	text	12
	vs1hin	vs1sum1	text	12
	vs1hin	vs1sum2	text	12
	vs1hp	vs1sum	text	3
	vs1hp	vs1sum1	text	3
	vs1hp	vs1sum2	text	3
	vs1hull	vs1sum	text	1
	vs1hull	vs1sum1	text	1
	vs1hull	vs1sum2	text	1
	vs1lenft	vs1sum	integer	
	vs1lenft	vs1sum1	integer	
	vs1lenft	vs1sum2	integer	
	vs1lenin	vs1sum	integer	
	vs1lenin	vs1sum1	integer	
	vs1lenin	vs1sum2	integer	
	vs1make	vs1sum	text	10
	vs1make	vs1sum1	text	10
	vs1make	vs1sum2	text	10
	vs1marks	vs1sum	text	40
	vs1marks	vs1sum1	text	40
	vs1marks	vs1sum2	text	40
	vs1masts	vs1sum	text	1
	vs1masts	vs1sum1	text	1
	vs1masts	vs1sum2	text	1
	vs1model	vs1sum	text	10
	vs1model	vs1sum1	text	10

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	----
vessel	vsmodel	vsisum2	text	10
	vsname	vsisum	text	17
	vsname	vsisum1	text	17
	vsname	vsisum2	text	17
	vsno	vsisum	text	8
	vsno	vsisum1	text	8
	vsno	vsisum2	text	8
	vsloffno	vsisum	text	10
	vsloffno	vsisum1	text	10
	vsloffno	vsisum2	text	10
	vsprop	vsisum	text	1
	vsprop	vsisum1	text	1
	vsprop	vsisum2	text	1
	vsisuper	vsisum	text	12
	vsisuper	vsisum1	text	12
	vsisuper	vsisum2	text	12
	vsitons	vsisum	integer	
	vsitons	vsisum1	integer	
	vsitons	vsisum2	integer	
	vsotype	vsisum	text	2
	vsotype	vsisum1	text	2
	vsotype	vsisum2	text	2
	vsuse	vsisum	text	2
	vsuse	vsisum1	text	2
	vsuse	vsisum2	text	2
	vsvalue	vsisum	dollar	
	vsvalue	vsisum1	dollar	
	vsvalue	vsisum2	dollar	
	vsyear	vsisum	text	4
	vsyear	vsisum1	text	4
	vsyear	vsisum2	text	4
violfreq	bono	frqchart	text	7
	tmp	temp	text	2
	uns69	frqchart	text	1
	uns70	frqchart	text	1
	uns71	frqchart	text	1
	uns72	frqchart	text	1
	uns73	frqchart	text	1
	uns74	frqchart	text	1
	uns75	frqchart	text	1
	uns76	frqchart	text	1
	uns77	frqchart	text	1
	uns78	frqchart	text	1
	uns79	frqchart	text	1
	viol54	frqchart	text	1
	viol55	frqchart	text	1
	viol56	frqchart	text	1
	viol57	frqchart	text	1
	viol58	frqchart	text	1
	viol59	frqchart	text	1
	viol60	frqchart	text	1
	viol61	frqchart	text	1
	viol62	frqchart	text	1
	viol63	frqchart	text	1
	viol64	frqchart	text	1
	viol65	frqchart	text	1
	viol66	frqchart	text	1
	viol67	frqchart	text	1
	viol68	frqchart	text	1
vsloper	cbcolor	opvsis2	text	3
	cmedecal	opvsis2	text	1
	cmeyear	cbvsis2	text	4
	dkcolor	opvsis2	text	3
	hlcolor	opvsis2	text	3
	homeport	opvsis2	text	25



Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	---
vsloper	idoper	opvsls1	integer	
	idoper	opvsls2	integer	
	opaddr	opervsls	text	25
	opaddr	opvsls1	text	25
	opaddr	opvsls2	text	25
	opcify	opervsls	text	18
	opcify	opvsls1	text	18
	opcify	opvsls2	text	18
	opcouse	opvsls1	text	1
	opcouse	opvsls2	text	1
	opdob	opervsls	date	
	opdob	opvsls1	date	
	opdob	opvsls2	date	
	opfame	opervsls	text	15
	opfame	opvsls1	text	15
	opfame	opvsls2	text	15
	opid	opvsls1	integer	
	opid	opvsls2	integer	
	oplame	opervsls	text	20
	oplame	opvsls1	text	20
	oplame	opvsls2	text	20
	opmi	opervsls	text	1
	opmi	opvsls1	text	1
	opmi	opvsls2	text	1
	opstate	opervsls	text	2
	opstate	opvsls1	text	2
	opstate	opvsls2	text	2
	optelno	opervsls	text	12
	optelno	opvsls1	text	12
	optelno	opvsls2	text	12
	opzip	opervsls	text	9
	opzip	opvsls1	text	9
	opzip	opvsls2	text	9
	sailno	opvsls2	text	8
	slcolor	opvsls2	text	3
	trcolor	opvsls2	text	3
	vhinoper	opvsls1	text	12
	vhinoper	opvsls2	text	12
	vsllcall	opvsls2	text	12
	vsllconst	opvsls2	text	1
	vslleng	opvsls2	text	1
	vsllfuel	opvsls2	text	1
	vsllhin	opervsls	text	12
	vsllhin	opvsls2	text	12
	vsllhp	opvsls2	text	3
	vsllhull	opvsls2	text	1
	vsllenft	opvsls2	integer	
	vsllenin	opvsls2	integer	
	vsllmake	opvsls2	text	10
	vsllmarks	opvsls2	text	40
	vsllmasts	opvsls2	text	1
	vsllmodel	opvsls2	text	10
	vsllname	opervsls	text	17
	vsllname	opvsls2	text	17
	vsllno	opvsls2	text	8
	vsloffno	opvsls2	text	10
	vsllprop	opvsls2	text	1
	vsllsuper	opvsls2	text	12
	vslltons	opvsls2	integer	
	vslltype	opvsls2	text	2
	vslluse	opvsls2	text	2
	vsllvalue	opvsls2	dollar	
	vsllyear	opvsls2	text	4

Used In	AttName	RelName	Type	Len
-----	-----	-----	-----	---
vslowner	cbcolor	ownvsls2	text	3
	cmedecal	ownvsls2	text	1
	cmeyear	ownvsls2	text	4
	dkcolor	ownvsls2	text	3
	hlcolor	ownvsls2	text	3
	homeport	ownvsls2	text	25
	idowner	ownvsls1	integer	
	idowner	ownvsls2	integer	
	ownaddr	ownvsls	text	25
	ownaddr	ownvsls1	text	25
	ownaddr	ownvsls2	text	25
	owncity	ownvsls	text	18
	owncity	ownvsls1	text	18
	owncity	ownvsls2	text	18
	owndob	ownvsls	date	
	owndob	ownvsls1	date	
	owndob	ownvsls2	date	
	ownfname	ownvsls	text	15
	ownfname	ownvsls1	text	15
	ownfname	ownvsls2	text	15
	ownid	ownvsls1	integer	
	ownid	ownvsls2	integer	
	ownlname	ownvsls	text	20
	ownlname	ownvsls1	text	20
	ownlname	ownvsls2	text	20
	ownmi	ownvsls	text	1
	ownmi	ownvsls1	text	1
	ownmi	ownvsls2	text	1
	ownstate	ownvsls	text	2
	ownstate	ownvsls1	text	2
	ownstate	ownvsls2	text	2
	owntelno	ownvsls	text	12
	owntelno	ownvsls1	text	12
	owntelno	ownvsls2	text	12
	ownzip	ownvsls	text	9
	ownzip	ownvsls1	text	9
	ownzip	ownvsls2	text	9
	sailno	ownvsls2	text	8
	slcolor	ownvsls2	text	3
	trcolor	ownvsls2	text	3
	vhinown	ownvsls1	text	12
	vhinown	ownvsls2	text	12
	vslcall	ownvsls2	text	12
	vslconst	ownvsls2	text	1
	vsleng	ownvsls2	text	1
	vslfuel	ownvsls2	text	1
	vslhin	ownvsls	text	12
	vslhin	ownvsls2	text	12
	vslhp	ownvsls2	text	3
	vslhull	ownvsls2	text	1
	vslleft	ownvsls2	integer	
	vslleft	ownvsls2	integer	
	vslmake	ownvsls2	text	10
	vslmarks	ownvsls2	text	40
	vslmasts	ownvsls2	text	1
	vslmodel	ownvsls2	text	10
	vslname	ownvsls	text	17
	vslname	ownvsls2	text	17
	vslno	ownvsls2	text	8
	vslloffno	ownvsls2	text	10
	vslprop	ownvsls2	text	1
	vslsuper	ownvsls2	text	12
	vsltons	ownvsls2	integer	
	vsltype	ownvsls2	text	2
	vsluse	ownvsls2	text	2
	vslvalue	ownvsls2	dollar	
	vslyear	ownvsls2	text	4

### Program Variables Sorted by Variable Name

Name	Type	Used In	Description
addl_opr	text	add_sbd.prg	user input
addl_own	text	add_sbd.prg	user input
addlownr	text	add_sar.prg	user input
		add_sbd.prg	
after90	integer	cmerpt.prg	counting variable
algavg	real	sartimes.prg	average alongside time
algtimes	integer	sartimes.prg	counting variable
allrecs	text	opervsl.prg	flag - all records?
		opervsls.prg	
		ownvsl.prg	
		ownvsl.prg	
		vsloper.prg	
		vsloper.prg	
		vslowner.prg	
		vslowner.prg	
anytype	text	vessel.prg	flag variable
aprdate1	date	sarday.prg	starting date
aprdate2	date	sarday.prg	ending date
aprsar	integer	sarday.prg	summation variable
augdate1	date	sarday.prg	starting date
augdate2	date	sarday.prg	ending date
augsar	integer	sarday.prg	summation variable
b1	date	add_brd.prg	bodate in boarding
		add_sbd.prg	
		mod_brd.prg	
b10	text	mod_brd.prg	obsclty
b11	text	mod_brd.prg	obsstate in boarding
b12	real	mod_brd.prg	obslat in boarding
b13	real	mod_brd.prg	obslong in boarding
b14	text	mod_brd.prg	viol54 in boarding
b15	text	mod_brd.prg	viol55 in boarding
b16	text	mod_brd.prg	viol56 in boarding
b17	text	mod_brd.prg	viol57 in boarding
b18	text	mod_brd.prg	viol58 in boarding
b19	text	mod_brd.prg	viol59 in boarding
b2	time	add_brd.prg	botime in boarding
		add_sbd.prg	
		mod_brd.prg	
b20	text	mod_brd.prg	viol61 in boarding
b21	text	mod_brd.prg	viol61 in boarding
b22	text	mod_brd.prg	viol62 in boarding
b23	text	mod_brd.prg	viol63 in boarding
b24	text	mod_brd.prg	viol64 in boarding
b25	text	mod_brd.prg	viol65 in boarding
b26	text	mod_brd.prg	viol66 in boarding
b27	text	mod_brd.prg	viol67 in boarding
b28	text	mod_brd.prg	viol68 in boarding
b29	text	mod_brd.prg	uns69 in boarding
b3	text	mod_brd.prg	bono in boarding
	real	add_brd.prg	obslat in boarding
		add_sbd.prg	
b30	text	mod_brd.prg	uns70 in boarding
b31	text	mod_brd.prg	uns71 in boarding
b32	text	mod_brd.prg	uns72 in boarding
b33	text	mod_brd.prg	uns73 in boarding
b34	text	mod_brd.prg	uns74 in boarding
b35	text	mod_brd.prg	uns75 in boarding
b36	text	mod_brd.prg	uns76 in boarding
b37	text	mod_brd.prg	uns77 in boarding
b38	text	mod_brd.prg	uns78 in boarding
b39	text	mod_brd.prg	uns79 in boarding

Name	Type	Used In	Description
b4	integer real	mod_brd.prg add_brd.prg add_sbd.prg	vslpob in boarding obslong in boarding
b40	text	mod_brd.prg	borem1 in boarding
b41	text	mod_brd.prg	borem2 in boarding
b42	text	mod_brd.prg	borem3 in boarding
b43	text	mod_brd.prg	boname in boarding
b44	text	mod_brd.prg	borate in boarding
b45	text	mod_brd.prg	bounit in boarding
b46	text	mod_brd.prg	bodist in boarding
b47	text	mod_brd.prg	boopfac in boarding
b48	text	mod_brd.prg	boday in boarding
b49	time	mod_brd.prg	bsunrise in boarding
b5	integer	mod_brd.prg	adultpfd in boarding
b50	time	mod_brd.prg	bsunset in boarding
b51	text	mod_brd.prg	bovhin in boarding
b52	integer	mod_brd.prg	weapons in boarding
b6	integer	mod_brd.prg	childpfd in boarding
b7	text	mod_brd.prg	owstatus in boarding
b8	text	mod_brd.prg	obsbody in boarding
b9	text	mod_brd.prg	obscount in boarding
backup	text	add_brd.prg add_sar.prg add_sbd.prg	flag variable
before70	integer	cmerpt.prg	counting variable
bohisprn	text	quer_per.prg quer_vsl.prg	user input
both	text	mod_sut.prg	flag variable
chances	integer	startup.prg	chances to logon
change	text	mod_sar.prg mod_sut.prg sarday.prg	flag variable
chk_hin	text	mod_brd.prg	flag variable
chk_name	text	mod_vhin.prg mod_brd.prg mod_vhin.prg	flag variable
chk_ownr	text	mod_owop.prg	flag variable
chk_hin	text	quer_vsl.prg	flag variable
chk_intl	text	quer_vsl.prg	flag variable
chk_name	text	quer_vsl.prg	flag variable
chk_no	text	quer_vsl.prg	flag variable
chk_op	text	quer_per.prg	flag variable
chkoffno	text	quer_vsl.prg	flag variable
choice	text	add_brd.prg add_sar.prg add_sbd.prg am_pint.prg am_vint.prg mod_owop.prg mod_owop.prg packdbms.prg quer_vsl.prg vessel.prg	user input variable
cmecount	integer	cmerpt.prg	counting variable
code	integer	intelrpt.prg	input variable
constrds	text	intelrpt.prg	= consdesc in CONSTR
consttst	text	intelrpt.prg	= constype in CONSTR
cont	text	add_brd.prg add_sar.prg add_sbd.prg	user input
correct	text	am_pint.prg am_vint.prg mod_brd.prg mod_sar.prg mod_sut.prg	user input

Name	Type	Used In	Description
correct	text	mod_vhin.prg	user input
count	integer	mod_vhin.prg quer_per.prg quer_vsl.prg sarday.prg startup.prg	counting variable
datadiff	integer	bominor.prg	date difference
datdiff	integer	bomajor.prg	date difference
datediff	integer	boarding.prg bominor.prg cmerpt.prg daynight.prg epicdump.prg immedsar.prg intelrpt.prg operator.prg owners.prg perintel.prg sardump.prg sarmajor.prg sarminor.prg sarsmbt.prg sartimes.prg smboatrp.prg violfreq.prg	date difference
datedour	real	sartimes.prg	time computation variable
daybrd	integer	daynight.prg	counting variable
daysar	integer	daynight.prg	counting variable
decdate1	date	sarday.prg	starting date
decdate2	date	sarday.prg	ending date
decsar	integer	sarday.prg	summation variable
difbo	text	add_sbd.prg add_brd.prg	flag variable
difsar	text	add_sar.prg	flag variable
done	text	add_sbd.prg add_ownr.prg add_sut.prg mod_sut.prg	flag variable
easttst	real	quer_per.prg bomajor.prg bominor.prg sarmajor.prg sarminor.prg	nautical position coord.
edsc1	text	epicdump.prg	= epicdsc1 in VSLINTEL
edsc2	text	epicdump.prg	= epicdsc2 in VSLINTEL
edsc3	text	epicdump.prg	= epicdsc3 in VSLINTEL
edsc4	text	epicdump.prg	= epicdsc4 in VSLINTEL
enddate	date	boarding.prg bomajor.prg bominor.prg cmerpt.prg daynight.prg epicdump.prg immedsar.prg	ending date

Name -----	Type -----	Used In -----	Description -----
enddate	date	intelsum.prg operator.prg owners.prg perintel.prg sarday.prg sardump.prg sarmajor.prg sarminor.prg sarsmbt.prg sartimes.prg smboatrp.prg violfreq.prg	ending date
endltr	text	operator.prg opervsl.prg opervsls.prg owners.prg ownvsl.prg perintel.prg vessel.prg vsloper.prg vslowner.prg	ending letter
engdescr	text	intelrpt.prg	= ecomptyp in ENGCOMP
engtst	text	intelrpt.prg	= ecomptype in ENGCOMP
epicnum	integer	epicdump.prg	counting variable
epictest	text	epicdump.prg	= epiccode in VSLINTEL
er	text	mod_brd.prg mod_brd.prg mod_owop.prg mod_sar.prg mod_vhin.prg	user input
error	text	mod_brd.prg mod_owop.prg mod_owop.prg mod_vhin.prg	flag variable
fdesc	text	intelrpt.prg	= fcompdes in FUELCOMP
febdate1	date	sarday.prg	starting date
febdate2	date	sarday.prg	ending date
febsar	integer	sarday.prg	summation variable
fixopr	text	add_brd.prg add_sar.prg add_sbd.prg	flag variable
fixown	text	add_brd.prg add_sar.prg add_sbd.prg	flag variable
fixvsl	text	am_vint.prg	user input
foldok	text	mod_sut.prg	flag variable
found	text	sarday.prg	flag variable
foundv	text	mod_vhin.prg	user input
friday	integer	sarday.prg	counting variable
fuelst	text	intelrpt.prg	= fcomptyp in FUELCOMP
go	text	mod_owop.prg	user input
gridcnt	integer	sarmajor.prg sarminor.prg	counting variable
hdesc	text	intelrpt.prg	= hmatdesc in HULLMAT
hulltst	text	intelrpt.prg	= hmattyp in HULLMAT
inarea	integer	bomajor.prg bominor.prg sarmajor.prg sarminor.prg	summation variable
initdate	date	sarday.prg	starting date
inpct	real	bomajor.prg bominor.prg sarmajor.prg sarminor.prg sarsmbt.prg	percentage

Name	Type	Used In	Description
inpcttmp	real	sarsmbt.prg	percentage
inside	integer	sarsmbt.prg smboatrp.prg	summation variable
jandatel	date	sarday.prg	starting date
jandate2	date	sarday.prg	ending date
jansar	integer	sarday.prg	summation variable
juldate1	date	sarday.prg	starting date
juldate2	date	sarday.prg	ending date
julsar	integer	sarday.prg	summation variable
jundatel	date	sardates.prg sarday.prg	time computation variable
jundate2	date	sarday.prg	ending date
junsar	integer	sarday.prg	summation variable
legalch	text	vessel.prg	flag variable
legaltyp	text	vessel.prg	flag variable
legaluse	text	vessel.prg	flag variable
len2030	integer	intelrpt.prg	counting variable
len3040	integer	intelrpt.prg	counting variable
len4050	integer	intelrpt.prg	counting variable
len5060	integer	intelrpt.prg	counting variable
len6070	integer	intelrpt.prg	counting variable
len7080	integer	intelrpt.prg	counting variable
len8090	integer	intelrpt.prg	counting variable
len90100	integer	intelrpt.prg	counting variable
len<20	integer	intelrpt.prg	counting variable
len>100	integer	intelrpt.prg	counting variable
loadmenu	text	add_brd.prg add_sar.prg add_sbd.prg	flag variable
loadok	text	add_owndr.prg	flag variable
ltrdiff	integer	operator.prg opervsl.prg opervsls.prg owners.prg ownvsl.prg perintel.prg vessel.prg vsloper.prg vslowndr.prg	letter difference
mardatel	date	sarday.prg	starting date
mardate2	date	sarday.prg	ending date
marsar	integer	sarday.prg	summation variable
maxaltim	real	sartimes.prg	maximum alongside time
maxostim	real	sartimes.prg	maximum on scene time
maxshtim	real	sartimes.prg	maximum search time
maxtttim	real	sartimes.prg	maximum total case time
maxtwtim	real	sartimes.prg	maximum towing time
maydate1	date	sarday.prg	starting date
maydate2	date	sarday.prg	ending date
maysar	integer	sarday.prg	summation variable
menu	text	quer_vsl.prg	flag variable
minaltim	real	sartimes.prg	minimum alongside time
minostim	real	sartimes.prg	minimum on scene time
minshtim	real	sartimes.prg	minimum search time
mintttim	real	sartimes.prg	minimum total case time
mintwtim	real	sartimes.prg	minimum towing time
monday	integer	sarday.prg	counting variable
more	text	add_sbd.prg add_brd.prg add_owndr.prg add_sar.prg am_pint.prg am_vint.prg mod_brd.prg	flag variable

Name	Type	Used In	Description
more	text	mod_sar.prg mod_sut.prg mod_vhin.prg quer_per.prg quer_vsl.prg	flag variable
mrintel	text	am_pint.prg am_vint.prg	user input
mrname	text	quer_per.prg	user input
mropers	text	add_brd.prg add_sbd.prg	user input
mrownrs	text	add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg	user input
mrsar	text	mod_sar.prg	user input
mrsut	text	mod_sut.prg	user input
mrunits	text	add_sar.prg add_sbd.prg add_sut.prg	user input
mrvsls	text	mod_brd.prg mod_vhin.prg	user input
name	text	mod_sut.prg	flag variable
nameok	text	quer_vsl.prg	flag variable
new	integer	sarday.prg	this year's sar cases
nitebrd	integer	daynight.prg	counting variable
nitesar	integer	daynight.prg	counting variable
nmchange	text	mod_owop.prg	flag variable
northtst	real	bomajor.prg bominor.prg sarmajor.prg sarminor.prg	nautical position coord.
notimmed	integer	immedsar.prg	non-immediate SAR Cases
novdate1	date	sarday.prg	starting date
novdate2	date	sarday.prg	ending date
novsar	integer	sarday.prg	summation variable
numrows	integer	boarding.prg immedsar.prg intelrpt.prg operator.prg opervsls.prg owners.prg ownvsl.prg perintel.prg sarday.prg sardump.prg sarmajor.prg sarminor.prg sarsmbt.prg vessel.prg vsloper.prg vslowner.prg	counting variable
numyears	integer	sarday.prg	counting variable
obslat	real	smboatrp.prg	nautical position coord.
obslong	real	smboatrp.prg	nautical position coord.
octdate1	date	sarday.prg	starting date
octdate2	date	sarday.prg	ending date
octsar	integer	sarday.prg	summation variable
old	integer	sarday.prg	previous year's sar cases
oldfold	text	mod_sar.prg	folder number
opl	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	oplname in operator



Name	Type	Used In	Description
op10	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opcourse in operator
op11	integer	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opid in operator
op2	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opfname in operator
op3	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opmi in operator
op4	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opaddr in operator
op5	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opcity in operator
op6	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opstate in operator
op7	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opzip in operator
op8	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	optelno in operator
op9	date	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg	opdob in operator
opchange	text	mod_owop.prg	flag variable
opfound	text	mod_owop.prg	flag variable
opid	integer	mod_owop.prg quer_per.prg quer_vsl.prg	operator id (system)
oprfound	text	quer_per.prg	flag variable
oscavg	real	sartimes.prg	average on scene time
osdate	date	sartimes.prg	on scene date
ossum	real	sartimes.prg	summation variable
ostime	time	sartimes.prg	on scene time
ostimes	integer	sartimes.prg	counting variable
out	text	add_ownr.prg	flag variable
outarea	integer	bomajor.prg bominor.prg sarmajor.prg sarminor.prg	summation variable
outpct	real	bomajor.prg bominor.prg sarmajor.prg sarminor.prg	percentage
outpcttm	real	sarsmbt.prg	percentage
outside	integer	sarsmbt.prg sarsmbt.prg smboatrp.prg	summation variable

Name	Type	Used In	Description
ow1	text	add_brd.prg add_sar.prg add_sbd.prg	ownlname in owners
ow10	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	ownid in owners
ow2	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	ownfname in owners
ow3	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	ownmi in owners
ow4	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	ownaddr in owners
ow5	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	owncity in owners
ow6	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	ownstate in owners
ow7	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	ownzip in owners
ow8	text	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	owntelno in owners
ow9	date	mod_owop.prg add_brd.prg add_sar.prg add_sbd.prg	owndob in owners
owchange	text	mod_owop.prg	flag variable
owfound	text	mod_owop.prg	flag variable
owhisprn	text	quer_vsl.prg	user input
owid	integer	quer_vsl.prg	owner id (system)
owndone	text	quer_per.prg	flag variable
ownfound	text	quer_per.prg	flag variable
owoptest	text	quer_per.prg	flag variable
pcik6	integer	brd_main.prg	counting variable
pct2030	real	intelrpt.prg	percentage
pct3040	real	intelrpt.prg	percentage
pct4050	real	intelrpt.prg	percentage
pct5060	real	intelrpt.prg	percentage
pct54	real	violfreq.prg	percentage
pct54tmp	real	violfreq.prg	percentage
pct55	real	violfreq.prg	percentage
pct55tmp	real	violfreq.prg	percentage
pct56	real	violfreq.prg	percentage
pct56tmp	real	violfreq.prg	percentage
pct57	real	violfreq.prg	percentage
pct57tmp	real	violfreq.prg	percentage
pct58	real	violfreq.prg	percentage
pct58tmp	real	violfreq.prg	percentage
pct59	real	violfreq.prg	percentage
pct59tmp	real	violfreq.prg	percentage
pct60	real	violfreq.prg	percentage

Name	Type	Used In	Description
pct6070	real	intelrpt.prg	percentage
pct60tmp	real	violfreq.prg	percentage
pct61	real	violfreq.prg	percentage
pct61tmp	real	violfreq.prg	percentage
pct62	real	violfreq.prg	percentage
pct62tmp	real	violfreq.prg	percentage
pct63	real	violfreq.prg	percentage
pct63tmp	real	violfreq.prg	percentage
pct64	real	violfreq.prg	percentage
pct64tmp	real	violfreq.prg	percentage
pct65	real	violfreq.prg	percentage
pct65tmp	real	violfreq.prg	percentage
pct66	real	violfreq.prg	percentage
pct66tmp	real	violfreq.prg	percentage
pct67	real	violfreq.prg	percentage
pct67tmp	real	violfreq.prg	percentage
pct68	integer	violfreq.prg	percentage
pct68tmp	real	violfreq.prg	percentage
pct69	real	violfreq.prg	percentage
pct69tmp	real	violfreq.prg	percentage
pct70	real	violfreq.prg	percentage
pct7080	real	intelrpt.prg	percentage
pct71 tmp	real	violfreq.prg	percentage
pct71	real	violfreq.prg	percentage
pct7175	real	cmerpt.prg	percentage
pct71tmp	real	violfreq.prg	percentage
pct72	real	violfreq.prg	percentage
pct72tmp	real	violfreq.prg	percentage
pct73	real	violfreq.prg	percentage
pct73tmp	real	violfreq.prg	percentage
pct74	real	violfreq.prg	percentage
pct74tmp	real	violfreq.prg	percentage
pct75	real	violfreq.prg	percentage
pct75tmp	real	violfreq.prg	percentage
pct76	real	violfreq.prg	percentage
pct7679	real	cmerpt.prg	percentage
pct76tmp	real	violfreq.prg	percentage
pct77	real	violfreq.prg	percentage
pct77tmp	real	violfreq.prg	percentage
pct78	real	violfreq.prg	percentage
pct78tmp	real	violfreq.prg	percentage
pct79	real	violfreq.prg	percentage
pct79tmp	real	violfreq.prg	percentage
pct8081	real	cmerpt.prg	percentage
pct8090	real	intelrpt.prg	percentage
pct8283	real	cmerpt.prg	percentage
pct8485	real	cmerpt.prg	percentage
pct8687	real	cmerpt.prg	percentage
pct8889	real	cmerpt.prg	percentage
pct9010	real	intelrpt.prg	percentage
pct90100	real	intelrpt.prg	percentage
pct<00	real	intelrpt.prg	percentage
pct<20	real	intelrpt.prg	percentage
pct<60	real	intelrpt.prg	percentage
pct<65	real	intelrpt.prg	percentage
pct<70	real	intelrpt.prg	percentage
pct<75	real	intelrpt.prg	percentage
pct<80	real	intelrpt.prg	percentage
pct<85	real	intelrpt.prg	percentage
pct<90	real	intelrpt.prg	percentage
pct<95	real	intelrpt.prg	percentage
pct>00	real	intelrpt.prg	percentage
pct>100	real	intelrpt.prg	percentage
pctapr	real	sarday.prg	percentage
pctaug	real	sarday.prg	percentage

Name	Type	Used In	Description
pctchang	real	sarday.prg	percentage
pctcme	real	cmerpt.prg	percentage
pctdayb	real	daynight.prg	percentage
pctdays	real	daynight.prg	percentage
pctdec	real	sarday.prg	percentage
pctfeb	real	sarday.prg	percentage
pctfri	real	sarday.prg	percentage
pctgt90	real	cmerpt.prg	percentage
pctimmed	real	immedsar.prg	% immediate SAR cases
pctjan	real	sarday.prg	percentage
pctjul	real	sarday.prg	percentage
pctjun	real	sarday.prg	percentage
pctl70	real	cmerpt.prg	percentage
pctmar	real	sarday.prg	percentage
pctmay	real	sarday.prg	percentage
pctmon	real	sarday.prg	percentage
pctniteb	real	daynight.prg	percentage
pctnites	real	daynight.prg	percentage
pctnotim	real	immedsar.prg	% non-immediate SAR Cases
pctnov	real	sarday.prg	percentage
pctoct	real	sarday.prg	percentage
pctsat	real	sarday.prg	percentage
pctsep	real	sarday.prg	percentage
pctsun	real	sarday.prg	percentage
pcttemp1	real	epicdump.prg	% epiccode / total vsls
pcttemp2	real	epicdump.prg	% epiccode / total vsls
pctthu	real	sarday.prg	percentage
pcttue	real	sarday.prg	percentage
pctwed	real	sarday.prg	percentage
perintpr	text	quer_per.prg	user input
persprn	text	quer_per.prg	user input
pg	integer	add_brd.prg	counting variable
		add_sar.prg	
		add_sbd.prg	
pgcount	integer	mod_brd.prg	
		add_brd.prg	counting variable
		add_sar.prg	
		add_sbd.prg	
pick1	integer	sarsys.prg	menu variable
pick10	integer	qrymain.prg	menu variable
pick11	integer	utlmain.prg	menu variable
pick2	integer	inpmain.prg	menu variable
pick3	integer	modmain.prg	menu variable
pick4	integer	rptmain.prg	menu variable
pick5	integer	int_main.prg	menu variable
pick7	integer	sar_main.prg	menu variable
pick8	integer	vsl_main.prg	menu variable
pick9	integer	prs_main.prg	menu variable
prdesc	text	intelrpt.prg	= propdesc in BOATPROP
proptst	text	intelrpt.prg	= proptype in BOATPROP
reenter	text	add_owmr.prg	user input
		am_pint.prg	
		am_vint.prg	
		mod_sar.prg	
review	text	mod_sut.prg	
		add_brd.prg	flag variable
		add_sar.prg	
		add_sbd.prg	
sunits	text	mod_brd.prg	
		add_sar.prg	user input
		add_sbd.prg	

Name	Type	Used In	Description
s1	date	add_sar.prg	sardate in sar
	text	add_sbd.prg	
s10	integer	mod_sar.prg	folderno in sar
s11	text	mod_sar.prg	sarpob in sar
s12	real	mod_sar.prg	sarvhin in sar
s13	real	mod_sar.prg	sarlat in sar
s14	integer	mod_sar.prg	sarlong in sar
s15	text	mod_sar.prg	distoff in sar
s16	text	mod_sar.prg	immedsar in sar
s17	text	mod_sar.prg	winddir in sar
s18	text	mod_sar.prg	windspd in sar
s19	text	mod_sar.prg	visdist in sar
s2	time	mod_sar.prg	clouds in sar
	text	add_sar.prg	sartime in sar
	text	add_sbd.prg	
s20	text	mod_sar.prg	ucn in sar
s21	text	mod_sar.prg	ceiling in sar
s22	text	mod_sar.prg	seas in sar
s3	real	mod_sar.prg	swells in sar
	text	add_sar.prg	sarlat in sar
	text	add_sbd.prg	
s4	real	mod_sar.prg	mucn in sar
	text	add_sar.prg	sarlong in sar
	text	add_sbd.prg	
s5	date	mod_sar.prg	sardate in sar
	text	add_sar.prg	sarnod in sar
	text	add_sbd.prg	
s6	text	mod_sar.prg	sarday in sar
	text	add_sar.prg	sarvhin in sar
	text	add_sbd.prg	
s7	time	mod_sar.prg	sartime in sar
s8	time	mod_sar.prg	ssunrise in sar
s9	text	mod_sar.prg	ssunset
sar00	integer	mod_sar.prg	sarnod in sar
sar01	integer	sarday.prg	counting variable
sar02	integer	sarday.prg	counting variable
sar03	integer	sarday.prg	counting variable
sar04	integer	sarday.prg	counting variable
sar05	integer	sarday.prg	counting variable
sar06	integer	sarday.prg	counting variable
sar07	integer	sarday.prg	counting variable
sar08	integer	sarday.prg	counting variable
sar09	integer	sarday.prg	counting variable
sar10	integer	sarday.prg	counting variable
sar11	integer	sarday.prg	counting variable
sar12	integer	sarday.prg	counting variable
sar81	integer	sarday.prg	counting variable
sar82	integer	sarday.prg	counting variable
sar83	integer	sarday.prg	counting variable
sar84	integer	sarday.prg	counting variable
sar85	integer	sarday.prg	counting variable
sar86	integer	sarday.prg	counting variable
sar87	integer	sarday.prg	counting variable
sar88	integer	sarday.prg	counting variable
sar89	integer	sarday.prg	counting variable
sar90	integer	sarday.prg	counting variable
sar91	integer	sarday.prg	counting variable
sar92	integer	sarday.prg	counting variable
sar93	integer	sarday.prg	counting variable
sar94	integer	sarday.prg	counting variable
sar95	integer	sarday.prg	counting variable
sar96	integer	sarday.prg	counting variable
sar97	integer	sarday.prg	counting variable
sar98	integer	sarday.prg	counting variable

Name	Type	Used In	Description
sar99	integer	sarday.prg	counting variable
sarhsprn	text	quer_per.prg	user input
		quer_vsl.prg	
saturday	integer	sarday.prg	counting variable
schavg	real	sartimes.prg	average search time
schtimes	integer	sartimes.prg	counting variable
searchok	text	quer_per.prg	flag variable
sepdate1	date	sarday.prg	starting date
sepdate2	date	sarday.prg	ending date
sepsar	integer	sarday.prg	summation variable
southtst	real	bomajor.prg	nautical position coord.
		bominor.prg	
		sarmajor.prg	
		sarminor.prg	
status	text	quer_per.prg	flag variable
strtdate	date	boarding.prg	starting date
		bomajor.prg	
		bominor.prg	
		cmerpt.prg	
		daynight.prg	
		epicdump.prg	
		immedsar.prg	
		intelrpt.prg	
		operator.prg	
		owners.prg	
		perintel.prg	
		sardump.prg	
		sarmajor.prg	
		sarminor.prg	
		sarsmbt.prg	
		sartimes.prg	
		smboatrp.prg	
		violfreq.prg	
strtltr	text	operator.prg	starting letter
		opervsl.prg	
		opervsls.prg	
		owners.prg	
		ownvsl.prg	
		perintel.prg	
		vessel.prg	
		vsloper.prg	
		vslowner.prg	
su1	text	mod_sut.prg	foldno in sarunits
su10	date	mod_sut.prg	alngdate in sarunits
su11	time	mod_sut.prg	towtime in sarunits
su12	date	mod_sut.prg	towdate in sarunits
su13	time	mod_sut.prg	dvmoored in sarunits
su14	date	mod_sut.prg	dvmdate in sarunits
su15	time	mod_sut.prg	sutmoor in sarunits
su16	date	mod_sut.prg	sutdate in sarunits
su2	text	mod_sut.prg	unit in sarunits
su3	time	mod_sut.prg	uwtime in sarunits
su4	date	mod_sut.prg	uupdate
su5	time	mod_sut.prg	oseta in sarunits
su6	date	mod_sut.prg	etadate in sarunits
su7	time	mod_sut.prg	ostime in sarunits
su8	date	mod_sut.prg	osdate in sarunits
su9	text	mod_sut.prg	alngtime in sarunits
sum1	integer	sarday.prg	summation variable
sum10	integer	sarday.prg	summation variable
sum11	integer	sarday.prg	summation variable
sum12	integer	sarday.prg	summation variable
sum2	integer	sarday.prg	summation variable
sum20	integer	sarday.prg	summation variable
sum3	integer	sarday.prg	summation variable

Name	Type	Used In	Description
sum4	integer	sarday.prg	summation variable
sum5	integer	sarday.prg	summation variable
sum6	integer	sarday.prg	summation variable
sumconst	integer	intelrpt.prg	counting variable
sumeng	integer	intelrpt.prg	counting variable
sumfuel	integer	intelrpt.prg	counting variable
sumhull	integer	intelrpt.prg	counting variable
sumprop	integer	intelrpt.prg	counting variable
sumtype	integer	intelrpt.prg	counting variable
sumuse	integer	intelrpt.prg	counting variable
sunday	integer	sarday.prg	counting variable
sutdate	date	sartimes.prg	sar unit moored date
sutmoor	time	sartimes.prg	sar unit moored time
tempcpt	real	bomajor.prg	percentage
		bominor.prg	
		sarmajor.prg	
		sarminor.prg	
test	real	sartimes.prg	comparison variable
thursday	integer	sarday.prg	counting variable
timeadd	real	sartimes.prg	time computation variable
timehour	real	sartimes.prg	time computation variable
totavg	real	sartimes.prg	average total case time
totbrds	integer	cmerpt.prg	counting variable
		daynight.prg	
		intelrpt.prg	
		smboatrp.prg	
totepics	integer	epicdump.prg	counting variable
totimmed	integer	immedsar.prg	counting variable
totsars	integer	daynight.prg	total sars
		immedsar.prg	
		sarday.prg	
		sarmajor.prg	
		sarsmbt.prg	
totsum	real	sartimes.prg	summation variable
tottimes	integer	sartimes.prg	counting variable
totviols	integer	intelrpt.prg	summation variable
		intelrpt.prg	
towavg	real	sartimes.prg	average towing time
towsum	real	sartimes.prg	summation variable
towtimes	integer	sartimes.prg	counting variable
tuesday	integer	sarday.prg	counting variable
tv1	integer	intelrpt.prg	summation variable
tv10	integer	intelrpt.prg	summation variable
tv2	integer	intelrpt.prg	summation variable
tv20	integer	intelrpt.prg	summation variable
tv3	integer	intelrpt.prg	summation variable
tv30	integer	intelrpt.prg	summation variable
tv4	integer	intelrpt.prg	summation variable
tv5	integer	intelrpt.prg	summation variable
typchoic	text	vessel.prg	user type choice
typdesc1	text	intelrpt.prg	= vtypedes in BOATTYPE
typetest	text	intelrpt.prg	= vtype in BOATTYPE
		vessel.prg	
uns69s	integer	violfreq.prg	counting variable
uns70s	integer	violfreq.prg	counting variable
uns71s	integer	violfreq.prg	counting variable
uns72s	integer	violfreq.prg	counting variable
uns73s	integer	violfreq.prg	counting variable
uns74s	integer	violfreq.prg	counting variable
uns75s	integer	violfreq.prg	counting variable
uns76s	integer	violfreq.prg	counting variable
uns77s	integer	violfreq.prg	counting variable
uns78s	integer	violfreq.prg	counting variable
uns79s	integer	violfreq.prg	counting variable
unstot1	integer	violfreq.prg	summation variable

Name	Type	Used In	Description
unstot2	integer	violfreq.prg	summation variable
unstot3	integer	violfreq.prg	summation variable
unstot4	integer	violfreq.prg	summation variable
unstot5	integer	violfreq.prg	summation variable
unstot6	integer	violfreq.prg	summation variable
unstot7	integer	violfreq.prg	summation variable
unstotal	integer	violfreq.prg	total unsafe conditions
usechoic	text	vessel.prg	user vessel use choice
usedesc1	text	intelrpt.prg	= vusedesc in BOATUSE
username	text	startup.prg	user name input
userpass	text	startup.prg	user password
usetest	text	intelrpt.prg	= vuse in BOATUSE
uupdate	date	vessel.prg	
uwtime	time	sartimes.prg	underway date
v1	text	sartimes.prg	underway time
		add_brd.prg	vslno in vessel
		add_sar.prg	
		add_sbd.prg	
v10	text	add_brd.prg	vslhp in vessel
		add_sar.prg	
		add_sbd.prg	
v11	text	add_brd.prg	vsluse in vessel
		add_sar.prg	
		add_sbd.prg	
v12	text	add_brd.prg	vsltype in vessel
		add_sar.prg	
		add_sbd.prg	
v13	text	add_brd.prg	vslprop in vessel
		add_sar.prg	
		add_sbd.prg	
v14	text	add_brd.prg	vslhull in vessel
		add_sar.prg	
		add_sbd.prg	
v15	text	add_brd.prg	vsleng in vessel
		add_sar.prg	
		add_sbd.prg	
v16	text	add_brd.prg	vslfuel in vessel
		add_sar.prg	
		add_sbd.prg	
v17	text	add_brd.prg	vslconst in vessel
		add_sar.prg	
		add_sbd.prg	
v18	text	add_brd.prg	cmedecal in vessel
		add_sar.prg	
		add_sbd.prg	
v19	text	add_brd.prg	cmeyuear in vessel
		add_sar.prg	
		add_sbd.prg	
v2	text	add_brd.prg	vslname in vessel
		add_sar.prg	
		add_sbd.prg	
v20	text	add_brd.prg	vsloffno in vessel
		add_sar.prg	
		add_sbd.prg	
v21	text	add_brd.prg	homeport in vessel
		add_sar.prg	
		add_sbd.prg	
v22	text	add_brd.prg	vslcall in vessel
		add_sar.prg	
		add_sbd.prg	
v23	text	add_brd.prg	vslvalue in vessel
		add_sar.prg	
		add_sbd.prg	



Name	Type	Used In	Description
v24	text	add_brd.prg add_sar.prg add_sbd.prg	vs1super in vessel
v25	text	add_brd.prg add_sar.prg add_sbd.prg	vs1masts in vessel
v26	text	add_brd.prg add_sar.prg add_sbd.prg	sailno in vessel
v27	text	add_brd.prg add_sar.prg add_sbd.prg	hlcolor in vessel
v28	text	add_brd.prg add_sar.prg add_sbd.prg	trcolor in vessel
v29	text	add_brd.prg add_sar.prg add_sbd.prg	slcolor in vessel
v3	text	add_brd.prg add_sar.prg add_sbd.prg	vs1hin in vessel
v30	text	add_brd.prg add_sar.prg add_sbd.prg	cbcolor in vessel
v31	text	add_brd.prg add_sar.prg add_sbd.prg	dkcolor in vessel
v32	text	add_brd.prg add_sar.prg add_sbd.prg	vs1marks in vessel
v4	text	add_brd.prg add_sar.prg add_sbd.prg	vs1make in vessel
v5	text	add_brd.prg add_sar.prg add_sbd.prg	vs1model in vessel
v6	text	add_brd.prg add_sar.prg add_sbd.prg	vs1year in vessel
v7	integer	add_brd.prg add_sar.prg add_sbd.prg	vs1tons in vessel
v8	integer	add_brd.prg add_sar.prg add_sbd.prg	vs1lenft in vessel
v9	integer	add_brd.prg add_sar.prg add_sbd.prg	vs1lenin in vessel
vadult	integer	add_brd.prg add_sbd.prg mod_brd.prg	adultpfd in boarding
valc	text	quer_per.prg quer_vs1.prg	operator alcohol conditio
valgdate	date	add_sar.prg add_sbd.prg add_sut.prg	date alongside
valgtime	time	mod_sut.prg add_sar.prg add_sbd.prg add_sut.prg	time alongside
validusr	text	mod_sut.prg startup.prg	flag variable
vbadhin	text	mod_vhin.prg	vs1hin in vessel

Name	Type	Used In	Description
vbodate	date	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	boarding date
vboday	text	add_brd.prg add_sbd.prg mod_brd.prg	boday in boarding
vbodist	text	add_brd.prg add_sbd.prg mod_brd.prg	bodist in boarding
vbolat	real	quer_per.prg quer_vsl.prg	latitude position
vbolong	real	quer_per.prg quer_vsl.prg	longitude position
vboname	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	boname in boarding
vbono	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	boarding report number
vboopfac	text	add_brd.prg add_sbd.prg mod_brd.prg	boopfac in boarding
vborate	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	borate in boarding
vborem1	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	borem1 in boarding
vborem2	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	borem2 in boarding
vborem3	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	borem3 in boarding
vbosrise	time	add_brd.prg add_sbd.prg mod_brd.prg	bsunrise in boarding
vbosset	time	add_brd.prg add_sbd.prg mod_brd.prg	bsunset in boarding
vbotime	time	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	boarding time
vbounit	text	add_brd.prg add_sbd.prg mod_brd.prg	bounit in boarding
vcall	text	add_brd.prg add_sar.prg add_sbd.prg	vessel call sign

Name	Type	Used In	Description
vcbcolor	text	add_brd.prg add_sar.prg add_sbd.prg	cabin color
vceiling	text	add_sar.prg add_sbd.prg	ceiling in sar
vchild	integer	mod_sar.prg add_brd.prg add_sbd.prg	childpfd in baording
vclouds	text	mod_brd.prg add_sar.prg add_sbd.prg	clouds in sar
vcmeyear	text	add_brd.prg add_sar.prg add_sbd.prg	cme decal year
vconstr	text	add_brd.prg add_sar.prg add_sbd.prg	coded vessel construction
vdate	date	mod_vhin.prg quer_per.prg quer_vsl.prg	intelligence date
vdateos	date	add_sar.prg add_sbd.prg add_sut.prg	on scene date
vdecal	text	mod_sut.prg add_brd.prg add_sar.prg	cme decal?
vdistoff	integer	add_sbd.prg add_sar.prg add_sbd.prg	distance offshore
vdkcolor	text	mod_sar.prg quer_per.prg quer_vsl.prg	deck color
vdob	date	add_brd.prg add_sar.prg add_sbd.prg	date of birth
vdvmoord	date	add_sut.prg mod_sut.prg add_sar.prg	date distressed vessel mo
vdvmoort	time	add_sbd.prg add_sut.prg mod_sut.prg	time distressed vessel mo
vepic	text	am_vint.prg quer_per.prg quer_vsl.prg	epiccode in vslintel
vetadate	date	add_sar.prg add_sbd.prg add_sut.prg	on scene eta date
vfname	text	mod_sut.prg am_pint.prg quer_per.prg	intfname in perintel
vfoldno	text	quer_vsl.prg add_sar.prg add_sbd.prg	sar folder number
vhcolor	text	add_sut.prg mod_sar.prg mod_sut.prg	hull color
		quer_per.prg quer_vsl.prg add_brd.prg add_sar.prg add_sbd.prg	

Name	Type	Used In	Description
vhome	text	add_brd.prg add_sar.prg add_sbd.prg	vessel homeport
vimmed	text	add_sar.prg add_sbd.prg mod_sar.prg quer_per.prg quer_vsl.prg	immediate sar?
vintdate	date	am_pint.prg am_pint.prg am_vint.prg quer_per.prg quer_vsl.prg	pintdate in perintel
vintdob	date	am_pint.prg	intdob in perintel
vintmi	text	am_pint.prg	intmi in perintel
vintprn	text	quer_vsl.prg	user input
vintrem1	text	am_pint.prg am_vint.prg	pintrem1 in perintel
vintrem2	text	am_pint.prg am_vint.prg	pintrem2 in perintel
vintrem3	text	am_pint.prg am_vint.prg	pintrem3 in perintel
viol54s	integer	violfreq.prg	counting variable
viol55s	integer	violfreq.prg	counting variable
viol56s	integer	violfreq.prg	counting variable
viol57s	integer	violfreq.prg	counting variable
viol58s	integer	violfreq.prg	counting variable
viol59s	integer	violfreq.prg	counting variable
viol60s	integer	violfreq.prg	counting variable
viol61s	integer	violfreq.prg	counting variable
viol62s	integer	violfreq.prg	counting variable
viol63s	integer	violfreq.prg	counting variable
viol64s	integer	violfreq.prg	counting variable
viol65s	integer	violfreq.prg	counting variable
viol66s	integer	violfreq.prg	counting variable
viol67s	integer	violfreq.prg	counting variable
viol68s	integer	violfreq.prg	counting variable
vlname	text	am_pint.prg quer_per.prg quer_vsl.prg	intlname in perintel
vlndesc	text	intelrpt.prg	= violdesc in VIOLS
vmarks	text	add_brd.prg add_sar.prg add_sbd.prg	vessel unusual markings
vmasts	text	add_brd.prg add_sar.prg add_sbd.prg	number of vessel masts
vmaxop	integer	add_brd.prg add_sar.prg add_sbd.prg	comparison variable
vmaxoper	integer	add_sbd.prg	comparison variable
vmaxown	integer	add_brd.prg add_sar.prg add_sbd.prg	comparison variable
vmi	text	quer_per.prg quer_vsl.prg	middle initial
vmucn	text	add_sar.prg add_sbd.prg mod_sar.prg quer_per.prg quer_vsl.prg	multi-unit case number
vno	text	intelrpt.prg	= violno in VIOLS

Name	Type	Used In	Description
vobcount	text	add_brd.prg add_sbd.prg mod_brd.prg	obscount in boarding
vobsbody	text	add_brd.prg add_sbd.prg mod_brd.prg	obsbody in boarding
vobscity	text	add_brd.prg add_sbd.prg mod_brd.prg	obscity in boarding
vobslat	real	add_brd.prg add_sbd.prg mod_brd.prg	latitude position
vobslong	real	add_brd.prg add_sbd.prg mod_brd.prg	longitude position
vobstate	text	add_brd.prg add_sbd.prg mod_brd.prg	obsstate in boarding
voffno	text	add_brd.prg add_sar.prg add_sbd.prg mod_vhin.prg quer_per.prg quer_vsl.prg	vessel official numbers
vopaddr	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator street address
vopcity	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator city address
vopcrse	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator course code
vopdob	date	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator date of birth
vopfname	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator first name
vopid	integer	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator id (system)
voplname	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator last name

Name	Type	Used In	Description
vopmi	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator middle initial
vopst	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator state address
voptelno	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator telephone number
vopzip	text	add_brd.prg add_sar.prg add_sbd.prg mod_owop.prg quer_per.prg quer_vsl.prg	operator zip code
voseta	time	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	on scene eta time
vostatus	text	add_brd.prg add_sbd.prg mod_brd.prg	owstatus in boarding
vostime	time	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	on scene time
vowaddr	text	add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner street address
vowcity	text	add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner city address
vowdob	date	add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner date of birth
vowfname	text	add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner first name
vowid	integer	quer_per.prg	owner record id number
vowlname	text	add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner last name

Name	Type	Used In	Description
vowmi	text	add_brd.prg add_owr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner middle initial
vownid	text	add_brd.prg add_brd.prg add_owr.prg add_sar.prg add_sbd.prg add_sbd.prg mod_owop.prg mod_owop.prg	owner id (system)
vowst	text	add_brd.prg add_owr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner state address
vowtelno	text	add_brd.prg add_owr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner telephone number
vowzip	text	add_brd.prg add_owr.prg add_sar.prg add_sbd.prg mod_owop.prg quer_vsl.prg	owner zip code
vpct2030	real	intelrpt.prg	percentage
vpct3040	real	intelrpt.prg	percentage
vpct4050	real	intelrpt.prg	percentage
vpct5060	real	intelrpt.prg	percentage
vpct6070	real	intelrpt.prg	percentage
vpct70	real	cmerpt.prg	percentage
vpct7080	real	intelrpt.prg	percentage
vpct71	real	cmerpt.prg	percentage
vpct76	real	cmerpt.prg	percentage
vpct80	real	cmerpt.prg	percentage
vpct8090	real	intelrpt.prg	percentage
vpct82	real	cmerpt.prg	percentage
vpct84	real	cmerpt.prg	percentage
vpct86	real	cmerpt.prg	percentage
vpct88	real	cmerpt.prg	percentage
vpct90	real	cmerpt.prg	percentage
vpct9010	real	intelrpt.prg	percentage
vpct<00	real	intelrpt.prg	percentage
vpct<20	real	intelrpt.prg	percentage
vpct<60	real	intelrpt.prg	percentage
vpct<65	real	intelrpt.prg	percentage
vpct<70	real	intelrpt.prg	percentage
vpct<75	real	intelrpt.prg	percentage
vpct<80	real	intelrpt.prg	percentage
vpct<85	real	intelrpt.prg	percentage
vpct<90	real	intelrpt.prg	percentage
vpct<95	real	intelrpt.prg	percentage
vpct>00	real	intelrpt.prg	percentage
vpct>100	real	intelrpt.prg	percentage
vperaddr	text	quer_per.prg	street address
vpercitiy	text	quer_per.prg	city address
vperdob	date	quer_per.prg	date of birth
vpermi	text	quer_per.prg	middle initial

Name	Type	Used In	Description
vperst	text	quer_per.prg	state address
vpertel	text	quer_per.prg	telephone number
vperzip	text	quer_per.prg	zip code
vpfname	text	quer_per.prg	first name
vplname	text	quer_per.prg	last name
vrem1	text	quer_per.prg quer_vsl.prg	personnel intelligence re
vrem2	text	quer_per.prg quer_vsl.prg	personnel intelligence re
vrem3	text	quer_per.prg quer_vsl.prg	personnel intelligence re
vsailno	text	add_brd.prg add_sar.prg add_sbd.prg	sail number
vsardate	date	add_sar.prg add_sbd.prg mod_sar.prg	sar date
vsarday	text	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg mod_sar.prg	sar day of the week
vsarhin	text	quer_vsl.prg mod_sar.prg	sarvhin in sar
vsarlat	real	add_sar.prg add_sbd.prg mod_sar.prg	latitude position
vsarlong	real	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg mod_sar.prg	longitude position
vsarnod	text	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg	nature of distress
vsarpob	integer	mod_sar.prg add_sar.prg add_sbd.prg mod_sar.prg	personnel on board
vsartime	time	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg mod_sar.prg	sar time
vseas	text	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg	seas in sar
vslcolor	text	mod_sar.prg add_brd.prg add_sar.prg add_sbd.prg	sail color
vslfound	text	mod_vhin.prg	flag variable
vslprn	text	quer_per.prg	user input
vstolen	text	quer_vsl.prg am_vint.prg	stolen in vslintel
vsumoord	date	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	date sar unit moored



Name	Type	Used In	Description
vsumoort	time	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	time sar unit moored
vsunrise	time	add_sar.prg add_sbd.prg mod_sar.prg	bsunrise in boarding
vsunset	time	add_sar.prg add_sbd.prg mod_sar.prg	bsunset in boarding
vsuper	text	add_brdr.prg add_sar.prg add_sbd.prg	vessel superstructure
vswells	text	add_sar.prg add_sbd.prg mod_sar.prg	swells in sar
vtot1	integer	violfreq.prg	summation variable
vtot10	integer	violfreq.prg	summation variable
vtot11	integer	violfreq.prg	summation variable
vtot12	integer	violfreq.prg	summation variable
vtot13	integer	violfreq.prg	summation variable
vtot2	integer	violfreq.prg	summation variable
vtot3	integer	violfreq.prg	summation variable
vtot4	integer	violfreq.prg	summation variable
vtot5	integer	violfreq.prg	summation variable
vtot6	integer	violfreq.prg	summation variable
vtot7	integer	violfreq.prg	summation variable
vtot8	integer	violfreq.prg	summation variable
vtot9	integer	violfreq.prg	summation variable
vtotal	integer	violfreq.prg	total violations
vtowdate	date	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	date started towing
vtowtime	time	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	time started towing
vtrcolor	text	add_brdr.prg add_sar.prg add_sbd.prg	trim color
vucn	text	add_sar.prg add_sbd.prg mod_sar.prg	unit case number
vunit	text	quer_per.prg quer_vsl.prg add_sar.prg add_sbd.prg add_sut.prg	sar unit name
vuns69	text	mod_sut.prg add_brdr.prg add_sbd.prg mod_brdr.prg	unsafe condition 69
vuns70	text	quer_per.prg quer_vsl.prg add_brdr.prg add_sbd.prg mod_brdr.prg	unsafe condition 70
vuns71	text	quer_per.prg quer_vsl.prg add_brdr.prg add_sbd.prg mod_brdr.prg quer_per.prg quer_vsl.prg	unsafe condition 71

Name	Type	Used In	Description
vuns72	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 72
vuns73	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 73
vuns74	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 74
vuns75	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 75
vuns76	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 76
vuns77	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 77
vuns78	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 78
vuns79	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	unsafe condition 79
vuwdate	date	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	underway date
vuwtime	time	add_sar.prg add_sbd.prg add_sut.prg mod_sut.prg	underway time
vvalue	dollar	add_brd.prg add_sar.prg add_sbd.prg	vessel value
vviol54	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 54
vviol55	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 55

Name	Type	Used In	Description
vviol56	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 56
vviol57	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 57
vviol58	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 58
vviol59	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 59
vviol60	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 60
vviol61	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 61
vviol62	text	add_brd.prg add_sbi.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 62
vviol63	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 63
vviol64	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 64
vviol65	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 65
vviol66	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 66
vviol67	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 67
vviol68	text	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	violation code 68

Name	Type	Used In	Description
vvisdist	integer	add_sar.prg add_sbd.prg mod_sar.prg	visdist in sar
vvrem1	text	quer_per.prg quer_vsl.prg	vessel intelligence remar
vvrem2	text	quer_per.prg quer_vsl.prg	vessel intelligence remar
vvrem3	text	quer_per.prg quer_vsl.prg	vessel intelligence remar
vvsleng	text	add_brd.prg add_sar.prg add_sbd.prg	coded vessel engine compa
vvslft	integer	mod_vhin.prg add_brd.prg add_sar.prg add_sbd.prg	vessel length (feet)
vvslfuel	text	mod_vhin.prg add_brd.prg add_sar.prg add_sbd.prg	coded fuel compartment
vvslhin	text	mod_vhin.prg add_brd.prg add_ownr.prg add_sar.prg add_sbd.prg mod_brd.prg	vslhin in vessel
vvslhp	text	mod_vhin.prg quer_per.prg quer_vsl.prg add_brd.prg add_sar.prg add_sbd.prg	vessel horsepower
vvslhull	text	mod_vhin.prg add_brd.prg add_sar.prg add_sbd.prg	coded vessel hull materia
vvslin	integer	mod_vhin.prg add_brd.prg add_sar.prg add_sbd.prg	vessel length (inches)
vvslmake	text	mod_vhin.prg add_brd.prg add_sar.prg add_sbd.prg	vessel make
vvslmod	text	mod_vhin.prg quer_per.prg quer_vsl.prg add_brd.prg add_sar.prg add_sbd.prg	vslmodel in vessel
vvslname	text	mod_vhin.prg add_brd.prg add_sar.prg add_sbd.prg am_vint.prg mod_vhin.prg	vessel name
vvslno	text	quer_per.prg quer_vsl.prg add_brd.prg add_sar.prg add_sbd.prg mod_vhin.prg quer_per.prg quer_vsl.prg	vessel number

Name	Type	Used In	Description
vvslpob	integer	add_brd.prg add_sbd.prg mod_brd.prg	personnel on board
vvslprop	text	quer_per.prg quer_vsl.prg add_brd.prg add_sar.prg add_sbd.prg mod_vhin.prg	coded vessel propulsion
vvslton	integer	add_brd.prg add_sar.prg add_sbd.prg mod_vhin.prg	vsltons in vessel
vvsltype	text	add_sar.prg add_sbd.prg add_brd.prg mod_vhin.prg	coded vessel type
vvsluse	text	add_brd.prg add_sar.prg add_sbd.prg mod_vhin.prg	coded vessel use
vvslyear	text	add_brd.prg add_sar.prg add_sbd.prg mod_vhin.prg	vessel year
vweapons	integer	add_brd.prg add_sbd.prg mod_brd.prg quer_per.prg quer_vsl.prg	weapons in boarding
vwinddir	text	add_sar.prg add_sbd.prg mod_sar.prg	winddir in sar
vwindspd	text	add_sar.prg add_sbd.prg mod_sar.prg	windspd in sar
wednesday	integer	sarday.prg	counting variable
westtst	real	bomajor.prg bominor.prg sarmajor.prg sarminor.prg	nautical position coord.
year	integer	sarday.prg	saryear
yr1981	date	sarday.prg	starting date
yr1981a	date	sarday.prg	ending date
yr1982	date	sarday.prg	starting date
yr1982a	date	sarday.prg	ending date
yr1983	date	sarday.prg	starting date
yr1983a	date	sarday.prg	ending date
yr1984	date	sarday.prg	starting date
yr1984a	date	sarday.prg	ending date
yr1985	date	sarday.prg	starting date
yr1985a	date	sarday.prg	ending date
yr1986	date	sarday.prg	starting date
yr1986a	date	sarday.prg	ending date
yr1987	date	sarday.prg	starting date
yr1987a	date	sarday.prg	ending date
yr1988	date	sarday.prg	starting date
yr1988a	date	sarday.prg	ending date
yr1989	date	sarday.prg	starting date
yr1989a	date	sarday.prg	ending date
yr1990	date	sarday.prg	starting date
yr1990a	date	sarday.prg	ending date
yr1991	date	sarday.prg	starting date
yr1991a	date	sarday.prg	ending date
yr1992	date	sarday.prg	starting date

Name	Type	Used In	Description
yr1992a	date	sarday.prg	ending date
yr1993	date	sarday.prg	starting date
yr1993a	date	sarday.prg	ending date
yr1994	date	sarday.prg	starting date
yr1994a	date	sarday.prg	ending date
yr1995	date	sarday.prg	starting date
yr1995a	date	sarday.prg	ending date
yr1996	date	sarday.prg	starting date
yr1996a	date	sarday.prg	ending date
yr1997	date	sarday.prg	starting date
yr1997a	date	sarday.prg	ending date
yr1998	date	sarday.prg	starting date
yr1998a	date	sarday.prg	ending date
yr1999	date	sarday.prg	starting date
yr1999a	date	sarday.prg	ending date
yr2000	date	sarday.prg	starting date
yr2000a	date	sarday.prg	ending date
yr2001	date	sarday.prg	starting date
yr2001a	date	sarday.prg	ending date
yr2002	date	sarday.prg	starting date
yr2002a	date	sarday.prg	ending date
yr2003	date	sarday.prg	starting date
yr2003a	date	sarday.prg	ending date
yr2004	date	sarday.prg	starting date
yr2004a	date	sarday.prg	ending date
yr2005	date	sarday.prg	starting date
yr2005a	date	sarday.prg	ending date
yr2006	date	sarday.prg	starting date
yr2006a	date	sarday.prg	ending date
yr2007	date	sarday.prg	starting date
yr2007a	date	sarday.prg	ending date
yr2008	date	sarday.prg	starting date
yr2008a	date	sarday.prg	ending date
yr2009	date	sarday.prg	starting date
yr2009a	date	sarday.prg	ending date
yr2010	date	sarday.prg	starting date
yr2010a	date	sarday.prg	ending date
yr2011	date	sarday.prg	starting date
yr2011a	date	sarday.prg	ending date
yr2012	date	sarday.prg	starting date
yr2012a	date	sarday.prg	ending date
yr71to75	integer	cmerpt.prg	counting variable
yr76to79	integer	cmerpt.prg	counting variable
yr80to81	integer	cmerpt.prg	counting variable
yr82to83	integer	cmerpt.prg	counting variable
yr84to85	integer	cmerpt.prg	counting variable
yr86to87	integer	cmerpt.prg	counting variable
yr88to89	integer	cmerpt.prg	counting variable
yr<1960	integer	intelrpt.prg	counting variable
yr<1965	integer	intelrpt.prg	counting variable
yr<1970	integer	intelrpt.prg	counting variable
yr<1975	integer	intelrpt.prg	counting variable
yr<1980	integer	intelrpt.prg	counting variable
yr<1985	integer	intelrpt.prg	counting variable
yr<1990	integer	intelrpt.prg	counting variable
yr<1995	integer	intelrpt.prg	counting variable
yr<2000	integer	intelrpt.prg	counting variable
yr>2000	integer	intelrpt.prg	counting variable
yrtest1	integer	sarday.prg	leap year test
yrtest2	integer	sarday.prg	leap year test

# *Program Variables Sorted by Where Used*

Used In	Name	Type	Description
add_brd.prg	b1	date	bodate in boarding
	b2	time	botime in boarding
	b3	real	obslat in boarding
	b4	real	bolong in boarding
	backup	text	flag variable
	choice	text	user input variable
	cont	text	user input
	difbo	text	flag variable
	fixopr	text	flag variable
	fixown	text	flag variable
	loadmenu	text	flag variable
	more	text	flag variable
	mropers	text	user input
	mrownrs	text	user input
	op1	text	oplname in operator
	op10	text	opcourse in operator
	op11	integer	opid in operator
	op2	text	opfname in operator
	op3	text	opmi in operator
	op4	text	opaddr in operator
	op5	text	opcity in operator
	op6	text	opstate in operator
	op7	text	opzip in operator
	op8	text	optelno in operator
	op9	date	opdob in operator
	ow1	text	ownlname in owners
	ow10	text	ownid in owners
	ow2	text	ownfname in owners
	ow3	text	ownmi in owners
	ow4	text	ownaddr in owners
	ow5	text	owncity in owners
	ow6	text	ownstate in owners
	ow7	text	ownzip in owners
	ow8	text	owntelno in owners
	ow9	date	owndob in owners
	pg	integer	counting variable
	pgcount	integer	counting variable
	review	text	flag variable
	v1	text	vslno in vessel
	v10	text	vslhp in vessel
	v11	text	vsluse in vessel
	v12	text	vsltype in vessel
	v13	text	vslprop in vessel
	v14	text	vslhull in vessel
	v15	text	vsleng in vessel
	v16	text	vslfuel in vessel
	v17	text	vslconst in vessel
	v18	text	cmedecal in vessel
	v19	text	cmeyuear in vessel
	v2	text	vslname in vessel
	v20	text	vsloffno in vessel
	v21	text	homeport in vessel
	v22	text	vslcall in vessel
	v23	text	vslvalue in vessel
	v24	text	vslsuper in vessel
	v25	text	vslmasts in vessel
	v26	text	sailno in vessel
	v27	text	hlcolor in vessel
	v28	text	trcolor in vessel
	v29	text	slcolor in vessel
	v3	text	vslhin in vessel
	v30	text	cbcolor in vessel
	v31	text	dkcolor in vessel
	v32	text	vslmarks in vessel
	v4	text	vslmake in vessel

Used In	Name	Type	Description
add_brd.prg	v5	text	vslmodel in vessel
	v6	text	vslyear in vessel
	v7	integer	vsitons in vessel
	v8	integer	vsllenft in vessel
	v9	integer	vsllenin in vessel
	vadult	integer	adultpfd in boarding
	vbodate	date	boarding date
	vboday	text	boday in boarding
	vbodist	text	bodist in boarding
	vboname	text	boname in boarding
	vbono	text	boarding report number
	vboopf	text	boopf in boarding
	vborate	text	borate in boarding
	vboreml	text	boreml in boarding
	vborem2	text	borem2 in boarding
	vborem3	text	borem3 in boarding
	vbosrise	time	bsunrise in boarding
	vbosset	time	bsunset in boarding
	vbotime	time	boarding time
	vbounit	text	bounit in boarding
	vcall	text	vessel call sign
	vcbcolor	text	cabin color
	vchild	integer	childpfd in boarding
	vcmeyear	text	cme decal year
	vconstr	text	coded vessel construction
	vdecal	text	cme decal?
	vdcolor	text	deck color
	vhlcolor	text	hull color
	vhome	text	vessel homeport
	vmarks	text	vessel unusual markings
	vmasts	text	number of vessel masts
	vmaxop	integer	comparison variable
	vmaxown	integer	comparison variable
	vobcount	text	obscount in boarding
	vobsbody	text	obsbody in boarding
	vobscity	text	obscity in boarding
	vobslat	real	latitude position
	vobslong	real	longitude position
	vobstate	text	obsstate in boarding
	voffno	text	vessel official numbers
	vopaddr	text	operator street address
	vopcity	text	operator city address
	vopcrse	text	operator course code
	vopdob	date	operator date of birth
	vopfname	text	operator first name
	vopid	integer	operator id (system)
	voplname	text	operator last name
	vopmi	text	operator middle initial
	vopst	text	operator state address
	voptelno	text	operator telephone number
	vopzip	text	operator zip code
	vostatus	text	owstatus in boarding
	vowaddr	text	owner street address
	vowcity	text	owner city address
	vowdob	date	owner date of birth
	vowfname	text	owner first name
	vowlname	text	owner last name
	vowmi	text	owner middle initial
	vownid	text	owner id (system)



Used In	Name	Type	Description
add_brd.prg	vownid	integer	owner id (system)
	vowst	text	owner state address
	vowtelno	text	owner telephone number
	vowzip	text	owner zip code
	vsailno	text	sail number
	vslcolor	text	sail color
	vsuper	text	vessel superstructure
	vtrcolor	text	trim color
	vuns69	text	unsafe condition 69
	vuns70	text	unsafe condition 70
	vuns71	text	unsafe condition 71
	vuns72	text	unsafe condition 72
	vuns73	text	unsafe condition 73
	vuns74	text	unsafe condition 74
	vuns75	text	unsafe condition 75
	vuns76	text	unsafe condition 76
	vuns77	text	unsafe condition 77
	vuns78	text	unsafe condition 78
	vuns79	text	unsafe condition 79
	vvalue	dollar	vessel value
	vviol54	text	violation code 54
	vviol55	text	violation code 55
	vviol56	text	violation code 56
	vviol57	text	violation code 57
	vviol58	text	violation code 58
	vviol59	text	violation code 59
	vviol60	text	violation code 60
	vviol61	text	violation code 61
	vviol62	text	violation code 62
	vviol63	text	violation code 63
	vviol64	text	violation code 64
	vviol65	text	violation code 65
	vviol66	text	violation code 66
	vviol67	text	violation code 67
	vviol68	text	violation code 68
	vvsleng	text	coded vessel engine compa
	vvslft	integer	vessel length (feet)
	vvslfuel	text	coded fuel compartment
	vvslhin	text	vslhin in vessel
	vvslhp	text	vessel horsepower
	vvslhull	text	coded vessel hull materia
	vvslin	integer	vessel length (inches)
	vvslmake	text	vessel make
	vvslmod	text	vslmodel in vessel
	vvslname	text	vessel name
	vvslno	text	vessel number
	vvslpob	integer	personnel on board
	vvslprop	text	coded vessel propulsion
	vvslton	integer	vsltons in vessel
	vvsltype	text	coded vessel type
	vvsluse	text	coded vessel use
	vvslyear	text	vessel year
	vweapons	integer	weapons in boarding
add_ownr.prg	done	text	flag variable
	loadok	text	flag variable
	more	text	flag variable
	mrownrs	text	user input
	out	text	flag variable
	reenter	text	user input
	vowaddr	text	owner street address
	vowcity	text	owner city address
	vowdob	date	owner date of birth
	vowfname	text	owner first name
	vowlname	text	owner last name
	vowmi	text	owner middle initial

Used In	Name	Type	Description
-----	-----	-----	-----
add_ownr.prg	vownid	integer	owner id (system)
	vowst	text	owner state address
	vowtelno	text	owner telephone number
	vowzip	text	owner zip code
	vslhin	text	vslhin in vessel
add_sar.prg	addlownr	text	user input
	backup	text	flag variable
	choice	text	user input variable
	cont	text	user input
	difsar	text	flag variable
	fixopr	text	flag variable
	fixown	text	flag variable
	loadmenu	text	flag variable
	more	text	flag variable
	mrownrs	text	user input
	mrunits	text	user input
	op1	text	oplname in operator
	op10	text	opcourse in operator
	op11	integer	opid in operator
	op2	text	opfname in operator
	op3	text	opmi in operator
	op4	text	opaddr in operator
	op5	text	opcity in operator
	op6	text	opstate in operator
	op7	text	opzip in operator
	op8	text	optelno in operator
	op9	date	opdob in operator
	ow1	text	ownlname in owners
	ow10	text	ownid in owners
	ow2	text	ownfname in owners
	ow3	text	ownmi in owners
	ow4	text	ownaddr in owners
	ow5	text	owncity in owners
	ow6	text	ownstate in owners
	ow7	text	ownzip in owners
	ow8	text	owntelno in owners
	ow9	date	owndob in owners
	pg	integer	counting variable
	pgcount	integer	counting variable
	review	text	flag variable
	s1	date	sardate in sar
	s2	time	sartime in sar
	s3	real	sarlat in sar
	s4	real	sarlong in sar
	s5	text	sarnod in sar
	s6	text	sarvhin in sar
	sunits	text	user input
	v1	text	vslno in vessel
	v10	text	vslhp in vessel
	v11	text	vsluse in vessel
	v12	text	vsltype in vessel
	v13	text	vslprop in vessel
	v14	text	vslhull in vessel
	v15	text	vsleng in vessel
	v16	text	vslfuel in vessel
	v17	text	vslconst in vessel
	v18	text	cmedecal in vessel
	v19	text	cmeyuear in vessel
	v2	text	vslname in vessel
	v20	text	vsloffno in vessel
	v21	text	homeport in vessel
	v22	text	vslcall in vessel
	v23	text	vslvalue in vessel
	v24	text	vslsuper in vessel
	v25	text	vslmasts in vessel

Used In	Name	Type	Description
-----	-----	-----	-----
add_sar.prg	v26	text	sailno in vessel
	v27	text	hlcolor in vessel
	v28	text	trcolor in vessel
	v29	text	slcolor in vessel
	v3	text	vsllhin in vessel
	v30	text	cbcolor in vessel
	v31	text	dkcolor in vessel
	v32	text	vsllmarks in vessel
	v4	text	vsllmake in vessel
	v5	text	vsllmodel in vessel
	v6	text	vsllyear in vessel
	v7	integer	vslltons in vessel
	v8	integer	vslllenft in vessel
	v9	integer	vslllenin in vessel
	valgdate	date	date alongside
	valgtime	time	time alongside
	vcall	text	vessel call sign
	vcbcolor	text	cabin color
	vceiling	text	ceiling in sar
	vclouds	text	clouds in sar
	vcmyear	text	cme decal year
	vconstr	text	coded vessel construction
	vdateos	date	on scene date
	vdecal	text	cme decal?
	vdistoff	integer	distance offshore
	vdkcolor	text	deck color
	vdvmoord	date	date distressed vessel mo
	vdvmoort	time	time distressed vessel mo
	vetadate	date	on scene eta date
	vfoldno	text	sar folder number
	vhicolor	text	hull color
	vhome	text	vessel homeport
	vimmed	text	immediate sar?
	vmarks	text	vessel unusual markings
	vmasts	text	number of vessel masts
	vmaxop	integer	comparison variable
	vmaxown	integer	comparison variable
	vmucn	text	multi-unit case number
	voffno	text	vessel official numbers
	vopaddr	text	operator street address
	vopcity	text	operator city address
	vopcrse	text	operator course code
	vopdob	date	operator date of birth
	vopfname	text	operator first name
	vopid	integer	operator id (system)
	voplname	text	operator last name
	vopmi	text	operator middle initial
	vopst	text	operator state address
	voptelno	text	operator telephone number
	vopzip	text	operator zip code
	voseta	time	on scene eta time
	vostime	time	on scene time
	vowaddr	text	owner street address
	vowcity	text	owner city address
	vowdob	date	owner date of birth
	vowfname	text	owner first name
	vowlname	text	owner last name
	vowmi	text	owner middle initial
	vownid	text	owner id (system)
	vowst	text	owner state address
	vowtelno	text	owner telephone number
	vowzip	text	owner zip code
	vsailno	text	sail number
	vsardate	date	sar date
	vsarday	text	sar day of the week

Used In	Name	Type	Description
-----	-----	-----	-----
add_sar.prg	vsarlat	real	latitude position
	vsarlong	real	longitude position
	vsarnod	text	nature of distress
	vsarpob	integer	personnel on board
	vsartime	time	sar time
	vseas	text	seas in sar
	vslcolor	text	sail color
	vsltype	text	coded vessel type
	vsumoord	date	date sar unit moored
	vsumoort	time	time sar unit moored
	vsunrise	time	bsunrise in boarding
	vsunset	time	bsunset in boarding
	vsuper	text	vessel superstructure
	vswells	text	swells in sar
	vtowdate	date	date started towing
	vtowtime	time	time started towing
	vtrcolor	text	trim color
	vucn	text	unit case number
	vunit	text	sar unit name
	vuwdate	date	underway date
	vuwtime	time	underway time
	vvalue	dollar	vessel value
	visdist	integer	visdist in sar
	vsleng	text	coded vessel engine compa
	vslft	integer	vessel length (feet)
	vslfuel	text	coded fuel compartment
	vslhin	text	vslhin in vessel
	vslhp	text	vessel horsepower
	vslhull	text	coded vessel hull materia
	vslin	integer	vessel length (inches)
	vslmake	text	vessel make
	vslmod	text	vslmodel in vessel
	vslname	text	vessel name
	vslno	text	vessel number
	vslprop	text	coded vessel propulsion
	vslton	integer	vsltons in vessel
	vsluse	text	coded vessel use
	vslyear	text	vessel year
	vwinddir	text	winddir in sar
	vwindspd	text	windspd in sar
add_sbd.prg	addl_opr	text	user input
	addl_own	text	user input
	b1	date	bodate in boarding
	b2	time	botime in boarding
	b3	real	obslat in boarding
	b4	real	bolong in boarding
	backup	text	flag variable
	choice	text	user input variable
	cont	text	user input
	difbo	text	flag variable
	difsar	text	flag variable
	fixopr	text	flag variable
	fixown	text	flag variable
	loadmenu	text	flag variable
	more	text	flag variable
	mropers	text	user input
	mrownrs	text	user input
	mrunits	text	user input
	op1	text	oplname in operator
	op10	text	opcouse in operator
	op11	integer	opid in operator
	op2	text	opfname in operator
	op3	text	opmi in operator
	op4	text	opaddr in operator
	op5	text	opcity in operator

Used In	Name	Type	Description
-----	-----	-----	-----
add_sbd.prg	op6	text	opstate in operator
	op7	text	opzip in operator
	op8	text	optelno in operator
	op9	date	opdob in operator
	ow1	text	ownlname in owners
	ow10	text	ownid in owners
	ow2	text	ownfname in owners
	ow3	text	ownmi in owners
	ow4	text	ownaddr in owners
	ow5	text	owncity in owners
	ow6	text	ownstate in owners
	ow7	text	ownzip in owners
	ow8	text	owntelno in owners
	ow9	date	owndob in owners
	pg	integer	counting variable
	pgcount	integer	counting variable
	review	text	flag variable
	s1	date	sardate in sar
	s2	time	sartime in sar
	s3	real	sarlat in sar
	s4	real	sarlong in sar
	s5	text	sarnod in sar
	s6	text	sarvhin in sar
	sunits	text	user input
	v1	text	vslno in vessel
	v10	text	vslhp in vessel
	v11	text	vsluse in vessel
	v12	text	vsltype in vessel
	v13	text	vslprop in vessel
	v14	text	vslhull in vessel
	v15	text	vsleng in vessel
	v16	text	vslfuel in vessel
	v17	text	vslconst in vessel
	v18	text	cmedecal in vessel
	v19	text	cmeyuear in vessel
	v2	text	vslname in vessel
	v20	text	vsloffno in vessel
	v21	text	homeport in vessel
	v22	text	vslcall in vessel
	v23	text	vslvalue in vessel
	v24	text	vslsuper in vessel
	v25	text	vslmasts in vessel
	v26	text	sailno in vessel
	v27	text	hlcolor in vessel
	v28	text	trcolor in vessel
	v29	text	slcolor in vessel
	v3	text	vslhin in vessel
	v30	text	cbcolor in vessel
	v31	text	dkcolor in vessel
	v32	text	vslmarks in vessel
	v4	text	vslmake in vessel
	v5	text	vslmodel in vessel
	v6	text	vslyear in vessel
	v7	integer	vsltons in vessel
	v8	integer	vsllefft in vessel
	v9	integer	vsllefft in vessel
	vadult	integer	adultpfd in boarding
	valgdate	date	date alongside
	valgtime	time	time alongside
	vbodate	date	boarding date
	vboday	text	boday in boarding
	vbodist	text	bodist in boarding
	vboname	text	boname in boarding
	vbono	text	boarding report number
	vboopfac	text	boopfac in boarding

Used In	Name	Type	Description
add_sbd.prg	vborate	text	borate in boarding
	vborem1	text	borem1 in boarding
	vborem2	text	borem2 in boarding
	vborem3	text	borem3 in boarding
	vbosrise	time	bsunrise in boarding
	vbosset	time	bsunset in boarding
	vbotime	time	boarding time
	vbounit	text	bounit in boarding
	vcall	text	vessel call sign
	vcbcolor	text	cabin color
	vceiling	text	ceiling in sar
	vchild	integer	childpfd in boarding
	vclouds	text	clouds in sar
	vcmeyear	text	cme decal year
	vconstr	text	coded vessel construction
	vdateos	date	on scene date
	vdecal	text	cme decal?
	vdistoff	integer	distance offshore
	vdicolor	text	deck color
	vdvmoord	date	date distressed vessel mo
	vdvmoort	time	time distressed vessel mo
	vetadate	date	on scene eta date
	vfoldno	text	sar folder number
	vhlcolor	text	hull color
	vhome	text	vessel homeport
	vimmed	text	immediate sar?
	vmarks	text	vessel unusual markings
	vmasts	text	number of vessel masts
	vmaxop	integer	comparison variable
	vmaxoper	integer	comparison variable
	vmaxown	integer	comparison variable
	vmucn	text	multi-unit case number
	vobcount	text	obscount in boarding
	vobsbody	text	obsbody in boarding
	vobscity	text	obscity in boarding
	vobslat	real	latitude position
	vobslong	real	longitude position
	vobstate	text	obsstate in boarding
	voffno	text	vessel official numbers
	vopaddr	text	operator street address
	vopcity	text	operator city address
	vopcrse	text	operator course code
	vopdob	date	operator date of birth
	vopfname	text	operator first name
	vopid	integer	operator id (system)
	voplname	text	operator last name
	vopmi	text	operator middle initial
	vopst	text	operator state address
	voptelno	text	operator telephone number
	vopzip	text	operator zip code
	voseta	time	on scene eta time
	vostatus	text	owstatus in boarding
	vostime	time	on scene time
	vowaddr	text	owner street address
	vowcity	text	owner city address
	vowdob	date	owner date of birth
	vowfname	text	owner first name
	vowlname	text	owner last name
	vowmi	text	owner middle initial
	vownid	text	owner id (system)
	vownid	integer	owner id (system)
	vowst	text	owner state address
	vowtelno	text	owner telephone number
	vowzip	text	owner zip code
	vsailno	text	sail number

Used In	Name	Type	Description
add_sbd.prg	vsardate	date	sar date
	vsarday	text	sar day of the week
	vsarlat	real	latitude position
	vsarlong	real	longitude position
	vsarnod	text	nature of distress
	vsarpob	integer	personnel on board
	vsartime	time	sar time
	vseas	text	seas in sar
	vslcolor	text	sail color
	vsltype	text	coded vessel type
	vsumoord	date	date sar unit moored
	vsumoort	time	time sar unit moored
	vsunrise	time	bsunrise in boarding
	vsunset	time	bsunset in boarding
	vsuper	text	vessel superstructure
	vswells	text	swells in sar
	vtowdate	date	date started towing
	vtowtime	time	time started towing
	vtrcolor	text	trim color
	vucn	text	unit case number
	vunit	text	sar unit name
	vuns69	text	unsafe condition 69
	vuns70	text	unsafe condition 70
	vuns71	text	unsafe condition 71
	vuns72	text	unsafe condition 72
	vuns73	text	unsafe condition 73
	vuns74	text	unsafe condition 74
	vuns75	text	unsafe condition 75
	vuns76	text	unsafe condition 76
	vuns77	text	unsafe condition 77
	vuns78	text	unsafe condition 78
	vuns79	text	unsafe condition 79
	vuwdate	date	underway date
	vuwtime	time	underway time
	vvalue	dollar	vessel value
	vviol54	text	violation code 54
	vviol55	text	violation code 55
	vviol56	text	violation code 56
	vviol57	text	violation code 57
	vviol58	text	violation code 58
	vviol59	text	violation code 59
	vviol60	text	violation code 60
	vviol61	text	violation code 61
	vviol62	text	violation code 62
	vviol63	text	violation code 63
	vviol64	text	violation code 64
	vviol65	text	violation code 65
	vviol66	text	violation code 66
	vviol67	text	violation code 67
	vviol68	text	violation code 68
	visdist	integer	visdist in sar
	vsleng	text	coded vessel engine compa
	vslft	integer	vessel length (feet)
	vslfuel	text	coded fuel compartment
	vslhin	text	vslhin in vessel
	vslhp	text	vessel horsepower
	vslhull	text	coded vessel hull materia
	vslin	integer	vessel length (inches)
	vslmake	text	vessel make
	vslmod	text	vslmodel in vessel
	vslname	text	vessel name
	vslno	text	vessel number
	vslpob	integer	personnel on board
	vslprop	text	coded vessel propulsion
	vslton	integer	vsltons in vessel

Used In	Name	Type	Description
add_sbd.prg	vvsluse	text	coded vessel use
	vvslyear	text	vessel year
	vweapons	integer	weapons in boarding
	vwinddir	text	winddir in sar
add_sut.prg	vwindspd	text	windspd in sar
	done	text	flag variable
	mrunits	text	user input
	valgdate	date	date alongside
	valgtime	time	time alongside
	vdateos	date	on scene date
	vdvmoord	date	date distressed vessel mo
	vdvmoort	time	time distressed vessel mo
	vetadate	date	on scene eta date
	vfoldno	text	sar folder number
	voseta	time	on scene eta time
	vostime	time	on scene time
	vsumoord	date	date sar unit moored
	vsumoort	time	time sar unit moored
	vtowdate	date	date started towing
	vtowtime	time	time started towing
	vunit	text	sar unit name
	vuwdate	date	underway date
	vuwtime	time	underway time
am_pint.prg	choice	text	user input
	correct	text	user input
	more	text	flag variable
	mrintel	text	user input
	reenter	text	user input
	vfname	text	intfname in perintel
	vintdate	date	pintdate in perintel
	vintdate	date	intdate in vslintel
	vintdob	date	intdob in perintel
	vintmi	text	intmi in perintel
	vintrem1	text	pintrem1 in perintel
	vintrem2	text	pintrem2 in perintel
	vintrem3	text	pintrem3 in perintel
	vlname	text	intlname in perintel
am_vint.prg	choice	text	user input
	correct	text	user input
	fixvsl	text	user input
	more	text	flag variable
	mrintel	text	user input
	reenter	text	user input
	vepic	text	epiccode in vslintel
	vintdate	date	intdate in vslintel
	vintrem1	text	vremark1 in vslintel
	vintrem2	text	vremark2 in vslintel
	vintrem3	text	vremark3 in vslintel
	vstolen	text	stolen in vslintel
boarding.prg	vvslname	text	vessel name
	datediff	integer	date difference
	enddate	date	ending date
	numrows	integer	counting variable
bomajor.prg	strtdate	date	starting date
	datdiff	integer	date difference
	easttst	real	nautical position coord.
	enddate	date	ending date
	inarea	integer	summation variable
	inpct	real	percentage
	northtst	real	nautical position coord.
	outarea	integer	summation variable
	outpct	real	percentage
	southtst	real	nautical position coord.
	strtdate	date	starting date
	tempct	real	percentage
	westtst	real	nautical position coord.



Used In	Name	Type	Description
-----	-----	-----	-----
bominor.prg	datadiff	integer	date difference
	datediff	integer	date difference
	easttst	real	nautical position coord.
	enddate	date	ending date
	inarea	integer	counting variable
	inpct	real	percentage
	northtst	real	nautical position coord.
	outarea	integer	counting variable
	outpct	real	percentage
	southtst	real	nautical position coord.
	strtdate	date	starting date
	tempcpt	real	percentage
	westtst	real	nautical position coord.
	pcik6	integer	counting variable
	after90	integer	counting variable
	before70	integer	counting variable
	cmecount	integer	counting variable
	datediff	integer	date difference
	enddate	date	ending date
	pct7175	real	percentage
	pct7679	real	percentage
	pct8081	real	percentage
	pct8283	real	percentage
	pct8485	real	percentage
	pct8687	real	percentage
	pct8889	real	percentage
	pctcme	real	percentage
	pctgt90	real	percentage
	pctlt70	real	percentage
brd_main.prg cmerpt.prg	strtdate	date	starting date
	totbrds	integer	counting variable
	vpct70	real	percentage
	vpct71	real	percentage
	vpct76	real	percentage
	vpct80	real	percentage
	vpct82	real	percentage
	vpct84	real	percentage
	vpct86	real	percentage
	vpct88	real	percentage
	vpct90	real	percentage
	yr71to75	integer	counting variable
	yr76to79	integer	counting variable
	yr80to81	integer	counting variable
	yr82to83	integer	counting variable
	yr84to85	integer	counting variable
	yr86to87	integer	counting variable
	yr88to89	integer	counting variable
	datediff	integer	date difference
	daybrd	integer	counting variable
	daysar	integer	counting variable
	enddate	date	ending date
	nitebrd	integer	counting variable
	nitesar	integer	counting variable
	pctdayb	real	percentage
	pctdays	real	percentage
	pctniteb	real	percentage
	pctnites	real	percentage
	strtdate	date	starting date
daynight.prg	totbrds	integer	total boardings
	totsars	integer	total sars

Used In	Name	Type	Description
-----	-----	-----	-----
epicdump.prg	datediff	integer	date difference
	edsc1	text	= epicdsc1 in VSLINTEL
	edsc2	text	= epicdsc2 in VSLINTEL
	edsc3	text	= epicdsc3 in VSLINTEL
	edsc4	text	= epicdsc4 in VSLINTEL
	enddate	date	ending date
	epicnum	integer	counting variable
	epictest	text	= epiccode in VSLINTEL
	pcttemp1	real	% epiccode / total vsls
	pcttemp2	real	% epiccode / total vsls
	strtdate	date	starting date
	totepics	integer	counting variable
immedsar.prg	datediff	integer	date difference
	enddate	date	ending date
	notimmed	integer	non-immediate SAR Cases
	numrows	integer	counting variable
	pctimmed	real	% immediate SAR cases
	pctimmed	real	percentage
	pctnotim	real	% non-immediate SAR Cases
	pctnotim	real	percentage
	strtdate	date	starting date
	totimmed	integer	counting variable
	totsars	integer	counting variable
inpmain.prg	pick2	integer	menu variable
int_main.prg	pick5	integer	menu variable
intelrpt.prg	code	integer	input variable
	constrds	text	= consdesc in CONSTR
	consttst	text	= constype in CONSTR
	datediff	integer	date difference
	enddate	date	ending date
	engdescr	text	= ecomptyp in ENGCOMP
	engtst	text	= ecomptype in ENGCOMP
	fdesc	text	= fcompdes in FUELCOMP
	fuelst	text	= fcomptyp in FUELCOMP
	hdesc	text	= hmatdesc in HULLMAT
	hulltst	text	= hmattyp in HULLMAT
	len2030	integer	counting variable
	len3040	integer	counting variable
	len4050	integer	counting variable
	len5060	integer	counting variable
	len6070	integer	counting variable
	len7080	integer	counting variable
	len8090	integer	counting variable
	len90100	integer	counting variable
	len<20	integer	counting variable
	len>100	integer	counting variable
	numrows	integer	counting variable
	pct2030	real	percentage
	pct3040	real	percentage
	pct4050	real	percentage
	pct5060	real	percentage
	pct6070	real	percentage
	pct7080	real	percentage
	pct8090	real	percentage
	pct9010	real	percentage
	pct90100	real	percentage
	pct<00	real	percentage
	pct<20	real	percentage
	pct<60	real	percentage
	pct<65	real	percentage
	pct<70	real	percentage
	pct<75	real	percentage
	pct<80	real	percentage
	pct<85	real	percentage
	pct<90	real	percentage

Used In	Name	Type	Description
-----	-----	-----	-----
intelrpt.prg	pct<95	real	percentage
	pct>00	real	percentage
	pct>100	real	percentage
	prdesc	text	= propdesc in BOATPROP
	proptst	text	= proptype in BOATPROP
	strtdate	date	starting date
	sumconst	integer	counting variable
	sumeng	integer	counting variable
	sumfuel	integer	counting variable
	sumhull	integer	counting variable
	sumprop	integer	counting variable
	sumtype	integer	counting variable
	sumuse	integer	counting variable
	totbrds	integer	counting variable
	totviols	integer	summation variable
	totviols	integer	counting variable
	tv1	integer	summation variable
	tv10	integer	summation variable
	tv2	integer	summation variable
	tv20	integer	summation variable
	tv3	integer	summation variable
	tv30	integer	summation variable
	tv4	integer	summation variable
	tv5	integer	summation variable
	typdesc1	text	= vtypedes in BOATTYPE
	typetest	text	= vtype in BOATTYPE
	usedesc1	text	= vusedesc in BOATUSE
	usetest	text	= vuse in BOATUSE
	vltndesc	text	= violdesc in VIOLS
	vno	text	= violno in VIOLS
	vpct2030	real	percentage
	vpct3040	real	percentage
	vpct4050	real	percentage
	vpct5060	real	percentage
	vpct6070	real	percentage
	vpct7080	real	percentage
	vpct8090	real	percentage
	vpct9010	real	percentage
	vpct<00	real	percentage
	vpct<20	real	percentage
	vpct<60	real	percentage
	vpct<65	real	percentage
	vpct<70	real	percentage
	vpct<75	real	percentage
	vpct<80	real	percentage
	vpct<85	real	percentage
	vpct<90	real	percentage
	vpct<95	real	percentage
	vpct>00	real	percentage
	vpct>100	real	percentage
	yr<1960	integer	counting variable
	yr<1965	integer	counting variable
	yr<1970	integer	counting variable
	yr<1975	integer	counting variable
	yr<1980	integer	counting variable
	yr<1985	integer	counting variable
	yr<1990	integer	counting variable
	yr<1995	integer	counting variable
	yr<2000	integer	counting variable
	yr>2000	integer	counting variable
modmain.prg	pick3	integer	menu variable

Used In	Name	Type	Description
mod_brd.prg	b1	date	bodate in boarding
	b14	text	viol54 in boarding
	b24	text	viol64 in boarding
	b45	text	bounit in boarding
	b10	text	obscity
	b11	text	obsstate in boarding
	b12	real	obslat in boarding
	b13	real	obslong in boarding
	b15	text	viol55
	b16	text	viol56 in boarding
	b17	text	viol57 in boarding
	b18	text	viol58 in boarding
	b19	text	viol59 in boarding
	b2	time	botime in boarding
	b20	text	viol61 in boarding
	b21	text	viol61 in boarding
	b22	text	viol62 in boarding
	b23	text	viol63 in boarding
	b25	text	viol65 in boarding
	b26	text	viol66 in boarding
	b27	text	viol67 in boarding
	b28	text	viol68 in boarding
	b29	text	uns69 in boarding
	b30	text	uns70 in boarding
	b31	text	uns71 in boarding
	b32	text	uns72 in boarding
	b33	text	uns73 in boarding
	b34	text	uns74 in boarding
	b35	text	uns75 in boarding
	b36	text	uns76 in boarding
	b37	text	uns77 in boarding
	b38	text	uns78 in boarding
	b39	text	uns79 in boarding
	b40	text	borem1 in boarding
	b41	text	borem2 in boarding
	b42	text	borem3 in boarding
	b43	text	boname in boarding
	b44	text	borate in boarding
	b46	text	bodist in boarding
	b47	text	boopfacc in boarding
	b48	text	boday in boarding
	b49	time	bsunrise in boarding
	b5	integer	adultpfd in boarding
	b50	time	bsunset in boarding
	b51	text	bovhin in boarding
	b52	integer	weapons in boarding
	b6	integer	childpfd in boarding
	b7	text	owstatus in boarding
	b8	text	obsbody in boarding
	b9	text	obscount in boarding
	chk hin	text	flag variable
	chk name	text	flag variable
	correct	text	user input
	er	text	user input
	er	text	flag variable
	error	text	flag variable
	more	text	flag variable
	mrvsls	text	user input
	pg	integer	counting variable
	review	text	flag variable
	vadult	integer	adultpfd in boarding
	vbodate	date	boarding date
	vboday	text	boday in boarding
	vbodist	text	bodist in boarding
	vbname	text	boname in boarding

Used In	Name	Type	Description
mod_brd.prg	vbono	text	boarding report number
	vboopfac	text	boopfac in boarding
	vborate	text	borate in boarding
	vborem1	text	borem1 in boarding
	vborem2	text	borem2 in boarding
	vborem3	text	borem3 in boarding
	vbosrise	time	bsunrise in boarding
	vbosset	time	bsunset in boarding
	vbotime	time	boarding time
	vbounit	text	bounit in boarding
	vchild	integer	childpfd in boarding
	vobcount	text	obscount in boarding
	vobsbody	text	obsbody in boarding
	vobscity	text	obscity in boarding
	vobslat	real	latitude position
	vobslong	real	longitude position
	vobstate	text	obsstate in boarding
	vostatus	text	owstatus in boarding
	vuns69	text	unsafe condition 69
	vuns70	text	unsafe condition 70
	vuns71	text	unsafe condition 71
	vuns72	text	unsafe condition 72
	vuns73	text	unsafe condition 73
	vuns74	text	unsafe condition 74
	vuns75	text	unsafe condition 75
	vuns76	text	unsafe condition 76
	vuns77	text	unsafe condition 77
	vuns78	text	unsafe condition 78
	vuns79	text	unsafe condition 79
	vviol54	text	violation code 54
	vviol55	text	violation code 55
	vviol56	text	violation code 56
	vviol57	text	violation code 57
	vviol58	text	violation code 58
	vviol59	text	violation code 59
	vviol60	text	violation code 60
	vviol61	text	violation code 61
	vviol62	text	violation code 62
	vviol63	text	violation code 63
	vviol64	text	violation code 64
	vviol65	text	violation code 65
	vviol66	text	violation code 66
	vviol67	text	violation code 67
	vviol68	text	violation code 68
	vvslhin	text	vslhin in vessel
	vvslpob	integer	personnel on board
	vweapons	integer	weapons in boarding
mod_owop.prg	chk ownr	text	flag variable
	choice	text	user input variable
	choice	integer	user input
	er	text	flag variable
	error	text	flag variable
	error	text	user input
	go	text	user input
	nmchange	text	flag variable
	op1	text	oplname in operator
	op10	text	opcouse in operator
	op11	integer	opid in operator
	op2	text	opfname in operator
	op3	text	opmi in operator
	op4	text	opaddr in operator
	op5	text	opcity in operator
	op6	text	opstate in operator
	op7	text	opzip in operator
	op8	text	optelno in operator

Used In	Name	Type	Description
mod_owop.prg	op9	date	opdob in operator
	opchange	text	flag variable
	opfound	text	flag variable
	opid	integer	operator id (system)
	ow1	text	ownlname in owners
	ow10	text	ownid in owners
	ow2	text	ownfname in owners
	ow3	text	ownmi in owners
	ow4	text	ownaddr in owners
	ow5	text	owncity in owners
	ow6	text	ownstate in owners
	ow7	text	ownzip in owners
	ow8	text	owntelno in owners
	ow9	date	owndob in owners
	owchange	text	flag variable
	owfound	text	flag variable
	vopaddr	text	operator street address
	vopcity	text	operator city address
	vopcrse	text	operator course code
	vopdob	date	operator date of birth
	vopfname	text	operator first name
	vopid	integer	operator id (system)
	voplname	text	operator last name
	vopmi	text	operator middle initial
	vopst	text	operator state address
	voptelno	text	operator telephone number
	vopzip	text	operator zip code
	vowaddr	text	owner street address
	vowcity	text	owner city address
	vowdob	date	owner date of birth
	vowfname	text	owner first name
	vowlname	text	owner last name
	vowmi	text	owner middle initial
	vownid	text	owner id (system)
	vownid	integer	owner id (system)
	vowst	text	owner state address
	vowtelno	text	owner telephone number
	vowzip	text	owner zip code
mod_sar.prg	change	text	flag variable
	correct	text	user input
	er	text	user input
	more	text	flag variable
	mrsar	text	user input
	oldfold	text	folder number
	reenter	text	flag variable
	s1	text	folderno in sar
	s10	integer	sarpob in sar
	s11	text	sarvhin in sar
	s12	real	sarlat in sar
	s13	real	sarlong in sar
	s14	integer	distoff in sar
	s15	text	immedsar in sar
	s16	text	winddir in sar
	s17	text	windspd in sar
	s18	text	visdist in sar
	s19	text	clouds in sar
	s2	text	ucn in sar
	s20	text	ceiling in sar
	s21	text	seas in sar
	s22	text	swells in sar
	s3	text	mucn in sar
	s4	date	sardate in sar
	s5	text	sarday in sar
	s6	time	sartime in sar
	s7	time	ssunrise in sar

Used In	Name	Type	Description
mod_sar.prg	s8	time	ssunset
	s9	text	sarnod in sar
	vceiling	text	ceiling in sar
	vdistoff	integer	distance offshore
	vfoldno	text	sar folder number
	vimmed	text	immediate sar?
	vmucn	text	multi-unit case number
	vsardate	date	sar date
	vsarday	text	sar day of the week
	vsarhin	text	sarvhin in sar
	vsarlat	real	latitude position
	vsarlong	real	longitude position
	vsarnod	text	nature of distress
	vsarpob	integer	personnel on board
	vsartime	time	sar time
	vseas	text	seas in sar
	vsunrise	time	bsunrise in boarding
	vsunset	time	bsunset in boarding
	vswells	text	swells in sar
	vucn	text	unit case number
	vvisdist	text	visdist in sar
	vwinddir	text	winddir in sar
	vwindspd	text	windspd in sar
mod_sut.prg	both	text	flag variable
	change	text	flag variable
	correct	text	user input
	done	text	flag variable
	foldok	text	flag variable
	more	text	flag variable
	mrsut	text	user input
	name	text	flag variable
	reenter	text	user input
	su10	date	alngdate in sarunits
	su11	time	towtime in sarunits
	su12	date	towdate in sarunits
	su13	time	dvmoored in sarunits
	su14	date	dvmdate in sarunits
	su15	time	sutmoor in sarunits
	su16	date	sutdate in sarunits
	su1	text	foldno in sarunits
	su2	text	unit in sarunits
	su3	time	uwtime in sarunits
	su4	date	uupdate
	su5	time	oseta in sarunits
	su6	date	etadate in sarunits
	su7	time	ostime in sarunits
	su8	date	osdate in sarunits
	su9	text	alngtime in sarunits
	valgdate	date	date alongside
	valgtime	time	time alongside
	vdateos	date	on scene date
	vdvmoord	date	date distressed vessel mo
	vdvmoort	time	time distressed vessel mo
	vetadate	date	on scene eta date
	vfoldno	text	sar folder number
	voseta	time	on scene eta time
	vostime	time	on scene time
	vsumoord	date	date sar unit moored
	vsumoort	time	time sar unit moored
	vtowdate	date	date started towing
	vtowtime	time	time started towing
	vunit	text	sar unit name
	vupdate	date	underway date
	vuptime	time	underway time

Used In	Name	Type	Description
mod_vhin.prg	chk hin	text	flag variable
	chk name	text	flag variable
	correct	text	user input
	correct	text	flag variable
	er	text	user input
	error	text	user input
	foundv	text	user input
	more	text	flag variable
	mrvs1s	text	user input
	vbadhin	text	vslhin in vessel
	vconstr	text	coded vessel construction
	voffno	text	vessel official numbers
	vslfound	text	flag variable
	vvs1eng	text	coded vessel engine compa
	vvs1ft	integer	vessel length (feet)
	vvs1fuel	text	coded fuel compartment
	vvs1hin	text	vslhin in vessel
	vvs1hp	text	vessel horsepower
	vvs1hull	text	coded vessel hull materia
	vvs1in	integer	vessel length (inches)
	vvs1make	text	vessel make
	vvs1mod	text	vslmodel in vessel
	vvs1name	text	vessel name
	vvs1no	text	vessel number
	vvs1 rop	text	coded vessel propulsion
	vvs1ton	integer	vsltons in vessel
	vvs1type	text	coded vessel type
	vvs1use	text	coded vessel use
	vvs1year	text	vessel year
operator.prg	datediff	integer	date difference
	enddate	date	ending date
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtdate	date	starting date
	strtltr	text	starting letter
opervs1.prg	allrecs	text	flag - all records?
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	strtltr	text	start letter
opervs1s.prg	allrecs	text	user all records input
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtdate	date	starting date
	strtltr	text	starting letter
owners.prg	datediff	integer	date difference
	enddate	date	ending date
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtdate	date	starting date
	strtltr	text	starting letter
ownvs1.prg	allrecs	text	flag --- all records?
	allrecs	text	user all records input
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtltr	text	starting letter
packdbms.prg	choice	text	user choice input
perintel.prg	datediff	integer	date difference
	enddate	date	ending date
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtdate	date	starting date
	strtltr	text	starting letter



Used In	Name	Type	Description
prs_main.prg	pick9	integer	menu variable
qrymain.prg	pick10	integer	menu variable
quer_per.prg	bohisprn	text	user input
	chk-op	text	flag variable
	count	integer	counting variable
	done	text	flag variable
	more	text	flag variable
	mrname	text	user input
	opid	integer	operator id (system)
	oprfound	text	flag variable
	owndone	text	flag variable
	ownfound	text	flag variable
	owoptest	text	flag variable
	perintpr	text	user input
	persprn	text	user input
	sarhsprn	text	user input
	searchok	text	flag variable
	status	text	flag variable
	valc	text	operator alcohol conditio
	vbodate	date	boarding date
	vbolat	real	latitude position
	vbolong	real	longitude position
	vboname	text	boname in boarding
	vbono	text	boarding report number
	vborate	text	borate in boarding
	vborem1	text	borem1 in boarding
	vborem2	text	borem2 in boarding
	vborem3	text	borem3 in boarding
	vbotime	time	boarding time
	vdate	date	intelligence date
	vdistoff	integer	distance offshore
	vepic	text	epic code
	vfname	text	first name
	vfoldno	text	sar folder number
	vimmed	text	immediate sar?
	vintdate	date	vessel intelligence date
	vlname	text	last name
	vmi	text	middle initial
	vmucn	text	multi-unit case number
	voffno	text	vessel official numbers
	vopaddr	text	operator street address
	vopc City	text	operator city address
	vopcrse	text	operator course code
	vopdob	date	operator date of birth
	vopfname	text	operator first name
	voplname	text	operator last name
	vopmi	text	operator middle initial
	vopst	text	operator state address
	voptelno	text	operator telephone number
	vopzip	text	operator zip code
	vowid	integer	owner record id number
	vperaddr	text	street address
	vperc City	text	city address
	vperdob	date	date of birth
	vpermi	text	middle initial
	vperst	text	state address
	vpertel	text	telephone number
	vperzip	text	zip code
	vpfname	text	first name
	vplname	text	last name
	vrem1	text	personnel intelligence re
	vrem2	text	personnel intelligence re
	vrem3	text	personnel intelligence re
	vsardate	date	sar date
	vsarday	text	sar day of the week

Used In	Name	Type	Description
quer_per.prg	vsarlat	real	latitude position
	vsarlong	real	longitude position
	vsarpob	integer	personnel on board
	vsartime	time	sar time
	vslprn	text	user input
	vstolen	text	stolen vessel
	vucn	text	unit case number
	vuns69	text	unsafe condition 69
	vuns70	text	unsafe condition 70
	vuns71	text	unsafe condition 71
	vuns72	text	unsafe condition 72
	vuns73	text	unsafe condition 73
	vuns74	text	unsafe condition 74
	vuns75	text	unsafe condition 75
	vuns76	text	unsafe condition 76
	vuns77	text	unsafe condition 77
	vuns78	text	unsafe condition 78
	vuns79	text	unsafe condition 79
	vviol54	text	violation code 54
	vviol55	text	violation code 55
	vviol56	text	violation code 56
	vviol57	text	violation code 57
	vviol58	text	violation code 58
	vviol59	text	violation code 59
	vviol60	text	violation code 60
	vviol61	text	violation code 61
	vviol62	text	violation code 62
	vviol63	text	violation code 63
	vviol64	text	violation code 64
	vviol65	text	violation code 65
	vviol66	text	violation code 66
	vviol67	text	violation code 67
	vviol68	text	violation code 68
	vvrem1	text	vessel intelligence remar
	vvrem2	text	vessel intelligence remar
	vvrem3	text	vessel intelligence remar
	vvslhin	text	vslhin in vessel
	vvslmake	text	vessel make
	vvslname	text	vessel name
	vvslno	text	vessel number
	vvslpob	integer	personnel on board
quer_vsl.prg	vweapons	integer	weapons in boarding
	bohisprn	text	user input
	chk-hin	text	flag variable
	chk-intl	text	flag variable
	chk-name	text	flag variable
	chk-no	text	flag variable
	chkoffno	text	flag variable
	choice	integer	user input choice
	count	integer	counting variable
	menu	text	flag variable
	more	text	flag variable
	nameok	text	flag variable
	opid	integer	operator id (system)
	owhisprn	text	user input
	owid	integer	owner id (system)
	sarhsprn	text	user input
	valc	text	operator alcohol conditio
	vbodate	date	boarding date
	vbolat	real	latitude position
	vbolong	real	longitude position
	vboname	text	boname in boarding
	vbono	text	boarding report number
	vborate	text	borate in boarding
	vboreml	text	boreml in boarding

Used In	Name	Type	Description
quer_vsl.prg	vborem2	text	borem2 in boarding
	vborem3	text	borem3 in boarding
	vbotime	time	boarding time
	vdate	date	intelligence date
	vdistoff	integer	distance offshore
	vdob	date	date of birth
	vepic	text	epic code
	vfname	text	first name
	vfoldno	text	sar folder number
	vimmed	text	immediate sar?
	vintdate	date	vessel intelligence date
	vintprn	text	user input
	vlname	text	last name
	vmi	text	middle initial
	vmucn	text	multi-unit case number
	voffno	text	vessel official numbers
	vopaddr	text	operator street address
	vopcity	text	operator city address
	vopcrse	text	operator course code
	vopdob	date	operator date of birth
	vopfname	text	operator first name
	voplname	text	operator last name
	vopmi	text	operator middle initial
	vopst	text	operator state address
	voptelno	text	operator telephone number
	vopzip	text	operator zip code
	vowaddr	text	owner street address
	vowcity	text	owner city address
	vowdob	date	owner date of birth
	vowfname	text	owner first name
	vowlname	text	owner last name
	vowmi	text	owner middle initial
	vowst	text	owner state address
	vowtelno	text	owner telephone number
	vowzip	text	owner zip code
	vrem1	text	personnel intelligence re
	vrem2	text	personnel intelligence re
	vrem3	text	personnel intelligence re
	vsardate	date	sar date
	vsarday	text	sar day of the week
	vsarlat	real	latitude position
	vsarlong	real	longitude position
	vsarpob	integer	personnel on board
	vsartime	time	sar time
	vslprn	text	flag variable
	vstolen	text	stolen vessel
	vucn	text	unit case number
	vuns69	text	unsafe condition 69
	vuns70	text	unsafe condition 70
	vuns71	text	unsafe condition 71
	vuns72	text	unsafe condition 72
	vuns73	text	unsafe condition 73
	vuns74	text	unsafe condition 74
	vuns75	text	unsafe condition 75
	vuns76	text	unsafe condition 76
	vuns77	text	unsafe condition 77
	vuns78	text	unsafe condition 78
	vuns79	text	unsafe condition 79
	vviol54	text	violation code 54
	vviol55	text	violation code 55
	vviol56	text	violation code 56
	vviol57	text	violation code 57
	vviol58	text	violation code 58
	vviol59	text	violation code 59
	vviol60	text	violation code 60

Used In	Name	Type	Description
quer_vsl.prg	vviol61	text	violation code 61
	vviol62	text	violation code 62
	vviol63	text	violation code 63
	vviol64	text	violation code 64
	vviol65	text	violation code 65
	vviol66	text	violation code 66
	vviol67	text	violation code 67
	vviol68	text	violation code 68
	vvrem1	text	vessel intelligence remar
	vvrem2	text	vessel intelligence remar
	vvrem3	text	vessel intelligence remar
	vvslhin	text	vslnhin in vessel
	vvslmake	text	vessel make
	vvslname	text	vessel name
	vvslno	text	vessel number
	vvslpob	integer	personnel on board
	vweapons	integer	weapons in boarding
rptmain.prg	pick4	integer	menu variable
sar_main.prg	pick7	integer	menu variable
sardates.prg	jundatel	date	time computation variable
sarday.prg	aprdate1	date	starting date
	aprdate2	date	ending date
	aprsar	integer	summation variable
	augdate1	date	starting date
	augdate2	date	ending date
	augsar	integer	summation variable
	change	real	percentage
	count	integer	counting variable
	decdate1	date	starting date
	decdate2	date	ending date
	decsar	integer	summation variable
	enddate	date	ending date
	febdate1	date	starting date
	febdate2	date	ending date
	febsar	integer	summation variable
	found	text	flag variable
	friday	integer	counting variable
	initdate	date	starting date
	jandatel	date	starting date
	jandate2	date	ending date
	jansar	integer	summation variable
	juldate1	date	starting date
	juldate2	date	ending date
	julsar	integer	summation variable
	jundatel	date	starting date
	jundate2	date	ending date
	junsar	integer	summation variable
	mardate1	date	starting date
	mardate2	date	ending date
	marsar	integer	summation variable
	maydate1	date	starting date
	maydate2	date	ending date
	maysar	integer	summation variable
	monday	integer	counting variable
	new	integer	this year's sar cases
	novdate1	date	starting date
	novdate2	date	ending date
	novsar	integer	summation variable
	numrows	integer	counting variable
	numyears	integer	counting variable
	octdate1	date	starting date
	octdate2	date	ending date
	octsar	integer	summation variable
	old	integer	previous year's sar cases
	pctapr	real	percentage

Used In	Name	Type	Description
sarday.prg	pctaug	real	percentage
	pctchang	real	percentage
	pctdec	real	percentage
	pctfeb	real	percentage
	pctfri	real	percentage
	pctjan	real	percentage
	pctjul	real	percentage
	pctjun	real	percentage
	pctmar	real	percentage
	pctmay	real	percentage
	pctmon	real	percentage
	pctnov	real	percentage
	pctoct	real	percentage
	pctsat	real	percentage
	pctsep	real	percentage
	pctsun	real	percentage
	pctthu	real	percentage
	pcttue	real	percentage
	pctwed	real	percentage
	sar00	integer	counting variable
	sar01	integer	counting variable
	sar02	integer	counting variable
	sar03	integer	counting variable
	sar04	integer	counting variable
	sar05	integer	counting variable
	sar06	integer	counting variable
	sar07	integer	counting variable
	sar08	integer	counting variable
	sar09	integer	counting variable
	sar10	integer	counting variable
	sar11	integer	counting variable
	sar12	integer	counting variable
	sar81	integer	counting variable
	sar82	integer	counting variable
	sar83	integer	counting variable
	sar84	integer	counting variable
	sar85	integer	counting variable
	sar86	integer	counting variable
	sar87	integer	counting variable
	sar88	integer	counting variable
	sar89	integer	counting variable
	sar90	integer	counting variable
	sar91	integer	counting variable
	sar92	integer	counting variable
	sar93	integer	counting variable
	sar94	integer	counting variable
	sar95	integer	counting variable
	sar96	integer	counting variable
	sar97	integer	counting variable
	sar98	integer	counting variable
	sar99	integer	counting variable
	saturday	integer	counting variable
	sepdate1	date	starting date
	sepdate2	date	ending date
	sepsar	integer	summation variable
	sum1	integer	summation variable
	sum10	integer	summation variable
	sum11	integer	summation variable
	sum12	integer	summation variable
	sum2	integer	summation variable
	sum20	integer	summation variable
	sum3	integer	summation variable
	sum4	integer	summation variable
	sum5	integer	summation variable
	sum6	integer	summation variable

Used In	Name	Type	Description
sarday.prg	sunday	integer	counting variable
	thursday	integer	counting variable
	totsars	integer	summation variable
	tuesday	integer	counting variable
	wednesday	integer	counting variable
	year	integer	saryear
	yr1981	date	starting date
	yr1981a	date	ending date
	yr1982	date	starting date
	yr1982a	date	ending date
	yr1983	date	starting date
	yr1983a	date	ending date
	yr1984	date	starting date
	yr1984a	date	ending date
	yr1985	date	starting date
	yr1985a	date	ending date
	yr1986	date	starting date
	yr1986a	date	ending date
	yr1987	date	starting date
	yr1987a	date	ending date
	yr1988	date	starting date
	yr1988a	date	ending date
	yr1989	date	starting date
	yr1989a	date	ending date
	yr1990	date	starting date
	yr1990a	date	ending date
	yr1991	date	starting date
	yr1991a	date	ending date
	yr1992	date	starting date
	yr1992a	date	ending date
	yr1993	date	starting date
	yr1993a	date	ending date
	yr1994	date	starting date
	yr1994a	date	ending date
	yr1995	date	starting date
	yr1995a	date	ending date
	yr1996	date	starting date
	yr1996a	date	ending date
	yr1997	date	starting date
	yr1997a	date	ending date
	yr1998	date	starting date
	yr1998a	date	ending date
	yr1999	date	starting date
	yr1999a	date	ending date
	yr2000	date	starting date
	yr2000a	date	ending date
	yr2001	date	starting date
	yr2001a	date	ending date
	yr2002	date	starting date
	yr2002a	date	ending date
	yr2003	date	starting date
	yr2003a	date	ending date
	yr2004	date	starting date
	yr2004a	date	ending date
	yr2005	date	starting date
	yr2005a	date	ending date
	yr2006	date	starting date
	yr2006a	date	ending date
	yr2007	date	starting date
	yr2007a	date	ending date
	yr2008	date	starting date
	yr2008a	date	ending date
	yr2009	date	starting date
	yr2009a	date	ending date
	yr2010	date	starting date

Used In	Name	Type	Description
-----	-----	-----	-----
sarday.prg	yr2010a	date	ending date
	yr2011	date	starting date
	yr2011a	date	ending date
	yr2012	date	starting date
	yr2012a	date	ending date
sardump.prg	yrtest1	integer	leap year test
	yrtest2	integer	leap year test
	datediff	integer	date difference
	enddate	date	ending date
	numrows	integer	counting variable
sarmajor.prg	strtdate	date	starting date
	datediff	integer	date difference
	easttst	real	nautical position coord.
	enddate	date	ending date
	gridcnt	integer	counting variable
	inarea	integer	counting variable
	inpct	real	percentage
	northtst	real	nautical position coord.
	numrows	integer	counting variable
	outarea	integer	counting variable
	outpct	real	percentage
	southtst	real	nautical position coord.
	strtdate	date	starting date
	tempct	real	percentage
	totsars	integer	counting variable
sarminor.prg	westtst	real	nautical position coord.
	datediff	integer	date difference
	easttst	real	nautical position coord.
	enddate	date	ending date
	gridcnt	integer	counting variable
	inarea	integer	counting variable
	inpct	real	percentage
	northtst	real	nautical position coord.
	numrows	integer	counting variable
	outarea	integer	counting variable
	outpct	real	percentage
	southtst	real	nautical position coord.
	strtdate	date	starting date
	tempct	real	percentage
	westtst	real	nautical position coord.
sarsmbt.prg	datediff	integer	date difference
	enddate	date	starting date
	inpct	real	percentage
	inpcttmp	real	percentage
	inside	integer	summation variable
	numrows	integer	counting variable
	outpct	real	percentage
	outpcttm	real	percentage
	outside	integer	summation variable
	strtdate	date	starting date
	totsars	integer	counting variable
	pick1	integer	menu variable
	algavg	real	average alongside time
	algtimes	integer	counting variable
	datediff	integer	date difference
sarsys.prg sartimes.prg	datedour	real	time computation variable
	enddate	date	ending date
	maxaltim	real	maximum alongside time
	maxostim	real	maximum on scene time
	maxshtim	real	maximum search time
	maxtttim	real	maximum total case time
	maxtwtim	real	maximum towing time
	minaltim	real	minimum alongside time
	minostim	real	minimum on scene time
	minshtim	real	minimum search time

Used In	Name	Type	Description
-----	-----	-----	-----
sartimes.prg	mintttim	real	minimum total case time
	mintwtim	real	minimum towing time
	oscavg	real	average on scene time
	osdate	date	on scene date
	ossum	real	summation variable
	ostime	time	on scene time
	ostimes	integer	counting variable
	schavg	real	average search time
	schtimes	integer	counting variable
	strtdate	date	starting date
	sutdate	date	sar unit moored date
	sutmoor	time	sar unit moored time
	test	real	comparison variable
	timeadd	real	time computation variable
	timehour	real	time computation variable
	totavg	real	average total case time
	totsum	real	summation variable
	tottimes	integer	counting variable
	towavg	real	average towing time
	towsum	real	summation variable
	towtimes	integer	counting variable
	uwnate	date	underway date
	uwnate	time	underway time
smboatrp.prg	datediff	integer	date difference
	enddate	date	ending date
	inside	integer	counting variable
	obslat	real	nautical position coord.
	obslong	real	nautical position coord.
	outside	integer	counting variable
	strtdate	date	starting date
	totbrds	integer	counting variable
startup.prg	chances	integer	chances to logon
	count	integer	counting variable
	username	text	user name input
	userpass	text	user password
	validusr	text	flag variable
utlmain.prg	pick11	integer	menu variable
vessel.prg	anytype	text	flag variable
	choice	text	user choice input
	endltr	text	ending letter
	legalch	text	flag variable
	legaltyp	text	flag variable
	legaluse	text	flag variable
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtltr	text	starting letter
	typchoic	text	user type choice
	typetest	text	vessel type
	usechoic	text	user vessel use choice
	usetest	text	vessel use
violfreq.prg	datediff	integer	date difference
	enddate	date	ending date
	pct54	real	percentage
	pct54tmp	real	percentage
	pct55	real	percentage
	pct55tmp	real	percentage
	pct56	real	percentage
	pct56tmp	real	percentage
	pct57	real	percentage
	pct57tmp	real	percentage
	pct58	real	percentage
	pct58tmp	real	percentage
	pct59	real	percentage
	pct59tmp	real	percentage
	pct60	real	percentage



Used In	Name	Type	Description
-----	-----	-----	-----
violfreq.prg	pct60tmp	real	percentage
	pct61	real	percentage
	pct61tmp	real	percentage
	pct62	real	percentage
	pct62tmp	real	percentage
	pct63	real	percentage
	pct63tmp	real	percentage
	pct64	real	percentage
	pct64tmp	real	percentage
	pct65	real	percentage
	pct65tmp	real	percentage
	pct66	real	percentage
	pct66tmp	real	percentage
	pct67	real	percentage
	pct67tmp	real	percentage
	pct68	integer	percentage
	pct68tmp	real	percentage
	pct69	real	percentage
	pct69tmp	real	percentage
	pct70	real	percentage
	pct70tmp	real	percentage
	pct71	real	percentage
	pct71tmp	real	percentage
	pct72	real	percentage
	pct72tmp	real	percentage
	pct73	real	percentage
	pct73tmp	real	percentage
	pct74	real	percentage
	pct74tmp	real	percentage
	pct75	real	percentage
	pct75tmp	real	percentage
	pct76	real	percentage
	pct76tmp	real	percentage
	pct77	real	percentage
	pct77tmp	real	percentage
	pct78	real	percentage
	pct78tmp	real	percentage
	pct79	real	percentage
	pct79tmp	real	percentage
	strtdate	date	starting date
	uns69s	integer	counting variable
	uns70s	integer	counting variable
	uns71s	integer	counting variable
	uns72s	integer	counting variable
	uns73s	integer	counting variable
	uns74s	integer	counting variable
	uns75s	integer	counting variable
	uns76s	integer	counting variable
	uns77s	integer	counting variable
	uns78s	integer	counting variable
	uns79s	integer	counting variable
	unstot1	integer	summation variable
	unstot2	integer	summation variable
	unstot3	integer	summation variable
	unstot4	integer	summation variable
	unstot5	integer	summation variable
	unstot6	integer	summation variable
	unstot7	integer	summation variable
	unstotal	integer	total unsafe conditions
	viol54s	integer	counting variable
	viol55s	integer	counting variable
	viol56s	integer	counting variable
	viol57s	integer	counting variable
	viol58s	integer	counting variable
	viol59s	integer	counting variable

Used In	Name	Type	Description
violfreq.prg	viol60s	integer	counting variable
	viol61s	integer	counting variable
	viol62s	integer	counting variable
	viol63s	integer	counting variable
	viol64s	integer	counting variable
	viol65s	integer	counting variable
	viol66s	integer	counting variable
	viol67s	integer	counting variable
	viol68s	integer	counting variable
	vtot1	integer	summation variable
	vtot10	integer	summation variable
	vtot11	integer	summation variable
	vtot12	integer	summation variable
	vtot13	integer	summation variable
	vtot2	integer	summation variable
	vtot3	integer	summation variable
	vtot4	integer	summation variable
	vtot5	integer	summation variable
	vtot6	integer	summation variable
	vtot7	integer	summation variable
	vtot8	integer	summation variable
	vtot9	integer	summation variable
	vtotal	integer	total violations
vsl_main.prg	pick8	integer	menu variable
vsloper.prg	allrecs	text	user all records input
	allrecs	text	flag - all records?
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
vslowner.prg	strtltr	text	starting letter
	allrecs	text	flag - all records?
	allrecs	text	user all records input
	endltr	text	ending letter
	ltrdiff	integer	letter difference
	numrows	integer	counting variable
	strtltr	text	starting letter

*Data Entry / Edit Rules*

RULE 1 vslyear IN vessel fail

or vslyear IN vessel ge 0

Message:\*\*\* Invalid Vessel Year \*\*\*

RULE 2 vslhp IN vessel fail

or vslhp IN vessel ge 0

Message:\*\*\* Invalid Vessel Horsepower \*\*\*

RULE 3 vsluse IN vessel fail

or vsluse IN vessel eqa vuse IN boatuse

Message:\*\*\* Invalid Vessel Use \*\*\*

RULE 4 vsltype IN vessel fail

or vsltype IN vessel eqa vtype IN boattype

Message:\*\*\* Invalid Vessel Type \*\*\*

RULE 5 vslprop IN vessel fail

or vslprop IN vessel eqa proptype IN boatprop

Message:\*\*\* Invalid Vessel Propulsion \*\*\*

RULE 6 vslhull IN vessel fail

or vslhull IN vessel eqa hmatttype IN hullmat

Message:\*\*\* Invalid Vessel hull Type \*\*\*

RULE 7 vsleng IN vessel fail

or vsleng IN vessel eqa ecomptyp IN engcomp

Message:\*\*\* Invalid Engine Compartment Type \*\*\*

RULE 8 vslfuel IN vessel fail

or vslfuel IN vessel eqa fcomptyp IN fuelcomp

Message:\*\*\* Invalid Fuel Compartment Type \*\*\*

RULE 9 vslconst IN vessel fail  
or vslconst IN vessel eqa constype IN constr  
Message:\*\*\* Invalid Vessel Construction \*\*\*

RULE 10 cmeyear IN vessel fail  
or cmeyear IN vessel ge 0  
Message:\*\*\* Invalid CME Decal Year \*\*\*

RULE 11 vslmasts IN vessel fail  
or vslmasts IN vessel ge 0  
Message:\*\*\* Invalid No. Vessel Masts \*\*\*

RULE 12 sailno IN vessel fail  
or sailno IN vessel ge 0  
Message:\*\*\* Invalid Sail Number \*\*\*

RULE 13 hlcolor IN vessel eqa shade IN colors  
and trcolor IN vessel eqa shade IN colors  
and slcolor IN vessel eqa shade IN colors  
and cbcolor IN vessel eqa shade IN colors  
and dkcolor IN vessel eqa shade IN colors  
Message:\*\*\* Invalid Color Entry \*\*\*

RULE 14 vsltons IN vessel  $\geq 0$   
Message:\*\*\* Invalid Vessel Tons \*\*\*

RULE 15 vsllenft IN vessel  $\geq 0$   
Message:\*\*\* Invalid Vessel Length (ft) \*\*\*

RULE 16 vsllenin IN vessel  $\geq 0$   
and vsllenin IN vessel  $\leq 12$   
Message:\*\*\* Invalid Vessel Length (in) \*\*\*

RULE 17 vslvalue IN vessel  $\geq 0$   
Message:\*\*\* Invalid Vessel Value \*\*\*

RULE 18 cmedecal IN vessel fail  
or cmedecal IN vessel = Y  
or cmedecal IN vessel = N  
Message:\*\*\* Invalid CME Decal Entry [Y/N] \*\*\*

RULE 19 opstate IN operator fail  
or opstate IN operator eqa abbrev IN states  
or opstate IN operator eqa symbol IN nations  
Message:\*\*\* Invalid Operator State/Nation \*\*\*

RULE 20 opzip IN operator fail  
or opzip IN operator > = 0  
Message:\*\*\* Invalid Operator Zip Code \*\*\*

RULE 21 optelno IN operator fail  
or optelno IN operator > = 0  
Message:\*\*\* Invalid Operator Phone Number \*\*\*

RULE 22 opcourse IN operator fail  
or opcourse IN operator eqa coursetp IN courses  
Message:\*\*\* Invalid Operator Course Code \*\*\*

RULE 23 ownzip IN owners fail  
or ownzip IN owners > = 0  
Message:\*\*\* Invalid Owner Zip Code \*\*\*

RULE 24 ownstate IN owners fail  
or ownstate IN owners eqa symbol IN nations  
or ownstate IN owners eqa abbrev IN states  
Message:\*\*\* Invalid Owner State/Nation \*\*\*

RULE 25 owntelno IN owners fail  
or owntelno IN owners > = 0  
Message:\*\*\* Invalid Owner Phone Number \*\*\*

RULE 26 sarday IN sar fail  
or sarday IN sar eqa dayabbr IN days  
Message:\*\*\* Invalid SAR Day of Week \*\*\*

RULE 27 sarpob IN sar  $\geq 0$   
Message:\*\*\* Invalid SAR POB \*\*\*

RULE 28 sarlat IN sar  $\geq 0.0$   
and sarlat IN sar  $\leq 90.0$   
Message:\*\*\* Invalid SAR Latitude \*\*\*

RULE 29 sarlong IN sar  $\geq 0.0$   
and sarlong IN sar  $\leq 180.0$   
Message:\*\*\* Invalid SAR Longitude \*\*\*

RULE 30 offshore IN sar  $\geq 0$   
Message:\*\*\* Invalid Distance Offshore \*\*\*

RULE 31 immedsar IN sar = Y  
or immedsar IN sar = N  
or immedsar IN sar fail  
Message:\*\*\* Invalid Immediate SAR Entry [Y/N] \*\*

RULE 32 winddir IN sar  $\geq 000$   
and winddir IN sar  $< 360$   
Message:\*\*\* Invalid Wind Direction \*\*\*

RULE 33 windspd IN sar  $\geq 0$   
Message:\*\*\* Invalid Wind Speed \*\*\*

RULE 34 visdist IN sar  $\geq 0$   
Message:\*\*\* Invalid Visual Distance \*\*\*

RULE 35 clouds IN sar  $\geq 0$   
and clouds IN sar  $\leq 10$   
Message:\*\*\* Invalid Cloud Percentage (Tenths) \*\*

RULE 36 ceiling IN sar  $\geq 0$   
Message:\*\*\* Invalid Cloud Ceiling (Feet) \*\*\*

RULE 37 seas IN sar  $\geq 0$   
Message:\*\*\* Invalid Sea Height (Feet) \*\*\*

RULE 38 swells IN sar  $\geq 0$   
Message:\*\*\* Invalid Swell Height (Feet) \*\*\*

RULE 39 epiccode IN vslintel eqa epicno IN epic  
or epiccode IN vslintel fail  
Message:\*\*\* Invalid EPIC Code Entry \*\*\*

RULE 40 folderno IN sar nea folderno IN sar  
Message:\*\*\* Duplicate SAR Folder Number \*\*\*

RULE 41 bono IN boarding nea bono IN boarding  
Message:\*\*\* Duplicate Boarding Report Number \*\*\*

RULE 42 vslpob IN boarding  $\geq 0$   
Message:\*\*\* Invalid Boarding POB \*\*\*

RULE 43 adultpfd IN boarding  $\geq 0$   
Message:\*\*\* Invalid Adult PFD/POB \*\*\*

RULE 44 childpfd IN boarding  $\geq 0$   
Message:\*\*\* Invalid Child PFD/POB \*\*\*

RULE 45 owstatus IN boarding eqa ostattyp IN status  
or owstatus IN boarding fail  
Message:\*\*\* Invalid Owner Status \*\*\*

RULE 46 obsstate IN boarding eqa abbrev IN states  
or obsstate IN boarding eqa symbol IN nations  
or obsstate IN boarding fail

Message:\*\*\* Invalid Boarding State/Nation \*\*\*

RULE 47 obslat IN boarding  $\geq 0.0$   
and obslat IN boarding  $\leq 90.0$

Message:\*\*\* Invalid Boarding Latitude \*\*\*

RULE 48 obslong IN boarding  $\geq 0.0$   
and obslong IN boarding  $\leq 180.0$

Message:\*\*\* Invalid Boarding Longitude \*\*\*

RULE 49 boday IN boarding eqa dayabbr IN days  
or boday IN boarding fail

Message:\*\*\* Invalid Boarding Day of Week \*\*\*

RULE 50 weapons IN boarding  $\geq 0$

Message:\*\*\* Invalid Number of Weapons \*\*\*

RULE 51 bodist IN boarding eqa distno IN district  
or bodist IN boarding fail

Message:\*\*\* Invalid Boarding District \*\*\*

RULE 52 vslhin IN vessel nea vslhin IN vessel

Message:\*\*\* Error: Duplicate Vessel HIN \*\*\*



## APPENDIX D

### MODULE FUNCTIONAL DESCRIPTIONS

The US Coast Guard Group Monterey SARELTIS prototype design includes eleven sets of application programs that access one central relational database. These sets of application programs include:

- SARSYS.PRG -- Main Menu Programs
- SENTRY.PRG -- Data Entry Menu and Programs
- MODIFY.PRG -- Data Modification Menu and Programs
- SREPORTS.PRG -- Reports Master Menu Programs
- INTRPTS.PRG -- Intelligence Reports Menu and Programs
- BRDRPTS.PRG -- Boarding Reports Menu and Programs
- SARRPTS.PRG -- Sar Reports Menu and Programs
- VSLRPTS.PRG -- Vessel Reports Menu and Programs
- PRSRPTS.PRG -- Personnel Reports Menu and Programs
- SQUERY.PRG -- Database Query Menu and Programs
- SUTILITY.PRG -- Utilities Menu and Programs

Each application program set consists of a master menu block and numerous modules that perform specific functions. The modules and menus are called Command and Menu files within the R:base 5000 programming language. Functional descriptions of each module, grouped by application program set, are contained in this appendix.

#### 1. SARSYS.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)  
MAIN MENU and STARTUP APPLICATION

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

\*(\*\*\*\*\*

Program: Access Input Module  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the input master menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Access Modify Module  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the modify master menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Access Query Module  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the query master menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Access Reports Module  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the reports master menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Access Utilities Module  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the utility master menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Access Ad Hoc Module  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program allows the user to exit the  
menus to the R:base 5000 command prompt to  
execute ad hoc queries.  
  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

## 2. SENTRY.PRG

\*(\*\*\*\*\*)

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

INPUT MASTER MENU and INPUT PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*)

Program: Add Sar  
Author: H R Lang and J D Allen  
Date Written: July 1987  
Description: This program allows the user to input  
sar case information.  
Tables Used: vessel, sar, owners, operators, owvsl, opvsl  
Temp Tables: none  
Reports Used: none  
Forms Used: sarform1, sarform2, sarform3, sarform4,  
sarform5, sarform6, sarform7, sarform8,  
sarform9

\*(\*\*\*\*\*)

Program: Add Sar with Boarding  
Author: H R Lang and J D Allen  
Date Written: July 1987  
Description: This program allows the user to enter sar  
and boarding information.  
Tables Used: boarding, vessel, owners, operator, owvsl,  
opvsl, sar  
Temp Tables: none  
Reports Used: none  
Forms Used: cg4100a1, cg4100a2, cg4100a3, cg4100a4,  
cg4100a5, cg4100a6, cg4100a7, cg4100a8,  
cg4100a9, sbdform1, sarform1, sarform8,  
sarform9, sarform5

\*(\*\*\*\*\*)

Program: Add Sar Units  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to input sar  
unit data.  
Tables Used: sar, sarunits  
Temp Tables: none  
Reports Used: none  
Forms Used: sarform8

\*(\*\*\*\*\*)

\*(\*\*\*\*\*

Program: Add Boarding  
Author: H R Lang and J D Allen  
Date Written: July 1987  
Description: This program allows the user to input  
boarding information.  
Tables Used: boarding, vessel, owners, operator, owvsl,  
opvsl,  
Temp Tables: none  
Reports Used: none  
Forms Used: cg4100a1, cg4100a2, cg4100a3, cg4100a4,  
cg4100a5, cg4100a6, cg4100a7, cg4100a8,  
cg4100a9, sarform5

\*(\*\*\*\*\*

Program: Add Owner  
Author: H R Lang and J D Allen  
Date Written: July 1987  
Description: This program allows the user to input  
additional owner information.  
Tables Used: vessel, owners, owvsl  
Temp Tables: none  
Reports Used: none  
Forms Used: ownrmod1, ownrmod2

\*\*\*\*\*)

### 3. MODIFY.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)  
MODIFY MAIN MENU and APPLICATIONS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

Program: Modify Sar  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
sar information in the database.  
Tables Used: sar, vessel  
Temp Tables: none  
Reports Used: none  
Forms Used: sarmod

\*(\*\*\*\*\*

\*(\*\*\*\*\*

Program: Modify Boarding  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
boarding information in the database.  
Tables Used: boarding, vessel  
Temp Tables: none  
Reports Used: none  
Forms Used: bomod1, bomod2, bomod3

\*(\*\*\*\*\*

Program: Modify Vessel  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
vessel information in the database.  
Tables Used: vessel  
Temp Tables: none  
Reports Used: none  
Forms Used: vslmod1, vslmod2

\*(\*\*\*\*\*

Program: Modify Owner and Operator  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
owner and operator information in the  
database.  
Tables Used: owners, operator, opown  
Temp Tables: none  
Reports Used: none  
Forms Used: ownrmod1, ownrmod2, opermod1, opermod2

\*(\*\*\*\*\*

Program: Modify Sar Unit  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
sar unit data in the database.  
Tables Used: sar, sarunits  
Temp Tables: none  
Reports Used: none  
Forms Used: sunitmod

\*(\*\*\*\*\*

Program: Modify Vessel HIN  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
vessel hull identification numbers in  
the database.  
Tables Used: vessel, sar, boarding, owvs1, opvs1  
Temp Tables: none  
Reports Used: none  
Forms Used: vhinform

\*(\*\*\*\*\*

\*(\*\*\*\*\*

Program: Add and Modify Vessel Intelligence  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to input  
and modify vessel intelligence  
information.  
Tables Used: vslintel  
Temp Tables: none  
Reports Used: none  
Forms Used: vintform

\*(\*\*\*\*\*

Program: Add and Modify Personnel Intelligence  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to input  
and modify personnel intelligence  
information.  
Tables Used: perintel  
Temp Tables: none  
Reports Used: none  
Forms Used: pintform

\*\*\*\*\*)

#### 4. SREPORTS.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)  
REPORTS MAIN MENU APPLICATION PROGRAM

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

Program: Access Intelligence Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the intelligence reports  
master menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Access Boarding Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the boarding reports  
master menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

```

*(*****
Program:      Access Sar Reports
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program calls the SAR reports master
              menu and application programs.
Tables Used:  none
Temp Tables:  none
Reports Used: none
Forms Used:   none

*(*****
Program:      Access Vessel Reports
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program calls the vessel reports
              master menu and application programs.
Tables Used:  none
Temp Tables:  none
Reports Used: none
Forms Used:   none

*(*****
Program:      Access Personnel Reports
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program calls the personnel reports
              master menu and application programs.
Tables Used:  none
Temp Tables:  none
Reports Used: none
Forms Used:   none

*****
5. INTRPTS.PRG

*(*****
                US COAST GUARD GROUP MONTEREY
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
                INTELLIGENCE SYSTEM (SARELTIS)
                INTELLIGENCE REPORTS MENU and APPLICATION PROGRAMS

                Author:  Jon D. Allen, LT, USCG
                        Heidi R. Lang, LT, USN
                        AUGUST 1987

*(*****
Program:      Personnel Intelligence Dump Program
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a listing by date and
              by alphabetic search of those personnel in
              the table PERINTEL (personnel intelligence).
Tables Used:  perintel
Temp Tables:  persum
Reports Used: perintel
Forms Used:   none

*(*****

```

\*(\*\*\*\*\*

Program: EPIC Intelligence Analysis  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: Performs a dump of all vessels in the  
VSLINTEL table within a specified time  
period. Four reports are generated  
providing listings by EPIC Code, by  
stolen vessels, and by intelligence  
remarks, and a frequency breakdown  
and analysis of EPIC Codes.  
  
Tables Used: vslintel  
Temp Tables: epicsum, stolesum, intelsum, epictmpl,  
epictmp2, epictmp  
Reports Used: epicsum, stolesum, intelsum, epicrpt  
Forms Used: none

\*(\*\*\*\*\*

Program: Violation Vessel Profile Intelligence  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program examines vessel boardings to  
create a profile of vessel which violate  
specific laws during a specified time period.  
  
Tables Used: boarding, vessel, viols, boattype, boatuse,  
constr, engcomp, fuelcomp, hullmat, boatprop  
Temp Tables: bosum, vslsum, violsum, vslmo,  
summary1, summary2, summary3, summary4,  
summary5, summary6, summary7, temp  
Reports Used: vtypemo, vusemo, vconstmo, vengmo,  
vfuelmo, vhullmo, vpropmo, vlenftmo,  
vyearmo  
Forms Used: none

\*\*\*\*\*)

## 6. BRDRPTS.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)  
BOARDING REPORTS MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

Program: Violation / Unsafe Condition Frequency Analysis  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis  
of boarding violations and unsafe conditions  
within a specified time period.  
  
Tables Used: boarding  
Temp Tables: frqchart, temp  
Reports Used: violfreq, unsfreq  
Forms Used: none

\*(\*\*\*\*\*



\*(\*\*\*\*\*

Program: Boarding Summary Listing Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a listing of the BOARDING table during a specified time period. The report is sorted by date before being printed.  
  
Tables Used: boarding  
Temp Tables: bosum  
Reports Used: boarding  
Forms Used: none

\*(\*\*\*\*\*

Program: Boarding Major Grid Area Frequency Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of Boardings to determine percentage of cases which occur in areas specified by coordinates found in the MAJAREA table during a specified time period.  
  
Tables Used: majarea, boarding  
Temp Tables: bosum, positfrq  
Reports Used: bomajor  
Forms Used: none

\*(\*\*\*\*\*

Program: Boarding Minor Grid Area Frequency Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of Boardings to determine percentage of cases which occur in a specified location defined in the MINAREA table during a specified time period.  
  
Tables Used: boarding, minarea  
Temp Tables: bosum, positfrq  
Reports Used: bominor  
Forms Used: none

\*(\*\*\*\*\*

Program: Boarding Small Boat Area Frequency Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of Boardings to determine percentage of cases which occur in the small boat operating as defined by Coast Guard Group Monterey's OPLAN during a specified time period.  
  
Tables Used: boarding  
Temp Tables: temp, bosum  
Reports Used: smboatrp  
Forms Used: none

\*(\*\*\*\*\*

```

*(*****
Program:      Courtesy Motorboat Examinations (CME's)
              Statistical Analysis
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of vessels that were boarded to determine
              the frequency of CME's and their year of
              issue during a specified time period.
Tables Used:  boarding, vessel
Temp Tables:  bosum, vslsum, bovsisum, temp
Reports Used: cmerpt
Forms Used:   none

```

```

*(*****
Program:      Daytime vs. Nighttime Frequency Analysis
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of SAR cases and Boardings to determine
              percentage of cases which occur in the
              daytime vs those that occur at night during
              a specified time period.
Tables Used:  sar, boarding
Temp Tables:  sarsum, bosum, temp
Reports Used: daynight
Forms Used:   none

```

\*\*\*\*\*)

## 7. SARRPTS.PRG

```

*(*****
              US COAST GUARD GROUP MONTEREY
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
              INTELLIGENCE SYSTEM (SARELTIS)
              SAR REPORTS MENU and APPLICATION PROGRAMS

              Author:   Jon D. Allen, LT, USCG
                      Heidi R. Lang, LT, USN
                      AUGUST 1987

```

```

*(*****
Program:      SAR Major Grid Area Frequency Analysis
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of SAR cases to determine percentage of
              cases which occur in specified locations in
              the table MAJAREA during a specified time
              period.
Tables Used:  majarea, sar
Temp Tables:  sarsum, positfrq
Reports Used: sarmajor
Forms Used:   none

```

\*\*\*\*\*)

\*(\*\*\*\*\*

Program: SAR Minor Grid Area Frequency Analysis  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of SAR cases to determine percentage of cases which occur in locations specified by coordinates contained in the table MINAREA during a specified time period.  
  
Tables Used: sar, minarea  
Temp Tables: sarsum, positfrq  
Reports Used: sarminor  
Forms Used: none

\*(\*\*\*\*\*

Program: SAR Case Small Boat Area Frequency Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of SAR Cases to determine percentage of cases which occur in the small boat operating as defined by Coast Guard Group Monterey's OPLAN during a specified time period.  
  
Tables Used: sar  
Temp Tables: temp, sarsum  
Reports Used: sarsmbt  
Forms Used: none

\*(\*\*\*\*\*

Program: SAR Case Units Time Expended Frequency  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of SAR cases to determine total time expended, time to being on scene, time to being alongside, time involved in searches, and time involved in towing. These times are analyzed to produce totals, averages, minimums, and maximums for a specific time period.  
  
Tables Used: sarunits  
Temp Tables: sartime1, sartime2, sartime3, sartime4, sartime5, temp  
Reports Used: sartimes  
Forms Used: none

\*(\*\*\*\*\*

Program: SAR Days, SAR Months, SAR Years Frequency Analysis  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of SAR cases to determine percentage of cases which occurred on specific days of the week, months of the year and years during a specified time period.  
  
Tables Used: sar  
Temp Tables: sarsum1, sarstat, sarsum, temp  
Reports Used: sardates, sardays  
Forms Used: none

\*(\*\*\*\*\*

\*(\*\*\*\*\*

Program: Daytime vs. Nighttime Frequency Analysis  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of SAR cases and Boardings to determine percentage of cases which occur in the daytime vs those that occur at night during a specified time period.  
Tables Used: sar, boarding  
Temp Tables: sarsum, bosum, temp  
Reports Used: daynight  
Forms Used: none

\*(\*\*\*\*\*

Program: SAR Summary Listing Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a dump of the table SAR of those SAR cases that occurred during a specified time period. The listing is sorted by date prior to being printed.  
Tables Used: sar  
Temp Tables: sarsum  
Reports Used: sar  
Forms Used: none

\*(\*\*\*\*\*

Program: Immediate SAR Frequency Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a statistical analysis of SAR cases to determine percentage of cases which are of immediate nature during a specified time period.  
Tables Used: sar  
Temp Tables: sarsum, temp  
Reports Used: immedsar  
Forms Used: none

\*\*\*\*\*)

## 8. VSLRPTS.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)  
VESSEL REPORTS MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

\*(\*\*\*\*\*

Program: Vessel Summary Listing Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a dump of the VESSEL table. Listing entries are selected by vessel type, vessel use, and by an alphabetic search.  
Tables Used: vessel, boattype, boatuse  
Temp Tables: vslsum, vslsum1, vslsum2  
Reports Used: vessel  
Forms Used: none

\*(\*\*\*\*\*

Program: Vessel - Owner Dump Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a listing sorted by vessel name of those vessels which are owned by a specified group of owners. All of the vessels in the VESSEL table may be selected or only a group specified in an alphabetic search.  
Tables Used: owvsl, owners, vessel  
Temp Tables: ownvsls, ownvsls1, ownvsls2  
Reports Used: vsloowner  
Forms Used: none

\*(\*\*\*\*\*

Program: Vessel - Operator Dump Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a listing sorted by vessel name of those vessels which are operated by a specified group of operators. The entire list of vessels may be printed or a specified group based on an alphabetic search.  
Tables Used: opvsl, operator, vessel  
Temp Tables: opervsls, opvsls1, opvsls2  
Reports Used: vsloper  
Forms Used: none

\*\*\*\*\*)

## 9. PRSRPTS.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

PERSONNEL REPORTS MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

\*(\*\*\*\*\*

Program: Vessel Owners Table Dump  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program prints a sorted listing of vessel owners contained in the database based on the owner's last name and date of birth.  
  
Tables Used: owners  
Temp Tables: ownsum1, ownsum2  
Reports Used: owners  
Forms Used: none

\*(\*\*\*\*\*

Program: Vessel Operator Listing  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a listing of operators of vessels contained in the table OPERATOR. They are selected by date of birth and by the first letter of the last name. The listing is sorted alphabetically before being printed.  
  
Tables Used: operator  
Temp Tables: opsum1, opsum2  
Reports Used: operator  
Forms Used: none

\*(\*\*\*\*\*

Program: Operator - Vessel Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a listing sorted by operator last name of those vessels which are used by specified operators. Operators may be selected by an alphabetic search or may be selected in their entirety.  
  
Tables Used: opvsl, operator, vessel  
Temp Tables: opervsls, opvsls1, opvsls2  
Reports Used: opervsls  
Forms Used: none

\*(\*\*\*\*\*

Program: Owner - Vessel Dump Program  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program performs a listing sorted by owner last name of those owners which own specific vessels. Owners may be selected in their entirety or may be selected by an alphabetic search.  
  
Tables Used: owvsl, owners, vessel  
Temp Tables: ownvsls, ownvsls1, ownvsls2  
Reports Used: ownvsls  
Forms Used: none

\*\*\*\*\*)

## 10. SQUERY.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

QUERY MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

Program: Query Vessel  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program searches database for all  
information concerning a particular vessel.  
Tables Used: vessel, sar, boarding, owner, operator,  
owvsl, opvsl, vslintel, perintel  
Temp Tables: temp, vslint, perint, bohisl, sarhis  
Reports Used: vslqprn, boqprn, sarqprn, owqprn, opqprn,  
pintqprn, vintqprn  
Forms Used: vslquery, brdquery, sarquery, ownquery,  
opquery, pintquer, vintquer

\*(\*\*\*\*\*

Program: Query Personnel  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program searches database for all  
information concerning a particular person,  
including all vessels owned or operated  
and all historical information concerning  
these vessels.  
Tables Used: vessel, sar, boarding, owner, operator,  
owvsl, opvsl, opown, vslintel, perintel  
Temp Tables: temp, vslint, perint, bohisl, sarhis,  
vslsown, vslsopr, wvsljoin, pvsjoin  
Reports Used: vslqprn, boqprn, sarqprn, perqprn,  
pintqprn, vintqprn  
Forms Used: vslquery, brdquery, sarquery, perquer1,  
perquer2, pintquer, vintquer

\*\*\*\*\*)

## 11. SUTILITY.PRG

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

UTILITIES MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*(\*\*\*\*\*

Program: Initialize SARSYS  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program removes all temporary  
tables that can be created by the system.  
Tables Used: none  
Temp Tables: all  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Pack Database  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program packs/compresses the database.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Backup Database  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program provides instructions for  
backing up the database.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*(\*\*\*\*\*

Program: Restore Database  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program provides instructions for  
restoring the database from a backup.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)



## APPENDIX E

### SOURCE CODE FOR ANCILLARY PROGRAM MODULES

The Search and Rescue and Enforcement of Laws and Treaties Intelligence System (SARELTIS) Prototype for US Coast Guard Group Monterey consists of eleven sets of application programs written in the R:base 5000 command language, and sixteen ancillary program modules written in either the R:base 5000 command language or as DOS batch or data files. All of these programs have access to one common relational database structure, named SARSYS.

This appendix contains the source code for the sixteen ancillary program modules of SARELTIS. These modules include the following:

- RESTBRD.cmd - Runs the Boarding Reports Menu Program
- RESTINPT.cmd - Runs the Data Entry Menu Program
- RESTINT.cmd - Runs the Intelligence Reports Menu Program
- RESTMAIN.cmd - Runs the Main Menu Program
- RESTMOD.cmd - Runs the Data Modification Menu Program
- RESTPRS.cmd - Runs the Personnel Reports Menu Program
- RESTQRY.cmd - Runs the Query Menu Program
- RESTRPTS.cmd - Runs the Reports Master Menu Program
- RESTSAR.cmd - Runs the Sar Reports Menu Program
- RESTUTLY.cmd - Runs the Utilities Menu Program
- RESTVSL.cmd - Runs the Vessel Reports Menu Program
- STARTUP.BIN - Runs the Title Page and Security Program
- RBASE.DAT - Runs Startup.bin when R:base is loaded
- SARSYS.BAT - Automatically loads application from main directory
- BACKDBMS.BAT - Batch file to backup the database and programs
- RESTDBMS.BAT - Batch file to restore the database and programs

The source code for the application program sets is contained in Appendix F through Appendix P. All programs for this project were developed by the writers. Internal formats for the Reports and Entry/Edit forms are contained within the R:base 5000 database structure itself and were considered inappropriate for listing.

```

*(*****
Program:          RESTBRD.cmd
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program calls the boarding reports menu.
Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none
*****)

run brd_main in brdrpts.apx
*( end )

*(*****
Program:          RESTINPT.cmd
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program calls the input main menu.
Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none
*****)

run inpmain in sentry.apx
*( end )

*(*****
Program:          RESTINT.cmd
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program calls the intelligence reports menu.
Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none
*****)

run int_main in intrpts.apx
*( end )

*(*****
Program:          RESTMAIN.cmd
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program calls the main menu of the system.
Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none
*****)

run sarsys in sarsys.apx
*( end )

```

\*(\*\*\*\*\*

Program: RESTMOD.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the modify main menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run modmain in modify.apx  
\*( end )

\*(\*\*\*\*\*

Program: RESTPRS.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the personnel reports menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run prs\_main in prsrpts.apx  
\*( end )

\*(\*\*\*\*\*

Program: RESTORY.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the modify main menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run grymain in squery.apx  
\*( end )

\*(\*\*\*\*\*

Program: RESTRPTS.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the reports main menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run rptmain in sreports.apx

\*( end )

\*(\*\*\*\*\*

Program: RESTSAR.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the sar reports menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run sar\_main in sarrrpts.apx

\*( end )

\*(\*\*\*\*\*

Program: RESTUTLY.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the utility main menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run utlmain in sutility.apx

\*( end )

\*(\*\*\*\*\*

Program: RESTVSL.cmd  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the vessel reports menu.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run vsl\_main in vslrpts.apx

\*( end )

\*(\*\*\*\*\*

Program: STARTUP.prg (uncompiled version of STARTUP.BIN)  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program displays the title screen and  
verifies user access.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

```

*****)

set error messages off
set escape off
set messages off
newpage
clear all variables
write "                                WELCOME                                +
" at 3 5
write "                                This is the                            +
" at 5 5
write "                                Search & Rescue /                      +
" at 8 5
write "                                Enforcement of Laws and Treaties        +
" at 9 5
write "                                Intelligence Information System (SARELTIS) +
" at 10 5
write "                                Authors: LT Jon D. Allen,  US Coast Guard +
" at 14 5
write "                                LT Heidi R. Lang,  US Navy              +
" at 15 5
write "                                Date: September 1987                  +
" at 16 5
write "                                Please press any key to continue       +
" at 22 5
pause
newpage
set var username text
set var userpass text
set var validusr text
set var validusr to no
set var chances integer
set var chances to 3
set error messages on
while validusr eq no then
    write "Please enter your user name and your user password" at 3 1
    fillin username using "User Name: " at 5 20
    fillin userpass using "Password: " at 6 21
    set error messages off
    newpage
    if username eq "*****" and userpass eq "*****" then
        set var validusr to yes
        break
    endif
    if username eq "***" and userpass eq "*****" then
        set var validusr to yes
        break
    endif
    set var chances to .chances - 1
    if chances le 0 then
        newpage
        set var count to 20
        while count ne 0 then
            write "Improper LOGON attempt....SARELTIS Terminated!" at 10 1
            set var count to .count - 1
        endwhile
        newpage
        exit
    endif
    write "Invalid user name or password, Please try again." at 10 1
endwhile
if username eq sysop then
    user sarsys
    newpage
    write "Initializing SARELTIS" at 10 25
    run sarsys in sarsys.apx
endif
if username eq ood then
    newpage
    write "Initializing SARELTIS" at 10 25

```

```

run sarsys in sarsys.apx
endif
exit
*( end )

```

```

*(*****

```

```

Program:          RBASE.DAT
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program loads the title screen and security
                  module when R:base 5000 is loaded.

Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none

```

```

*****

```

```

run startup.bin
exit
*( end )

```

```

*(*****

```

```

Program:          SARSYS.BAT
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This file loads R:base and enters the
                  SARELTIS application directly from the
                  main directory.

Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none

```

```

*****

```

```

cd c:\dbdir
path = c:\r5k
rbase
*( end )

```

```

*(*****

```

```

Program:          BACKDBMS.BAT
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This file performs a backup of the
                  database structure and all application
                  programs.

Tables Used:      none
Temp Tables:      none
Reports Used:     none
Forms Used:       none

```

```

*****

```

```

path = c: ;c:\util
cd \dbdir
backup *.apx a:
backup sarsys?.rbs a:
backup *.cmd a:
backup startup.bin

```

```

backup rbase.dat
path = c:\dbdir;c:\r5k
rbase
*( end )

```

```

*(*****

```

```

    Program:      RESTDBMS.BAT
    Author:       J D Allen and H R Lang
    Date Written: August 1987
    Description:  This file restores a backup copy of
                  the database structure and application
                  programs.
    Tables Used:  none
    Temp Tables:  none
    Reports Used: none
    Forms Used:   none

```

```

*****

```

```

path = c:\dbdir;c:\util
cd \dbdir
restore a: \dbdir
restore a: \dbdir
restore a: \dbdir
restore a: \dbdir
restore a: \dbdir
path = c:\dbdir;c:\r5k
rbase
*( end )

```

## APPENDIX F

### SARSYS SOURCE CODE

```

$COMMAND
SARSYS
*(*****
      US COAST GUARD GROUP MONTEREY
    SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
      INTELLIGENCE SYSTEM (SARELTIS)

    MAIN MENU and STARTUP APPLICATION

    Author:   Jon D. Allen, LT, USCG
              Heidi R. Lang, LT, USN
              AUGUST 1987

*****)

set escape off
set messages off
set error messages off
open sarsys
clear all variables
run INITIAL in sutility.apx
set var pick1 integer
newpage
choose pick1 from mainmenu in sarsys.apx
if pick1 eq 0 then
  quit to restmain.cmd
endif
if pick1 eq 1 then
  run SINPUTS in sarsys.apx
  quit to restmain.cmd
endif
if pick1 eq 2 then
  run MODIFY in sarsys.apx
  quit to restmain.cmd
endif
if pick1 eq 3 then
  run QUERY in sarsys.apx
  quit to restmain.cmd
endif
if pick1 eq 4 then
  run SREPORTS in sarsys.apx
  quit to restmain.cmd
endif
if pick1 eq 5 then
  run UTILITY in sarsys.apx
  quit to restmain.cmd
endif
if pick1 eq 6 then
  run ADHOC in sarsys.apx
  quit to restmain.cmd
endif
if pick1 eq 7 then
  set var exitprg text
  set var exitprg to yes
endif
write "You have completed this session...." at 10 1
write "REMEMBER --- Do frequent backups!" at 12 1
write "Please press any key to exit" at 18 1
pause

```



```

newpage
set escape on
set messages on
set error messages on
exit
$menu
mainmenu
column SARELTIS --- MASTER MENU
INPUT INFORMATION
MODIFY INFORMATION
QUERY INFORMATION
REPORTS
UTILITIES
AD HOC QUERIES
EXIT SARELTIS
*( end )

```

# \$COMMAND

## SINPUTS

```

*(*****

```

```

Program:      Access Input Module
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program calls the input master menu.
Tables Used:  none
Temp Tables:  none
Reports Used: none
Forms Used:   none

```

```

*****

```

```

run INPMAIN in SENTRY.apx
return
*( end )

```

# \$COMMAND

## MODIFY

```

*(*****

```

```

Program:      Access Modify Module
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program calls the modify master menu.
Tables Used:  none
Temp Tables:  none
Reports Used: none
Forms Used:   none

```

```

*****

```

```

run MODMAIN in MODIFY.apx
return
*( end )

```

# \$COMMAND

## QUERY

```

*(*****

```

```

Program:      Access Query Module
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program calls the query master menu.
Tables Used:  none

```

Temp Tables: none  
 Reports Used: none  
 Forms Used: none

\*\*\*\*\*)

run QRYMAIN in SQUERY.apx  
 return  
 \*( end )

\$COMMAND  
 SREPORTS

\*(\*\*\*\*\*)

Program: Access Reports Module  
 Author: J D Allen and H R Lang  
 Date Written: August 1987  
 Description: This program calls the reports master menu.  
 Tables Used: none  
 Temp Tables: none  
 Reports Used: none  
 Forms Used: none

\*\*\*\*\*)

run RPTMAIN in SREPORTS.apx  
 return  
 \*( end )

\$COMMAND  
 UTILITY

\*(\*\*\*\*\*)

Program: Access Utilities Module  
 Author: J D Allen and H R Lang  
 Date Written: August 1987  
 Description: This program calls the utility master menu.  
 Tables Used: none  
 Temp Tables: none  
 Reports Used: none  
 Forms Used: none

\*\*\*\*\*)

run UTLMAIN in SUTILITY.apx  
 return  
 \*( end )

\$COMMAND  
 ADHOC

\*(\*\*\*\*\*)

Program: Access Ad Hoc Module  
 Author: J D Allen and H R Lang  
 Date Written: August 1987  
 Description: This program allows the user to exit the  
 menus to the RBase 5000 command prompt to  
 execute ad hoc queries.  
 Tables Used: none  
 Temp Tables: none  
 Reports Used: none  
 Forms Used: none

```

*****)
newpage
write "You are now exiting the menu system of SARELTIS. Before +
exercising " at 4 1
write "this option, you should become very familiar with RBase 5000 " +
at 5 1
write "query commands found in the reference manuals and the actual " +
at 6 1
write "database structure." at 7 1
write "Do you wish to return to the SARELTIS menus? (Y)" at 10 1
set var choice text
fillin choice using "(" at 10 46
if choice eq n then
    newpage
    write "You are now exiting the SARELTIS menu system" at 8 10
    write "If you wish to return to the menu system, please" at 10 10
    write "type RUN STARTUP at the RBase 5000 prompt." at 11 10
    write "Please press any key to continue" at 16 10
    pause
    set escape on
    set messages on
    set error messages on
    clear all variables
    set bell on
    newpage
    quit
endif
return
*( end )

```

## APPENDIX G

### SENTRY SOURCE CODE

```
$COMMAND
INPMAIN
*(*****
```

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

INPUT MASTER MENU and INPUT PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

```
*****)
```

```
newpage
set messages off
set escape off
clear all variables
set var pick2 integer
newpage
choose pick2 from inp_menu in sentry.apx
if pick2 eq 0 then
    quit to restinpt.cmd
endif
if pick2 eq 1 then
    run add_sar in sentry.apx
    quit to restinpt.cmd
endif
if pick2 eq 2 then
    run add_sbd in sentry.apx
    quit to restinpt.cmd
endif
if pick2 eq 3 then
    run add_sut in sentry.apx
    quit to restinpt.cmd
endif
if pick2 eq 4 then
    run add_brd in sentry.apx
    quit to restinpt.cmd
endif
if pick2 eq 5 then
    run add_owmr in sentry.apx
    quit to restinpt.cmd
endif
if pick2 eq 6 then
    run am_vint in modify.apx
    quit to restinpt.cmd
endif
if pick2 eq 7 then
    run am_pint in modify.apx
    quit to restinpt.cmd
endif
if pick2 eq 8 then
    quit to restmain.cmd
endif
quit to restinpt.cmd
return
```

```

$menu
inp_menu
column SARELTIS --- INPUT MENU
INPUT SAR INFORMATION (NO BOARDING)
INPUT SAR INFORMATION WITH BOARDING
INPUT MULTIPLE SAR UNITS
INPUT BOARDING INFORMATION
INPUT MULTIPLE VESSEL OWNERS
INPUT VESSEL INTELLIGENCE
INPUT PERSONNEL INTELLIGENCE
RETURN TO MAIN MENU
*( end )

```

# \$COMMAND

## ADD SAR

```

*(*****

```

```

Program:      Add Sar
Author:       H R Lang and J D Allen
Date Written: July 1987
Description:   This program allows the user to input
               sar case information.
Tables Used:  vessel, sar, owners, operators, owvs1, opvs1
Temp Tables:  none
Reports Used: none
Forms Used:   sarform1, sarform2, sarform3, sarform4,
               sarform5, sarform6, sarform7, sarform8,
               sarform9

```

```

*****

```

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var pg to 1
*(initialize edit and load control variables)
set var review to N
set var loadmenu to N
label begin
set var Backup to N
set var pgcount to 0
while pg gt 0 then *(main loop)
  newpage
  if pg eq 1 then
    *(enter general sar information)
    if review eq N and backup eq N then
      set var pgcount to 1
      set var vsardate to .#date
      set var vsartime to 12:00:00
      set var vsarlat to 0.0
      set var vsarlong to 0.0
      set var vdistoff to 0
      set var vsarpob to 0
    endif
    write "Press [ESC] to quit or [PGDN] to move down a page" at 1 1
    draw sarform1 with all at 3
    if review eq N then
      edit var return esc pgdn
    else
      edit var vfoldno vucn vmucn vsardate vsarday vsartime vsarnod +
        vimmed vsarlat vsarlong vdistoff vsarpob return esc pgdn
    endif
  endif
endif

```

```

if pg eq 2 then
  *(enter vessel information)
  if review eq N and backup eq N then
    set var pgcount to 2
    while vvslnhin exists then
      set pointer #1 e1 for vessel where vslhin = .vvslnhin
      newpage
      if e1 eq 0 then
        *(vessel exists in database)
        set var vvslnno to vslno in #1
        set var vvslnname to vslname in #1
        set var vvslnmake to vslmake in #1
        set var vvslnmod to vslmodel in #1
        set var vvslnyear to vslyear in #1
        set var vvslnon to vsltons in #1
        set var vvslnft to vsllenft in #1
        set var vvslnin to vsllenin in #1
        set var vvslnhp to vslhp in #1
        set var vvslnuse to vsluse in #1
        set var vvslnype to vslype in #1
        set var vvslnprop to vslprop in #1
        set var vvslnhull to vslhull in #1
        set var vvslneng to vslen in #1
        set var vvslnfuel to vslfuel in #1
        set var vconstr to vslconst in #1
        set var vdecals to cmedecals in #1
        set var vcmeyear to cmeyear in #1
        set var voffno to vsloffno in #1
        set var vhome to homeport in #1
        set var vcall to vsllcall in #1
        set var vvalue to vsllvalue in #1
        set var vsuper to vsllsuper in #1
        set var vmasts to vsllmasts in #1
        set var vsailno to sailno in #1
        set var vhlcolor to hlcolor in #1
        set var vtrcolor to trcolor in #1
        set var vsllcolor to slcolor in #1
        set var vcbcolor to cbcolor in #1
        set var vdkcolor to dkcolor in #1
        set var vmarks to vsllmarks in #1
        set var v1 to vslno in #1
        set var v2 to vslname in #1
        set var v3 to .slnhin in #1
        set var v4 to vslmake in #1
        set var v5 to vslmodel in #1
        set var v6 to vslyear in #1
        set var v7 to vsltons in #1
        set var v8 to vsllenft in #1
        set var v9 to vsllenin in #1
        set var v10 to vslhp in #1
        set var v11 to vsluse in #1
        set var v12 to vslype in #1
        set var v13 to vslprop in #1
        set var v14 to vslhull in #1
        set var v15 to vslen in #1
        set var v16 to vslfuel in #1
        set var v17 to vslconst in #1
        set var v18 to cmedecals in #1
        set var v19 to cmeyear in #1
        set var v20 to vsloffno in #1
        set var v21 to homeport in #1
        set var v22 to vsllcall in #1
        set var v23 to vsllvalue in #1
        set var v24 to vsllsuper in #1
        set var v25 to vsllmasts in #1
        set var v26 to sailno in #1
        set var v27 to hlcolor in #1
        set var v28 to trcolor in #1
        set var v29 to slcolor in #1
        set var v30 to cbcolor in #1

```

```

        set var v31 to dkcolor in #1
        set var v32 to vslmarks in #1
    else
        set var vvslytype text
        set var vvslytype to 9
        set var vvslyuse text
        set var vvslyuse to 0
        set var vvslyyear text
        set var vvslyyear to 1901
        set var vvslyhp text
        set var vvslyhp to 0
        set var vvslyft to 0
        set var vvslylin to 0
        set var vvslyton to 0
        set var vvalue to $0
        set var vdecals text
        set var vcmeyear text
    endif
    break
endwhile
endif
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw sarform2 with all at 3
edit var vvslyno vvslyft vvslylin vvslyhp vvslyton return +
vvslymake vvslymod vvslyyear vvslyft vvslylin vvslyhp vvslyton return +
esc pgup pgdn
endif
if pg eq 3 then
    *(enter vessel information)
    if review eq N and backup eq N then
        set var pgcount to 3
        if el ne 0 then
            set var vvslyhull text
            set var vvslyhull to 8
            set var vvslyfuel text
            set var vvslyfuel to 0
            set var vvslyleng text
            set var vvslyleng to 0
            set var vvslyconstr text
            set var vvslyconstr to 0
            set var vvslyprop text
            set var vvslyprop to 9
            set var vslcolor to unk
            set var vhlcolor to unk
            set var vtrcolor to unk
            set var vcbcolor to unk
            set var vdkcolor to unk
        endif
    endif
    write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
    draw sarform3 with all at 3
    edit var vvslyhull vvslyfuel vvslyleng vvslyconstr vvslyprop vsuper vmasts +
    vslcolor vsailno vhlcolor vtrcolor vcbcolor vdkcolor vmarks +
    return esc pgup pgdn
endif
if pg eq 4 then
    *(enter owner information)
    if review eq N and backup eq N then
        set var pgcount to 4
        set var vowlname to unk
        set var vowlfname to unk
        write "Press [PGDN] after entering initial information to check
if" at 1 5
        write "owner exists in database. Press [ESC] to quit" at 2 10
        draw sarform4 with all at 4
        edit var return esc pgdn
    endif
    if #return ne esc then

```

```

if review eq N and backup eq N then
  while vowelname exists and vowelname exists then
    set pointer #2 e2 for owners where ownlname = .vowelname and +
    ownfname = .vowelname
    newpage
    while e2 eq 0 then
      *(owner last/first name exists in database)
      set var vowelmi to ownmi in #2
      set var vowelob to owndob in #2
      set var voweladdr to ownaddr in #2
      set var vowelcity to owncity in #2
      set var vowelst to ownstate in #2
      set var vowelzip to ownzip in #2
      set var voweltno to owntelno in #2
      newpage
      draw sarform4 with all at 3
      draw sarform5 with all at 8
      write "Correct owner? (N)" at 21 20
      fillin owfound using "(" at 21 35
      if owfound exists and owfound eq Y then
        set var ow1 to .vowelname
        set var ow2 to .vowelname
        set var ow3 to ownmi in #2
        set var ow4 to ownaddr in #2
        set var ow5 to owncity in #2
        set var ow6 to ownstate in #2
        set var ow7 to ownzip in #2
        set var ow8 to owntelno in #2
        set var ow9 to owndob in #2
        set var ow10 to ownid in #2
        set var vownid to ownid in #2
        break
      endif
    endwhile
    next #2 e2
  endwhile
  if e2 ne 0 then
    newpage
    write "This owner does not exist in the database" at 5 5
    fillin go using "Press [ENTER] to continue" at 9 5
    clear vowelmi
    clear voweladdr
    clear vowelcity
    set var vowelst to CA
    clear vowelzip
    clear voweltno
    set var vowelob to 01/01/1901
    compute vmaxown as max ownid from owners
    if vmaxown fails then
      set var vmaxown to 0
    endif
    set var vownid to .vmaxown + 1
  endif
  break
endwhile
endif
newpage
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw sarform4 with all at 3
draw sarform5 with all at 8
edit var return esc pgup pgdn
endif
endif
if pg eq 5 then
  *(enter operator information)
  if review eq N and backup eq N then
    set var pgcount to 5
    write "Press [PGDN] after entering initial information to check
if" at 1 5
    write "operator exists in database. Press [ESC] to quit" at 2 10

```



```

set var voplname to .vowlname
set var vopfname to .vowfname
draw sarform6 with all at 4
edit var return esc pgdn
endif
if #return ne esc then
  if review eq N and backup eq N then
    while voplname exists and vopfname exists then
      set pointer #3 e3 for operator where oplname = .voplname +
      and opfname = .vopfname
      newpage
      while e3 eq 0 then
        *(operator last/first name exists in database)
        set var vopmi to opmi in #3
        set var vopdob to opdob in #3
        set var vopaddr to opaddr in #3
        set var vopcity to opcity in #3
        set var vopst to opstate in #3
        set var vopzip to opzip in #3
        set var voptelno to optelno in #3
        set var vopcrse to opcourse in #3
        newpage
        draw sarform6 with all at 3
        draw sarform7 with all at 8
        write "Correct operator? (N)" at 21 20
        fillin opfound using "(" at 21 38
        if opfound exists and opfound eq Y then
          set var op1 to .voplname
          set var op2 to .vopfname
          set var op3 to opmi in #3
          set var op4 to opaddr in #3
          set var op5 to opcity in #3
          set var op6 to opstate in #3
          set var op7 to opzip in #3
          set var op8 to optelno in #3
          set var op9 to opdob in #3
          set var op10 to opcourse in #3
          set var op11 to opid in #3
          set var vopid to opid in #3
          break
        endif
        next #3 e3
      endwhile
      if e3 ne 0 then
        newpage
        write "This operator does not exist in the database" at 5 5
        fillin go using "Press [ENTER] to continue" at 9 5
        if vowlname eq .voplname and vowfname eq .vopfname then
          set var vopmi to .vowmi
          set var vopaddr to .vowaddr
          set var vopcity to .vowcity
          set var vopst to .vowst
          set var vopzip to .vowzip
          set var voptelno to .vowtelno
          set var vopdob to .vowdob
        else
          clear vopmi
          clear vopaddr
          clear vopcity
          set var vopst to CA
          clear vopzip
          clear voptelno
          set var vopdob to 01/01/1901
        endif
        clear vopcrse
        compute vmaxop as max opid from operator
        if vmaxop fails then
          set var vmaxop to 0
        endif
      endif
    endwhile
  endif
endif

```

```

        endif
        set var vopid to .vmaxop + 1
    endif
    break
endwhile
endif
newpage
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw sarform6 with all at 3
draw sarform7 with all at 8
edit var return esc pgup pgdn
endif
endif
if pg eq 6 then
*(enter sar weather information)
if review eq N and backup eq N then
    set var pgcount to 6
    set var vsunrise to 06:00:00
    set var vsunset to 19:00:00
    set var vceiling to 0
    set var vclouds to 0
    set var vvisdist to 0
    set var vwinddir to 0
    set var vwindspd to 0
    set var vseas to 0
    set var vswells to 0
endif
write "Press [ESC] to quit or [PGUP] to move up a page" at 1 1
draw sarform9 with all at 3
edit var vsunrise vsunset vceiling vclouds vvisdist vwinddir +
vwindspd vseas vswells return esc pgup
set var loadmenu to "Y"
endif
if #return eq pgup then
    set var backup to Y
    if pg gt 1 then
        set var pg to .pg - 1
    else
        set var pg to 1
    endif
endif
if #return eq pgdn then
    if pg lt 6 then
        set var pg to .pg + 1
        if pgcount lt .pg then
            set var backup to N
        endif
    else
        set var pg to 6
    endif
endif
if #return eq esc then
    set var backup to N
    set var pg to 0
endif
endwhile *(end of main loop)
newpage
write "Program loading in progress. Please stand by ....." at 10 10
if loadmenu eq "Y" then
    set var choice to 0
    while choice lt 1 or choice gt 3 then
        newpage
        write "Data Load Options" at 2 20
        write "-----" at 3 20
        write "Enter:" at 5 20
        write "1-To load the data into the database" at 6 20
        write "2-To ignore the data entered" at 7 20
        write "3-To go back and verify data entered" at 8 20
        write "Your choice: " at 10 20
    endwhile
endif

```

```

fillin choice using " " at 10 33
newpage
if choice eq 1 then
  *(test for required information)
  if vsardate exists and vfoldno exists and vucn exists and +
  vvslname exists and vsarlat exists and vsarlong exists and +
  vsarnod exists and vimmed exists then
    set error messages off
    if e1 eq 0 then
      *(vessel exists in database)
      write "changing values in vessel"
      delete rows from #1
    else
      write "loading vessel"
    endif
    load vessel
    .vvslnno .vvslnname .vvslnhin .vvslnmake .vvslnmod .vvslnyear +
    .vvslnlon .vvslnlat .vvslnlin .vvslnhp .vvslnuse .vvslnltype +
    .vvslnprop .vvslnhull .vvslnleng .vvslnfuel .vvslnconstr .vvslnvdec +
    .vvslnyear .vvslnvoffno .vvslnvhome .vvslnvcall .vvslnvvalue .vvslnvsuper .vvslnvmasts +
    .vvslnvsailno .vvslnvhcolor .vvslnvtrcolor .vvslnvslcolor .vvslnvcbcolor .vvslnvdkcolor +
    .vvslnvmarks
  end
  if e1 eq 0 then
    set pointer #1 e1 for vessel where vslhin eq .v3
    if e1 ne 0 then
      load vessel
      .v1 .v2 .v3 .v4 .v5 .v6 .v7 .v8 .v9 .v10 .v11 .v12 .v13 +
      .v14 .v15 .v16 .v17 .v18 .v19 .v20 .v21 .v22 .v23 .v24 +
      .v25 .v26 .v27 .v28 .v29 .v30 .v31 .v32
    end
  endif
endif
set pointer #1 e1 for sar where folderno = .foldno
if e1 eq 0 then
  set var difsar to "F"
  set var s1 to sardate in #1
  set var s2 to sartime in #1
  set var s3 to sarlat in #1
  set var s4 to sarlong in #1
  set var s5 to sarnod in #1
  set var s6 to sarvhin in #1
  if s1 ne .vsardate or s2 ne .vsartime or s3 ne .vsarlat or +
  s4 ne .vsarlong or s5 ne .vsarnod or s6 ne .vvslnhin then
    set var difsar to "T"
  endif
else
  set var difsar to "T"
endif
if difsar eq T then
  write "loading sar"
  load sar
  .vfoldno .vucn .vmucn .vsardate .vsarday .vsartime +
  .vsunrise .vsunset .vsarnod .vsarpob .vvslnhin .vsarlat +
  .vsarlong .vdistoff .vimmed .vwinddir .vwindspd .vvisdist +
  .vclouds .vceiling .vseas .vswells
end
endif
write "loading owvs1"
load owvs1
.vvslnhin .vownid
end
write "loading opvs1"
load opvs1
.vvslnhin .vopid
end
if e2 eq 0 then
  *(owner exists in database)
  write "changing values in owner"
  delete rows from #2

```

```

else
    write "loading owner"
endif
load owners
.vowlname .vowfname .vowmi .vowaddr .vowcity .vowst .vowzip +
.vowtelno .vowdob .vownid
end
if e2 eq 0 then
    set pointer #2 e2 for owners whe ownid eq .ow10
    if e2 ne 0 then
        load owners
        .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
    end
endif
endif
if e3 eq 0 then
    *(operator exists in database)
    write "changing values in operator"
    delete rows from #3
else
    write "loading operator"
    set var vopcrse text
endif
load operator
.voplname .vopfname .vopmi .vopaddr .vopcity .vopst .vopzip +
.voptelno .vopdob .vopcrse .vopid
end
if e3 eq 0 then
    set pointer #3 e3 for operator where opid eq .op11
    if e3 ne 0 then
        load operator
        .op1 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 .op10 +
        .op11
    end
endif
endif
set error messages on
write " "
write "Return to correct data entered? (Y)" at 20 10
write "Note: correct only errors indicated by messages" +
at 22 5
fillin er using "(" at 20 42
if er fails or er eq "Y" then
    set var review to "Y"
    set var pg to 1
    set pointer #1 e1 for vessel where vslhin eq .vvs1hin
    set pointer #2 e2 for owners where ownid eq .vownid
    set pointer #3 e3 for operator where opid eq .vopid
    break
else
    newpage
    write "Removing duplicate entries from tables" at 10 10
    write "Please stand by ....." at 15 12
    delete duplicates from vessel
    delete duplicates from owvsl
    delete duplicates from opvsl
    delete duplicates from owners
    delete duplicates from operator
endif
else
    newpage
    write "Load not performed. Required information missing." +
at 5 20
    write "Required information includes:" at 10 30
    write "Sar Date, Folder Number, Unit Case Number" at 12 35
    write "Vessel Name, Sar Latitude, Sar Longitude" at 13 35
    write "Sar Nature of Distress" at 14 35
    fillin go using "Press [ENTER] to return to data entry" +
at 16 25
    set var pg to 1

```

```

    set var review to "Y"
    break
endif
endif
if choice eq 1 or choice eq 2 then
  *(enter sar units)
  newpage
  write "Enter sar units? (Y)" at 12 20
  fillin s_units using "(" at 12 37
  if s_units fails or s_units eq Y then
    set var more to "Y"
    while more eq Y then
      set var vuwtime to .vsartime
      set var vuwdate to .vsardate
      set var vetadate to .vsardate
      set var vdateos to .vsardate
      set var valgdate to .vsardate
      set var vtowdate to .vsardate
      set var vdvmoort to .vsardate
      set var vsumoord to .vsardate
      newpage
      write "Press [PGDN] to load data or [ESC] to quit" at 1 1
      draw sarform8 with all at 3
      edit var vunit vuwtime vuwdate voseta vetadate vostime +
        vdateos valgtime valgdate vtowtime vtowdate vdvmoort +
        vdvmoort vsumoord vsumoord return esc pgdn
      if #return eq pgdn then
        if voseta fails then
          clear vetadate
          set var vetadate date
        endif
        if vostime fails then
          clear vdateos
          set var vdateos date
        endif
        if valgtime fails then
          clear valgdate
          set var valgdate date
        endif
        if vtowtime fails then
          clear vtowdate
          set var vtowdate date
        endif
        if vdvmoort fails then
          clear vdvmoort
          set var vdvmoort date
        endif
        if vsumoord fails then
          clear vsumoord
          set var vsumoord date
        endif
        set pointer #1 e1 for sarunits whe foldno eq .vfoldno and +
        unithname eq .vunit
        newpage
        if e1 eq 0 then
          write "Duplicate entry not loaded"
        else
          write "Loading sarunits"
          load sarunits
          .vfoldno .vunit .vuwtime .vuwdate .voseta .vetadate +
            .vostime .vdateos .valgtime .valgdate .vtowtime +
            .vtowdate .vdvmoort .vdvmoort .vsumoord .vsumoord
          end
        endif
        write "More units to enter? (N)" at 23 20
        fillin mrunits using "(" at 23 41
        if mrunits fails or mrunits eq N then
          set var more to N
        else
          clear vunit

```

```

        clear voseta
        clear vostime
        clear valgtime
        clear vtowtime
        clear vdvmoort
        clear vsumoort
    endif
endif
if #return eq esc then
    set var more to N
endif
endwhile
endif
*(enter owner information)
newpage
write "Enter additional owners? (N)" at 12 20
fillin addlownr using "(" at 12 45
if addlownr exists and addlownr eq Y then
    set var more to "Y"
    while more eq Y then
        newpage
        set var vowelname to unk
        set var vowfname to unk
        write "Press [PGDN] after entering initial information to +
check if" at 1 5
        write "owner exists in database. Press [ESC] to quit" +
        at 2 10
        draw sarform4 with all at 4
        edit var return esc pgdn
        if #return ne esc then
            while vowelname exists and vowfname exists then
                set pointer #2 e2 for owners where ownlname = .vowelname +
                and ownfname = .vowfname
                newpage
                while e2 eq 0 then
                    *(owner last/first name exists in database)
                    set var vowmi to ownmi in #2
                    set var vovdob to owndob in #2
                    set var vovaddr to ownaddr in #2
                    set var vovcity to owncity in #2
                    set var vovst to ownstate in #2
                    set var vovzip to ownzip in #2
                    set var vovtelno to owntelno in #2
                    newpage
                    draw sarform4 with all at 3
                    draw sarform5 with all at 8
                    write "Correct owner? (N)" at 21 20
                    fillin owfound using "(" at 21 35
                    if owfound exists and owfound eq Y then
                        set var ow1 to .vowelname
                        set var ow2 to .vowfname
                        set var ow3 to ownmi in #2
                        set var ow4 to ownaddr in #2
                        set var ow5 to owncity in #2
                        set var ow6 to ownstate in #2
                        set var ow7 to ownzip in #2
                        set var ow8 to owntelno in #2
                        set var ow9 to owndob in #2
                        set var ow10 to ownid in #2
                        set var vownid to ownid in #2
                        break
                    endif
                    next #2 e2
                endwhile
            if e2 ne 0 then
                newpage
                write "This owner does not exist in the database" +
                at 5 5
                fillin go using "Press [ENTER] to continue" at 9 5
                clear vovmi
            endif
        endif
    endwhile
endif

```

```

clear vowaddr
clear vowcity
set var vowst to CA
clear vowzip
clear vowtelno
set var vowdob to 01/01/1901
compute vmaxown as max ownid from owners
if vmaxown fails then
    set var vmaxown to 0
endif
set var vownid to .vmaxown + 1
endif
break
endwhile
label redoown
newpage
write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw sarform4 with all at 3
draw sarform5 with all at 8
edit var return esc pgup pgdn
if #return eq pgdn then
    newpage
    set error messages off
    if e2 eq 0 then
        *(owner exists in database)
        write "changing values in owner"
        delete rows from #2
    else
        write "loading owner"
    endif
    load owners
    .vowlname .vowfname .vowmi .vowaddr .vowcity .vowst +
    .vowzip .vowtelno .vowdob .vownid
end
if e2 eq 0 then
    set pointer #2 e2 for owners where ownid eq .ow10
    if e2 ne 0 then
        load owners
        .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
    end
endif
endif
set error messages on
write "Return to correct errors? (N)" at 15 10
write "Note: correct only errors indicated by +
messages" at 20 5
fillin fixown using "(" at 15 36
if fixown exists and fixown eq Y then
    goto redoown
endif
set pointer #2 e2 for owvsl where vhinown eq .vvsllhin +
and idowner eq .vownid
*(check if record already exists)
newpage
if e2 ne 0 then
    load owvsl
    .vvsllhin .vownid
end
endif
endif
endif
write "More owners to enter? (N)" at 20 20
fillin mrownrs using "(" at 20 42
if mrownrs fails or mrownrs eq N then
    set var more to N
endif
endwhile
endif
newpage
write "Enter additional operators? (N)" at 12 20

```

```

fillin addloper using "(" at 12 48
if addloper exists and addloper eq Y then
    set var more to "Y"
    while more eq Y then
        newpage
        *(enter operator information)
        write "Press [PGDN] after entering initial information to +
check if" at 1 5
        write "operator exists in database. Press [ESC] to quit" +
        at 2 10
        set var voplname to unk
        set var vopfname to unk
        draw sarform6 with all at 4
        edit var return esc pgdn
        if #return ne esc then
            while voplname exists and vopfname exists then
                set pointer #3 e3 for operator where oplname = +
                .voplname and opfname = .vopfname
                newpage
                while e3 eq 0 then
                    *(operator last/first name exists in database)
                    set var vopmi to opmi in #3
                    set var vopdob to opdob in #3
                    set var vopaddr to opaddr in #3
                    set var vopcity to opcity in #3
                    set var vopst to opstate in #3
                    set var vopzip to opzip in #3
                    set var voptelno to optelno in #3
                    set var vopid to opid in #3
                    set var vopcrse to opcourse in #3
                    newpage
                    draw sarform6 with all at 3
                    draw sarform7 with all at 8
                    write "Correct operator? (N)" at 21 20
                    fillin opfound using "(" at 21 38
                    if opfound exists and opfound eq Y then
                        set var op1 to .voplname
                        set var op2 to .vopfname
                        set var op3 to opmi in #3
                        set var op4 to opaddr in #3
                        set var op5 to opcity in #3
                        set var op6 to opstate in #3
                        set var op7 to opzip in #3
                        set var op8 to optelno in #3
                        set var op9 to opdob in #3
                        set var op10 to opcourse in #3
                        set var op11 to opid in #3
                        break
                    endif
                next #3 e3
            endwhile
            if e3 ne 0 then
                newpage
                write "This operator does not exist in the database" +
                at 5 5
                fillin go using "Press [ENTER] to continue" at 9 5
                clear vopmi
                clear vopaddr
                clear vopcity
                set var vopst to CA
                clear vopzip
                clear voptelno
                set var vopdob to 01/01/1901
                clear vopcrse
                compute vmaxop as max opid from operator
                if vmaxop fails then
                    set var vmaxop to 0
                endif
                set var vopid to .vmaxop + 1
            endif
        endif
    endwhile
endif

```



```

        break
    endwhile
    label redooper
    newpage
    write "Press [PGDN] to load data or [ESC] to quit" at 1 1
    draw sarform6 with all at 3
    draw sarform7 with all at 8
    edit var return esc pgup pgdn
    if #return eq pgdn then
        newpage
        set error messages off
        if e3 eq 0 then
            *(operator exists in database)
            write "changing values in operator"
            delete rows from #3
        else
            write "loading operator"
            set var vopcrse text
        endif
        load operator
        .voplname .vopfname .vopmi .vopaddr .vopcity .vopst +
        .vopzip .voptelno .vopdob .vopcrse .vopid
    end
    if e3 eq 0 then
        set pointer #3 e3 for operator where opid eq .op11
        if e3 ne 0 then
            load operator
            .op1 .op2 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 +
            .op10 .op11
        end
    endif
    endif
    set error messages on
    write "Return to correct errors? (N)" at 15 10
    write "Note: correct only errors indicated by messages" +
    at 20 5
    fillin fixopr using "(" at 15 36
    if fixopr exists and fixopr eq Y then
        goto redooper
    endif
    set pointer #3 e3 for opvsl where vhinoper eq .vvslnhin +
    and ldoper eq .vopid
    *(check if record already exists)
    newpage
    if e3 ne 0 then
        load opvsl
        .vvslnhin .vopid
    end
    endif
    endif
    endif
    write "More operators to enter? (N)" at 20 20
    fillin mroper using "(" at 20 45
    if mroper fails or mroper eq N then
        set var more to N
    endif
    endif
endwhile
endif
newpage
write "Enter another sar case? (Y)" at 12 20
fillin cont using "(" at 12 44
if cont fails or cont eq Y then
    clear all variables
    set var pg to 1
    set var review to "N"
    set var loadmenu to "N"
    break
else
    set null -0-
    set var pg to 0

```

```

endif
endif
if choice eq 3 then
    set var review to "Y"
    set var pg to 1
endif
endwhile
else
    newpage
    write "Enter another sar case? (Y)" at 12 20
    fillin cont using "(" at 12 44
    if cont fails or cont eq Y then
        clear all variables
        set var pg to 1
        set var review to "N"
        set var loadmenu to "N"
    else
        set error messages off
        set null -0-
        set var pg to 0
    endif
endif
endif
if pg eq 1 then
    goto begin
endif
return
*( end )

```

# \$COMMAND

## ADD SBD

```

*(*****

```

```

Program:      Add Sar with Boarding
Author:       H R Lang and J D Allen
Date Written: July 1987
Description:  This program allows the user to enter sar
              and boarding information.
Tables Used:  boarding, vessel, owners, operator, owvsl,
              opvsl, sar
Temp Tables:  none
Reports Used: none
Forms Used:   cg4100a1, cg4100a2, cg4100a3, cg4100a4,
              cg4100a5, cg4100a6, cg4100a7, cg4100a8,
              cg4100a9, sbdform1, sarform1, sarform8,
              sarform9, sarform5

```

```

*****

```

```

set error messages off
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var pg to 1
*(initialize edit and load control variables)
set var review to "N"
set var loadmenu to "N"
label begin
set var Backup to N
set var pgcount to 0
while pg gt 0 then *(main loop)
    newpage
    if pg eq 1 then
        *(enter boarding/vessel information)
        if review eq N and backup eq N then

```

```

set var pgcount to 1
set var vbodate to .#date
set var vbotime to 12:00:00
set var vvslname to unk
write "Press [PGDN] after entering initial information to check +
if" at 1 5
write "vessel exists in database. Press [ESC] to quit" at 2 10
draw cg4100a1 with all at 4
edit var return esc pgdn
else
write "Press [PGDN] after review/correction or [ESC] to quit" +
at 1 5
draw cg4100a1 with all at 4
edit var vvslname vbodate vbotime vbono return esc pgdn
endif
if #return ne esc then
while vvslnhin exists then
if review eq N and backup eq N then
set pointer #1 el for vessel where vslhin = .vvslnhin
newpage
set var vvslpob to 0
set var vadult to 0
set var vchild to 0
if el eq 0 then
*(vessel exists in database)
set var vvslnno to vslno in #1
set var vvslnname to vslname in #1
set var vvslnmake to vslmake in #1
set var vvslnmod to vslmodel in #1
set var vvslnyear to vslyear in #1
set var vvslnon to vsltons in #1
set var vvslnft to vslenft in #1
set var vvslnin to vsllein in #1
set var vvslnhp to vslhp in #1
set var vvslnuse to vsluse in #1
set var vvslnst to vslst in #1
set var vvslnprop to vslprop in #1
set var vvslnhull to vslhull in #1
set var vvslneng to vsleng in #1
set var vvslnfuel to vslfuel in #1
set var vvslnconst to vslconst in #1
set var vvslnmedecal to vslmedecal in #1
set var vvslnmeyer to vslmeyer in #1
set var vvslnoffno to vslloffno in #1
set var vvslnhome to vslhomeport in #1
set var vvslnvcall to vslvcall in #1
set var vvslnvalue to vslvalue in #1
set var vvslnsuper to vslsuper in #1
set var vvslnmasts to vslmasts in #1
set var vvslnsailno to vslsailno in #1
set var vvslnhcolor to vslhcolor in #1
set var vvslntrcolor to vsltrcolor in #1
set var vvslnslcolor to vslslcolor in #1
set var vvslnvcbcolor to vslvcbcolor in #1
set var vvslnvdkcolor to vslvdkcolor in #1
set var vvslnmarks to vslmarks in #1
set var v1 to vslno in #1
set var v2 to vslname in #1
set var v3 to vslhin in #1
set var v4 to vslmake in #1
set var v5 to vslmodel in #1
set var v6 to vslyear in #1
set var v7 to vsltons in #1
set var v8 to vslenft in #1
set var v9 to vsllein in #1
set var v10 to vslhp in #1
set var v11 to vsluse in #1
set var v12 to vslst in #1
set var v13 to vslprop in #1
set var v14 to vslhull in #1

```

```

set var v15 to vsleng in #1
set var v16 to vslfuel in #1
set var v17 to vslconst in #1
set var v18 to cmedecal in #1
set var v19 to cmeyear in #1
set var v20 to vsloffno in #1
set var v21 to homeport in #1
set var v22 to vslcall in #1
set var v23 to vslvalue in #1
set var v24 to vslsuper in #1
set var v25 to vslmasts in #1
set var v26 to sailno in #1
set var v27 to hlcolor in #1
set var v28 to trcolor in #1
set var v29 to slcolor in #1
set var v30 to cbcolor in #1
set var v31 to dkcolor in #1
set var v32 to vslmarks in #1
else
*(vessel does not exist in database)
set var vvslmake to unk
set var vvslmod to unk
set var vvslyear text
set var vvslyear to 1901
set var vvslhp text
set var vvslhp to 0
set var vvsluse text
set var vvsluse to 0
set var vvsltype text
set var vvsltype to 9
set var vvslprop text
set var vvslprop to 9
set var vvslhull text
set var vvslhull to 8
set var vvsleng text
set var vvsleng to 0
set var vvslfuel text
set var vvslfuel to 0
set var vconstr text
set var vconstr to 0
set var vvslton to 0
set var vvslft to 0
set var vvslin to 0
set var vdecal to N
endif
endif
newpage
write "Press [ESC] to quit or [PGDN] to move down a page" +
at 1 1
draw cg4100a1 with all at 3
draw cg4100a2 with all at 10
edit var return esc pgdn
break
endwhile
endif
endif
if pg eq 2 then
*(enter owner information)
if review eq N and backup eq N then
set var pgcount to 2
set var vowelname to unk
set var vowelname to unk
write "Press [PGDN] after entering initial information to check +
if" at 1 5
write "owner exists in database. Press [ESC] to quit" at 2 10
draw cg4100a3 with all at 4
edit var return esc pgdn
endif
if #return ne esc then
if review eq N and backup eq N then

```

```

while vowlname exists and vowfname exists then
  set pointer #2 e2 for owners where ownlname = .vowlname and +
  ownfname = .vowfname
  newpage
  while e2 eq 0 then
    *(owner last/first name exist in database)
    set var vowmi to ownmi in #2
    set var vowdob to owndob in #2
    set var vowaddr to ownaddr in #2
    set var vowcity to owncity in #2
    set var vowst to ownstate in #2
    set var vowzip to ownzip in #2
    set var vowtelno to owntelno in #2
    newpage
    draw cg4100a3 with all at 3
    draw cg4100a4 with all at 8
    write "Correct owner? (N)" at 21 20
    fillin owfound using "(" at 21 35
    if owfound exists and owfound eq Y then
      set var ow1 to .vowlname
      set var ow2 to .vowfname
      set var ow3 to ownmi in #2
      set var ow4 to ownaddr in #2
      set var ow5 to owncity in #2
      set var ow6 to ownstate in #2
      set var ow7 to ownzip in #2
      set var ow8 to owntelno in #2
      set var ow9 to owndob in #2
      set var ow10 to ownid in #2
      set var vownid to ownid in #2
      break
    endif
    next #2 e2
  endwhile
  if e2 ne 0 then
    newpage
    write "This owner does not exist in the database" at 5 5
    fillin go using "Press [ENTER] to continue" at 9 5
    clear vowmi
    clear vowaddr
    clear vowcity
    set var vowst to CA
    clear vowzip
    clear vowtelno
    set var vowdob to 01/01/1901
    clear vstatus
    compute vmaxown as max ownid from owners
    if vmaxown fails then
      set var vmaxown to 0
    endif
    set var vownid to .vmaxown + 1
  endif
  break
endwhile
endif
newpage
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw cg4100a3 with all at 3
draw cg4100a4 with all at 8
edit var return esc pgup pgdn
endif
endif
if pg eq 3 then
  *(enter operator information)
  if review eq N and backup eq N then
    set var pgcount to 3
    if vstatus eq 1 then
      set var voplname to .vowlname
      set var vopfname to .vowfname
    endif
  endif
endif

```

```

    set var #return to pgdn
else
    set var voplname to unk
    set var vopfname to unk
    write "Press [PGDN] after entering initial information to +
check if" at 1 5
    write "operator exists in database. Press [ESC] to quit" +
    at 2 10
    draw cg4100a5 with all at 4
    edit var return esc pgdn
endif
endif
if #return ne esc then
    if review eq N and backup eq N then
        while voplname exists and vopfname exists then
            set pointer #3 e3 for operator where oplname = .voplname and +
            opfname = .vopfname
            newpage
            while e3 eq 0 then
                *(operator last/first name exist in database)
                set var vopmi to opmi in #3
                set var vopdob to opdob in #3
                set var vopaddr to opaddr in #3
                set var vopcity to opcity in #3
                set var vopst to opstate in #3
                set var vopzip to opzip in #3
                set var voptelno to optelno in #3
                set var vopcrse to opcourse in #3
                newpage
                draw cg4100a5 with all at 3
                draw cg4100a6 with all at 8
                write "Correct operator? (N)" at 21 20
                fillin opfound using "(" at 21 38
                if opfound exists and opfound eq Y then
                    set var op1 to .voplname
                    set var op2 to .vopfname
                    set var op3 to opmi in #3
                    set var op4 to opaddr in #3
                    set var op5 to opcity in #3
                    set var op6 to opstate in #3
                    set var op7 to opzip in #3
                    set var op8 to optelno in #3
                    set var op9 to opdob in #3
                    set var op10 to opcourse in #3
                    set var op11 to opid in #3
                    set var vopid to opid in #3
                    break
                endif
            next #3 e3
        endwhile
        if e3 ne 0 then
            newpage
            write "This operator does not exist in the database" at 5 5
            fillin go using "Press [ENTER] to continue" at 9 5
            if vstatus eq 1 then
                set var vopmi to .vowmi
                set var vopaddr to .vowaddr
                set var vopcity to .vowcity
                set var vopst to .vowst
                set var vopzip text
                set var vopzip to .vowzip
                set var voptelno text
                set var voptelno to .vowtelno
                set var vopcrse text
                set var vopdob to .vowdob
            else
                clear vopmi
                clear vopaddr
                clear vopcity
                set var vopst to CA
            endif
        endif
    endif
endif

```

```

        clear vopzip
        clear voptelno
        set var vopdob to 01/01/1901
    endif
    clear vopcrse
    compute vmaxop as max vopid from operator
    if vmaxop fails then
        set var vmaxop to 0
    endif
    set var vopid to .vmaxop + 1
endif
break
endwhile
endif
newpage
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw cg4100a5 with all at 3
draw cg4100a6 with all at 8
if vstatus eq 1 then
    edit var vopcrse return esc pgup pgdn
else
    edit var return esc pgup pgdn
endif
endif
endif
if pg eq 4 then
    *(enter boarding location information)
    if review eq N and backup eq N then
        set var pgcount to 4
        set var vobsbody to text
        set var vobsbody to "Monterey Bay"
        set var vobcount to Monterey
        set var vobscity to Monterey
        set var vobstate to CA
        set var vobslat to 00.000
        set var vobslong to 000.000
    endif
    write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move down +
a page" at 1 1
    draw cg4100a7 with all at 3
    edit var return esc pgup pgdn
endif
if pg eq 5 then
    *(enter boarding violation/unsafe condition information)
    if review eq N and backup eq N then
        set var pgcount to 5
    endif
    write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
    draw cg4100a8 with all at 3
    edit var return esc pgup pgdn
endif
if pg eq 6 then
    *(enter boarding officer information)
    if review eq N and backup eq N then
        set var pgcount to 6
        set var vbounit text
        set var vbounit to "CG Group Monterey"
        set var vbodist text
        set var vbodist to 11
        set var vboopfacs text
        set var vboopfacs to 36268
        set var vbosrise to 06:00:00
        set var vbosset to 19:00:00
        set var vweapons to 0
    endif
    write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
    draw cg4100a9 with all at 3

```

```

edit var return esc pgup pgdn
endif
if pg eq 7 then
*(enter additional vessel information)
if review eq N and backup eq N then
set var pgcount to 7
if el ne 0 then
set var vvalue to $0
set var vmasts text
set var vmasts to 0
set var vsicolor to unk
set var vhlcolor to unk
set var vtrcolor to unk
set var vcbcolor to unk
set var vdkcolor to unk
endif
endif
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw sbdform1 with all at 3
edit var voffno vhome vcall vvalue vsuper vmasts vsicolor vsailno +
vhlcolor vtrcolor vcbcolor vdkcolor vmarks return esc pgup pgdn
endif
if pg eq 8 then
*(enter general sar information)
if review eq N and backup eq N then
set var pgcount to 8
set var vsardate to .vbodate
set var vsartime to .vbotime
set var vsarlat to .vobslat
set var vsarlong to .vobslong
set var vdistoff to 0
set var vsarpob to .vvslpob
set var vsarday to .vboday
endif
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw sarform1 with all at 3
edit var vfoldno vucn vmucn vsardate vsarday vsartime vsarnod +
vimmed vsarlat vsarlong vdistoff vsarpob return esc pgdn
endif
if pg eq 9 then
*(enter sar weather information)
if review eq N and backup eq N then
set var pgcount to 9
set var vsunrise to .vbosrise
set var vsunset to .vbosset
set var vceiling to 0
set var vclouds to 0
set var vvisdist to 0
set var vwinddir to 0
set var vwindspd to 0
set var vseas to 0
set var vswells to 0
endif
write "Press [ESC] to quit or [PGUP] to move up a page" at 1 1
draw sarform9 with all at 3
edit var vsunrise vsunset vceiling vclouds vvisdist vwinddir +
vwindspd vseas vswells return esc pgup
set var loadmenu to "Y"
endif
if #return eq pgup then
set var backup to Y
if pg gt 1 then
set var pg to .pg - 1
else
set var pg to 1
endif
endif
endif
if #return eq pgdn then

```



```

if pg lt 9 then
  set var pg to .pg + 1
  if pgcount lt .pg then
    set var backup to N
  endif
else
  set var pg to 9
endif
endif
if #return eq esc then
  set var pg to 0
  set var backup to N
endif
endwhile *(end of main loop)
newpage
write "Program loading in progress. Please stand by ....." at 10 10
if loadmenu eq "Y" then
  set var choice to 0
  while choice lt 1 or choice gt 3 then
    newpage
    write "Data Load Options" at 2 20
    write "-----" at 3 20
    write "Enter:" at 5 20
    write "1-To load the data into the database" at 6 20
    write "2-To ignore the data entered" at 7 20
    write "3-To go back and verify data entered" at 8 20
    write "Your choice: " at 10 20
    fillin choice using " " at 10 33
    newpage
    if choice eq 1 then
      *(test for required information)
      set var test to "F"
      if vbodate exists and vbotime exists and vbono exists and +
        vvslname exists and vobslat exists and vobslong exists then
        if vsardate exists and vfoldno exists and vucn exists and +
          vvslname exists and vsarlat exists and vsarlong exists and +
            vsarnod exists and vimmed exists then
          if vviol54 exists or vviol55 exists or vviol56 exists or +
            vviol57 exists or vviol58 exists or vviol59 exists or +
              vviol60 exists or vviol61 exists or vviol62 exists or +
                vviol63 exists then
            set var test to "T"
          endif
          if vviol64 exists or vviol65 exists or vviol66 exists or +
            vviol67 exists or vviol68 exists or vuns69 exists or vuns70 +
              exists or vuns71 exists or vuns72 exists or vuns73 exists then
            set var test to "T"
          endif
          if vuns74 exists or vuns75 exists or vuns76 exists or vuns77 +
            exists or vuns78 exists or vuns79 exists then
            set var test to "T"
          endif
          if test eq "T" then
            set error messages off
            if el eq 0 then
              *(vessel exists in database)
              write "changing values in vessel"
              delete rows from #1
            else
              write "loading vessel"
            endif
            load vessel
            .vvslnno .vvslnname .vvslnhin .vvslnmake .vvslnmod .vvslnyear +
              .vvslnon .vvslnft .vvslnin .vvslnhp .vvslnuse .vvslnype +
              .vvslnprop .vvslnhull .vvslneng .vvslnfuel .vconstr .vdecals +
              .vcmeyear .voffno .vhome .vcall .vvalue .vsuper .vmasts +
              .vsalno .vhlcolor .vtrcolor .vslcolor .vcbcolor +
              .vdkcolor .vmarks
          end
          if el eq 0 then

```

```

set pointer #1 e1 for vessel whe vslhin eq .v3
if e1 ne 0 then
  load vessel
  .v1 .v2 .v3 .v4 .v5 .v6 .v7 .v8 .v9 .v10 .v11 .v12 +
  .v13 .v14 .v15 .v16 .v17 .v18 .v19 .v20 .v21 .v22 +
  .v23 .v24 .v25 .v26 .v27 .v28 .v29 .v30 .v31 .v32
end
endif
endif
write "loading owvsl"
load owvsl
.vvslhin .vownid
end
write "loading opvsl"
load opvsl
.vvslhin .vopid
end
if vstatus eq 1 then
  load opown
  .vownid .vopid
end
endif
set pointer #1 e1 for boarding where bono = .vbono
if e1 eq 0 then
  set var difbo to "F"
  set var b1 to bodate in #1
  set var b2 to botime in #1
  set var b3 to obslat in #1
  set var b4 to obslong in #1
  if b1 ne .vbodate or b2 ne .vbotime or b3 ne .vobslat or +
  b4 ne .vobslong then
    set var difbo to "T"
  endif
endif
else
  set var difbo to "T"
endif
if difbo eq T then
  write "loading boarding"
  load boarding
  .vbodate .vbotime .vbono .vvslopob .vadult .vchild +
  .vstatus .vobsbody .vobcount .vobscity .vobstate +
  .vobslat .vobslong .vviol54 .vviol55 .vviol56 +
  .vviol57 .vviol58 .vviol59 .vviol60 .vviol61 .vviol62 +
  .vviol63 .vviol64 .vviol65 .vviol66 .vviol67 .vviol68 +
  .vuns69 .vuns70 .vuns71 .vuns72 .vuns73 .vuns74 +
  .vuns75 .vuns76 .vuns77 .vuns78 .vuns79 .vborem1 +
  .vborem2 .vborem3 .vbname .vborate .vbounit .vbodist +
  .vboopfacc .vboday .vbosrise .vbosset .vvslnh +
  .vweapons
end
endif
set pointer #1 e1 for sar where folderno = .vfoldno
if e1 eq 0 then
  set var difsar to "F"
  set var s1 to sardate in #1
  set var s2 to sartime in #1
  set var s3 to sarlat in #1
  set var s4 to sarlong in #1
  set var s5 to sarnod in #1
  set var s6 to sarvhn in #1
  if s1 ne .vsardate or s2 ne .vsartime or s3 ne .vsarlat +
  or s4 ne .vsarlong or s5 ne .vsarnod or s6 ne .vvslnh +
  then
    set var difsar to "T"
  endif
else
  set var difsar to "T"
endif
if difsar eq T then
  write "loading sar"

```

```

load sar
.vfoldno .vucn .vmucn .vsardate .vsarday .vsartime +
.vsunrise .vsunset .vsarnod .vsarpob .vvslnhin +
.vsarlat .vsarlong .vdistoff .vimmed .vwinddir +
.vwindspd .vvisdist .vclouds .vceiling .vseas .vswells
end
endif
if e2 eq 0 then
*(owner exists in database)
write "changing values in owner"
delete rows from #2
else
write "loading owner"
endif
load owners
.vowlname .vowfname .vowmi .vowaddr .vowcity .vowst +
.vowzip .vowtelno .vowdob .vownid
end
if e2 eq 0 then
set pointer #2 e2 for owners whe ownid eq .ow10
if e2 ne 0 then
load owners
.ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
end
endif
endif
if e3 eq 0 then
*(operator exists in database)
write "changing values in operator"
delete rows from #3
else
write "loading operator"
endif
load operator
.voplname .vopfname .vopmi .vopaddr .vopcity .vopst +
.vopzip .voptelno .vopdob .vopcrse .vopid
end
if e3 eq 0 then
set pointer #3 e3 for operator where opid eq .op11
if e3 ne 0 then
load operator
.op1 .op2 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 +
.op10 .op11
end
endif
endif
write " "
set error messages on
*(return option in case of entry/edit errors)
write "Return to correct data entered? (Y)" at 20 10
write "Note: correct only errors indicated by messages" +
at 22 5
fillin er using "(" at 20 42
if er fails or er eq "Y" then
set var review to "Y"
set var pg to 1
set pointer #1 e1 for vessel where vslhin eq .vvslnhin
set pointer #2 e2 for owners where ownid eq .vownid
set pointer #3 e3 for operator where opid eq .vopid
break
else
newpage
write "Removing duplicate entries from tables" at 10 10
write "Please stand by....." at 15 12
delete duplicates from vessel
delete duplicates from owsl
delete duplicates from opvsl
delete duplicates from opown
delete duplicates from owners
delete duplicates from operator

```

```

endif
endif
endif
else
newpage
write "Load not performed. Required information missing." +
at 5 20
write "Required information includes:" at 10 30
write "Boarding Date, Boarding Time, Boarding Number" at 12 35
write "Vessel Name, Boarding Latitude, Boarding Longitude" +
at 13 35
write "A Violation or Unsafe Condition" at 14 35
write "Sar Date, Folder Number, Unit Case Number" at 15 35
write "Vessel Name, Sar Latitude, Sar Longitude" at 16 35
write "Sar Nature of Distress" at 17 35
fillin go using "Press [ENTER] to return to data entry" +
at 18 25
set var pg to 1
set var review to "Y"
break
endif
endif
if choice eq 1 or choice eq 2 then
*(enter sar units)
newpage
write "Enter sar units? (Y)" at 12 20
fillin s_units using "(" at 12 37
if s_units fails or s_units eq Y then
set var more to "Y"
while more eq Y then
set var vuwtime to .vsartime
set var vuwdate to .vsardate
set var vetadate to .vsardate
set var vdateos to .vsardate
set var valgdate to .vsardate
set var vtowdate to .vsardate
set var vdvmoort to .vsardate
set var vsumoord to .vsardate
newpage
write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw sarform8 with all at 3
edit var vunit vuwtime vuwdate voseta vetadate vostime +
vdateos valgtime valgdate vtowtime vtowdate vdvmoort +
vdvmoort vsumoord vsumoord return esc pgdn
if #return eq pgdn then
if voseta fails then
clear vetadate
set var vetadate date
endif
if vostime fails then
clear vdateos
set var vdateos date
endif
if valgtime fails then
clear valgdate
set var valgdate date
endif
if vtowtime fails then
clear vtowdate
set var vtowdate date
endif
if vdvmoort fails then
clear vdvmoort
set var vdvmoort date
endif
if vsumoord fails then
clear vsumoord
set var vsumoord date
endif
set pointer #1 e1 for sarunits whe foldno eq .vfoldno and +

```

```

unitname eq .vunit
newpage
if e1 eq 0 then
    write "Duplicate entry not loaded"
else
    write "Loading sarunits"
    load sarunits
        .vfoldno .vunit .vuwtime .vuwdate .voseta .vetadate +
        .vostime .vdateos .valgtime .valgdate .vtowtime +
        .vtowdate .vdvmoort .vdvmoord .vsumoort .vsumoord
    end
endif
write "More units to enter? (N)" at 23 20
fillin mrunits using "(" at 23 41
if mrunits fails or mrunits eq N then
    set var more to N
else
    clear vunit
    clear voseta
    clear vostime
    clear valgtime
    clear vtowtime
    clear vdvmoort
    clear vsumoord
endif
endif
if #return eq esc then
    set var more to N
endif
endwhile
endif
*(enter additional owners)
newpage
write "Enter additional owners? (N)" at 12 20
fillin addl_own using "(" at 12 45
if addl_own exists and addl_own eq Y then
    set var more to "Y"
    while more eq Y then
        set var vowelname to unk
        set var vowelname to unk
        newpage
        write "Press [PGDN] after entering initial information to +
check if" at 1 5
        write "owner exists in database. Press [ESC] to quit" at 2 10
        draw cg4100a3 with all at 4
        edit var return esc pgdn
        if #return ne esc then
            while vowelname exists and vowelname exists then
                set pointer #2 e2 for owners where ownlname = .vowelname +
                and ownfname = .vowelname
                newpage
                while e2 eq 0 then
                    *(owner last/first name exist in database)
                    set var vowelname to ownlmi in #2
                    set var vowelname to owndob in #2
                    set var vowelname to ownaddr in #2
                    set var vowelname to owncity in #2
                    set var vowelname to ownstate in #2
                    set var vowelname to ownzip in #2
                    set var vowelname to owntelno in #2
                    newpage
                    draw cg4100a3 with all at 3
                    draw cg4100a4 with all at 8
                    write "Correct owner? (N)" at 21 20
                    fillin owfound using "(" at 21 35
                    if owfound exists and owfound eq Y then
                        set var owl to .vowelname
                        set var owl to .vowelname
                        set var owl to ownlmi in #2
                        set var owl to ownaddr in #2

```

```

        set var ow5 to owncity in #2
        set var ow6 to ownstate in #2
        set var ow7 to ownzip in #2
        set var ow8 to owntelno in #2
        set var ow9 to owndob in #2
        set var ow10 to ownid in #2
        set var vownid to ownid in #2
        break
    endif
    next #2 e2
endwhile
if e2 ne 0 then
    newpage
    write "This owner does not exist in the database" +
    at 5 5
    fillin go using "Press [ENTER] to continue" at 9 5
    clear vowmi
    clear vowaddr
    clear vowcity
    set var vowst to CA
    clear vowzip
    clear vowntelno
    set var vowdob to 01/01/1901
    clear vovstatus
    compute vmaxown as max ownid from owners
    if vmaxown fails then
        set var vmaxown to 0
    endif
    set var vownid to .vmaxown + 1
endif
break
endwhile
label redoown
newpage
write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw cg4100a3 with all at 3
draw sarform5 with all at 8
edit var return esc pgup pgdn
if #return eq pgdn then
    set error messages off
    newpage
    if e2 eq 0 then
        *(owner exists in database)
        write "changing values in owner"
        delete rows from #2
    else
        write "loading owner"
    endif
    load owners
        .vowlname .vowfname .vowmi .vowaddr .vowcity .vowst +
        .vowzip .vowntelno .vowdob .vownid
    end
    if e2 eq 0 then
        set pointer #2 e2 for owners whe ownid eq .ow10
        if e2 ne 0 then
            load owners
                .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
            end
        endif
    endif
    set error messages on
    write "Return to correct errors? (N)" at 15 10
    write "Note: correct only errors indicated by messages" +
    at 20 5
    fillin fixown using "(" at 15 36
    if fixown exists and fixown eq Y then
        goto redoown
    endif
    set pointer #2 e2 for owvsl where vhinown eq .vvs1hin +
    and idowner eq .vownid

```

```

        *(check if record already exists)
        newpage
        if e2 ne 0 then
            load owvsl
            .vvsln .vownid
        end
    endif
endif
endif
write "More owners to enter? (N)" at 20 20
fillin mrownrs using "(" at 20 42
if mrownrs fails or mrownrs eq N then
    set var more to N
endif
endwhile
endif
*(enter additional operators)
newpage
write "Enter additional operators? (N)" at 12 20
fillin addl_opr using "(" at 12 48
if addl_opr exists and addl_opr eq Y then
    set var more to "Y"
    while more eq Y then
        set var voplname to unk
        set var vopfname to unk
        newpage
        write "Press [PGDN] after entering initial information to
check if" at 1 5
        write "operator exists in database. Press [ESC] to quit" +
        at 2 10
        draw cg4100a5 with all at 4
        edit var return esc pgdn
        if #return ne esc then
            while voplname exists and vopfname exists then
                set pointer #3 e3 for operator where oplname = .voplname +
                and opfname = .vopfname
                newpage
                while e3 eq 0 then
                    *(operator last/first name exist in database)
                    set var vopmi to opmi in #3
                    set var vopdob to opdob in #3
                    set var vopaddr to opaddr in #3
                    set var vopcity to opcity in #3
                    set var vopst to opstate in #3
                    set var vopzip to opzip in #3
                    set var voptelno to optelno in #3
                    set var vopcrse to opcourse in #3
                    newpage
                    draw cg4100a5 with all at 3
                    draw cg4100a6 with all at 8
                    write "Correct operator? (N)" at 21 20
                    fillin opfound using "(" at 21 39
                    if opfound exists and opfound eq Y then
                        set var op1 to .voplname
                        set var op2 to .vopfname
                        set var op3 to opmi in #3
                        set var op4 to opaddr in #3
                        set var op5 to opcity in #3
                        set var op6 to opstate in #3
                        set var op7 to opzip in #3
                        set var op8 to optelno in #3
                        set var op9 to opdob in #3
                        set var op10 to opcourse in #3
                        set var op11 to opid in #3
                        set var vopid to opid in #3
                        break
                    endif
                next #3 e3
            endwhile
        if e3 ne 0 then

```

```

newpage
write "This operator does not exist in the database"
at 5 5
fillin go using "Press [ENTER] to continue" at 9 5
clear vopmi
clear vopaddr
clear vopcity
set var vopst to CA
clear vopzip
clear voptelno
clear vopcrse
set var vopdob to 01/01/1901
compute vmaxoper as max opid from operator
if vmaxoper fails then
    set var vmaxoper to 0
endif
set var vopid to .vmaxoper + 1
endif
break
endwhile
label redooper
newpage
write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw cg4100a5 with all at 3
draw cg4100a6 with all at 8
edit var return esc pgup pgdn
if #return eq pgdn then
    newpage
    set error messages off
    if e3 eq 0 then
        *(operator exists in database)
        write "changing values in operator"
        delete rows from #3
    else
        write "loading operator"
    endif
    load operator
    .voplname .vopfname .vopmi .vopaddr .vopcity .vopst +
    .vopzip .voptelno .vopdob .vopcrse .vopid
end
if e3 eq 0 then
    set pointer #3 e3 for operator where opid eq .op11
    if e3 ne 0 then
        load operator
        .op1 .op2 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 +
        .op10 .op11
    end
endif
endif
set error messages on
write "Return to correct errors? (N)" at 15 10
write "Note: correct only errors indicated by messages" +
at 20 5
fillin fixopr using "(" at 15 36
if fixopr exists and fixopr eq Y then
    goto redooper
endif
set pointer #3 e3 for opvsl where vhinoper eq .vvs1hin +
and ldoper eq .vopid
*(check if record already exists)
newpage
if e3 ne 0 then
    load opvsl
    .vvs1hin .vopid
end
endif
endif
endif
write "More operators to enter? (N)" at 20 20
fillin mroper using "(" at 20 45

```



```

        if mproper fails or mproper eq N then
            set var more to N
        endif
    endwhile
endif
newpage
write "Enter another sar with boarding? (Y)" at 12 20
fillin cont using "(" at 12 53
if cont fails or cont eq Y then
    *(reset variables to start condition)
    clear all variables
    set var pg to 1
    set var review to "N"
    set var loadmenu to "N"
    break
else
    set null -0-
    set var pg to 0
endif
endif
if choice eq 3 then
    set var review to "Y"
    set var pg to 1
endif
endwhile
else
    newpage
    write "Enter another sar with boarding? (Y)" at 12 20
    fillin cont using "(" at 12 53
    if cont fails or cont eq Y then
        *(reset variables to start condition)
        clear all variables
        set var pg to 1
        set var review to "N"
        set var loadmenu to "N"
    else
        set error messages off
        set null -0-
        set var pg to 0
    endif
endif
if pg eq 1 then
    goto begin
endif
return
*( end )

```

# \$COMMAND

ADD SUT

\*(\*\*\*\*\*

Program:	Add Sar Units
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program allows the user to input sar unit data.
Tables Used:	sar, sarunits
Temp Tables:	none
Reports Used:	none
Forms Used:	sarform8

\*\*\*\*\*)

```

set error messages on
set messages off
set escape off
newpage

```

```

write "Program loading in progress. Please stand by ...." at 10 10
clear all variables
set null ?
set var more to Y
set var vfoldno text
set var vunit text
while more eq Y then *(main loop)
    set var done to Y
    newpage
    write "Enter folder number of sar case: " at 10 5
    fillin vfoldno using " " at 10 37
    write "Enter name of sar unit to be added: " at 15 5
    fillin vunit using " " at 15 40
    if vfoldno exists and vunit exists then
        set pointer #1 e1 for sar where folderno eq .vfoldno
        if e1 eq 0 then
            set pointer #2 e2 for sarunits where foldno eq .vfoldno and +
            unithname eq .vunit
            if e2 eq 0 then
                newpage
                write "This record already exists in the database" at 15 15
                write "Press any key to continue" at 18 20
                pause
            else
                set var vuwtime to sartime in #1
                set var vuwdate to sardate in #1
                set var vetadate to sardate in #1
                set var vdateos to sardate in #1
                set var valgdate to sardate in #1
                set var vtowdate to sardate in #1
                set var vdvmoort to sardate in #1
                set var vsumoort to sardate in #1
                newpage
                write "Press [PGDN] to load data or [ESC] to quit" at 1 1
                draw sarform8 with all at 3
                edit var vunit vuwtime vuwdate voseta vetadate vostime vdateos +
                valgtime valgdate vtowtime vtowdate vdvmoort vdvmoort vsumoort +
                vsumoort return esc pgdn
                if #return eq pgdn then
                    if voseta fails then
                        clear vetadate
                        set var vetadate date
                    endif
                    if vostime fails then
                        clear vdateos
                        set var vdateos date
                    endif
                    if valgtime fails then
                        clear valgdate
                        set var valgdate date
                    endif
                    if vtowtime fails then
                        clear vtowdate
                        set var vtowdate date
                    endif
                    if vdvmoort fails then
                        clear vdvmoort
                        set var vdvmoort date
                    endif
                    if vsumoort fails then
                        clear vsumoort
                        set var vsumoort date
                    endif
                    load sarunits
                    .vfoldno .vunit .vuwtime .vuwdate .voseta .vetadate +
                    .vostime .vdateos .valgtime .valgdate .vtowtime +
                    .vtowdate .vdvmoort .vdvmoort .vsumoort .vsumoort
                end
            endif
        endif
    endif
end

```

```

else
  newpage
  write "This folder number does not exist in the database" at 10 10
  write "Do you wish to reenter folder number? (Y)" at 15 10
  fillin reenter using "(" at 15 48
  if reenter fails or reenter eq Y then
    set var done to N
  endif
endif
endif
if done eq Y then
  newpage
  write "More sar units to enter? (N)" at 15 20
  fillin mrunits using "(" at 15 45
  if mrunits fails or mrunits eq N then
    set var more to N
  else
    clear all variables
    set var more to Y
  endif
endif
endwhile *(end main loop)
set error messages off
set null -0-
return
*( end )

```

# \$COMMAND

ADD BRD

\*(\*\*\*\*\*

```

Program:      Add Boarding
Author:       H R Lang and J D Allen
Date Written: July 1987
Description:  This program allows the user to input
              boarding information.
Tables Used:  boarding, vessel, owners, operator, owvsl,
              opvsl,
Temp Tables:  none
Reports Used: none
Forms Used:   cg4100a1, cg4100a2, cg4100a3, cg4100a4,
              cg4100a5, cg4100a6, cg4100a7, cg4100a8,
              cg4100a9, sarform5

```

\*\*\*\*\*)

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var pg to 1
*(initialize edit and load control variables)
set var review to N
set var loadmenu to N
label begin
set var backup to N
set var fixhin to N
set var pgcount to 0
while pg gt 0 then *(main loop)
  newpage
  if pg eq 1 then
    *(enter boarding/vessel information)
    if review eq N and backup eq N then
      set var pgcount to 1
    endif
  endif
endif

```

```

set var vbodate to .#date
set var vbotime to 12:00:00
set var vvslname to unk
write "Press [PGDN] after entering initial information to check +
if" at 1 5
write "vessel exists in database. Press [ESC] to quit" at 2 10
draw cg4100a1 with all at 4
edit var return esc pgdn
else
write "Press [PGDN] after review/correction or [ESC] to quit" +
at 1 5
draw cg4100a1 with all at 4
if fixhin eq N then
edit var vvslname vbodate vbotime vbono vvslnr return esc pgdn
else
edit var return esc pgdn
endif
endif
if #return ne esc then
if review eq N and backup eq N or fixhin eq Y then
set var pgcount to 1
while vvslnr exists then
set pointer #1 el for vessel where vslhin = .vvslnr
newpage
set var vvslnr to 0
set var vadult to 0
set var vchild to 0
if el eq 0 then
*(vessel exists in database)
set var vvslnr to vslno in #1
set var vvslname to vslname in #1
set var vvslnmake to vslmake in #1
set var vvslnmod to vslmodel in #1
set var vvslnyear to vslyear in #1
set var vvslnlon to vsltons in #1
set var vvslnft to vslenft in #1
set var vvslnin to vslenin in #1
set var vvslnhp to vslhp in #1
set var vvslnuse to vsluse in #1
set var vvslnype to vsltype in #1
set var vvslnprop to vslprop in #1
set var vvslnhull to vslhull in #1
set var vvslneng to vsleng in #1
set var vvslnfuel to vslfuel in #1
set var vvslnstr to vslconst in #1
set var vvslnecal to cmedecal in #1
set var vvslnyear to cmeyear in #1
set var vvslnfno to vslfno in #1
set var vvslnhome to homeport in #1
set var vvslnall to vslcall in #1
set var vvslnvalue to vslvalue in #1
set var vvslnsuper to vslsuper in #1
set var vvslnmasts to vslmasts in #1
set var vvslnsailno to sailno in #1
set var vvslnhcolor to hlcolor in #1
set var vvslntrcolor to trcolor in #1
set var vvslnslcolor to slcolor in #1
set var vvslnvcbcolor to cbcolor in #1
set var vvslnvdkcolor to dkcolor in #1
set var vvslnmarks to vslmarks in #1
set var v1 to vslno in #1
set var v2 to vslname in #1
set var v3 to vslhin in #1
set var v4 to vslmake in #1
set var v5 to vslmodel in #1
set var v6 to vslyear in #1
set var v7 to vsltons in #1
set var v8 to vslenft in #1
set var v9 to vslenin in #1
set var v10 to vslhp in #1

```

```

set var v11 to vsluse in #1
set var v12 to vsltype in #1
set var v13 to vslprop in #1
set var v14 to vslhull in #1
set var v15 to vsleng in #1
set var v16 to vslfuel in #1
set var v17 to vslconst in #1
set var v18 to cmedecal in #1
set var v19 to cmeyear in #1
set var v20 to vsloffno in #1
set var v21 to homeport in #1
set var v22 to vslcall in #1
set var v23 to vslvalue in #1
set var v24 to vslsuper in #1
set var v25 to vslmasts in #1
set var v26 to sailno in #1
set var v27 to hlcolor in #1
set var v28 to trcolor in #1
set var v29 to slcolor in #1
set var v30 to cbcolor in #1
set var v31 to dkcolor in #1
set var v32 to vslmarks in #1
else
  *(vessel does not exist in database)
  set var vvs1make to unk
  set var vvs1mod to unk
  set var vvs1year text
  set var vvs1year to 1901
  set var vvs1hp text
  set var vvs1hp to 0
  set var vvs1use text
  set var vvs1use to 0
  set var vvs1type text
  set var vvs1type to 9
  set var vvs1prop text
  set var vvs1prop to 9
  set var vvs1hull text
  set var vvs1hull to 8
  set var vvs1eng text
  set var vvs1eng to 0
  set var vvs1fuel text
  set var vvs1fuel to 0
  set var vconstr text
  set var vconstr to 0
  set var vvs1ton to 0
  set var vvs1ft to 0
  set var vvs1in to 0
  set var vdecal to N
endif
break
endwhile
newpage
write "Press [ESC] to quit or [PGDN] to move down a page" at 1 1
draw cg4100a1 with all at 3
draw cg4100a2 with all at 10
edit var return esc pgdn
endif
endif
if pg eq 2 then
  *(enter owner information)
  if review eq N and backup eq N then
    set var pgcount to 2
    set var vowlname to unk
    set var vowfname to unk
    write "Press [PGDN] after entering initial information to check +
if" at 1 5
    write "owner exists in database. Press [ESC] to quit" at 2 10
    draw cg4100a3 with all at 4
    edit var return esc pgdn

```

```

endif
if #return ne esc then
  if review eq N and backup eq N then
    while vowelname exists and vowelname exists then
      set pointer #2 e2 for owners where ownlname = .vowelname and +
      ownfname = .vowelname
      newpage
      while e2 eq 0 then
        *(owner last/first name exist in database)
        set var vowelmi to ownmi in #2
        set var vowelob to owndob in #2
        set var voweladdr to ownaddr in #2
        set var vowelcity to owncity in #2
        set var vowelst to ownstate in #2
        set var vowelzip to ownzip in #2
        set var voweltno to owntelno in #2
        newpage
        draw cg4100a3 with all at 3
        draw cg4100a4 with all at 8
        write "Correct owner? (N)" at 21 20
        fillin owfound using "(" at 21 35
        if owfound exists and owfound eq Y then
          set var owl to .vowelname
          set var ow2 to .vowelname
          set var ow3 to ownmi in #2
          set var ow4 to ownaddr in #2
          set var ow5 to owncity in #2
          set var ow6 to ownstate in #2
          set var ow7 to ownzip in #2
          set var ow8 to owntelno in #2
          set var ow9 to owndob in #2
          set var owl0 to ownid in #2
          set var vownid to ownid in #2
          break
        endif
        next #2 e2
      endwhile
      if e2 ne 0 then
        newpage
        write "This owner does not exist in the database" at 5 5
        fillin go using "Press [ENTER] to continue" at 9 5
        clear vowelmi
        clear voweladdr
        clear vowelcity
        set var vowelst to CA
        clear vowelzip
        clear voweltno
        set var vowelob to 01/01/1901
        clear vstatus
        compute vmaxown as max ownid from owners
        if vmaxown fails then
          set var vmaxown to 0
        endif
        set var vownid to .vmaxown + 1
      endif
      break
    endwhile
  endif
  newpage
  write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
  draw cg4100a3 with all at 3
  draw cg4100a4 with all at 8
  edit var return esc pgup pgdn
endif
endif
if pg eq 3 then
  *(enter operator information)
  if review eq N and backup eq N then
    set var pgcount to 3

```

```

if vstatus eq 1 then
  set var voplname to .vowlname
  set var vopfname to .vowfname
  set var #return to pgdn
else
  write "Press [PGDN] after entering initial information to +
check if" at 1 5
  write "operator exists in database. Press [ESC] to quit" +
  at 2 10
  set var voplname to unk
  set var vopfname to unk
  draw cg4100a5 with all at 4
  edit var return esc pgdn
endif
endif
if #return ne esc then
  if review eq N and backup eq N then
    while voplname exists and vopfname exists then
      set pointer #3 e3 for operator where oplname = .voplname and +
      opfname = .vopfname
      newpage
      while e3 eq 0 then
        *(operator last/first name exist in database)
        set var vopmi to opmi in #3
        set var vopdob to opdob in #3
        set var vopaddr to opaddr in #3
        set var vopcity to opcity in #3
        set var vopst to opstate in #3
        set var vopzip to opzip in #3
        set var voptelno to optelno in #3
        set var vopcrse to opcouse in #3
        newpage
        draw cg4100a5 with all at 3
        draw cg4100a6 with all at 8
        write "Correct operator? (N)" at 21 20
        fillin opfound using "(" at 21 38
        if opfound exists and opfound eq Y then
          set var op1 to .voplname
          set var op2 to .vopfname
          set var op3 to opmi in #3
          set var op4 to opaddr in #3
          set var op5 to opcity in #3
          set var op6 to opstate in #3
          set var op7 to opzip in #3
          set var op8 to optelno in #3
          set var op9 to opdob in #3
          set var op10 to opcouse in #3
          set var op11 to opid in #3
          set var vopid to opid in #3
          break
        endif
        next #3 e3
      endwhile
      if e3 ne 0 then
        newpage
        write "This operator does not exist in the database" at 5 5
        fillin go using "Press [ENTER] to continue" at 9 5
        if vstatus eq 1 then
          set var vopmi to .vowmi
          set var vopaddr to .vowaddr
          set var vopcity to .vowcity
          set var vopst to .vowst
          set var vopzip to .vowzip
          set var voptelno to .vowtelno
          set var vopdob to .vowdob
        else
          clear vopmi
          clear vopaddr

```

```

        clear vopcitty
        set var vopst to CA
        clear vopzip
        clear voptelno
        set var vopdob to 01/01/1901
    endif
    clear vopcrse
    compute vmaxop as max opid from operator
    if vmaxop fails then
        set var vmaxop to 0
    endif
    set var vopid to .vmaxop + 1
    endif
    break
endwhile
endif
newpage
write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" at 1 1
draw cg4100a5 with all at 3
draw cg4100a6 with all at 8
if vstatus eq 1 then
    edit var vopcrse return esc pgup pgdn
else
    edit var return esc pgup pgdn
endif
endif
endif
if pg eq 4 then
    *(enter boarding location information)
    if review eq N and backup eq N then
        set var pgcount to 4
        set var vobsbody to text
        set var vobsbody to "Monterey Bay"
        set var vobcount to Monterey
        set var vobscity to Monterey
        set var vobstate to CA
        set var vobslat to 00.000
        set var vobslong to 000.000
    endif
    write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move down +
a page" at 1 1
    draw cg4100a7 with all at 3
    edit var return esc pgup pgdn
endif
if pg eq 5 then
    *(enter boarding violation/unsafe condition information)
    if review eq N and backup eq N then
        set var pgcount to 5
    endif
    write "Press [ESC] to quit, [PGUP] to move up, [PGDN] to move +
down a page" +
    at 1 1
    draw cg4100a8 with all at 3
    edit var return esc pgup pgdn
endif
if pg eq 6 then
    *(enter boarding officer information)
    if review eq N and backup eq N then
        set var pgcount to 6
        set var vbounit text
        set var vbounit to "CG Group Monterey"
        set var vbodist text
        set var vbodist to 11
        set var vboopfacs text
        set var vboopfacs to 36268
        set var vbosrise to 06:00:00
        set var vbosset to 19:00:00
        set var vweapons to 0
    endif

```



```

write "Press [ESC] to quit or [PGUP] to move up a page" at 1 1
draw cg4100a9 with all at 3
edit var return esc pgup
set var loadmenu to "Y"
endif
if #return eq pgup then
set var backup to Y
if pg gt 1 then
set var pg to .pg - 1
else
set var pg to 1
endif
endif
if #return eq pgdn then
if pg lt 6 then
set var pg to .pg + 1
if pgcount lt .pg then
set var backup to N
endif
else
set var pg to 6
endif
endif
if #return eq esc then
set var pg to 0
endif
endwhile *(end of main loop)
newpage
write "Program loading in progress. Please stand by ....." at 10 10
if loadmenu eq "Y" then
set var choice to 0
while choice lt 1 or choice gt 3 then
newpage
write "Data Load Options" at 2 20
write "-----" at 3 20
write "Enter:" at 5 20
write "1-To load the data into the database" at 6 20
write "2-To ignore the data entered" at 7 20
write "3-To go back and verify data entered" at 8 20
write "Your choice: " at 10 20
fillin choice using " " at 10 33
newpage
if choice eq 1 then
*(test for required information)
set var test to "F"
if vbodate exists and vbotime exists and vbono exists and +
vvslname exists and vobslat exists and vobslong exists and +
vvsllin exists then
if vviol54 exists or vviol55 exists or vviol56 exists or +
vviol57 exists or vviol58 exists or vviol59 exists or vviol60 +
exists or vviol61 exists or vviol62 exists or vviol63 exists then
set var test to "T"
endif
if vviol64 exists or vviol65 exists or vviol66 exists or +
vviol67 exists or vviol68 exists or vuns69 exists or vuns70 +
exists or vuns71 exists or vuns72 exists or vuns73 exists then
set var test to "T"
endif
if vuns74 exists or vuns75 exists or vuns76 exists or vuns77 +
exists or vuns78 exists or vuns79 exists then
set var test to "T"
endif
if test eq "T" then
set error messages off
if el eq 0 then
*(vessel exists in database)
write "changing values in vessel"
delete rows from #1
else
write "loading vessel"

```

```

set var voffno text
set var vhome text
set var vcall text
set var vvalue dollar
set var vvalue to $0
set var vsuper text
set var vmasts text
set var vsailno text
set var vhlcolor to unk
set var vtrcolor to unk
set var vslcolor to unk
set var vcbcolor to unk
set var vdkcolor to unk
set var vmarks text
endif
load vessel
.vvslno .vvslname .vvslhin .vvslmake .vvslmod .vvslyear +
.vvslton .vvslft .vvslin .vvslhp .vvsluse .vvsltype +
.vvslprop .vvslhull .vvsleng .vvslfuel .vconstr .vdecals +
.vcmeyear .voffno .vhome .vcall .vvalue .vsuper .vmasts +
.vvslno .vhlcolor .vtrcolor .vslcolor .vcbcolor .vdkcolor +
.vmarks
end
if e1 eq 0 then
set pointer #1 e1 for vessel whe vslhin eq .v3
if e1 ne 0 then
load vessel
.v1 .v2 .v3 .v4 .v5 .v6 .v7 .v8 .v9 .v10 .v11 .v12 +
.v13 .v14 .v15 .v16 .v17 .v18 .v19 .v20 .v21 .v22 .v23 +
.v24 .v25 .v26 .v27 .v28 .v29 .v30 .v31 .v32
end
endif
endif
write "loading owvsl"
load owvsl
.vvslhin .vownid
end
write "loading opvsl"
load opvsl
.vvslhin .vopid
end
if vstatus eq 1 then
load opown
.vownid .vopid
end
endif
set pointer #1 e1 for boarding where bono = .vbono
if e1 eq 0 then
set var difbo to "F"
set var b1 to bodate in #1
set var b2 to botime in #1
set var b3 to obslat in #1
set var b4 to obslong in #1
if b1 ne .vbodate or b2 ne .vbotime or b3 ne .vobslat or +
b4 ne .vobslong then
set var difbo to "T"
endif
else
set var difbo to "T"
endif
if difbo eq T then
write "loading boarding"
load boarding
.vbodate .vbotime .vbono .vvslpob .vadult .vchild +
.vvstatus .vobsbody .vobcount .vobscity .vobstate +
.vvobslat .vobslong .vvviol54 .vvviol55 .vvviol56 .vvviol57 +
.vvviol58 .vvviol59 .vvviol60 .vvviol61 .vvviol62 .vvviol63 +
.vvviol64 .vvviol65 .vvviol66 .vvviol67 .vvviol68 .vuns69 +
.vuns70 .vuns71 .vuns72 .vuns73 .vuns74 .vuns75 .vuns76 +
.vuns77 .vuns78 .vuns79 .vborem1 .vborem2 .vborem3 +

```

```

        .vboname .vborate .vbounit .vbodist .vboopfac .vboday +
        .vbosrise .vbosset .vvslnhin .vweapons
    end
endif
if e2 eq 0 then
    *(owner exists in database)
    write "changing values in owner"
    delete rows from #2
else
    write "loading owner"
endif
load owners
    .vowlname .vowfname .vowmi .vowaddr .vowcity .vowst .vowzip +
    .vowtelno .vowdob .vownid
end
if e2 eq 0 then
    set pointer #2 e2 for owners whe ownid eq .ow10
    if e2 ne 0 then
        load owners
            .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
        end
    endif
endif
if e3 eq 0 then
    *(operator exists in database)
    write "changing values in operator"
    delete rows from #3
else
    write "loading operator"
endif
load operator
    .voplname .vopfname .vopmi .vopaddr .vopcity .vopst .vopzip +
    .voptelno .vopdob .vopcrse .vopid
end
if e3 eq 0 then
    set pointer #3 e3 for operator where opid eq .op11
    if e3 ne 0 then
        load operator
            .op1 .op2 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 .op10 +
            .op11
        end
    endif
endif
endif
set error messages on
write " "
*(return option in case of entry/edit errors)
write "Return to correct data entered? (Y)" at 20 10
write "Note: correct only errors indicated by messages" +
at 22 5
fillin er using "(" at 20 42
if er fails or er eq "Y" then
    set var review to "Y"
    set var pg to 1
    set pointer #1 e1 for vessel where vslhin eq .vvslnhin
    set pointer #2 e2 for owners where ownid eq .vownid
    set pointer #3 e3 for operator where opid eq .vopid
    break
else
    newpage
    write "Removing duplicate entries from tables" at 10 10
    write "Please stand by....." at 15 12
    delete duplicates from vessel
    delete duplicates from owvsl
    delete duplicates from opvsl
    delete duplicates from opown
    delete duplicates from owners
    delete duplicates from operator
endif
endif
else

```

```

newpage
write "Load not performed. Required information missing." +
at 5 20
write "Required information includes:" at 10 30
write "Boarding Date, Boarding Time, Boarding Number" at 12 35
write "Vessel Name, Boarding Latitude, Boarding Longitude" +
at 13 35
write "Vessel HIN, A Violation or Unsafe Condition" at 14 35
fillin go using "Press [ENTER] to return to data entry" at 16 25
set var pg to 1
set var review to Y
if vvslhin fails then
    set var fixhin to Y
endif
break
endif
endif
if choice eq 1 or choice eq 2 then
    *(enter additional owners)
    newpage
    write "Enter additional owners? (N)" at 12 20
    fillin addl_own using "(" at 12 45
    if addl_own exists and addl_own eq Y then
        set var more to "Y"
        while more eq Y then
            set var vowelname to unk
            set var vowelname to unk
            newpage
            write "Press [PGDN] after entering initial information to +
check if" at 1 5
            write "owner exists in database. Press [ESC] to quit" +
at 2 10
            draw cg4100a3 with all at 4
            edit var return esc pgdn
            if #return ne esc then
                while vowelname exists and vowelname exists then
                    set pointer #2 e2 for owners where ownlname = .vowelname +
and ownfname = .vowelname
                    newpage
                    while e2 eq 0 then
                        *(owner last/first name exist in database)
                        set var vowelname to ownmi in #2
                        set var vowelname to owndob in #2
                        set var vowelname to ownaddr in #2
                        set var vowelname to owncity in #2
                        set var vowelname to ownstate in #2
                        set var vowelname to ownzip in #2
                        set var vowelname to owntelno in #2
                        newpage
                        draw cg4100a3 with all at 3
                        draw cg4100a4 with all at 8
                        write "Correct owner? (N)" at 21 20
                        fillin owfound using "(" at 21 35
                        if owfound exists and owfound eq Y then
                            set var ow1 to .vowelname
                            set var ow2 to .vowelname
                            set var ow3 to ownmi in #2
                            set var ow4 to ownaddr in #2
                            set var ow5 to owncity in #2
                            set var ow6 to ownstate in #2
                            set var ow7 to ownzip in #2
                            set var ow8 to owntelno in #2
                            set var ow9 to owndob in #2
                            set var ow10 to ownid in #2
                            set var vowelname to ownid in #2
                            break
                        endif
                        next #2 e2
                    endwhile
                    if e2 ne 0 then

```

```

newpage
write "This owner does not exist in the database" at 5 5
fillin go using "Press [ENTER] to continue" at 9 5
clear vowmi
clear vowaddr
clear vowcity
set var vowst to CA
clear vowzip
clear vowtelno
set var vowdob to 01/01/1901
compute vmaxown as max ownid from owners
if vmaxown fails then
    set var vmaxown to 0
endif
set var vownid to .vmaxown + 1
endif
break
endwhile
label redoown
newpage
write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw cg4100a3 with all at 3
draw sarform5 with all at 8
edit var return esc pgup pgdn
if #return eq pgdn then
    newpage
    set error messages off
    if e2 eq 0 then
        *(owner exists in database)
        write "changing values in owner"
        delete rows from #2
    else
        write "loading owner"
    endif
    load owners
        .vowlname .vowfname .vowmi .vowaddr .vowcity .vowst +
        .vowzip .vowtelno .vowdob .vownid
    end
    if e2 eq 0 then
        set pointer #2 e2 for owners where ownid eq .ow10
        if e2 ne 0 then
            load owners
                .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
            end
        endif
    endif
    set error messages on
    write "Return to correct errors? (N)" at 15 10
    write "Note: correct only errors indicated by messages" +
    at 20 5
    fillin fixown using "(" at 15 36
    if fixown exists and fixown eq Y then
        set pointer #2 e2 for owners where ownid eq .vownid
        goto redoown
    endif
    set pointer #2 e2 for owvsl where vhinown eq .vvslhin +
    and idowner eq .vownid
    *(check if record already exists)
    newpage
    if e2 ne 0 then
        load owvsl
            .vvslhin .vownid
        end
    endif
endif
endif
write "More owners to enter? (N)" at 20 20
fillin mrownrs using "(" at 20 42
if mrownrs fails or mrownrs eq N then
    set var more to N

```

```

endif
endwhile
endif
*(enter additional operators)
newpage
write "Enter additional operators? (N)" at 12 20
fillin addl_opr using "(" at 12 48
if addl_opr exists and addl_opr eq Y then
    set var more to "Y"
    while more eq Y then
        set var voplname to unk
        set var vopfname to unk
        newpage
        write ".ress [PGDN] after entering initial information to +
check if" at 1 5
        write "operator exists in database. Press [ESC] to quit" +
        at 2 10
        draw cg4100a5 with all at 4
        edit var return esc pgdn
        if #return ne esc then
            while voplname exists and vopfname exists then
                set pointer #3 e3 for operator where oplname = .voplname +
                and opfname = .vopfname
                newpage
                while e3 eq 0 then
                    *(operator last/first name exist in database)
                    set var vopmi to opmi in #3
                    set var vopdob to opdob in #3
                    set var vopaddr to opaddr in #3
                    set var vopcity to opcity in #3
                    set var vopst to opstate in #3
                    set var vopzip to opzip in #3
                    set var voptelno to optelno in #3
                    set var vopcrse to opcourse in #3
                    newpage
                    draw cg4100a5 with all at 3
                    draw cg4100a6 with all at 8
                    write "Correct operator? (N)" at 21 20
                    fillin opfound using "(" at 21 38
                    if opfound exists and opfound eq Y then
                        set var op1 to .voplname
                        set var op2 to .vopfname
                        set var op3 to opmi in #3
                        set var op4 to opaddr in #3
                        set var op5 to opcity in #3
                        set var op6 to opstate in #3
                        set var op7 to opzip in #3
                        set var op8 to optelno in #3
                        set var op9 to opdob in #3
                        set var op10 to opcourse in #3
                        set var op11 to opid in #3
                        set var vopid to opid in #3
                        break
                    endif
                next #3 e3
            endwhile
            if e3 ne 0 then
                newpage
                write "This operator does not exist in the database" +
                at 5 5
                fillin go using "Press [ENTER] to continue" at 9 5
                clear vopmi
                clear vopaddr
                clear vopcity
                set var vopst to CA
                clear vopzip
                clear voptelno
                clear vopcrse
                set var vopdob to 01/01/1901
                compute vmaxoper as max opid from operator
            endif
        endif
    endwhile
endif

```

```

        if vmaxoper fails then
            set var vmaxoper to 0
        endif
        set var vopid to .vmaxoper + 1
    endif
    break
endwhile
label redooper
newpage
write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw cg4100a5 with all at 3
draw cg4100a6 with all at 8
edit var return esc pgup pgdn
if #return eq pgdn then
    newpage
    set error messages off
    if e3 eq 0 then
        *(operator exists in database)
        write "changing values in operator"
        delete rows from #3
    else
        write "loading operator"
    endif
    load operator
        .voplname .vopf.name .vopmi .vopaddr .vopcity .vopst +
        .vopzip .voptelno .vopdob .vopcrse .vopid
    end
    if e3 eq 0 then
        set pointer #3 e3 for operator where opid eq .op11
        if e3 ne 0 then
            load operator
                .op1 .op2 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 +
                .op10 .op11
            end
        endif
    endif
    set error messages on
    write "Return to correct errors? (N)" at 15 10
    write "Note: correct only errors indicated by messages" +
    at 20 5
    fillin fixopr using "(" at 15 36
    if fixopr exists and fixopr eq Y then
        set pointer #3 e3 for operator where opid eq .vopid
        goto redooper
    endif
    set pointer #3 e3 for opvsl where vhinoper eq .vvsln +
    and idoper eq .vopid
    *(check if record already exists)
    newpage
    if e3 ne 0 then
        load opvsl
            .vvsln .vopid
        end
    endif
endif
endif
endif
write "More operators to enter? (N)" at 20 20
fillin mroper using "(" at 20 45
if mroper fails or mroper eq N then
    set var more to N
endif
endwhile
endif
newpage
write "Enter another boarding? (Y)" at 12 20
fillin cont using "(" at 12 44
if cont fails or cont eq Y then
    *(reset variables to start condition)
    clear all variables
    set var pg to 1
endif

```

```

        set var review to "N"
        set var loadmenu to "N"
        break
    else
        set null -0-
        set var pg to 0
    endif
endif
if choice eq 3 then
    set var review to "Y"
    set var pg to 1
endif
endwhile
else
    newpage
    write "Enter another boarding? (Y)" at 12 20
    fillin cont using "(" at 12 44
    if cont fails or cont eq Y then
        *(reset variables to start condition)
        clear all variables
        set var pg to 1
        set var review to "N"
        set var loadmenu to "N"
    else
        set error messages off
        set null -0-
        set var pg to 0
    endif
endif
if pg eq 1 then
    goto begin
endif
return
*( end )

```

# \$COMMAND

## ADD\_OWNER

```

*(*****

```

Program:	Add Owner
Author:	H R Lang and J D Allen
Date Written:	July 1987
Description:	This program allows the user to input additional owner information.
Tables Used:	vessel, owners, owvsl
Temp Tables:	none
Reports Used:	none
Forms Used:	ownrmod1, ownrmod2

```

*****

```

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var vvslnh text
set var more to Y
while more eq Y then *(main loop)
    set var done to Y
    newpage
    write "Enter HIN of vessel owned: " at 10 10
    fillin vvslnh using " " at 10 36
    if vvslnh exists then
        set pointer #1 el for vessel where vslhin eq .vvslnh
    endif
endif

```



```

if e1 eq 0 then
  newpage
  write "Press [PGDN] after entering initial information to check +
if" at 1 5
  write "owner exists in database. Press [ESC] to quit" at 2 10
  draw ownrmod1 with all at 4
  edit var return esc pgdn
  if #return eq pgdn then
    if vowelname exists and vowfname exists then
      set pointer #2 e2 for owners where ownlname = .vowelname and +
      ownfname = .vowfname
      while e2 eq 0 then
        *(owner last/first name exist in database)
        set var vowmi to ownmi in #2
        set var vowdob to owndob in #2
        set var vowaddr to ownaddr in #2
        set var vowcity to owncity in #2
        set var vowst to ownstate in #2
        set var vowzip to ownzip in #2
        set var vowtelno to owntelno in #2
        newpage
        draw ownrmod1 with all at 3
        draw ownrmod2 with all at 8
        write "Correct owner? (N)" at 21 20
        fillin owfound using "(" at 21 35
        if owfound exists and owfound eq Y then
          newpage
          write "This owner already exists in the database" at 10 10
          set var vownid to ownid in #2
          set pointer #3 e3 for owvsl where vhinown eq .vvsln +
          and idowner eq .vownid
          if e3 ne 0 then
            load owvsl
            .vvsln .vownid
          end
          write "The new owner-vessel record has been created" +
          at 15 10
        endif
        break
      endif
    next #2 e2
  endwhile
  if e2 ne 0 then
    clear vowmi
    clear vowaddr
    clear vowcity
    set var vowst to CA
    clear vowzip
    clear vowtelno
    set var vowdob to 01/01/1901
    clear vstatus
    compute vmaxown as max ownid from owners
    if vmaxown fails then
      set var vmaxown to 0
    endif
    set var vownid to .vmaxown + 1
    newpage
    write "Press [PGDN] to load data or [ESC] to quit" at 1 1
    draw ownrmod1 with all at 3
    draw ownrmod2 with all at 8
    edit var return esc pgdn
    if #return eq pgdn then
      set var out to N
      set var loadok to N
      while loadok eq N then
        newpage
        load owners
        .vowelname .vowfname .vowmi .vowaddr .vowcity .vowst +
        .vowzip .vowtelno .vowdob .vownid
      end
    end
  end
end

```

```

write "Return to correct errors? (N)" at 10 10
write "Note: correct only errors indicated by +
messages" at 15 5
fillin er using "(" at 10 36
if er fails or er eq N then
    set var loadok to Y
    set var done to Y
else
    *(edit record again)
    newpage
    write "Press [PGDN] to load data or [ESC] to quit" +
    at 1 1
    draw ownrmod1 with all at 3
    draw ownrmod2 with all at 8
    edit var return esc pgdn
    if #return eq esc then
        set var out to Y
        break
    endif
endif
endif
endwhile
if out eq N then
    load owvsl
    .vvs1hin .vownid
end
endif
endif
endif
endif
else
    newpage
    write "This HIN does not exist in the database" at 10 10
    write "Do you wish to reenter the HIN? (Y)" at 15 10
    fillin reenter using "(" at 15 42
    if reenter fails or reenter eq Y then
        set var done to N
    endif
endif
endif
if done eq Y then
    newpage
    write "More owners to be entered? (N)" at 12 20
    fillin mrownrs using "(" at 12 47
    if mrownrs fails or mrownrs eq N then
        set var more to N
    else
        clear all variables
        set var more to Y
    endif
endif
endwhile *(end main loop)
set error messages on
set null -0-
return
*( end )

```

## APPENDIX H

### MODIFY SOURCE CODE

\$COMMAND

MODMAIN

\*(\*\*\*\*\*)

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

MODIFY MAIN MENU and APPLICATIONS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*\*\*\*\*)

```
set messages off
set escape off
newpage
clear all variables
set var pick3 integer
newpage
choose pick3 from mod_menu in modify.apx
if pick3 eq 0 then
    quit to restmod.cmd
endif
if pick3 eq 1 then
    run mod_sar in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 2 then
    run mod_brd in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 3 then
    run mod_vsl in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 4 then
    run mod_owop in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 5 then
    run mod_sut in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 6 then
    run am_vint in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 7 then
    run am_pint in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 8 then
    run mod_vhin in modify.apx
    quit to restmod.cmd
endif
if pick3 eq 9 then
```

```

quit to restmain.cmd
endif
quit to restmod.cmd
return
$menu
mod_menu
column SARELTIS --- MODIFY MENU
MODIFY SAR INFORMATION
MODIFY BOARDING INFORMATION
MODIFY VESSEL INFORMATION
MODIFY OWNER/OPERATOR INFORMATION
MODIFY SAR UNIT INFORMATION
MODIFY VESSEL INTELLIGENCE
MODIFY PERSONNEL INTELLIGENCE
MODIFY VESSEL HIN
RETURN TO MAIN MENU
*( end )

```

# \$COMMAND

## MOD\_SAR

```

*(*****

```

```

Program:          Modify Sar
Author:           H R Lang and J D Allen
Date Written:     August 1987
Description:       This program allows the user to modify
                  sar information in the database.
Tables Used:      sar, vessel
Temp Tables:      none
Reports Used:     none
Forms Used:       sarmod

```

```

*****

```

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var more to Y
set var vfoldno text
while more eq Y then
  set var change to N
  set var reenter to N
  newpage
  write "Enter folder number of sar case requiring modification: " +
  at 10 5
  fillin vfoldno using " " at 10 60
  while vfoldno exists then
    newpage
    write "Searching SAR Table. Please stand by ...." at 10 10
    set pointer #1 el for sar where folderno eq .vfoldno
    if el eq 0 then
      *(sar case exists in database)
      set var vucn to ucn in #1
      set var vmucn to mucn in #1
      set var vsardate to sardate in #1
      set var vsarday to sarday in #1
      set var vsartime to sartime in #1
      set var vsunrise to ssunrise in #1
      set var vsunset to ssunset in #1
      set var vsarnod to sarnod in #1
      set var vsarpob to sarpob in #1
      set var vsarhin to sarvhin in #1
      set var vsarlat to sarlat in #1
    else
      set var more to N
    endif
  endwhile
endwhile

```

```

set var vsarlong to sarlong in #1
set var vdistoff to offshore in #1
set var vimmed to immedsar in #1
set var vwinddir to winddir in #1
set var vwindspd to windspd in #1
set var vvisdist to visdist in #1
set var vclouds to clouds in #1
set var vceiling to ceiling in #1
set var vseas to seas in #1
set var vswells to swells in #1
set var oldfold to .vfoldno
set var change to Y
set var s1 to folderno in #1
set var s2 to ucn in #1
set var s3 to mucn in #1
set var s4 to sardate in #1
set var s5 to sarday in #1
set var s6 to sartime in #1
set var s7 to ssunrise in #1
set var s8 to ssunset in #1
set var s9 to sarnod in #1
set var s10 to sarpob in #1
set var s11 to sarvhin in #1
set var s12 to sarlat in #1
set var s13 to sarlong in #1
set var s14 to offshore in #1
set var s15 to immedsar in #1
set var s16 to winddir in #1
set var s17 to windspd in #1
set var s18 to visdist in #1
set var s19 to clouds in #1
set var s20 to ceiling in #1
set var s21 to seas in #1
set var s22 to swells in #1
else
  newpage
  write "This folder number does not exist in the database" at 10 10
  write "Do you wish to reenter the folder number? (Y)" at 12 10
  fillin correct using "(" at 12 52
  if correct fails or correct eq Y then
    set var reenter to Y
  endif
endif
break
endwhile
while change eq Y then
  set pointer #2 e2 for vessel where vs1hin eq .vsarhin
  set var vvs1name to vs1name in #2
  newpage
  write "press [PGDN] to load changes or [ESC] to quit" at 1 1
  draw sarmod with all at 3
  edit var vfoldno vsardate vucn vmucn vsarday vsartime vsarpob +
  vsarnod vimmed vsarlat vsarlong vdistoff vvisdist vsunrise vsunset +
  vceiling vclouds vwinddir vwindspd vseas vswells return esc pgdn
  if #return eq pgdn then
    newpage
    write "Changing values in sar"
    if oldfold ne .vfoldno then
      set pointer #2 e2 for sarunits where foldno eq .oldfold
      while e2 eq 0 then
        change foldno to .vfoldno in #2
        next #2 e2
      endwhile
    endif
    delete rows from #1
    load sar
    .vfoldno .vucn .vmucn .vsardate .vsarday .vsartime .vsunrise +
    .vsunset .vsarnod .vsarpob .vsarhin .vsarlat .vsarlong +
    .vdistoff .vimmed .vwinddir .vwindspd .vvisdist .vclouds +
    .vceiling .vseas .vswells
  endif
endwhile

```

```

end
set pointer #2 e2 for sar where folderno eq .s1 or folderno eq +
.vfoldno
if e2 ne 0 then
  load sar
  .s1 .s2 .s3 .s4 .s5 .s6 .s7 .s8 .s9 .s10 .s11 .s12 .s13 .s14 +
  .s15 .s16 .s17 .s18 .s19 .s20 .s21 .s22
end
set pointer #3 e3 for sarunits where foldno eq .vfoldno
while e3 eq 0
  change foldno to .s1 in #3
  next #3 e3
endwhile
endif
write "Return to correct data entered? (N)" at 15 10
write "Note: correct only errors indicated by messages" at 20 5
fillin er using "(" at 15 42
if er fails or er eq N then
  set var change to N
endif
else
  set var change to N
endif
endwhile
if reenter eq N then
  newpage
  write "More sar cases to be changed? (N)" at 12 20
  fillin mrsar using "(" at 12 50
  if mrsar fails or mrsar eq N then
    set var more to N
  endif
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

# \$COMMAND

MOD BRD

\*\*\*\*\*

Program:	Modify Boarding
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program allows the user to modify boarding information in the database.
Tables Used:	boarding, vessel
Temp Tables:	none
Reports Used:	none
Forms Used:	bomod1, bomod2, bomod3

\*\*\*\*\*

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var pg to 1
set var review to N
*(controls relation search- if reviewing, don't search)
while pg gt 0 then *(main loop)
  if review eq N then
    newpage

```

```

set var fix to N
set var chk-mr to N
set var vbono text
write "Enter report number of boarding requiring modification: " +
at 10 5
fillin vbono using " " at 10 60
while vbono exists then
  newpage
  write "Searching Boarding Table. Please stand by ....." at 10 10
  set pointer #1 e1 for boarding where bono eq .vbono
  if e1 eq 0 then
    *(record exists in database)
    set var vbodate to bodate in #1
    set var vbotime to botime in #1
    set var vvslopob to vslopob in #1
    set var vadult to adultpfd in #1
    set var vchild to childpfd in #1
    set var vstatus to owstatus in #1
    set var vobsbody to obsbody in #1
    set var vobcount to obscount in #1
    set var vobscity to obscity in #1
    set var vobstate to obsstate in #1
    set var vobslat to obslat in #1
    set var vobslong to obslong in #1
    set var vviol54 to viol54 in #1
    set var vviol55 to viol55 in #1
    set var vviol56 to viol56 in #1
    set var vviol57 to viol57 in #1
    set var vviol58 to viol58 in #1
    set var vviol59 to viol59 in #1
    set var vviol60 to viol60 in #1
    set var vviol61 to viol61 in #1
    set var vviol62 to viol62 in #1
    set var vviol63 to viol63 in #1
    set var vviol64 to viol64 in #1
    set var vviol65 to viol65 in #1
    set var vviol66 to viol66 in #1
    set var vviol67 to viol67 in #1
    set var vviol68 to viol68 in #1
    set var vuns69 to uns69 in #1
    set var vuns70 to uns70 in #1
    set var vuns71 to uns71 in #1
    set var vuns72 to uns72 in #1
    set var vuns73 to uns73 in #1
    set var vuns74 to uns74 in #1
    set var vuns75 to uns75 in #1
    set var vuns76 to uns76 in #1
    set var vuns77 to uns77 in #1
    set var vuns78 to uns78 in #1
    set var vuns79 to uns79 in #1
    set var vborem1 to boreml in #1
    set var vborem2 to boreml in #1
    set var vborem3 to boreml in #1
    set var vbname to boname in #1
    set var vborate to borate in #1
    set var vbounit to bounit in #1
    set var vbodist to bodist in #1
    set var vboopfac to boopfac in #1
    set var vboday to boday in #1
    set var vbosrise to bsunrise in #1
    set var vbosset to bsunset in #1
    set var vvsllhin to bovlin in #1
    set var vweapons to weapons in #1
    set var b1 to bodate in #1
    set var b2 to botime in #1
    set var b3 to bono in #1
    set var b4 to vslopob in #1
    set var b5 to adultpfd in #1
    set var b6 to childpfd in #1
    set var b7 to owstatus in #1

```

```

set var b8 to obsbody in #1
set var b9 to obscount in #1
set var b10 to obscity in #1
set var b11 to obsstate in #1
set var b12 to obslat in #1
set var b13 to obslong in #1
set var b14 to viol54 in #1
set var b15 to viol55 in #1
set var b16 to viol56 in #1
set var b17 to viol57 in #1
set var b18 to viol58 in #1
set var b19 to viol59 in #1
set var b20 to viol60 in #1
set var b21 to viol61 in #1
set var b22 to viol62 in #1
set var b23 to viol63 in #1
set var b24 to viol64 in #1
set var b25 to viol65 in #1
set var b26 to viol66 in #1
set var b27 to viol67 in #1
set var b28 to viol68 in #1
set var b29 to uns69 in #1
set var b30 to uns70 in #1
set var b31 to uns71 in #1
set var b32 to uns72 in #1
set var b33 to uns73 in #1
set var b34 to uns74 in #1
set var b35 to uns75 in #1
set var b36 to uns76 in #1
set var b37 to uns77 in #1
set var b38 to uns78 in #1
set var b39 to uns79 in #1
set var b40 to boreml in #1
set var b41 to boreml2 in #1
set var b42 to boreml3 in #1
set var b43 to boname in #1
set var b44 to borate in #1
set var b45 to bounit in #1
set var b46 to bodist in #1
set var b47 to boopfacc in #1
set var b48 to boday in #1
set var b49 to bsunrise in #1
set var b50 to bsunset in #1
set var b51 to bovhin in #1
set var b52 to weapons in #1
set pointer #2 e2 for vessel where vslhin eq .vvslnhin
*(get vessel name)
set var vvslnname to vslname in #2
set var review to Y
break
else
  newpage
  write "This boarding report number does not exist in the +
database" at 10 10
  write "Do you wish to reenter the report number? (Y)" at 12 10
  fillin correct using "(" at 12 52
  if correct exists and correct eq N then
    set var chk-mr to Y
    set var fix to Y
    break
  else
    set var fix to Y
    break
  endif
endif
endif
endif
if fix eq N then
  if pg eq 1 then
    newpage

```



```

write "Press [PGDN] to move down a page or [ESC] to quit" at 1 1
draw bomod1 with all at 3
edit var vbono vbodate vbotime vboday vvslopob vadult vchild +
vostatus vobsbody vobcount vobscity vobstate vobslat vobslong +
return esc pgdn
endif
if pg eq 2 then
newpage
write "Press [ESC] to quit, [PGUP] to move up or [PGDN] to move +
down a page" at 1 1
draw bomod2 with all at 3
edit var return esc pgup pgdn
endif
if pg eq 3 then
newpage
write "Press [PGUP] to move up a page or [ESC] to quit" at 1 1
draw bomod3 with all at 3
edit var return esc pgup
endif
if #return eq pgup then
if pg gt 1 then
set var pg to .pg - 1
else
set var pg to 1
endif
endif
if #return eq pgdn then
if pg lt 3 then
set var pg to .pg + 1
else
set var pg to 3
endif
endif
if #return eq esc then
set var choice to 0
while choice lt 1 or choice gt 3 then .
newpage
write "Boarding Change Options" at 2 20
write "-----" at 3 20
write "1. Change values in the database" at 5 20
write "2. Go back and verify data " at 6 20
write "3. Quit " at 7 20
write "Your choice: " at 9 25
fillin choice using " " at 9 37
if choice eq 1 then
set error messages off
newpage
write "changing values in boarding"
delete rows from #1
load boarding
.vbodate .vbotime .vbono .vvslopob .vadult .vchild +
.vostatus .vobsbody .vobcount .vobscity .vobstate +
.vobslat .vobslong .vviol54 .vviol55 .vviol56 .vviol57 +
.vviol58 .vviol59 .vviol60 .vviol61 .vviol62 .vviol63 +
.vviol64 .vviol65 .vviol66 .vviol67 .vviol68 .vuns69 +
.vuns70 .vuns71 .vuns72 .vuns73 .vuns74 .vuns75 .vuns76
.vuns77 .vuns78 .vuns79 .vborem1 .vborem2 .vborem3 +
.vboname .vborate .vbounit .vbodist .vboopfacc .vboday +
.vbosrise .vbosset .vvsllhin .vweapons
end
set pointer #3 e3 for boarding where bono eq .b3
if e3 ne 0 then
load boarding
.b1 .b2 .b3 .b4 .b5 .b6 .b7 .b8 .b9 .b10 .b11 .b12 .b13 +
.b14 .b15 .b16 .b17 .b18 .b19 .b20 .b21 .b22 .b23 .b24 +
.b25 .b26 .b27 .b28 .b29 .b30 .b31 .b32 .b33 .b34 .b35 +
.b36 .b37 .b38 .b39 .b40 .b41 .b42 .b43 .b44 .b45 .b46 +
.b47 .b48 .b49 .b50 .b51 .b52
end
endif
endif

```

```

        set error messages on
        newpage
        write "Return to correct data entered? (N)" at 15 10
        fillin er using "(" at 15 42
        if er exists and er eq Y then
            set var pg to 1
        else
            set var chk-mr to Y
        endif
    endif
endif
if choice eq 2 then
    set var pg to 1
endif
if choice eq 3 then
    newpage
    write "More boardings to be changed? (N)" at 12 20
    fillin more using "(" at 12 50
    if more fails or more eq N then
        set var pg to 0
    else
        set var pg to 1
        set var review to N
    endif
endif
endwhile
endif
endif
if chk-mr eq Y then
    newpage
    write "More boardings to be changed? (N)" at 12 20
    fillin more using "(" at 12 50
    if more fails or more eq N then
        set var pg to 0
    else
        clear all variables
        set var pg to 1
        set var review to N
    endif
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

\$COMMAND

MOD VSL

\*(\*\*\*\*\*)

Program:	Modify Vessel
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program allows the user to modify vessel information in the database.
Tables Used:	vessel
Temp Tables:	none
Reports Used:	none
Forms Used:	vslmod1, vslmod2

\*\*\*\*\*)

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables

```

```

set null ?
set var pg to 1
set var more to Y
while more eq Y then *(main loop)
    set var chk_hin to Y
    set var chk_name to N
    while chk_hin eq Y then
        newpage
        set var vvslnhin text
        write "Enter HIN of vessel requiring modification: " at 10 10
        write "(enter 'xxx' to go directly to vessel name search)" at 12 5
        fillin vvslnhin using " " at 10 53
        while vvslnhin exists then
            if vvslnhin eq xxx then
                set var chk_hin to N
                set var chk_name to Y
                break
            endif
        newpage
        write "Searching Vessel Table. Please stand by ....." at 10 10
        set pointer #1 e1 for vessel where vslhin = .vvslnhin
        newpage
        if e1 eq 0 then
            *(vessel exists in database)
            set var vvslnno to vslno in #1
            set var vvslnname to vslname in #1
            set var vvslnmake to vslmake in #1
            set var vvslnmod to vslmodel in #1
            set var vvslnyear to vslyear in #1
            set var vvslnlon to vsltons in #1
            set var vvslnft to vsllefft in #1
            set var vvslnin to vsllefft in #1
            set var vvslnhp to vslhp in #1
            set var vvslnuse to vsluse in #1
            set var vvslnstpe to vslstpe in #1
            set var vvslnprop to vslprop in #1
            set var vvslnhull to vslhull in #1
            set var vvslnleng to vsleng in #1
            set var vvslnfuel to vslfuel in #1
            set var vvslnconstr to vslconst in #1
            set var vvslnmedcal to vslmedcal in #1
            set var vvslnmeyer to vslmeyer in #1
            set var vvslnoffno to vslloffno in #1
            set var vvslnhome to vslhomeport in #1
            set var vvslnvcall to vslvcall in #1
            set var vvslnvalue to vslvalue in #1
            set var vvslnsuper to vslsuper in #1
            set var vvslnmasts to vslmasts in #1
            set var vvslnsailno to vslsailno in #1
            set var vvslnhicolor to vslhicolor in #1
            set var vvslntrcolor to vsltrcolor in #1
            set var vvslnslcolor to vslslcolor in #1
            set var vvslnvcbcolor to vslvcbcolor in #1
            set var vvslnvdkcolor to vslvdkcolor in #1
            set var vvslnmarks to vslmarks in #1
            set var v1 to vslno in #1
            set var v2 to vslname in #1
            set var v3 to vslhin in #1
            set var v4 to vslmake in #1
            set var v5 to vslmodel in #1
            set var v6 to vslyear in #1
            set var v7 to vsltons in #1
            set var v8 to vsllefft in #1
            set var v9 to vsllefft in #1
            set var v10 to vslhp in #1
            set var v11 to vsluse in #1
            set var v12 to vslstpe in #1
            set var v13 to vslprop in #1
            set var v14 to vslhull in #1
            set var v15 to vsleng in #1

```

```

set var v16 to vslfuel in #1
set var v17 to vslconst in #1
set var v18 to cmedecal in #1
set var v19 to cmeyear in #1
set var v20 to vsloffno in #1
set var v21 to homeport in #1
set var v22 to vslcall in #1
set var v23 to vslvalue in #1
set var v24 to vslsuper in #1
set var v25 to vslmasts in #1
set var v26 to sailno in #1
set var v27 to hlcolor in #1
set var v28 to trcolor in #1
set var v29 to slcolor in #1
set var v30 to cbcolor in #1
set var v31 to dkcolor in #1
set var v32 to vslmarks in #1
set var chk_hin to N
break
else
  newpage
  write "This HIN does not exist in the database" at 10 20
  write "Do you wish to reenter the HIN? (Y)" at 12 20
  fillin correct using "(" at 12 52
  if correct exists and correct eq N then
    set var chk_hin to N
    set var chk_name to Y
  endif
  break
endif
endwhile
endwhile
while chk_name eq Y then
  newpage
  write "Enter name of vessel requiring modification: " at 10 10
  fillin vvslname using " " at 10 54
  while vvslname exists then
    newpage
    write "Searching Vessel Table. Please stand by ....." +
      at 10 10
    set pointer #1 e1 for vessel where vslname = .vvslname
    newpage
    while e1 eq 0 then
      *(vessel exists in database)
      set var vvslnno to vslnno in #1
      set var vvslname to vslname in #1
      set var vvslihin to vslihin in #1
      set var vvsllmake to vsllmake in #1
      set var vvsllmod to vsllmodel in #1
      set var vvslyear to vslyear in #1
      set var vvsllton to vslltons in #1
      set var vvsllft to vslllenft in #1
      set var vvsllin to vslllenin in #1
      set var vvsllhp to vsllhp in #1
      set var vvslluse to vslluse in #1
      set var vvslltype to vslltype in #1
      set var vvsllprop to vsllprop in #1
      set var vvsllhull to vsllhull in #1
      set var vvslleng to vslleng in #1
      set var vvsllfuel to vsllfuel in #1
      set var vvsllconst to vsllconst in #1
      set var vvsllmedecal to vsllmedecal in #1
      set var vvsllcmeyear to vsllcmeyear in #1
      set var vvsloffno to vsloffno in #1
      set var vvsllhome to vsllhomeport in #1
      set var vvsllcall to vsllcall in #1
      set var vvsllvalue to vsllvalue in #1
      set var vvsllsuper to vsllsuper in #1
      set var vvsllmasts to vsllmasts in #1
      set var vvsllsailno to vsllsailno in #1
    endwhile
  endwhile
endwhile

```

```

set var vhlcolor to hlcolor in #1
set var vtrcolor to trcolor in #1
set var vslcolor to slcolor in #1
set var vcbcolor to cbcolor in #1
set var vdkcolor to dkcolor in #1
set var vmarks to vslmarks in #1
newpage
draw vslmod1 with all at 1
write "Correct vessel? (N)" at 22 20
fillin vslfound using "(" at 22 36
if vslfound exists and vslfound eq Y then
    set var chk_name to N
    set var v1 to vslno in #1
    set var v2 to vslname in #1
    set var v3 to vslhin in #1
    set var v4 to vslmake in #1
    set var v5 to vslmodel in #1
    set var v6 to vslyear in #1
    set var v7 to vsltons in #1
    set var v8 to vsllefft in #1
    set var v9 to vsllefft in #1
    set var v10 to vslhp in #1
    set var v11 to vsluse in #1
    set var v12 to vsltype in #1
    set var v13 to vslprop in #1
    set var v14 to vslhull in #1
    set var v15 to vsleng in #1
    set var v16 to vslfuel in #1
    set var v17 to vslconst in #1
    set var v18 to cmedecal in #1
    set var v19 to cmeyear in #1
    set var v20 to vslloffno in #1
    set var v21 to homeport in #1
    set var v22 to vslcall in #1
    set var v23 to vslvalue in #1
    set var v24 to vslsuper in #1
    set var v25 to vslmasts in #1
    set var v26 to sailno in #1
    set var v27 to hlcolor in #1
    set var v28 to trcolor in #1
    set var v29 to slcolor in #1
    set var v30 to cbcolor in #1
    set var v31 to dkcolor in #1
    set var v32 to vslmarks in #1
    break
endif
next #1 e1
endwhile
if e1 ne 0 then
    newpage
    write "This vessel does not exist in the database" at 10 20
    write "Do you wish to reenter the vessel name? (Y)" at 12 20
    fillin correct using "(" at 12 60
    if correct exists and correct eq N then
        set var chk_name to N
    endif
endif
break
endwhile
endwhile
if e1 eq 0 then
    set var error to Y
    while error eq Y then
        set var error to N
        newpage
        write "Press [ESC] to quit or [PGDN] to move down a page" at 1 1
        draw vslmod1 with all at 3
        edit var vvslname vvslno voffno vvslmake vvslmod vvslyear vvslft +
vvslhp vvslton vvsluse vvsltype vvslprop vvslhull vvsleng +
vvslfuel vconstr return esc pgdn

```

```

if #return eq pgdn then
  newpage
  write "Press [ESC] to quit or [PGDN] to load changes" at 1 1
  draw vslmod2 with all at 3
  edit var vdecals vmeyear vhome vcall vvalue vsuper vmasts +
  vslcolor vsailno vhlcolor vtrcolor vcbcolor vdkcolor vmarks +
  return esc pgdn
if #return eq pgdn then
  *(vessel exists in database)
  set error messages off
  newpage
  write "changing values in vessel"
  delete rows from #1
  load vessel
  .vvsln .vvslname .vvsln .vvslnmake .vvslnmod .vvslnyear +
  .vvslnon .vvslnft .vvsln .vvslnhp .vvslnuse .vvsln type +
  .vvslnprop .vvslnhull .vvslneng .vvslnfuel .vvslnstr .vdecals +
  .vmeyear .voffno .vhome .vcall .vvalue .vsuper .vmasts +
  .vsailno .vhlcolor .vtrcolor .vslcolor .vcbcolor .vdkcolor +
  .vmarks
end
set pointer #2 e2 for vessel where vslhin eq .v3
if e2 ne 0 then
  load vessel
  .v1 .v2 .v3 .v4 .v5 .v6 .v7 .v8 .v9 .v10 .v11 .v12 .v13 +
  .v14 .v15 .v16 .v17 .v18 .v19 .v20 .v21 .v22 .v23 .v24 +
  .v25 .v26 .v27 .v28 .v29 .v30 .v31 .v32
end
endif
set error messages on
write "Return to correct data entered? (N)" at 15 10
write "Note: correct only errors identified by messages" +
at 20 5
fillin er using "(" at 15 42
if er exists and er eq Y then
  set var error to Y
endif
endif
endif
endwhile
endif
newpage
write "More vessels to be changed? (N)" at 12 20
fillin mrvsls using "(" at 12 48
if mrvsls fails or mrvsls eq N then
  set var more to N
endif
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

# \$COMMAND

MOD\_OWOP

\*(\*\*\*\*\*

Program:	Modify Owner and Operator
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program allows the user to modify owner and operator information in the database.
Tables Used:	owners, operator, opown
Temp Tables:	none
Reports Used:	none
Forms Used:	ownrmod1, ownrmod2, opermod1, opermod2

```

*****
set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var owchange to N
set var opchange to N
set var choice to 0
while choice gt 3 or choice lt 1 then *(main loop)
    newpage
    write "Owner / Operator Change Options" at 10 20
    write "-----" at 11 20
    write "1. change owner values" at 13 22
    write "2. change operator values" at 14 22
    write "3. quit" at 15 22
    write "Your choice: " at 17 25
    fillin choice using " " at 17 37
    if choice eq 1 then
        set var chk_ownr to Y
        while chk_ownr eq Y then
            *(change owner information)
            newpage
            write "Press [PGDN] after entering initial information to check +
if" at 1 5
            write "owner exists in database. Press [ESC] to quit" at 2 10
            draw ownrmod1 at 4
            enter var return esc pgdn
            if #return ne esc then
                while vowelname exists and vowelname exists then
                    set pointer #2 e2 for owners where ownlname = .vowelname and +
                    ownfname = .vowelname
                    newpage
                    while e2 eq 0 then
                        *(owner last/first name exist in database)
                        set var vowel1 to ownmi in #2
                        set var vowel2 to owndob in #2
                        set var vowel3 to ownaddr in #2
                        set var vowel4 to owncity in #2
                        set var vowel5 to ownstate in #2
                        set var vowel6 to ownzip in #2
                        set var vowel7 to owntelno in #2
                        newpage
                        draw ownrmod1 with all at 3
                        draw ownrmod2 with all at 8
                        write "Correct owner? (N)" at 21 20
                        fillin owfound using "(" at 21 35
                        if owfound exists and owfound eq Y then
                            set var ow1 to .vowelname
                            set var ow2 to .vowelname
                            set var ow3 to ownmi in #2
                            set var ow4 to ownaddr in #2
                            set var ow5 to owncity in #2
                            set var ow6 to ownstate in #2
                            set var ow7 to ownzip in #2
                            set var ow8 to owntelno in #2
                            set var ow9 to owndob in #2
                            set var ow10 to ownid in #2
                            set var ownid to ownid in #2
                            newpage
                            write "Do you wish to change name? (N)" at 10 10
                            fillin nmchange using "(" at 10 38
                            if nmchange exists and nmchange eq Y then
                                newpage
                                write "Press [PGDN] to make change or [ESC] to quit" +
                                at 1 1

```

```

draw ownrmod1 with all at 3
edit var return esc pgdn
if #return eq pgdn then
  change ownfname to .vowfname in #2
  change ownlname to .vowlname in #2
endif
set var chk_ownr to N
break
endif
newpage
write "Press [PGDN] to make changes or [ESC] to quit" +
at 1 1
draw ownrmod1 with all at 3
draw ownrmod2 with all at 8
edit var return esc pgdn
if #return eq pgdn then
  set var er to Y
  while er eq Y then
    set error messages off
    newpage
    write "changing values in owner"
    delete rows from #2
    load owners
      .vowlname .vowfname .vowmi .vowaddr .vowcity +
      .vowst .vowzip .vowtelno .vowdob .vownid
    end
    set pointer #3 e3 for owners whe ownid eq .ow10
    if e3 ne 0 then
      load owners
        .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 .ow10
      end
    endif
    set error messages on
    write "Return to make corrections? (N)" at 10 10
    write "Note: correct only errors identified by +
messages" at 15 5
    fillin error using "(" at 10 38
    if error exists and error eq Y then
      newpage
      write "Press [PGDN] to make changes"
      draw ownrmod1 with all at 3
      draw ownrmod2 with all at 8
      edit var return esc pgdn
    else
      set var er to N
    endif
  endwhile
  set pointer #1 e1 for opown where ownno eq .vownid
  newpage
  if e1 eq 0 then
    set var vopid to opno in #1
    set error messages off
    set pointer #1 e1 for operator where opid eq .vopid
    set var vopcrse to opcourse in #1
    delete rows from #1
    load operator
      .vowlname .vowfname .vowmi .vowaddr .vowcity +
      .vowst .vowzip .vowtelno .vowdob .vopcrse .vopid
    end
    set pointer #1 e1 for operator where opid eq .vopid
    if e1 ne 0 then
      load operator
        .ow1 .ow2 .ow3 .ow4 .ow5 .ow6 .ow7 .ow8 .ow9 +
        .vopcrse .vopid
      end
    endif
    set error messages on
    write "Values for this person also changed in +
operator"
    set var chk_ownr to N

```



```

        set var owchange to N
        break
    else
        set var owchange to Y
        if opchange eq Y then
            if vowlname eq .voplname then
                newpage
                draw owopform with all at 1
                write "Is this the same person? (N)" at 20 20
                fillin same using "(" at 20 45
                if same exists and same eq Y then
                    load opown
                    .vownid .vopid
                end
            endif
        endif
        set var chk_ownr to N
        break
    endif
else
    break
endif
endif
next #2 e2
endwhile
if e2 ne 0 then
    newpage
    write "This owner does not exist in the database" at 5 5
    write "Do you wish to reenter name? (Y)" at 10 5
    fillin go using "(" at 10 34
    if go exists and go eq N then
        set var chk_ownr to N
    endif
endif
break
endwhile
else
    set var chk_ownr to N
endif
endwhile
set var choice to 0
endif
if choice eq 2 then
    set var chk_oper to Y
    while chk_oper eq Y then
        *(change operator information)
        newpage
        write "Press [PGDN] after entering initial information to check +
if" at 1 5
        write "operator exists in database. Press [ESC] to quit" at 2 10
        draw opermod1 at 4
        enter var return esc pgdn
        if #return ne esc then
            while voplname exists and vopfname exists then
                set pointer #2 e2 for operator where oplname = .voplname and +
                opfname = .vopfname
                newpage
                while e2 eq 0 then
                    *(operator last/first name exist in database)
                    set var vopmi to opmi in #2
                    set var vopdob to opdob in #2
                    set var vopaddr to opaddr in #2
                    set var vopcity to opcity in #2
                    set var vopst to opstate in #2
                    set var vopzip to opzip in #2
                    set var voptelno to optelno in #2
                    set var vopcrse to opcourse in #2
                    newpage
                    draw opermod1 with all at 3

```

```

draw opermod2 with all at 8
write "Correct operator? (N)" at 22 20
fillin opfound using "(" at 22 38
if opfound exists and opfound eq Y then
    set var op1 to .voplname
    set var op2 to .vopfname
    set var op3 to opmi in #2
    set var op4 to opaddr in #2
    set var op5 to opcity in #2
    set var op6 to opstate in #2
    set var op7 to opzip in #2
    set var op8 to optelno in #2
    set var op9 to opdob in #2
    set var op10 to opcourse in #2
    set var op11 to opid in #2
    set var vopid to opid in #2
newpage
write "Do you wish to change name? (N)" at 10 10
fillin nmchange using "(" at 10 38
if nmchange exists and nmchange eq Y then
    newpage
    write "Press [PGDN] to make change or [ESC] to quit" +
    at 1 1
    draw opermod1 with all at 3
    edit var return esc pgdn
    if #return eq pgdn then
        change opfname to .vopfname in #2
        change oplname to .voplname in #2
    endif
    set var chk_oper to N
    break
endif
newpage
write "Press [PGDN] to make changes or [ESC] to quit" +
at 1 1
draw opermod1 with all at 3
draw opermod2 with all at 8
edit var return esc pgdn
if #return eq pgdn then
    set var er to Y
    while er eq Y then
        set error messages off
        newpage
        write "changing values in operator"
        delete rows from #2
        load operator
        .voplname .vopfname .vopmi .vopaddr .vopcity +
        .vopst .vopzip .voptelno .vopdob .vopcrse .vopid
        end
        set pointer #3 e3 for operator where opid eq .op11
        if e3 ne 0 then
            load operator
            .op1 .op2 .op2 .op3 .op4 .op5 .op6 .op7 .op8 .op9 +
            .op10 .op11
        end
    endwhile
    set error messages on
    write "Return to make corrections? (N)" at 10 10
    write "Note: correct only errors identified by +
messages" at 15 5
    fillin error using "(" at 10 38
    if error exists and error eq Y then
        newpage
        write "Press [PGDN] to make changes"
        draw opermod1 with all at 3
        draw opermod2 with all at 8
        edit var return esc pgdn
    else
        set var er to N
    endif
endif

```

```

endwhile
set pointer #1 e1 for opown where opno eq .vopid
newpage
if e1 eq 0 then
  set var vownid to ownno in #1
  set error messages off
  set pointer #1 e1 for owner where ownid eq .vownid
  change ownlname to .voplname in #1
  change ownfname to .vopfname in #1
  change ownmi to .vopmi in #1
  change ownaddr to .vopaddr in #1
  change owncity to .vopcity in #1
  change ownstate to .vopst in #1
  change ownzip to .vopzip in #1
  change owntelno to .voptelno in #1
  change owndob to .vopdob in #1
  set error messages on
  write "Values for this person also changed in owner"
  set var chk_oper to N
  set var opchange to N
  break
else
  set var opchange to Y
  if owchange eq Y then
    if voplname eq .vowlname then
      newpage
      draw owopform with all at 1
      write "Is this the same person? (N)" at 20 20
      fillin same using "(" at 20 45
      if same exists and same eq Y then
        load opown
        .vownid .vopid
      end
    endif
  endif
  set var chk_oper to N
  break
endif
endif
else
  break
endif
endif
next #2 e2
endwhile
if e2 ne 0 then
  newpage
  write "This operator does not exist in the database" at 5 5
  write "Do you wish to reenter name? (Y)" at 10 5
  fillin go using "(" at 10 34
  if go exists and go eq N then
    set var chk_oper to N
  endif
endif
break
endwhile
else
  set var chk_oper to N
endif
endwhile
set var choice to 0
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

\$COMMAND

MOD SUT

\*(\*\*\*\*\*)

Program: Modify Sar Unit  
Author: H R Lang and J D Allen  
Date Written: August 1987  
Description: This program allows the user to modify  
sar unit data in the database.  
Tables Used: sar, sarunits  
Temp Tables: none  
Reports Used: none  
Forms Used: sunitmod

\*\*\*\*\*)

```
set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var more to Y
set var vfoldno text
set var vunit text
set var foldok to N
while more eq Y then *(main loop)
    set var name to N
    set var both to Y
    set var done to N
    set var change to N
    while both eq Y then *(check both folder number and unit name)
        newpage
        if foldok eq N then
            write "Enter sar folder number of unit data requiring +
modification: " at 10 1
            fillin vfoldno using " " at 10 61
        endif
        write "Enter name of unit requiring modification: " at 12 1
        write "(or enter 'xxx' to list units)" at 13 5
        fillin vunit using " " at 12 43
        while vfoldno exists and vunit exists then
            set pointer #1 el for sarunits where foldno eq .vfoldno and +
            unitname eq .vunit
            newpage
            if el eq 0 then
                set var vunit to unitname in #1
                set var vuwtime to uwtime in #1
                set var vuwdate to uwdate in #1
                set var voeta to oeta in #1
                set var vetadate to etadate in #1
                set var vostime to ostime in #1
                set var vdateos to osdate in #1
                set var valgtime to alngtime in #1
                set var valgdate to alngdate in #1
                set var vtowtime to towtime in #1
                set var vtowdate to towdate in #1
                set var vdvmoort to dvmoored in #1
                set var vdvmoord to dvmdate in #1
                set var vsumoort to sutmoor in #1
                set var vsumoord to sutdate in #1
                set var su1 to foldno in #1
                set var su2 to unitname in #1
                set var su3 to uwtime in #1
                set var su4 to uwdate in #1
                set var su5 to oeta in #1
                set var su6 to etadate in #1
                set var su7 to ostime in #1
```

```

set var su8 to osdate in #1
set var su9 to alngtime in #1
set var su10 to alngdate in #1
set var su11 to towtime in #1
set var su12 to towdate in #1
set var su13 to dvmoored in #1
set var su14 to dvmdate in #1
set var su15 to sutmoor in #1
set var su16 to sutdate in #1
set var change to Y
set var both to N
break
else
set pointer #2 e2 for sarunits where foldno eq .vfoldno
newpage
if e2 eq 0 then
set var foldok to Y
if vunit eq xxx then
set var both to N
set var name to Y
break
endif
newpage
write "This unit name does not exist with this folder +
number" at 10 10
write "Do you wish to reenter the unit name? (Y)" at 12 10
fillin correct using "(" at 12 48
if correct exists and correct eq N then
set var both to N
set var name to Y
endif
break
else
newpage
write "This folder number does not exist in the database"
at 10 10
write "Do you wish to reenter the folder number? (Y)" at 12 10
fillin correct using "(" at 12 52
if correct fails or correct eq Y then
break
else
set var both to N
set var done to Y
break
endif
endif
endif
endwhile
endwhile
while name eq Y then *(search on name with existing folder number)
newpage
write "The following unit names exist within the indicated folder +
number" at 1 2
write " "
sel unitname from sarunits where foldno eq .vfoldno
write "Do you wish to enter/reenter the unit name? (Y)" at 20 10
fillin reenter using "(" at 20 54
if reenter exists and reenter eq N then
set var done to Y
endif
break
endwhile
if change eq Y then
newpage
write "press [PGDN] to load changes or [ESC] to quit" at 1 1
draw sunitmod with all at 3
edit var vunit vwtime ywdate voseta vetadate vostime vdateos +
valgtime valgdate vtowtime vtowdate vdvmoort vdvmoord vsumoort +
vsumoord return esc pgdn
if #return eq pgdn then

```

```

set error messages off
delete rows from #1
load sarunits
.vfoldno .vunit .vuwtime .vuwdate .voseta .vetadate .vostime +
.vdateos .valgtime .valgdate .vtowtime .vtowdate .vdmvoort +
.vdmvoort .vsumoort .vsumoort
end
set pointer #2 e2 for sarunits where foldno eq .su1 and +
unitname eq .su2
if e2 ne 0 then
load sarunits
.su1 .su2 .su3 .su4 .su5 .su6 .su7 .su8 .su9 .su10 .su11 +
.su12 .su13 .su14 .su15 .su16
end
endif
set error messages on
endif
set var done to Y
endif
if done eq Y then
newpage
write "More sar units to be changed? (N)" at 12 20
fillin mrsut using "(" at 12 50
if mrsut fails or mrsut eq N then
set var more to N
else
set var foldok to N
endif
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

# \$COMMAND

## MOD\_VHIN

```

*(*****

```

```

Program:          Modify Vessel HIN
Author:           H R Lang and J D Allen
Date Written:     August 1987
Description:       This program allows the user to modify
                   vessel hull identification numbers in
                   the database.
Tables Used:      vessel, sar, boarding, owvsl, opvsl
Temp Tables:      none
Reports Used:     none
Forms Used:       vhinform

```

```

*****

```

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var more to Y
while more eq Y then *(main loop)
set var vslfound to N
set var chk_hin to Y
set var chk_name to N
while chk_hin eq Y then
newpage
set var vvsllhin text

```

```

write "Enter incorrect vessel hin: " at 10 10
write "(enter 'xxx' to search by vessel name)" at 12 5
fillin vvsln using " " at 10 37
while vvsln exists then
  if vvsln eq xxx then
    set var chk_hin to N
    set var chk_name to Y
    break
  endif
  set pointer #1 e1 for vessel where vslhin = .vvsln
  newpage
  if e1 eq 0 then
    *(vessel exists in database)
    set var vvsln to vslno in #1
    set var vvslname to vslname in #1
    set var vvslnmake to vslmake in #1
    set var vvslnmod to vslmodel in #1
    set var vvslnyear to vslyear in #1
    set var vvslnon to vsltons in #1
    set var vvslnft to vslenft in #1
    set var vvslnin to vslennin in #1
    set var vvslnhp to vslhp in #1
    set var vvslnuse to vsluse in #1
    set var vvslnype to vsltype in #1
    set var vvslnprop to vslprop in #1
    set var vvslnhull to vslhull in #1
    set var vvslneng to vsleng in #1
    set var vvslnfuel to vslfuel in #1
    set var vvslnconst to vslconst in #1
    set var vvslnoffno to vslloffno in #1
    draw vhinform with all at 1
    write "Correct vessel? (Y)" at 22 20
    fillin vfound using "(" at 22 36
    if vfound fails or vfound eq Y then
      set var chk_hin to N
      set var vslfound to Y
      break
    else
      newpage
      write "Do you wish to reenter the HIN? (Y)" at 12 20
      fillin reenter using "(" at 12 52
      if reenter exists and reenter eq N then
        set var chk_hin to N
        set var chk_name to Y
        break
      endif
    endif
  else
    newpage
    write "This HIN does not exist in the database" at 10 20
    write "Do you wish to reenter the HIN? (Y)" at 12 20
    fillin correct using "(" at 12 52
    if correct exists and correct eq N then
      set var chk_hin to N
      set var chk_name to Y
    endif
    break
  endif
endif
endwhile
while chk_name eq Y then
  newpage
  write "Enter name of vessel requiring HIN correction: " at 10 10
  fillin vvslname using " " at 10 56
  while vvslname exists then
    set pointer #1 e1 for vessel where vslname = .vvslname
    newpage
    while e1 eq 0 then
      *(vessel exists in database)
      set var vvsln to vslno in #1

```

```

set var vvslname to vslname in #1
set var vvslnhin to vslhin in #1
set var vvslnmake to vslmake in #1
set var vvslnmod to vslmodel in #1
set var vvslnyear to vslyear in #1
set var vvslnon to vsltons in #1
set var vvslnft to vslenft in #1
set var vvslnin to vslennin in #1
set var vvslnhp to vslhp in #1
set var vvslnuse to vsluse in #1
set var vvslnype to vsltype in #1
set var vvslnprop to vslprop in #1
set var vvslnhull to vslhull in #1
set var vvslneng to vsleng in #1
set var vvslnfuel to vslfuel in #1
set var vconstr to vslconst in #1
set var voffno to vsloffno in #1
newpage
draw vhinform with all at 1
write "Correct vessel? (N)" at 22 20
fillin foundv using "(" at 22 36
if foundv exists and foundv eq Y then
    set var chk_name to N
    set var vslfound to Y
    break
endif
next #1 e1
endwhile
if e1 ne 0 then
    newpage
    write "This vessel does not exist in the database" at 10 20
    write "Do you wish to reenter the vessel name? (Y)" at 12 20
    fillin correct using "(" at 12 60
    if correct exists and correct eq N then
        set var chk_name to N
    endif
endif
break
endwhile
endwhile
if vslfound eq Y then
    set var vbadhin to .vvslnhin
    set var error to Y
    while error eq Y then
        set var error to N
        newpage
        write "Press [PGDN] to change HIN or [ESC] to quit" at 1 1
        draw vhinform with all at 3
        edit var vvslnhin return esc pgdn
        if #return eq pgdn then
            newpage
            change vslhin to .vvslnhin in #1
            write "Return to correct HIN entered? (Y)" at 15 10
            fillin er using "(" at 15 41
            if er fails or er eq Y then
                set var error to Y
            else
                set pointer #1 e1 for owvsl where vhinown eq .vbadhin
                write "Changing values in owvsl"
                while e1 eq 0 then
                    change vhinown to .vvslnhin in #1
                next #1 e1
            endwhile
            set pointer #1 e1 for opvsl where vhinoper eq .vbadhin
            write "Changing values in opvsl"
            while e1 eq 0 then
                change vhinoper to .vvslnhin in #1
            next #1 e1
            endwhile
            set pointer #1 e1 for sar where sarvhin eq .vbadhin

```



```

        write "Changing values in sar"
        while el eq 0 then
            change sarvhin to .vvsln in #1
            next #1 el
        endwhile
        set pointer #1 el for boarding where bovhn eq .vbadhn
        write "Changing values in boarding"
        while el eq 0 then
            change bovhn to .vvsln in #1
            next #1 el
        endwhile
    endif
endif
endwhile
endif
newpage
write "More vessels to be changed? (N)" at 12 20
fillin mrvs using "(" at 12 48
if mrvs fails or mrvs eq N then
    set var more to N
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

# SCOMMAND

AM VINT

\*(\*\*\*\*\*)

Program:	Add and Modify Vessel Intelligence
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program allows the user to input and modify vessel intelligence information.
Tables Used:	vslintel
Temp Tables:	none
Reports Used:	none
Forms Used:	vintform

\*\*\*\*\*)

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var more to Y
while more eq Y then *(main loop)
    newpage
    write "Do you wish to (A)dd or (M)odify information?" at 10 10
    fillin choice using ">" at 11 20
    if choice eq A then *(add information)
        set var vintdate to .#date
        set var vepic text
        label redovsl
        newpage
        write "Press [PGDN] to load data or [ESC] to quit" at 1 1
        draw vintform with all at 3
        edit var return esc pgdn
        if #return eq pgdn then
            newpage
            write "Loading vslintel"

```

```

set error messages off
load vslintel
.vvslname .vintdate .vepic .vstolen .vintrem1 .vintrem2 +
.vintrem3
end
set error messages on
write "Return to correct errors? (N)" at 15 10
write "Note: correct only errors indicated by messages" at 20 5
fillin fixvsl using "(" at 15 36
if fixvsl exists and fixvsl eq Y then
goto redovsl
endif
endif
endif
while choice eq M then *(modify information)
newpage
write "Enter name of vessel requiring changes then press [PGDN] +
to see if" at 1 1
write "vessel exists in the database or [ESC] to quit" at 2 1
draw vintform with all at 4
edit var vvslname return esc pgdn
if #return eq pgdn then
set pointer #1 e1 for vslintel where intvname eq .vvslname
while e1 eq 0 then
set var vvslname to intvname in #1
set var vintdate to intdate in #1
set var vepic to epiccode in #1
set var vstolen to stolen in #1
set var vintrem1 to vremark1 in #1
set var vintrem2 to vremark2 in #1
set var vintrem3 to vremark3 in #1
newpage
draw vintform with all at 1
write "Correct vessel? (Y)" at 23 25
fillin correct using "(" at 23 41
if correct fails or correct eq Y then
label corvsl
newpage
write "Press [PGDN] to change database or [ESC] to quit" +
at 1 1
draw vintform with all at 3
edit var return esc pgdn
if #return eq pgdn then
newpage
write "changing values in vslintel"
set error messages off
change intvname to .vvslname in #1
change intdate to .vintdate in #1
change epiccode to .vepic in #1
change stolen to .vstolen in #1
change vremark1 to .vintrem1 in #1
change vremark2 to .vintrem2 in #1
change vremark3 to .vintrem3 in #1
set error messages on
write "Return to correct errors? (N)" at 15 10
write "Note: correct only errors indicated by messages" +
at 20 5
fillin vslfix using "(" at 15 36
if vslfix exists and vslfix eq Y then
goto corvsl
endif
endif
endif
set var choice to N
break
endif
next #1 e1
endwhile
if e1 ne 0 then
newpage
write "This vessel does not exist in the vessel intelligence +

```

```

file" at 5 10
    write "Do you wish to reenter name? (Y)" at 15 10
    fillin reenter using "(" at 15 39
    if reenter exists and reenter eq N then
        break
    else
        clear vvslname
        clear vintdate
        clear vepic
        clear vstolen
        clear vintrem1
        clear vintrem2
        clear vintrem3
    endif
endif
else
    break
endif
endwhile
newpage
write "More intelligence to enter/modify? (N)" at 15 20
fillin mrintel using "(" at 15 55
if mrintel fails or mrintel eq Y then
    clear all variables
    set var more to Y
else
    set var more to N
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

# \$COMMAND

AM\_PINT

\*(\*\*\*\*\*)

Program:	Add and Modify Personnel Intelligence
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program allows the user to input and modify personnel intelligence information.
Tables Used:	perintel
Temp Tables:	none
Reports Used:	none
Forms Used:	pintform

\*\*\*\*\*)

```

set error messages on
set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ....." at 10 10
clear all variables
set null ?
set var more to Y
while more eq Y then *(main loop)
    newpage
    write "Do you wish to (A)dd or (M)odify information?" at 10 10
    fillin choice using ">" at 11 20
    if choice eq A then *(add information)
        newpage
        set var vintdate to .#date
        set var vintdob to 01/01/1901
    endif
endif
endwhile

```

```

write "Press [PGDN] to load data or [ESC] to quit" at 1 1
draw pintform with all at 3
edit var return esc pgdn
if #return eq pgdn then
    newpage
    write "Loading perintel"
    load perintel
    .vlname .vintdob .vintrem1 .vintrem2 .vintrem3 .vintdate +
    .vfname .vintmi
end
endif
endif
while choice eq M then *(modify information)
    newpage
    write "Enter last and first names of individual requiring +
changes, then press" at 1 1
    write "[PGDN] to see if person exists in the database or [ESC] +
to quit" at 2 1
    draw pintform with all at 4
    edit var vlname vfname return esc pgdn
    if #return eq pgdn then
        set pointer #1 e1 for perintel where intlname eq .vlname and +
        intfname eq .vfname
        while e1 eq 0 then
            set var vlname to intlname in #1
            set var vfname to intfname in #1
            set var vintdob to intdob in #1
            set var vintmi to intmi in #1
            set var vintrem1 to pintrem1 in #1
            set var vintrem2 to pintrem2 in #1
            set var vintrem3 to pintrem3 in #1
            set var vintdate to pintdate in #1
            newpage
            draw pintform with all at 1
            write "Correct individual (Y)" at 23 25
            fillin correct using "(" at 23 44
            if correct fails or correct eq Y then
                newpage
                write "Press [PGDN] to change database or [ESC] to quit" +
                at 1 1
                draw pintform with all at 3
                edit var return esc pgdn
                if #return eq pgdn then
                    set error messages off
                    change intlname to .vlname in #1
                    change intdob to .vintdob in #1
                    change pintrem1 to .vintrem1 in #1
                    change pintrem2 to .vintrem2 in #1
                    change pintrem3 to .vintrem3 in #1
                    change pintdate to .vintdate in #1
                    change intfname to .vfname in #1
                    change intmi to .vintmi in #1
                    set error messages on
                endif
                set var choice to N
                break
            endif
        endwhile
        next #1 e1
    endwhile
    if e1 ne 0 then
        newpage
        write "This individual does not exist in the personnel +
intelligence file" at 5 10
        write "Do you wish to reenter name? (Y)" at 15 10
        fillin reenter using "(" at 15 39
        if reenter exists and reenter eq N then
            break
        else
            clear vlname
            clear vfname
        endif
    endif
endif

```

```

        clear vintdob
        clear vintrem1
        clear vintrem2
        clear vintrem3
        clear vintmi
        clear vintdate
    endif
endif
else
    break
endif
endwhile
newpage
write "More intelligence to enter/modify? (Y)" at 15 20
fillin mrintel using "(" at 15 55
if mrintel fails or mrintel eq Y then
    clear all variables
    set var more to Y
else
    set var more to N
endif
endwhile *(end of main loop)
set error messages off
set null -0-
return
*( end )

```

# APPENDIX I

## SREPORTS SOURCE CODE

```

$COMMAND
RPTMAIN
*(*****
      US COAST GUARD GROUP MONTEREY
    SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
      INTELLIGENCE SYSTEM (SARELTIS)

    REPORTS MAIN MENU APPLICATION PROGRAM

    Author:   Jon D. Allen, LT, USCG
              Heidi R. Lang, LT, USN
              AUGUST 1987

*****)

set error messages off
set messages off
set escape off
clear all variables
newpage
set var pick4 integer
newpage
choose pick4 from rpt_menu in sreports.apx
if pick4 eq 0 then
  quit to restrpts.cmd
endif
if pick4 eq 1 then
  run INT_RPTS in sreports.apx
  quit to restrpts.cmd
endif
if pick4 eq 2 then
  run BRD_RPTS in sreports.apx
  quit to restrpts.cmd
endif
if pick4 eq 3 then
  run SAR_RPTS in sreports.apx
  quit to restrpts.cmd
endif
if pick4 eq 4 then
  run VSL_RPTS in sreports.apx
  quit to restrpts.cmd
endif
if pick4 eq 5 then
  run PRS_RPTS in sreports.apx
  quit to restrpts.cmd
endif
if pick4 eq 6 then
  quit to restmain.cmd
endif
quit to restrpts.cmd
return
$menu
rpt_menu
column SARELTIS --- REPORTS MENU
INTELLIGENCE REPORTS
BOARDING REPORTS
SAR REPORTS
VESSEL REPORTS
PERSONNEL REPORTS

```

RETURN TO MAIN MENU  
\*( end )

\$COMMAND  
INT\_RPTS

\*(\*\*\*\*\*)

Program: Access Intelligence Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the intelligence reports  
master menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run INT\_MAIN in intrpts.apx  
return  
\*( end )

\$COMMAND  
BRD\_RPTS

\*(\*\*\*\*\*)

Program: Access Boarding Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the boarding reports  
master menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run BRD\_MAIN in brdrpts.apx  
return  
\*( end )

\$COMMAND  
SAR\_RPTS

\*(\*\*\*\*\*)

Program: Access Sar Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the SAR reports master  
menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run SAR\_MAIN in sarpts.apx  
return  
\*( end )

\$COMMAND

VSL RPTS

\*(\*\*\*\*\*)

Program: Access Vessel Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the vessel reports  
master menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run VSL\_MAIN in vslrpts.apx

return

\*( end )

\$COMMAND

PRS RPTS

\*(\*\*\*\*\*)

Program: Access Personnel Reports  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program calls the personnel reports  
master menu and application programs.  
Tables Used: none  
Temp Tables: none  
Reports Used: none  
Forms Used: none

\*\*\*\*\*)

run PRS\_MAIN in prsrpts.apx

return

\*( end )



## APPENDIX J

### INTRPTS SOURCE CODE

```

$COMMAND
INT MAIN
*(*****

                US COAST GUARD GROUP MONTEREY
        SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
                INTELLIGENCE SYSTEM (SARELTIS)

        INTELLIGENCE REPORTS MENU and APPLICATION PROGRAMS

                Author:   Jon D. Allen, LT, USCG
                        Heidi R. Lang, LT, USN
                        AUGUST 1987

        *****)

set error messages off
set messages off
set escape off
clear all variables
newpage
choose pick5 from int_menu in intrpts.apx
if pick5 eq 0 then
    quit to restint.cmd
endif
if pick5 eq 1 then
    run EPICDUMP in intrpts.apx
    quit to restint.cmd
endif
if pick5 eq 2 then
    run INTEL RPT in intrpts.apx
    quit to restint.cmd
endif
if pick5 eq 3 then
    run PERINTEL in intrpts.apx
    quit to restint.cmd
endif
if pick5 eq 4 then
    quit to restrpts.cmd
endif
if pick5 eq 5 then
    quit to restint.cmd
endif
quit to restint.cmd
return
$menu
int_menu
column SARELTIS --- INTELLIGENCE REPORTS
VESSEL INTELLIGENCE ANALYSIS (EPIC)
VESSEL PROFILE FOR INDIVIDUAL VIOLATIONS ANALYSIS
PERSONNEL INTELLIGENCE SUMMARY
RETURN TO REPORTS MENU
*( end )

$COMMAND
PERINTEL
*(*****

```

Program:	Personnel Intelligence Dump Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a listing by date and by alphabetic search of those personnel in the table PERINTEL (personnel intelligence).
Tables Used:	perintel
Temp Tables:	persum
Reports Used:	perintel
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
set error messages off
write "This program will perform dump intelligence information" at 3 1
write "on people that are in the PERINTEL table. Information" at 4 1
write "may be selected by alphabetic and intelligence date." at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 53
    set var datediff to .enddate - .strtdate
endwhile
newpage
write "You will now be asked to provide beginning and ending " at 3 1
write "letters to start and end the alphabetic search. If you " at 4 1
write "enter an [a] and a [z] you will get all of the personnel" at 5 1
write "in the the table PERINTEL whose intelligence date is " at 6 1
write "between the dates that you previously entered." at 7 1
set var strtltr text
set var endltr text
set var ltrdiff to 0
while ltrdiff = 0 then
    fillin strtltr using "Please enter starting letter(s):" at 10 1
    fillin endltr using "Please enter ending letter(s):" at 12 1
    if endltr lt .strtltr then
        set var ltrdiff to 0
    else
        break
    endif
endwhile
set error messages off
remove persum
newpage
clear numrows
set var numrows integer
project persum from perintel using all sorted by intlname +
where pintdate ge .strtdate and pintdate le .enddate and +
intlname ge .strtltr and intlname le .endltr
compute numrows as rows from persum
newpage
write "Now preparing report"
if numrows fails or numrows = 0 then
    write "No records exist that match your selection criteria" at 10 10
    write "Please press any key to continue" at 16 15
    pause
else
    output printer with perintel.rpt
    newpage

```

```

    print perintel
    output screen
endif
remove persum
newpage
clear all variables
return
*( end )

```

# \$COMMAND EPICDUMP

\*(\*\*\*\*\*)

```

Program:          EPIC Intelligence Analysis
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       Performs a dump of all vessels in the
                   VSLINTEL table within a specified time
                   period. Four reports are generated
                   providing listings by EPIC Code, by
                   stolen vessels, and by intelligence
                   remarks, and a frequency breakdown
                   and analysis of EPIC Codes.

Tables Used:      vslintel
Temp Tables:      epicsum, stolesum, intelsum, epictmpl,
                   epictmp2, epictmp
Reports Used:     epicsum, stolesum, intelsum, epicrpt
Forms Used:       none

```

\*\*\*\*\*)

```

set error messages off
set messages off
set escape on
newpage
clear all variables
set null " "
newpage
write "This program performs a dump of all vessels, by EPIC +
Code/Stolen" at 2 1
write "codes, which intelligence information has been collected." +
at 3 1
write "Information to be analyzed can be selected within a specified" +
at 4 1
write "time period." at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove epicsum
remove stolesum
remove intelsum
newpage
project epicsum from vslintel using epiccode intdate intvname stolen +
sorted by epiccode intvname where intdate >= .strtdate and +
intdate <= .enddate and epiccode exists
compute numrows as rows from epicsum
newpage
write "Now preparing sorted vessel EPIC Code report....." at 10 1
if numrows fails or numrows = 0 then

```

```

write "No records exist that match your selection criteria" at 10 10
write "Please press any key to continue" at 16 15
pause
else
  output printer with epicsum.rpt
  newpage
  print epicsum
  output screen
endif
remove epicsum
newpage
clear numrows
project stolesum from vslintel using intdate intvname stolen sorted by +
intvname where intdate >= .strtdate and intdate <= .enddate and +
stolen = Y
compute numrows as rows from stolesum
write "Now preparing sorted stolen vessel report....." at 10 1
if numrows fails or numrows = 0 then
  write "No records exist that match your selection criteria" at 10 10
  write "Please press any key to continue" at 16 15
  pause
else
  output printer with stolesum.rpt
  newpage
  print stolesum
  output screen
endif
remove stolesum
newpage
clear numrows
project intelsum from vslintel using intdate vremark1 vremark2 +
vremark3 intvname sorted by intvname intdate where vremark1 exists +
or vremark2 exists or vremark3 exists
compute numrows as rows from intelsum
write "Now preparing sorted vessel intelligence remarks report" at 10 1
if numrows fails or numrows = 0 then
  write "No records exist that match your selection criteria" at 10 10
  write "Please press any key to continue" at 16 15
  pause
else
  output printer with intelsum.rpt
  newpage
  print intelsum
  output screen
endif
remove intelsum
remove epictmp1
remove epictmp2
newpage
project epictmp1 from vslintel using epiccode intdate where intdate +
>= .strtdate and intdate <= .enddate and epiccode exists
project epictmp2 from epic using all sorted by epicno
remove epictmp
define
attribute
ecpct real
ecnumber integer
relation
epictmp with epicno epicdsc1 epicdsc2 epicdsc3 epicdsc4 ecnumber ecpct
end
compute totopics as count epiccode from epictmp1 where epiccode exists
set var pcttmp1 real
set pointer #1 n1 for epictmp2
while n1 eq 0 then
  set var epictest to epicno in #1
  set var edscl to epicdsc1 in #1
  set var edsc2 to epicdsc2 in #1
  set var edsc3 to epicdsc3 in #1
  set var edsc4 to epicdsc4 in #1
  compute epicnum as count epiccode from epictmp1 where +

```

```

epiccode = .epictest
if totetpics = 0 then
  set var pcttmp1 to .epicnum / 1.0      *(prevents division by 0)
else
  set var pcttmp1 to .epicnum / .totetpics
endif
set var pcttmp2 to .pcttmp1 x 100.0
load epictmp
.epictest .edsc1 .edsc2 .edsc3 .edsc4 .epicnum .pcttmp2
end
next #1 n1
endwhile
write "Now preparing vessel EPIC code frequency report....." at 10 1
output printer with epicrpt.rpt
newpage
print epicrpt
newpage
output screen
remove epictmp2
remove epictmp
remove epictmp1
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## INTEL RPT

\*(\*\*\*\*\*

```

Program:      Violation Vessel Profile Intelligence
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program examines vessel boardings to
              create a profile of vessel which violate
              specific laws during a specified time period.
Tables Used:  boarding, vessel, viols, boattype, boatuse,
              constr, engcomp, fuelcomp, hullmat, boatprop
Temp Tables:  bosum, vslsum, violsum, vslmo,
              summary1, summary2, summary3, summary4,
              summary5, summary6, summary7, temp
Reports Used: vtypemo, vusemo, vconstmo, vengmo,
              vfuelmo, vhullmo, vpropmo, vlenftmo,
              vyearmo
Forms Used:   none

```

\*\*\*\*\*

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
remove vslsum
remove bosum
remove violsum
remove temp
remove summary1
remove summary2
remove summary3
remove summary4
remove summary5
remove summary6
remove summary7
newpage
clear all variables
write "This module performs a statistical analysis of vessel " at 2 1

```

```

write "intelligence information during a specified time period " at 3 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
write "Now finding information which meets date criteria....." at 14 1
project bosum from boarding using bodate bono viol54 viol55 viol56 +
viol57 viol58 viol59 viol60 viol61 viol62 viol63 viol64 viol65 viol66 +
viol67 viol68 uns69 uns70 uns71 uns72 uns73 uns74 uns75 uns76 uns77 +
uns78 uns79 bovhin weapons where bodate >= .strtdate and +
bodate <= .enddate
project vslsum from vessel using vslconst vsleng vslfuel vslhull +
vsllefft vslprop vsltype vsluse vslyear vsltons vslhin
join bosum using bovhin with vslsum using vslhin forming violsum +
where eq
remove bosum
remove vslsum
compute totbrds as count bono from violsum where bono exists
compute numrows as rows from violsum
newpage
set var code to 0
set error messages on
while code < 54 or code > 80 then
    write "Please enter in violation code or unsafe condition that " +
    at 1 1
    write "you wish to run a vessel desription statistical summary:" +
    at 2 1
    write "54 - Numbering          69 - Unsafe Conditions +
Causing" at 4 1
    write "55 - Certificate          Termination" at 5 1
    write "56 - Personal Flotation Device 70 - Corrected on the +
spot" at 6 1
    write "57 - Sound Producing Device 71 - Overloaded" at 7 1
    write "58 - Bell 72 - Accumulation of fuel +
in bilges" at 8 1
    write "59 - Fire Extinguisher 73 - Fuel Leak" at 9 1
    write "60 - Flame Control 74 - Manifestly Unsafe +
Voyage" at 10 1
    write "61 - Ventilation 75 - Hazardous Bars +
(13th District)" at 11 1
    write "62 - Nav./Anchor Lights 76 - Alcohol Condition" +
    at 12 1
    write "63 - Negligent Operation 77 - Other" at 13 1
    write "64 - Failure to Terminate 78 - Warning Issued" at 14 1
    write "65 - Pollution Placard Not Posted 79 - No Violation" at 15 1
    write "66 - Marine Sanitation Devices 80 - Weapons On Board" +
    at 16 1
    write "67 - Visual Distress Signals" at 17 1
    write "68 - Document/Official Numbers" at 18 1
    fillin code using "Please enter code: " at 20 24
endwhile
set error messages off
remove vslmo
newpage
write "Now evaluating vessel profile....." at 11 1
    *(this next section of code finds the information only
    dealing with the specific violation code)
if code = 54 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where viol54 exists
endif
if code = 55 then

```

```

    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol55 exists
endif
if code = 56 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol56 exists
endif
if code = 57 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol57 exists
endif
if code = 58 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol58 exists
endif
if code = 59 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol59 exists
endif
if code = 60 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol60 exists
endif
if code = 61 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol61 exists
endif
if code = 62 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol62 exists
endif
if code = 63 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol63 exists
endif
if code = 64 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol64 exists
endif
if code = 65 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol65 exists
endif
if code = 66 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol66 exists
endif
if code = 67 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol67 exists
endif
if code = 68 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where viol68 exists
endif
if code = 69 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where uns69 exists
endif
if code = 70 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where uns70 exists
endif
if code = 71 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where uns71 exists
endif
if code = 72 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllenft vslprop vsltype vsluse vslyear bono where uns72 exists

```

```

endif
if code = 73 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns73 exists
endif
if code = 74 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns74 exists
endif
if code = 75 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns75 exists
endif
if code = 76 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns76 exists
endif
if code = 77 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns77 exists
endif
if code = 78 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns78 exists
endif
if code = 79 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where uns79 exists
endif
if code = 80 then
    project vslmo from violsum using vslconst vsleng vslfuel vslhull +
    vsllefft vslprop vsltype vsluse vslyear bono where weapons exists
endif
compute numrows as rows from vslmo
remove violsum
remove summary1
remove summary2
remove summary3
remove summary4
newpage
remove summary5
remove summary6
remove summary7
newpage
if numrows fails or numrows = 0 then
    write "No records exist that match your selection criteria" at 10 10
    write "Please press any key to continue" at 16 15
    pause
else
    *(Now getting violation code description)
    set pointer #1 n1 for viols
    while n1 eq 0 then
        set var vno to violno in #1
        if code = .vno then
            set var vltndesc to violdesc in #1
            break
        endif
        next #1 n1
    endwhile
    newpage
    write "Preparing vessel type demographics....."
    define
        attributes
        counter integer
        typedesc text 15
        relation
        summary1 with vsltype typedesc counter
    end
    set pointer #1 n1 for boattype
    while n1 eq 0 then

```



```

set var typetest to vtype in #1
set var typdesc1 to vtypedes in #1
compute sumtype as count vsltype from vslmo where +
vsltype = .typetest
if sumtype fails then
    set var sumtype to 0
endif
load summary1
    .typetest .typdesc1 .sumtype
end
next #1 n1
endwhile
compute totviols as sum counter from summary1
output printer with vtypemo.rpt
newpage
print vtypemo
output screen
remove summary1
write "Preparing vessel use demographics....."
define
attributes
numuse integer
usedesc text 15
relations
summary2 with vsluse usedesc numuse
end
set pointer #1 n1 for boatuse
while n1 eq 0 then
    set var usetest to vuse in #1
    set var usedesc1 to vusedesc in #1
    compute sumuse as count vsluse in vslmo where vsluse = .usetest
    if sumuse fails then
        set var sumuse to 0
    endif
    load summary2
        .usetest .usedesc1 .sumuse
    end
    next #1 n1
endwhile
compute totviols as sum numuse from summary2
output printer with vusemo.rpt
newpage
print vusemo
output screen
remove summary2
write "Preparing vessel construction type demographics....."
define
attributes
numconst integer
constdes text 10
relations
summary3 with vslconst constdes numconst
end
set pointer #1 n1 for constr
while n1 eq 0 then
    set var consttst to constype in #1
    set var constrds to consdesc in #1
    compute sumconst as count vslconst in vslmo where +
    vslconst = .consttst
    if sumconst fails then
        set var sumconst to 0
    endif
    load summary3
        .consttst .constrds .sumconst
    end
    next #1 n1
endwhile
compute totviols as sum numconst from summary3
output printer with vconstmo.rpt
newpage

```

```

print vconstmo
output screen
remove summary3
write "Preparing vessel engine compartment demographics...."
define
attributes
numeng integer
engdesc text 10
relations
summary4 with vsleng engdesc numeng
end
set pointer #1 n1 for engcomp
while n1 eq 0 then
set var engtst to ecomptyp in #1
set var engdescr to ecompdes in #1
compute sumeng as count vsleng in vslmo where vsleng = .engtst
if sumeng fails then
set var sumeng to 0
endif
load summary4
.engtst .engdescr .sumeng
end
next #1 n1
endwhile
compute totviols as sum numeng from summary4
output printer with vengmo.rpt
newpage
print vengmo
output screen
remove summary4
write "Preparing fuel compartment type demographics....."
define
attributes
numfuel integer
fueldesc text 10
relations
summary5 with vslfuel fueldesc numfuel
end
set pointer #1 n1 for fuelcomp
while n1 eq 0 then
set var fueltst to fcomptyp in #1
set var fdesc to fcompdes in #1
compute sumfuel as count vslfuel in vslmo where vslfuel = .fueletst
if sumfuel fails then
set var sumfuel to 0
endif
load summary5
.fueletst .fdesc .sumfuel
end
next #1 n1
endwhile
compute totviols as sum numfuel from summary5
output printer with vfuelmo.rpt
newpage
print vfuelmo
output screen
remove summary5
write "Preparing hull material demographics....."
define
attributes
numhull integer
hulldesc text 15
relations
summary6 with vslhull hulldesc numhull
end
set pointer #1 n1 for hullmat
while n1 eq 0 then
set var hulltst to hmattype in #1
set var hdesc to hmatdesc in #1
compute sumhull as count vslhull in vslmo where vslhull = .hulltst

```

```

    if sumhull fails then
        set var sumhull to 0
    endif
    load summary6
    .hulltst .hdesc .sumhull
end
next #1 n1
endwhile
compute totviols as sum sumhull from summary6
output printer with vhullmo.rpt
newpage
print vhullmo
output screen
remove summary6
write "Preparing vessel propulsion demographics....."
define
    attributes
    numprop integer
    descprop text 15
    relations
    summary7 with vslprop descprop numprop
end
set pointer #1 n1 for boatprop
while n1 eq 0 then
    set var proptst to proptype in #1
    set var prdesc to propdesc in #1
    compute sumprop as count vslprop in vslmo where vslprop = .proptst
    if sumprop fails then
        set var sumprop to 0
    endif
    load summary7
    .proptst .prdesc .sumprop
end
next #1 n1
endwhile
compute totviols as sum numprop from summary7
output printer with vpropmo.rpt
newpage
print vpropmo
output screen
remove summary7
write "Preparing vessel length demographics....."
compute totvsls as count bono from vslmo where vsllenft exists
compute len<20 as count bono from vslmo where vsllenft < 20
compute len2030 as count bono from vslmo where vsllenft >= 20 and +
vsllenft < 30
compute len3040 as count bono from vslmo where vsllenft >= 30 and +
vsllenft < 40
compute len4050 as count bono from vslmo where vsllenft >= 40 and +
vsllenft < 50
compute len5060 as count bono from vslmo where vsllenft >= 50 and +
vsllenft < 60
compute len6070 as count bono from vslmo where vsllenft >= 60 and +
vsllenft < 70
compute len7080 as count bono from vslmo where vsllenft >= 70 and +
vsllenft < 80
compute len8090 as count bono from vslmo where vsllenft >= 80 and +
vsllenft < 90
compute len90100 as count bono from vslmo where vsllenft >= 90 and +
vsllenft < 100
compute len>100 as count bono from vslmo where vsllenft >= 100
*(computing total number of violations)
set var tv1 to .len<20 + .len2030
set var tv2 to .len3040 + .len4050
set var tv3 to .len5060 + .len6070
set var tv4 to .len7080 + .len8090
set var tv5 to .len>100 + .len90100
set var tv10 to .tv1 + .tv2
set var tv20 to .tv3 + .tv4
set var tv30 to .tv5 + .tv10

```

```

set var totviols to .tv20 + .tv30
set var pct<20 real
set var pct2030 real
set var pct3040 real
set var pct4050 real
set var pct5060 real
set var pct6070 real
set var pct7080 real
set var pct8090 real
set var pct90100 real
set var pct>100 real
*(Evaluating percentages based on total boardings)
set var pct<20 to .len<20 / .totbrds
set var pct2030 to .len2030 / .totbrds
set var pct3040 to .len3040 / .totbrds
set var pct4050 to .len4050 / .totbrds
set var pct5060 to .len5060 / .totbrds
set var pct6070 to .len6070 / .totbrds
set var pct7080 to .len7080 / .totbrds
set var pct8090 to .len8090 / .totbrds
set var pct90100 to .len90100 / .totbrds
set var pct>100 to .len>100 / .totbrds
set var vpct<20 real
set var vpct2030 real
set var vpct3040 real
set var vpct4050 real
set var vpct5060 real
set var vpct6070 real
set var vpct7080 real
set var vpct8090 real
set var vpct9010 real
set var vpct>100 real
*(Evaluating percentages based on total violations)
set var vpct<20 to .len<20 / .totviols
set var vpct2030 to .len2030 / .totviols
set var vpct3040 to .len3040 / .totviols
set var vpct4050 to .len4050 / .totviols
set var vpct5060 to .len5060 / .totviols
set var vpct6070 to .len6070 / .totviols
set var vpct7080 to .len7080 / .totviols
set var vpct8090 to .len8090 / .totviols
set var vpct9010 to .len9010 / .totviols
set var vpct>100 to .len>100 / .totviols
set var pcttbrds real
set var pcttbrds to .totviols / .totbrds
*(Defining temporary table for printing)
remove temp
define
attributes
tmp text 2
relations
temp with tmp
end
set var tmp to XX
load temp
.tmp
end
output printer with vlenftmo.rpt
newpage
print vlenftmo
output screen
write "Preparing vessel year demographics....."
compute yr<1960 as count bono in vslmo where vslyear < 1960
compute yr<1965 as count bono in vslmo where vslyear >= 1960 and +
vslyear < 1965
compute yr<1970 as count bono in vslmo where vslyear >= 1965 and +
vslyear < 1970
compute yr<1975 as count bono in vslmo where vslyear >= 1970 and +
vslyear < 1975
compute yr<1980 as count bono in vslmo where vslyear >= 1975 and +

```

```

vslyear < 1980
compute yr<1985 as count bono in vslmo where vslyear >= 1980 and +
vslyear < 1985
compute yr<1990 as count bono in vslmo where vslyear >= 1985 and +
vslyear < 1990
compute yr<1995 as count bono in vslmo where vslyear >= 1990 and +
vslyear < 1995
compute yr<2000 as count bono in vslmo where vslyear >= 1995 and +
vslyear < 2000
compute yr>2000 as count bono in vslmo where vslyear >= 2000
set var vpct<60 real
set var vpct<65 real
set var vpct<70 real
set var vpct<75 real
set var vpct<80 real
set var vpct<85 real
set var vpct<90 real
set var vpct<95 real
set var vpct<00 real
set var vpct>00 real
*(Evaluating percentages based on total violations)
set var vpct<60 to .yr<1960 / .totviols
set var vpct<65 to .yr<1965 / .totviols
set var vpct<70 to .yr<1970 / .totviols
set var vpct<75 to .yr<1975 / .totviols
set var vpct<80 to .yr<1980 / .totviols
set var vpct<85 to .yr<1985 / .totviols
set var vpct<90 to .yr<1990 / .totviols
set var vpct<95 to .yr<1995 / .totviols
set var vpct<00 to .yr<2000 / .totviols
set var vpct>00 to .yr>2000 / .totviols
set var pct<60 real
set var pct<65 real
set var pct<70 real
set var pct<75 real
set var pct<80 real
set var pct<85 real
set var pct<90 real
set var pct<95 real
set var pct<00 real
set var pct>00 real
*(Evaluating percentages based on total boardings)
set var pct<60 to .yr<1960 / .totbrds
set var pct<65 to .yr<1965 / .totbrds
set var pct<70 to .yr<1970 / .totbrds
set var pct<75 to .yr<1975 / .totbrds
set var pct<80 to .yr<1980 / .totbrds
set var pct<85 to .yr<1985 / .totbrds
set var pct<90 to .yr<1990 / .totbrds
set var pct<95 to .yr<1995 / .totbrds
set var pct<00 to .yr<2000 / .totbrds
set var pct>00 to .yr>2000 / .totbrds
output printer with vyearmo.rpt
newpage
print vyearmo
newpage
output screen
remove temp
remove vslmo
remove summary1
remove summary2
remove summary3
newpage
remove summary4
remove summary5
remove summary6
remove summary7
newpage
clear all variables
endif

```

return  
\*( end )

## APPENDIX K

### BRDRPTS SOURCE CODE

\$COMMAND  
BRD\_MAIN

\*(\*\*\*\*\*)

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

BOARDING REPORTS MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*\*\*\*\*)

```
set error messages off
set escape off
set messages off
clear all variables
newpage
set var pick6 integer
choose pick6 from brd_menu in brdrpts.apx
if pick6 eq 0 then
    quit to restbrd.cmd
endif
if pick6 eq 1 then
    run VIOLFREQ in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 2 then
    run BOARDING in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 3 then
    run CMERPT in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 4 then
    run BOMAJOR in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 5 then
    run BOMINOR in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 6 then
    run SMBOATRP in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 7 then
    run DAYNIGHT in brdrpts.apx
    quit to restbrd.cmd
endif
if pick6 eq 8 then
    quit to restrpts.cmd
endif
quit to restbrd.cmd
return
```

```

$menu
brd_menu
column SARELTIS --- BOARDING REPORTS
VIOLATION/UNSAFE CONDITION FREQUENCY
BOARDINGS SUMMARY LISTING
CME DECALS: ANALYSIS OF VESSELS BOARDED
LARGE SCALE AREA BOARDING LOCATION ANALYSIS
SMALL SCALE AND COASTLINE AREA BOARDING LOCATION ANALYSIS
SMALL BOAT OPERATIONS AREA BOARDING LOCATION ANALYSIS
TIME OF DAY BOARDING CASE ANALYSIS
RETURN TO REPORTS MENU
*( end )

```

```

$COMMAND
VIOLFREQ

```

```

*(*****

```

```

Program:      Violation / Unsafe Condition Frequency Analysis
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of boarding violations and unsafe conditions
              within a specified time period.

Tables Used:  boarding
Temp Tables:  frqchart, temp
Reports Used: violfreq, unsfreq
Forms Used:   none

```

```

*****

```

```

set null " "
set error messages off
set escape on
set messages off
newpage
clear all variables
write "This module performs a statistical analysis of boarding " at 2 1
write "violations and unsafe conditions within a specified " at 3 1
write "time period." at 4 1
set var strtdate date
set var enddate date
set error messages on
set var datediff to 0
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 6 1
    fillin strtdate using " " at 6 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 8 1
    fillin enddate using " " at 8 53
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
project frqchart from boarding using bono viol54 viol55 viol56 viol57 +
    viol58 viol59 viol60 viol61 viol62 viol63 viol64 viol65 viol66 +
    viol67 viol68 uns69 uns70 uns71 uns72 uns73 uns74 uns75 uns76 +
    uns77 uns78 uns79 where bodate ge .strtdate and bodate le .enddate
compute viol54s as count viol54 from frqchart where viol54 exists
compute viol55s as count viol55 from frqchart where viol55 exists
compute viol56s as count viol56 from frqchart where viol56 exists
compute viol57s as count viol57 from frqchart where viol57 exists
compute viol58s as count viol58 from frqchart where viol58 exists
compute viol59s as count viol59 from frqchart where viol59 exists
compute viol60s as count viol60 from frqchart where viol60 exists
compute viol61s as count viol61 from frqchart where viol61 exists
compute viol62s as count viol62 from frqchart where viol62 exists
compute viol63s as count viol63 from frqchart where viol63 exists
compute viol64s as count viol64 from frqchart where viol64 exists
compute viol65s as count viol65 from frqchart where viol65 exists

```



```

compute viol66s as count viol66 from frqchart where viol66 exists
compute viol67s as count viol67 from frqchart where viol67 exists
compute viol68s as count viol68 from frqchart where viol68 exists
*(computing total violations)
set var vtot1 to .viol54s + .viol55s
set var vtot2 to .viol56s + .viol57s
set var vtot3 to .viol58s + .viol59s
set var vtot4 to .viol60s + .viol61s
set var vtot5 to .viol62s + .viol63s
set var vtot6 to .viol64s + .viol65s
set var vtot7 to .viol66s + .viol67s
set var vtot8 to .vtot1 + .viol68s
set var vtot9 to .vtot2 + .vtot3
set var vtot10 to .vtot4 + .vtot5
set var vtot11 to .vtot6 + .vtot7
set var vtot12 to .vtot8 + .vtot9
set var vtot13 to .vtot10 + .vtot11
set var vttotal to .vtot12 + .vtot13
compute uns69s as count uns69 from frqchart where uns69 exists
compute uns70s as count uns70 from frqchart where uns70 exists
compute uns71s as count uns71 from frqchart where uns71 exists
compute uns72s as count uns72 from frqchart where uns72 exists
compute uns73s as count uns73 from frqchart where uns73 exists
compute uns74s as count uns74 from frqchart where uns74 exists
compute uns75s as count uns75 from frqchart where uns75 exists
compute uns76s as count uns76 from frqchart where uns76 exists
compute uns77s as count uns77 from frqchart where uns77 exists
compute uns78s as count uns78 from frqchart where uns78 exists
compute uns79s as count uns79 from frqchart where uns79 exists
*(computing total unsafe conditions)
set var unstot1 to .uns69s + .uns70s
set var unstot2 to .uns71s + .uns72s
set var unstot3 to .uns73s + .uns74s
set var unstot4 to .uns75s + .uns76s
set var unstot5 to .uns77s + .unstot1
set var unstot6 to .unstot2 + .unstot3
set var unstot7 to .unstot4 + .unstot5
set var unstotal to .unstot6 + .unstot7
compute totbrds as count bono from frqchart where bono exists
set var viol54s real
set var viol55s real
set var viol56s real
set var viol57s real
set var viol58s real
set var viol59s real
set var viol60s real
set var viol61s real
set var viol62s real
set var viol63s real
set var viol64s real
set var viol65s real
set var viol66s real
set var viol67s real
set var viol68s real
set var uns69s real
set var uns70s real
set var uns71s real
set var uns72s real
set var uns73s real
set var uns74s real
set var uns75s real
set var uns76s real
set var uns77s real
set var uns78s real
set var uns79s real
set var totbrds real
*(computing percentages based on total boardings)
set var pct54tmp to .viol54s / .totbrds
set var pct54 to .pct54tmp x 100.0
set var pct55tmp to .viol55s / .totbrds

```

```

set var pct55 to .pct55tmp x 100.0
set var pct56tmp to .viol56s / .totbrds
set var pct56 to .pct56tmp x 100.0
set var pct57tmp to .viol57s / .totbrds
set var pct57 to .pct57tmp x 100.0
set var pct58tmp to .viol58s / .totbrds
set var pct58 to .pct58tmp x 100.0
set var pct59tmp to .viol59s / .totbrds
set var pct59 to .pct59tmp x 100.0
set var pct60tmp to .viol60s / .totbrds
set var pct60 to .pct60tmp x 100.0
set var pct61tmp to .viol61s / .totbrds
set var pct61 to .pct61tmp x 100.0
set var pct62tmp to .viol62s / .totbrds
set var pct62 to .pct62tmp x 100.0
set var pct63tmp to .viol63s / .totbrds
set var pct63 to .pct63tmp x 100.0
set var pct64tmp to .viol64s / .totbrds
set var pct64 to .pct64tmp x 100.0
set var pct65tmp to .viol65s / .totbrds
set var pct65 to .pct65tmp x 100.0
set var pct66tmp to .viol66s / .totbrds
set var pct66 to .pct66tmp x 100.0
set var pct67tmp to .viol67s / .totbrds
set var pct67 to .pct67tmp x 100.0
set var pct68tmp to .viol68s / .totbrds
set var pct68 to .pct68tmp x 100.0
set var pct69tmp to .uns69s / .totbrds
set var pct69 to .pct69tmp x 100.0
set var pct70tmp to .uns70s / .totbrds
set var pct70 to .pct70tmp x 100.0
set var pct71tmp to .uns71s / .totbrds
set var pct71 to .pct71tmp x 100.0
set var pct72tmp to .uns72s / .totbrds
set var pct72 to .pct72tmp x 100.0
set var pct73tmp to .uns73s / .totbrds
set var pct73 to .pct73tmp x 100.0
set var pct74tmp to .uns74s / .totbrds
set var pct74 to .pct74tmp x 100.0
set var pct75tmp to .uns75s / .totbrds
set var pct75 to .pct75tmp x 100.0
set var pct76tmp to .uns76s / .totbrds
set var pct76 to .pct76tmp x 100.0
set var pct77tmp to .uns77s / .totbrds
set var pct77 to .pct77tmp x 100.0
set var pct78tmp to .uns78s / .totbrds
set var pct78 to .pct78tmp x 100.0
set var pct79tmp to .uns79s / .totbrds
set var pct79 to .pct79tmp x 100.0
set var viol54s integer
set var viol55s integer
set var viol56s integer
set var viol57s integer
set var viol58s integer
set var viol59s integer
set var viol60s integer
set var viol61s integer
set var viol62s integer
set var viol63s integer
set var viol64s integer
set var viol65s integer
set var viol66s integer
set var viol67s integer
set var viol68s integer
set var uns69s integer
set var uns70s integer
set var uns71s integer
set var uns72s integer
set var uns73s integer
set var uns74s integer

```

```

set var uns75s integer
set var uns76s integer
set var uns77s integer
set var uns78s integer
set var uns79s integer
set var totbrds integer
remove temp
  *(creating temporary table for printing purposes)
newpage
define
attributes
pgcount integer
relations
temp with pgcount
end
load temp
"1"
end
newpage
write "Preparing reports....."
output printer with violfreq.rpt
newpage
print violfreq
newpage
output printer with unsfreq.rpt
print unsfreq
newpage
output screen
remove frqchart
remove temp
newpage
clear all variables
return
*( end )

```

# \$COMMAND BOARDING

\*(\*\*\*\*\*)

Program:	Boarding Summary Listing Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a listing of the BOARDING table during a specified time period. The report is sorted by date before being printed.
Tables Used:	boarding
Temp Tables:	bosum
Reports Used:	boarding
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set escape on
set messages off
newpage
clear all variables
write "This program will dump all information on boardings " at 3 1
write "which are selected based on boarding date. If you wish to +
print" at 4 1
write "out the entire database of boardings, please enter the date " +
at 5 1
write "[01/01/1900] for the starting date and todays date for the " +
at 6 1
write "ending date..... " +

```

```

at 7 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 9 1
    fillin strtdate using " " at 9 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 11 1
    fillin enddate using " " at 11 53
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove bosum
newpage
project bosum from boarding using all sorted by bodate where +
    bodate >= .strtdate and bodate <= .enddate
compute numrows as rows from bosum
write "Now preparing report....." at 11 1
if numrows fails or numrows = 0 then
    write "No records match date selection criteria" at 10 10
    write "Please press any key to continue" at 16 10
    pause
else
    output printer with boarding.rpt
    newpage
    print boarding
    newpage
    output screen
endif
remove bosum
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## BOMAJOR

```

*(*****

```

Program:	Boarding Major Grid Area Frequency Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of Boardings to determine percentage of cases which occur in areas specified by coordinates found in the MAJAREA table during a specified time period.
Tables Used:	majarea, boarding
Temp Tables:	bosum, positfrq
Reports Used:	bomajor
Forms Used:	none

```

*****

```

```

set null " "
set error messages off
set escape on
set messages off
newpage
clear all variables
write "This module performs a statistical analysis of boarding " +
at 2 1
write "locations as defined by major grid areas during a specified " +
at 3 1
write "period. These major grid areas may be changed by modifying" +
at 4 1

```

```

write "the grid positions in table MAJAREA" at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove positfrq
remove bosum
newpage
set var northtst real
set var southtst real
set var westtst real
set var easttst real
set var gridcnt integer
project positfrq from majarea using all sorted by majgrid
expand positfrq with freqcnt integer
expand positfrq with gridpct real
newpage
write "This program will take several minutes to process the report." +
at 10 1
write "Please be patient....." at 11 1
project bosum from boarding using bono obslat obslong where +
bodate ge .strtdate and bodate le .enddate
compute totbrds as count bono from bosum
set var gridpct real
set var tempcpt real
set pointer #1 grid for positfrq
while grid eq 0 then
    set var northtst to majnorth in #1
    set var southtst to majsouth in #1
    set var easttst to majeast in #1
    set var westtst to majwest in #1
    compute gridcnt as count bono from bosum where obslat < .northtst +
    and obslat >= .southtst and obslong < .westtst and +
    obslong >= .easttst
    change freqcnt to .gridcnt in #1
    set var tempcpt to .gridcnt / .totbrds
    if tempcpt fails then
        set var tempcpt to 0.0
    endif
    assign gridpct to .tempcpt x 100.0 in #1
    next #1 grid
endwhile
set var inarea integer
set var outarea integer
set var inpct real
set var outpct real
compute inarea as sum freqcnt from positfrq
set var outarea to .totbrds - .inarea
set var inpct to .inarea / .totbrds
set var outpct to .outarea / .totbrds
set var inpct to .inpct x 100.0
set var outpct to .outpct x 100.0
newpage
write "Processing report information has been completed." at 3 1
write "Now preparing report....." at 4 1
output printer with bomajor.rpt
newpage
print bomajor
newpage
output terminal
remove positfrq
remove bosum

```

```

newpage
clear all variables
return
*( end )

```

\$COMMAND

BOMINOR

\*(\*\*\*\*\*)

```

Program:      Boarding Minor Grid Area Frequency Program
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of Boardings to determine percentage of
              cases which occur in a specified location
              defined in the MINAREA table during a
              specified time period.

Tables Used:  boarding, minarea
Temp Tables:  bosum, positfrq
Reports Used: bominor
Forms Used:   none

```

\*\*\*\*\*)

```

set null " "
set error messages off
set escape on
set messages off
newpage
clear all variables
write "This module performs a statistical analysis of boarding " +
at 2 1
write "locations as defined by minor grid areas during a specified " +
at 3 1
write "period. These minor grid areas may be changed by modifying" +
at 4 1
write "the grid positions in table MINAREA" at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove positfrq
remove bosum
newpage
set var northtst real
set var southtst real
set var westtst real
set var easttst real
set var gridcnt integer
project positfrq from minarea using all sorted by mingrid
expand positfrq with freqcnt integer
expand positfrq with gridpct real
newpage
write "This program will take several minutes to process the report." +
at 10 1
write "Please be patient....." at 11 1
project bosum from boarding using bono obslat obslong where +
bodate ge .strtdate and bodate le .enddate
compute totbrds as count bono from bosum

```

```

set var gridpct real
set var tempct real
set pointer #1 grid for positfrq
while grid eq 0 then
  set var northtst to minnorth in #1
  set var southtst to minsouth in #1
  set var easttst to mineast in #1
  set var westtst to minwest in #1
  compute gridcnt as count bono from bosum where obslat < .northtst +
  and obslat >= .southtst and obslong < .westtst and +
  obslong >= .easttst
  change freqcnt to .gridcnt in #1
  set var tempct to .gridcnt / .totbrds
  if tempct fails then
    set var tempct to 0.0
  endif
  assign gridpct to .tempct x 100.0 in #1
next #1 grid
endwhile
set var inarea integer
set var outarea integer
set var inpct real
set var outpct real
compute inarea as sum freqcnt from positfrq
set var outarea to .totbrds - .inarea
set var inpct to .inarea / .totbrds
set var outpct to .outarea / .totbrds
set var inpct to .inpct x 100.0
set var outpct to .outpct x 100.0
newpage
write "Processing report information has been completed." at 3 1
write "Now preparing report....." at 4 1
output printer with bomisor
newpage
print bomisor
newpage
output terminal
remove positfrq
remove bosum
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## SMBOATRP

\*(\*\*\*\*\*)

Program:	Boarding Small Boat Area Frequency Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of Boardings to determine percentage of cases which occur in the small boat operating as defined by Coast Guard Group Monterey's OPLAN during a specified time period.
Tables Used:	boarding
Temp Tables:	temp, bosum
Reports Used:	smboatrp
Forms Used:	none

\*\*\*\*\*)

```

set error messages off
set escape on
set messages off
newpage

```

```

clear all variables
remove temp
remove bosum
newpage
write "This module performs a statistical analysis of boarding " +
at 2 1
write "locations. This program examines the number of boardings " +
at 3 1
write "inside and outside of the small boat operational area during " +
at 4 1
write "a specified time period. " at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
newpage
write "This program will take several minutes to process the report." +
at 10 1
write "Please be patient....." at 11 1
project bosum from boarding using bono obslat obslong where +
bodate >= .strtdate and bodate <= .enddate
compute totbrds as count bono from bosum
set var inside to 0
set var outside to 0
set pointer #1 nl for bosum
while nl eq 0 then
    while nl eq 0 then
        set var obslat to obslat in #1
        set var obslong to obslong in #1
        if obslat < 36.100 then
            set var outside to .outside + 1
            break
        endif
        if obslong < 121.40 then
            set var outside to .outside + 1
            break
        endif
        if obslat >= 36.100 and obslat <= 36.180 and obslong >= 121.400 +
and obslong <= 122.200 then
            set var inside to .inside + 1
            break
        endif
        if obslat >= 36.180 and obslat <= 36.370 and obslong >= 121.400 +
and obslong <= 122.250 then
            set var inside to .inside + 1
            break
        endif
        if obslat >= 36.370 and obslat <= 36.480 and obslong >= 121.400 +
and obslong <= 122.300 then
            set var inside to .inside + 1
            break
        endif
        if obslat >= 36.480 and obslat <= 36.530 and obslong >= 121.400 +
and obslong <= 122.350 then
            set var inside to .inside + 1
            break
        endif
        if obslat >= 36.530 and obslat <= 36.570 and obslong >= 121.400 +
and obslong <= 122.400 then
            set var inside to .inside + 1
            break
        endif
    endwhile
endwhile

```



```

        if obslat >= 36.570 and obslat <= 37.000 and obslong >= 121.400 +
        and obslong <= 122.450 then
            set var inside to .inside + 1
            break
        endif
        if obslat >= 37.000 and obslat <= 37.050 and obslong >= 121.400 +
        and obslong <= 122.450 then
            set var inside to .inside + 1
            break
        endif
        if obslat >= 37.050 and obslat <= 37.100 and obslong >= 121.400 +
        and obslong <= 122.300 then
            set var inside to .inside + 1
            break
        endif
        set var outside to .outside + 1
        break
    endwhile
next #1 n1
endwhile
newpage
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
"XX"
end
write "Processing report information has been completed." at 3 1
write "Now preparing report....." at 4 1
output printer with smboatrp.rpt
newpage
print smboatrp
newpage
output terminal
remove temp
remove bosum
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## CMERPT

\*(\*\*\*\*\*)

```

Program:      Courtesy Motorboat Examinations (CME's)
               Statistical Analysis
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
               of vessels that were boarded to determine
               the frequency of CME's and their year of
               issue during a specified time period.

Tables Used:  boarding, vessel
Temp Tables:  bosum, vslsum, bovslsum, temp
Reports Used: cmerpt
Forms Used:   none

```

\*\*\*\*\*)

```

set error messages off
set escape on
set messages off
newpage

```

```

clear all variables
write "This program will perform statistical reports on" at 3 1
write "vessels that were boarded during a specified time with" at 4 1
write "USCG Auxiliary Courtesy Motorboat Examinations CMEs Decals" +
at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 53
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove bosum
remove vslsum
remove bovslsum
newpage
project bosum from boarding using bono bovhin where +
bodate ge .strtdate and bodate le .enddate
project vslsum from vessel using cmedecal cmeyear vslhin
join bosum using bovhin with vslsum using vslhin forming bovslsum +
where eq
compute totbrds as count bono from bovslsum
compute cmecount as count cmedecal from bovslsum where cmedecal = Y
if cmecount >= 1 and totbrds >= 1 then
    compute before70 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear <= 1970
    compute yr71to75 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1971 and cmeyear <= 1975
    compute yr76to79 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1976 and cmeyear <= 1979
    compute yr80to81 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1980 and cmeyear <= 1981
    compute yr82to83 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1982 and cmeyear <= 1983
    compute yr84to85 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1984 and cmeyear <= 1985
    compute yr86to87 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1986 and cmeyear <= 1987
    compute yr88to89 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1988 and cmeyear <= 1989
    compute after90 as count cmedecal from bovslsum where cmedecal = Y +
    and cmeyear >= 1990
    set var pctlt70 real
    set var pct71to75 real
    set var pct76to79 real
    set var pct80to81 real
    set var pct82to83 real
    set var pct84to85 real
    set var pct86to87 real
    set var pct88to89 real
    set var pctgt90 real
    if totbrds fails or totbrds = 0 then
        set var totbrds to 1
    endif
    set var pctlt70 to .before70 / .totbrds
    set var pct71to75 to .yr71to75 / .totbrds
    set var pct76to79 to .yr76to79 / .totbrds
    set var pct80to81 to .yr80to81 / .totbrds
    set var pct82to83 to .yr82to83 / .totbrds
    set var pct84to85 to .yr84to85 / .totbrds
    set var pct86to87 to .yr86to87 / .totbrds
    set var pct88to89 to .yr88to89 / .totbrds
    set var pctgt90 to .after90 / .totbrds
    set var vpct70 real
    set var vpct71 real

```

```

set var vpct76 real
set var vpct80 real
set var vpct82 real
set var vpct84 real
set var vpct86 real
set var vpct88 real
set var vpct90 real
if cmecount = 0 or cmecount fails then
  set var cmecount to 1
endif
set var vpct70 to .before70 / .cmecount
set var vpct71 to .yr71to75 / .cmecount
set var vpct76 to .yr76to79 / .cmecount
set var vpct80 to .yr80to81 / .cmecount
set var vpct82 to .yr82to83 / .cmecount
set var vpct84 to .yr84to85 / .cmecount
set var vpct86 to .yr86to87 / .cmecount
set var vpct88 to .yr88to89 / .cmecount
set var vpct90 to .after90 / .cmecount
set var pctcme real
set var pctcme to .cmecount / .totbrds
remove temp
newpage
write "Processing of statistical information completed." at 10 1
write "Now preparing report....." at 11 1
  *(creating temporary relation for printing purposes)
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
  "XX"
end
output printer with cmerpt.rpt
newpage
print cmerpt
newpage
output screen
else
  newpage
  write "No records match your selection criteria" at 10 15
  write "Please press any key to continue" at 15 20
  pause
  newpage
endif
remove bosum
remove vsisum
remove bovsisum
remove temp
clear all variables
return
*( end )

```

\$COMMAND  
DAYNIGHT

\*(\*\*\*\*\*

Program:	Daytime vs. Nighttime Frequency Analysis
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of SAR cases and Boardings to determine percentage of cases which occur in the daytime vs those that occur at night during a specified time period.
Tables Used:	sar, boarding

Temp Tables:	sarsum, bosum, temp
Reports Used:	daynight
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set escape on
set messages off
clear all variables
remove sarsum
newpage
write "This program performs a statistical analysis of Search &" at 2 1
write "Rescue cases and Boardings to determine the percentage of " +
at 3 1
write "cases which occurred during the day and at night during a " +
at 4 1
write "specified time period. " at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
project sarsum from sar using ssunrise ssunset sartime sardate where +
sardate >= .strtdate and sardate <= .enddate and ssunrise exists and +
sartime exists
compute daysar as count sartime from sarsum where sartime gea +
ssunrise and sartime lta ssunset
compute nitesar as count sartime from sarsum where sartime lta +
ssunrise or sartime gea ssunset
set var totsars to .daysar + .nitesar
set var pctdays real
set var pctnites real
set var pctdays to .daysar / .totsars
set var pctnites to .nitesar / .totsars
set var pctdays to .pctdays x 100.0
set var pctnites to .pctnites x 100.0
remove sarsum
remove bosum
newpage
project bosum from boarding using bsunset bsunrise botime bodate where +
bobate >= .strtdate and bobate <= .enddate and bsunrise exists and +
botime exists
compute daybrd as count botime from bosum where botime gea bsunrise++
and botime lta bsunset
compute nitebrd as count botime from bosum where botime lta bsunrise +
or botime gea bsunset
set var totbrds to .daybrd + .nitebrd
set var pctdayb real
set var pctniteb real
set var pctdayb to .daybrd / .totbrds
set var pctniteb to .nitebrd / .totbrds
set var pctdayb to .pctdayb x 100.0
set var pctniteb to .pctniteb x 100.0
remove bosum
remove temp
newpage
define
attributes
tmp text 2
relations

```

```
temp with tmp
end
load temp
  "XX"
end
newpage
write "Preparing report....."
output printer with daynight.rpt
newpage
print daynight
newpage
output screen
remove sarsum
remove bosum
remove temp
newpage
return
*( end )
```

## APPENDIX L

### SARRPTS SOURCE CODE

\$COMMAND  
SAR\_MAIN

\*(\*\*\*\*\*)

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

SAR REPORTS MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*\*\*\*\*)

```
set error messages off
set messages off
set escape off
clear all variables
newpage
set var pick7 integer
choose pick7 from sar_menu in sarrpts.apx
if pick7 eq 0 then
    quit to restsar.cmd
endif
if pick7 eq 1 then
    run IMMEDSAR in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 2 then
    run SARMINOR in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 3 then
    run SARMAJOR in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 4 then
    run SARSMBT in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 5 then
    run SARDUMP in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 6 then
    run SARTIMES in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 7 then
    run SARDAY in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 8 then
    run DAYNIGHT in sarrpts.apx
    quit to restsar.cmd
endif
if pick7 eq 9 then
```

```

quit to restrpts.cmd
endif
quit to restsar.cmd
return
$menu
sar_menu
column SARELTIS --- SAR REPORTS
ANALYSIS OF IMMEDIATE DISTRESS SAR CASES
MINOR AREA (MINAREA table) LOCATION ANALYSIS
MAJOR AREA (MAJAREA table) LOCATION ANALYSIS
INSIDE/OUTSIDE SMALL BOAT OPAREA LOCATION ANALYSIS
SAR TABLE SUMMARY LISTING
SAR UNIT TIME EXPENDED DURING SAR CASES
DAY OF THE WEEK, MONTH, AND YEAR ANALYSIS
SAR CASE ANALYSIS: DAYTIME/NIGHTTIME FREQUENCY
RETURN TO REPORTS MENU
*( end )

```

# \$COMMAND

## SARMAJOR

```

*(*****

```

```

Program:          SAR Major Grid Area Frequency Analysis
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program performs a statistical analysis
                   of SAR cases to determine percentage of
                   cases which occur in specified locations in
                   the table MAJAREA during a specified time
                   period.

Tables Used:      majarea, sar
Temp Tables:      sarsum, positfrq
Reports Used:     sarmajor
Forms Used:       none

```

```

*****

```

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This module performs a statistical analysis of SAR case " at 2 1
write "locations as defined by major grid areas during a specified " +
at 3 1
write "period. These major grid areas may be changed by modifying" +
at 4 1
write "the grid positions in table MAJAREA" at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
fillin strtdate using " " at 8 51
write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
fillin enddate using " " at 10 51
set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove positfrq
remove sarsum
newpage
set var northtst real
set var southtst real
set var westtst real

```

```

set var easttst real
set var gridcnt integer
project positfrq from majarea using all sorted by majgrid
expand positfrq with freqcnt integer
expand positfrq with gridpct real
newpage
write "This program will take several minutes to process the report." +
at 10 1
write "Please be patient....." at 11 1
project sarsum from sar using folderno sarlat sarlong where +
sardate ge .strtdat and sardate le .enddate
compute totsars as count folderno from sarsum
compute numrows as rows from sarsum
set var gridpct real
set var tempct real
set pointer #1 grid for positfrq
while grid eq 0 then
  set var northtst to majnorth in #1
  set var southtst to majsouth in #1
  set var easttst to majeast in #1
  set var westtst to majwest in #1
  compute gridcnt as count folderno from sarsum where +
  sarlat < .northtst and sarlat >= .southtst and sarlong < .westtst +
  and sarlong >= .easttst
  change freqcnt to .gridcnt in #1
  set var tempct to .gridcnt / .totsars
  if tempct fails then
    set var tempct to 0.0
  endif
  assign gridpct to .tempct x 100.0 in #1
  next #1 grid
endif
endwhile
set var inarea integer
set var outarea integer
set var inpct real
set var outpct real
compute inarea as sum freqcnt from positfrq
set var outarea to .totsars - .inarea
set var inpct to .inarea / .totsars
set var outpct to .outarea / .totsars
set var inpct to .inpct x 100.0
set var outpct to .outpct x 100.0
newpage
write "Processing report information has been completed." at 3 1
write "Now preparing report....." at 4 1
if numrows fails or numrows = 0 then
  newpage
  write "No records exist in the database matching your selection +
criteria" at 10 1
  write "Please press any key to return to menu" at 16 10
  pause
else
  output printer with sarmajor.rpt
  newpage
  print sarmajor
  newpage
  output terminal
endif
remove positfrq
remove sarsum
newpage
clear all variables
return
*( end )

```

\$COMMAND

SARMINOR

\*(\*\*\*\*\*



Program:	SAR Minor Grid Area Frequency Analysis
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of SAR cases to determine percentage of cases which occur in locations specified by coordinates contained in the table MINAREA during a specified time period.
Tables Used:	sar, minarea
Temp Tables:	sarsum, positfrq
Reports Used:	sarminor
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This module performs a statistical analysis of SAR case " at 2 1
write "locations as defined by minor grid areas during a specified " +
at 3 1
write "period. These major grid areas may be changed by modifying" +
at 4 1
write "the grid positions in table MINAREA" at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove positfrq
remove sarsum
newpage
set var northtst real
set var southtst real
set var westtst real
set var easttst real
set var gridcnt integer
project positfrq from minarea using all sorted by mingrid
expand positfrq with freqcnt integer
expand positfrq with gridpct real
newpage
write "This program will take several minutes to process the report." +
at 10 1
write "Please be patient....." at 11 1
project sarsum from sar using folderno sarlat sarlong where +
sardate ge .strtdate and sardate le .enddate
compute totsars as count folderno from sarsum
compute numrows as rows from sarsum
set var gridpct real
set var tempct real
set pointer #1 grid for positfrq
while grid eq 0 then
    set var northtst to minnorth in #1
    set var southtst to minsouth in #1
    set var easttst to mineast in #1
    set var westtst to minwest in #1
    compute gridcnt as count folderno from sarsum where +
    sarlat < .northtst and sarlat >= .southtst and sarlong < .westtst +

```

```

and sarlong >= .easttst
change freqcnt to .gridcnt in #1
set var tempcpt to .gridcnt / .totsars
if tempcpt fails then
    set var tempcpt to 0.0
endif
assign gridpct to .tempcpt x 100.0 in #1
next #1 grid
endwhile
set var inarea integer
set var outarea integer
set var inpct real
set var outpct real
compute inarea as sum freqcnt from positfrq
set var outarea to .totsars - .inarea
set var inpct to .inarea / .totsars
set var outpct to .outarea / .totsars
set var inpct to .inpct x 100.0
set var outpct to .outpct x 100.0
newpage
write "Processing report information has been completed." at 3 1
write "Now preparing report....." at 4 1
if numrows fails or numrows = 0 then
    newpage
    write "No records exist in the database matching your selection +
criteria" at 10 1
    write "Please press any key to return to menu" at 16 10
    pause
else
    output printer with sarminor.rpt
    newpage
    print sarminor
    newpage
    output terminal
endif
remove positfrq
remove sarsum
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## SARMBT

\*(\*\*\*\*\*)

Program:	SAR Case Small Boat Area Frequency Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of SAR Cases to determine percentage of cases which occur in the small boat operating as defined by Coast Guard Group Monterey's OPLAN during a specified time period.
Tables Used:	sar
Temp Tables:	temp, sarsum
Reports Used:	sarsmbt
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables

```

```

remove temp
remove sarsum
newpage
write "This module performs a statistical analysis of SAR Case " at 2 1
write "locations. This program examines the number of SAR Cases " +
at 3 1
write "inside and outside of the small boat operational area during " +
at 4 1
write "a specified time period. " at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
newpage
write "This program will take several minutes to process the report." +
at 10 1
write "Please be patient....." at 11 1
project sarsum from sar using folderno sarlat sarlong where +
sardate >= .strtdate and sardate <= .enddate
compute totsars as count folderno from sarsum
compute numrows as rows from sarsum
set var inside to 0
set var outside to 0
set pointer #1 nl for sarsum
while nl eq 0 then
    while nl eq 0 then
        set var sarlat to sarlat in #1
        set var sarlong to sarlong in #1
        if sarlat < 36.100 then
            set var outside to .outside + 1
            break
        endif
        if sarlong < 121.40 then
            set var outside to .outside + 1
            break
        endif
        if sarlat >= 36.100 and sarlat <= 36.180 and sarlong >= 121.400 +
and sarlong <= 122.200 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 36.180 and sarlat <= 36.370 and sarlong >= 121.400 +
and sarlong <= 122.250 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 36.370 and sarlat <= 36.480 and sarlong >= 121.400 +
and sarlong <= 122.300 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 36.480 and sarlat <= 36.530 and sarlong >= 121.400 +
and sarlong <= 122.350 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 36.530 and sarlat <= 36.570 and sarlong >= 121.400 +
and sarlong <= 122.400 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 36.570 and sarlat <= 37.000 and sarlong >= 121.400 +

```

```

        and sarlong <= 122.450 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 37.000 and sarlat <= 37.050 and sarlong >= 121.400 +
        and sarlong <= 122.450 then
            set var inside to .inside + 1
            break
        endif
        if sarlat >= 37.050 and sarlat <= 37.100 and sarlong >= 121.400 +
        and sarlong <= 122.300 then
            set var inside to .inside + 1
            break
        endif
        set var outside to .outside + 1
        break
    endwhile
    next #1 n1
endwhile
set var inpcttmp real
set var outpcttm real
set var inpct real
set var outpct real
set var totsars real
set var inside real
set var outside real
set var inpcttmp to .inside / .totsars
set var outpcttm to .outside / .totsars
set var inpct to .inpcttmp x 100.0
set var outpct to .outpcttm x 100.0
set var totsars integer
set var inside integer
set var outside integer
newpage
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
"XX"
end
write "Processing report information has been completed." at 3 1
write "Now preparing report....." at 4 1
if numrows fails or numrows = 0 then
    newpage
    write "No records exist in the database matching your selection +
    criteria" at 10 1
    write "Please press any key to return to menu" at 16 10
    pause
else
    output printer with sarsmbt.rpt
    newpage
    print sarsmbt
    newpage
    output terminal
endif
remove temp
remove sarsum
newpage
clear all variables
return
*( end )

$COMMAND
$ARTIMES
*(*****

```

Program:	SAR Case Units Time Expended Frequency
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of SAR cases to determine total time expended, time to being on scene, time to being alongside, time involved in searches, and time involved in towing. These times are analyzed to produce totals, averages, minimums, and maximums for a specific time period.
Tables Used:	sarunits
Temp Tables:	sartime1, sartime2, sartime3, sartime4, sartime5, temp
Reports Used:	sartimes
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will perform statistical reports on" at 3 1
write "SAR cases that occurred during a specified time period." at 4 1
write "Total sar unit time expended, time to on scene, time " at 5 1
write "to alongside distressed vessel, time expended in searches," +
at 6 1
write "and time engaged in towing will be analyzed." at 7 1
write "Since this program can take 5 to 10 minutes to run, you may" +
at 12 1
write "press the escape [ESC] key to exit to the RBase 5000 command" +
at 13 1
write "prompt where can either restart the menu system by typing:" +
at 14 1
write "                                RUN STARTUP.BIN" at 16 1
write "or exiting the system by typing:" at 18 1
write "                                EXIT" at 20 1
write "Press any key to continue " at 23 10
pause
newpage
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 10 1
    fillin strtdate using " " at 10 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 12 1
    fillin enddate using " " at 12 53
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
remove sartime1
newpage
project sartime1 from sarunits using uvertime uupdate ostime osdate +
foldno where uvertime exists and uupdate exists and ostime exists and +
osdate exists and uupdate lea osdate and uupdate >= .strtdate and +
sutdate <= .enddate
compute ostones as count foldno from sartime1
set var ossum real
set var timehour real
set var datehour real
set var test real
set var timeadd real
set var minostim real

```

```

set var maxostim real
set var ossum to 0.0
set var minostim to 1000.0
set var maxostim to 0.0
write "Now computing sar time statistics" at 10 15
set pointer #1 n1 for sartime1
while n1 eq 0 then
  set var uwtime to uwtime in #1
  set var udate to udate in #1
  set var ostime to ostime in #1
  set var osdate to osdate in #1
  if udate = .osdate then
    set var timediff to .ostime - .uwtime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var test to .timehour
    set var ossum to .ossum + .timehour
  else
    set var datediff to .osdate - .udate
    set var datehour to .datediff x 24.0
    *(converts days to hours)
    set var timediff to .ostime - .uwtime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var timeadd to .timehour + .datehour
    set var test to .timeadd
    set var ossum to .ossum + .timeadd
  endif
  if test <= .minostim then
    set var minostim to .test
  endif
  if test >= .maxostim then
    set var maxostim to .test
  endif
  next #1 n1
endwhile
remove sartime1
remove sartime2
newpage
project sartime2 from sarunits using uwtime udate sutmoor sutdate +
foldno where uwtime exists and udate exists and sutmoor exists and +
sutdate exists and udate lea sutdate and udate >= .strtdate and +
sutdate <= .enddate
compute tottimes as count foldno from sartime2
set var totsum real
set var mintttim real
set var maxtttim real
set var totsum to 0.0
set var mintttim to 1000.0
set var maxtttim to 0.0
set pointer #1 n1 for sartime2
while n1 eq 0 then
  set var uwtime to uwtime in #1
  set var udate to udate in #1
  set var sutmoor to sutmoor in #1
  set var sutdate to sutdate in #1
  if udate = .sutdate then
    set var timediff to .sutmoor - .uwtime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var test to .timehour
    set var totsum to .totsum + .timehour
  else
    set var datediff to .sutdate - .udate
    set var datehour to .datediff x 24.0
    *(converts days to hours)
    set var timediff to .sutmoor - .uwtime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var timeadd to .timehour + .datehour

```

```

        set var test to .timeadd
        set var totsum to .totsum + .timeadd
    endif
    if test <= .mintttim then
        set var mintttim to .test
    endif
    if test >= .maxtttim then
        set var maxtttim to .test
    endif
    next #1 n1
endwhile
remove sartime2
remove sartime3
newpage
project sartime3 from sarunits using uwtime udate alngtime alngdate +
foldno where uwtime exists and udate exists and alngtime exists and +
alngdate exists and udate lea alngdate and udate >= .strtdat and +
sutdate <= .enddate
compute algtimes as count foldno from sartime3
set var algsum real
set var minaltim real
set var maxaltim real
set var algsum to 0.0
set var minaltim to 1000.0
set var maxaltim to 0.0
set pointer #1 n1 for sartime3
while n1 eq 0 then
    set var uwtime to uwtime in #1
    set var udate to udate in #1
    set var alngtime to alngtime in #1
    set var alngdate to alngdate in #1
    if udate = .alngdate then
        set var timediff to .alngtime - .uwtime
        set var timehour to .timediff / 3600.0
        *(converts seconds to hours)
        set var test to .timehour
        set var algsum to .algsum + .timehour
    else
        set var datediff to .alngdate - .uupdate
        set var datehour to .datediff x 24.0
        *(converts days to hours)
        set var timediff to .alngtime - .uwtime
        set var timehour to .timediff / 3600.0
        *(converts seconds to hours)
        set var timeadd to .timehour + .datehour
        set var test to .timeadd
        set var algsum to .algsum + .timeadd
    endif
    if test <= .minaltim then
        set var minaltim to .test
    endif
    if test >= .maxaltim then
        set var maxaltim to .test
    endif
    next #1 n1
endwhile
remove sartime3
remove sartime4
newpage
project sartime4 from sarunits using ostime osdate alngtime alngdate +
foldno where ostime exists and osdate exists and alngtime exists and +
alngdate exists and osdate lea alngdate and udate >= .strtdat and +
sutdate <= .enddate
compute schtimes as count foldno from sartime4
set var schsum real
set var minshtim real
set var maxshtim real
set var schsum to 0.0
set var minshtim to 1000.0
set var maxshtim to 0.0

```

```

set pointer #1 n1 for sartime4
while n1 eq 0 then
  set var ostime to ostime in #1
  set var osdate to osdate in #1
  set var alptime to alptime in #1
  set var alqdate to alqdate in #1
  if osdate = .alqdate then
    set var timediff to .alptime - .ostime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var test to .timehour
    set var schsum to .schsum + .timehour
  else
    set var datediff to .alqdate - .osdate
    set var datehour to .datediff x 24.0
    *(converts days to hours)
    set var timediff to .alptime - .ostime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var timeadd to .timehour + .datehour
    set var test to .timeadd
    set var schsum to .schsum + .timeadd
  endif
  if test <= .minshum then
    set var minshum to .test
  endif
  if test >= .maxshtim then
    set var maxshtim to .test
  endif
  next #1 n1
endwhile
remove sartime4
remove sartime5
newpage
project sartime5 from sarunits using towtime towdate dvmoored dvmdate +
foldno where towtime exists and towdate exists and dvmoored exists +
and dvmdate exists and towdate lea dvmdate and udate >= .strtdate +
and sutdate <= .enddate
compute towtimes as count foldno from sartime5
set var towsum real
set var mintwtim real
set var maxtwtim real
set var towsum to 0.0
set var mintwtim to 1000.0
set var maxtwtim to 0.0
set pointer #1 n1 for sartime5
while n1 eq 0 then
  set var towtime to towtime in #1
  set var towdate to towdate in #1
  set var dvmtime to dvmoored in #1
  set var dvmdate to dvmdate in #1
  if towdate = .dvmdate then
    set var timediff to .dvmtime - .towtime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var test to .timehour
    set var towsum to .towsum + .timehour
  else
    set var datediff to .dvmdate - .towdate
    set var datehour to .datediff x 24.0
    *(converts days to hours)
    set var timediff to .dvmtime - .towtime
    set var timehour to .timediff / 3600.0
    *(converts seconds to hours)
    set var timeadd to .timehour + .datehour
    set var test to .timeadd
    set var towsum to .towsum + .timeadd
  endif
  if test <= .mintwtim then
    set var mintwtim to .test

```



```

endif
if test >= .maxtwtim then
  set var maxtwtim to .test
endif
next #1 n1
endwhile
remove sartime5
newpage
set var totavg real
set var oscavg real
set var algavg real
set var schavg real
set var towavg real
set var totavg to .totsum / .tottimes
set var oscavg to .ossum / .ostimes
set var algavg to .algsum / .algtimes
set var schavg to .schsum / .schtimes
set var towavg to .towsum / .towtimes
remove temp
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
"XX"
end
newpage
write "Now preparing report" at 10 15
output printer with sartimes.rpt
newpage
print sartimes
newpage
output screen
remove temp
clear all variables
set escape off
return
*( end )

```

# \$COMMAND

## SARDAY

```

*(*****

```

```

Program:      SAR Days, SAR Months, SAR Years Frequency
              Analysis
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of SAR cases to determine percentage of
              cases which occurred on specific days of the
              week, months of the year and years during a
              specified time period.

Tables Used:  sar
Temp Tables: sarsum1, sarstat, sarsum, temp
Reports Used: sardates, sardays
Forms Used:  none

```

```

*****

```

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables

```

```

remove sarsum1
write "This program will perform a statistical report on" at 3 1
write "days of the week, months of the year, and individual" at 4 1
write "years that SAR cases have occurred." at 5 1
write "This program will evaluate statistics starting from 1980." at 8 1
write "Please indicate how many years of data you wish to analyze." +
at 9 1
set var numyears integer
set var numyears to 999999
set error messages on
while numyears <= 0 or numyears > 32 then
    *(system will only do stats until 2012)
    fillin numyears using "Number of years: " at 12 20
    if numyears <= 0 or numyears > 32 then
        write "You must enter a number between 1 and 32" at 15 20
        write "Please reenter." at 16 30
    endif
endwhile
set var strtdate date
set var enddate date
set var strtdate to 01/01/1980
set var count integer
set var count to 1
set var daysadd integer
set var daysadd to 0
while count <= .numyears then
    set var yrtest1 to .numyears / 4
    set var yrtest2 to .yrtest1 x 4
    set var yrtest to .numyears - .yrtest2
    if yrtest = 0 then
        set var daysadd to .daysadd + 366
    else
        set var daysadd to .daysadd + 365
    endif
    set var count to .count + 1
endwhile
set var enddate to .strtdate + .daysadd
newpage
set error messages off
write "Since this program can take 5 to 10 minutes to run, you may" +
at 12 1
write "press the escape [ESC] key to exit to the RBase 5000 command" +
at 13 1
write "prompt where can either restart the menu system by typing:" +
at 14 1
write "RUN STARTUP.BIN" at 16 1
write "or exiting the system by typing:" at 18 1
write "EXIT" at 20 1
write "Press any key to continue" at 23 10
pause
newpage
project sarsum1 from sar using sardate sarday folderno sorted by +
sardate where sardate >= .strtdate and sardate <= .enddate
compute numrows as rows from sarsum1
set var begndate date
set var stopdate date
set var begndate to 01/01/1980
set var stopdate to 12/31/1980
set var count integer
set var count to 1
set var saryear integer
set var saryear to 1979
remove sarstat
set var sarnum integer
define
attributes
saryear integer
sarnum integer
relations
sarstat with saryear sarnum

```

```

end
while count <= .numyears then
  compute numsars as count sardate from sarsum1 where +
  sardate >= .begndate and sardate <= .stopdate
  set var saryear to .saryear + 1
  if numsars fails then
    set var sarnum to 0
  else
    set var sarnum to .numsars
  endif
  load sarstat
  .saryear .sarnum
end
set var yrtest1 to .saryear / 4
set var yrtest2 to .yrtest1 x 4
set var yrtest to .saryear - .yrtest2
if yrtest = 0 then
  set var begndate to .begndate + 366
  set var stopdate to .stopdate + 366
else
  set var begndate to .begndate + 365
  set var stopdate to .stopdate + 365
endif
set var count to .count + 1
endwhile
set var jansar integer
set var count integer
set var jandatel date
set var jandate2 date
set var febsar integer
set var febdate1 date
set var febdate2 date
set var marsar integer
set var mardatel date
set var mardate2 date
set var aprsar integer
set var aprdate1 date
set var aprdate2 date
set var maysar integer
set var maydate1 date
set var maydate2 date
set var junsar integer
set var jundatel date
set var jundate2 date
set var julsar integer
set var juldate1 date
set var juldate2 date
set var augsar integer
set var augdate1 date
set var augdate2 date
set var sepsar integer
set var sepdate1 date
set var sepdate2 date
set var octsar integer
set var octdate1 date
set var octdate2 date
set var novsar integer
set var novdate1 date
set var novdate2 date
set var decsar integer
set var decdate1 date
set var decdate2 date
set var jansar to 0
set var febsar to 0
set var marsar to 0
set var aprsar to 0
set var maysar to 0
set var junsar to 0
set var julsar to 0
set var augsar to 0

```

```

set var sepsar to 0
set var octsar to 0
set var novsar to 0
set var decsar to 0
set var jandatel to 01/01/1980
set var jandate2 to 01/31/1980
set var febdate1 to 02/01/1980
set var febdate2 to 02/28/1980
set var mardatel to 03/01/1980
set var mardate2 to 03/31/1980
set var aprdate1 to 04/01/1980
set var aprdate2 to 04/30/1980
set var maydate1 to 05/01/1980
set var maydate2 to 05/31/1980
set var jundatel to 06/01/1980
set var jundate2 to 06/30/1980
set var juldate1 to 07/01/1980
set var juldate2 to 07/31/1980
set var augdate1 to 08/01/1980
set var augdate2 to 08/31/1980
set var sepdate1 to 09/01/1980
set var sepdate2 to 09/30/1980
set var octdate1 to 10/01/1980
set var octdate2 to 10/31/1980
set var novdate1 to 11/01/1980
set var novdate2 to 11/30/1980
set var decdate1 to 12/01/1980
set var decdate2 to 12/31/1980
set var count to 1
newpage
write "Now performing statistical analysis" at 10 10
while count <= .numyears then
  compute janrows as count sardate from sarsum1 where +
  sardate >= .jandatel and sardate <= .jandate2
  if janrows exists then
    set var jansar to .jansar + .janrows
  endif
  compute febrows as count sardate from sarsum1 where +
  sardate >= .febdate1 and sardate <= .febdate2
  if febrows exists then
    set var febsar to .febsar + .febrows
  endif
  compute marrows as count sardate from sarsum1 where +
  sardate >= .mardatel and sardate <= .mardate2
  if marrows exists then
    set var marsar to .marsar + .marrows
  endif
  compute aprrows as count sardate from sarsum1 where +
  sardate >= .aprdate1 and sardate <= .aprdate2
  if aprrows exists then
    set var aprsar to .aprsar + .aprrows
  endif
  compute mayrows as count sardate from sarsum1 where +
  sardate >= .maydate1 and sardate <= .maydate2
  if mayrows exists then
    set var maysar to .maysar + .mayrows
  endif
  compute junrows as count sardate from sarsum1 where +
  sardate >= .jundatel and sardate <= .jundate2
  if junrows exists then
    set var junsar to .junsar + .junrows
  endif
  compute julrows as count sardate from sarsum1 where +
  sardate >= .juldate1 and sardate <= .juldate2
  if julrows exists then
    set var julsar to .julsar + .julrows
  endif
  compute augrows as count sardate from sarsum1 where +
  sardate >= .augdate1 and sardate <= .augdate2
  if augrows exists then

```

```

    set var augsar to .augsar + .augrows
endif
compute seprows as count sardate from sarsum1 where +
sardate >= .sepdate1 and sardate <= .sepdate2
if seprows exists then
    set var sepsar to .sepsar + .seprows
endif
compute octrows as count sardate from sarsum1 where +
sardate >= .octdate1 and sardate <= .octdate2
if octrows exists then
    set var octsar to .octsar + .octrows
endif
compute novrows as count sardate from sarsum1 where +
sardate >= .novdate1 and sardate <= .novdate2
if novrows exists then
    set var novsar to .novsar + .novrows
endif
compute decrows as count sardate from sarsum1 where +
sardate >= .decdate1 and sardate <= .decdate2
if decrows exists then
    set var decsar to .decsar + .decrows
endif
set var yrtest1 to .saryear / 4
set var yrtest2 to .yrtest1 x 4
set var yrtest to .saryear - .yrtest2
if yrtest = 0 then
    set var jandate1 to .jandate1 + 366
    set var jandate2 to .jandate2 + 366
    set var febdate1 to .febdate1 + 366
    set var febdate2 to .febdate2 + 366
    set var mardate1 to .mardate1 + 366
    set var mardate2 to .mardate2 + 366
    set var aprdate1 to .aprdate1 + 366
    set var aprdate2 to .aprdate2 + 366
    set var maydate1 to .maydate1 + 366
    set var maydate2 to .maydate2 + 366
    set var jundate1 to .jundate1 + 366
    set var jundate2 to .jundate2 + 366
    set var juldate1 to .juldate1 + 366
    set var juldate2 to .juldate2 + 366
    set var augdate1 to .augdate1 + 366
    set var augdate2 to .augdate2 + 366
    set var sepdate1 to .sepdate1 + 366
    set var sepdate2 to .sepdate2 + 366
    set var octdate1 to .octdate1 + 366
    set var octdate2 to .octdate2 + 366
    set var novdate1 to .novdate1 + 366
    set var novdate2 to .novdate2 + 366
    set var decdate1 to .decdate1 + 366
    set var decdate2 to .decdate2 + 366
else
    set var jandate1 to .jandate1 + 365
    set var jandate2 to .jandate2 + 365
    set var febdate1 to .febdate1 + 365
    set var febdate2 to .febdate2 + 365
    set var mardate1 to .mardate1 + 365
    set var mardate2 to .mardate2 + 365
    set var aprdate1 to .aprdate1 + 365
    set var aprdate2 to .aprdate2 + 365
    set var maydate1 to .maydate1 + 365
    set var maydate2 to .maydate2 + 365
    set var jundate1 to .jundate1 + 365
    set var jundate2 to .jundate2 + 365
    set var juldate1 to .juldate1 + 365
    set var juldate2 to .juldate2 + 365
    set var augdate1 to .augdate1 + 365
    set var augdate2 to .augdate2 + 365
    set var sepdate1 to .sepdate1 + 365
    set var sepdate2 to .sepdate2 + 365
    set var octdate1 to .octdate1 + 365

```

```

        set var octdate2 to .octdate2 + 365
        set var novdate1 to .novdate1 + 365
        set var novdate2 to .novdate2 + 365
        set var decdate1 to .decdate1 + 365
        set var decdate2 to .decdate2 + 365
    endif
    set var count to .count + 1
endwhile
newpage
compute totsars as rows from sarsum1
set var pctjan real
set var pctfeb real
set var pctmar real
set var pctapr real
set var pctmay real
set var pctjun real
set var pctjul real
set var pctaug real
set var pctsep real
set var pctoct real
set var pctnov real
set var pctdec real
    *(calculating percentages based on total SAR cases)
set var pctjan to .jansar / .totsars
set var pctfeb to .febsar / .totsars
set var pctmar to .marsar / .totsars
set var pctapr to .aprsar / .totsars
set var pctmay to .maysar / .totsars
set var pctjun to .junsar / .totsars
set var pctjul to .julsar / .totsars
set var pctaug to .augsar / .totsars
set var pctsep to .sepsar / .totsars
set var pctoct to .octsar / .totsars
set var pctnov to .novsar / .totsars
set var pctdec to .decsar / .totsars
newpage
write "Preparing report...."
if numrows fails or numrows = 0 then
    newpage
    write "No records exist in the database matching your selection +
criteria" at 10 1
    write "Please press any key to continue" at 16 10
    pause
else
    output printer with sardates.rpt
    newpage
    print sardates
    output screen
endif
remove sarsum
remove sarstat
newpage
clear numrows
project sarsum from sar using folderno sarday sardate where +
sarday exists and sardate exists
compute numrows as rows from sarsum
compute monday as count sarday from sarsum where sarday eq mon
compute tuesday as count sarday from sarsum where sarday eq tue
compute wednesday as count sarday from sarsum where sarday eq wed
compute thursday as count sarday from sarsum where sarday eq thu
compute friday as count sarday from sarsum where sarday eq fri
compute saturday as count sarday from sarsum where sarday eq sat
compute sunday as count sarday from sarsum where sarday eq sun
compute totdays as count sarday from sarsum where sarday exists
set var pctmon real
set var pcttue real
set var pctwed real
set var pctthu real
set var pctfri real
set var pctsat real

```

```

set var pctsun real
set var pctmon to .monday / .totdays
set var pcttue to .tuesday / .totdays
set var pctwed to .wednesday / .totdays
set var pctthu to .thursday / .totdays
set var pctfri to .friday / .totdays
set var pctsat to .saturday / .totdays
set var pctsun to .sunday / .totdays
write "Processing of statistical information completed." at 10 1
write "Now preparing report....." at 11 1
remove temp
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
"XX"
end
if numrows fails or numrows = 0 then
newpage
write "No records exist in the database matching your selection +
criteria" at 10 1
write "Please press any key to return to menu" at 16 10
pause
else
output printer with sardays.rpt
newpage
print sardays
newpage
output screen
endif
clear all variables
remove temp
remove sarstat
newpage
set escape off
return
*( end )

```

# \$COMMAND

## DAYNIGHT

```

*(*****

```

Program:	Daytime vs. Nighttime Frequency Analysis
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a statistical analysis of SAR cases and Boardings to determine percentage of cases which occur in the daytime vs those that occur at night during a specified time period.
Tables Used:	sar, boarding
Temp Tables:	sarsum, bosum, temp
Reports Used:	daynight
Forms Used:	none

```

*****

```

```

set null " "
set escape on
set messages off
set error messages off
clear all variables
remove sarsum
newpage

```

```

write "This program performs a statistical analysis of Search &" at 2 1
write "Rescue cases and Boardings to determine the percentage of " +
at 3 1
write "cases which occurred during the day and at night during a " +
at 4 1
write "specified time period. " at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
project sarsum from sar using ssunrise ssunset sartime sardate where +
sardate >= .strtdate and sardate <= .enddate and ssunrise exists and +
sartime exists
compute numrows as rows from sarsum
compute daysar as count sartime from sarsum where sartime gea +
ssunrise and sartime lta ssunset
compute nitesar as count sartime from sarsum where sartime lta +
ssunrise or sartime gea ssunset
set var totsars to .daysar + .nitesar
set var pctdays real
set var pctnites real
set var pctdays to .daysar / .totsars
set var pctnites to .nitesar / .totsars
set var pctdays to .pctdays x 100.0
set var pctnites to .pctnites x 100.0
remove sarsum
remove bosum
newpage
project bosum from boarding using bsunset bsunrise botime bodate where +
bobate >= .strtdate and bobate <= .enddate and bsunrise exists and +
botime exists
compute numrows1 as rows from bosum
compute daybrd as count botime from bosum where botime gea bsunrise +
and botime lta bsunset
compute nitebrd as count botime from bosum where botime lta bsunrise +
or botime gea bsunset
set var totbrds to .daybrd + .nitebrd
set var pctdayb real
set var pctniteb real
set var pctdayb to .daybrd / .totbrds
set var pctniteb to .nitebrd / .totbrds
set var pctdayb to .pctdayb x 100.0
set var pctniteb to .pctniteb x 100.0
remove bosum
remove temp
newpage
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
"XX"
end
newpage
write "Preparing report....."
if numrows fails or numrows = 0 then
    if numrows1 fails or numrows1 = 0 then
        newpage
        write "No records exist matching your selection criteria" +
        at 10 1

```



```

        write "Please press any key to return to menu" at 16 10
        pause
    else
        output printer with daynight.rpt
        newpage
        print daynight
        newpage
        output screen
    endif
else
    output printer
    newpage
    print daynight
    newpage
    output screen
endif
remove sarsum
remove bosum
remove temp
newpage
return
*( end )

```

# \$COMMAND

## SARDUMP

```

*(*****

```

```

Program:          SAR Summary Listing Program
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:       This program performs a dump of the table SAR
                   of those SAR cases that occurred during a
                   specified time period. The listing is sorted
                   by date prior to being printed.

Tables Used:      sar
Temp Tables:      sarsum
Reports Used:     sar
Forms Used:       none

```

```

*****

```

```

set null " "
set escape on
set messages off
set error messages off
newpage
clear all variables
write "This program will dump all information on SAR cases " at 3 1
write "which are selected based on SAR date. If you wish to print" +
at 4 1
write "out the entire database of SAR cases, please enter the date " +
at 5 1
write "[01/01/1900] for the starting date and todays date for the " +
at 6 1
write "ending date..... " +
at 7 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 9 1
    fillin strtdate using " " at 9 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 11 1
    fillin enddate using " " at 11 53
    set var datediff to .enddate - .strtdate
endwhile

```

```

set error messages off
remove sarsum
newpage
project sarsum from sar using all sorted by sardate where +
sardate >= .strtdate and sardate <= .enddate
compute numrows as rows from sarsum
newpage
write "Now preparing report....." at 11 1
if numrows fails or numrows = 0 then
    newpage
    write "No records exist matching your selection criteria" +
    at 10 1
    write "Please press any key to return to menu" at 16 10
    pause
else
    output printer with sar.rpt
    newpage
    print sar
    newpage
    output screen
endif
remove sarsum
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## IMMEDSAR

```

*(*****

```

```

Program:      Immediate SAR Frequency Program
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a statistical analysis
              of SAR cases to determine percentage of cases
              which are of immediate nature during a
              specified time period.

Tables Used:  sar
Temp Tables:  sarsum, temp
Reports Used: immedsar
Forms Used:   none

```

```

*****

```

```

set null " "
set escape on
set messages off
set error messages off
clear all variables
remove sarsum
newpage
write "This program performs a statistical analysis of Search &" at 2 1
write "Rescue cases to determine the percentage of cases which " at 3 1
write "are considered to be of an immediate nature or of " at 4 1
write "immediate peril to the vessel during a specified time period" +
at 5 1
set var strtdate date
set var enddate date
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 51
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 51
    set var datediff to .enddate - .strtdate

```

```

endwhile
set error messages off
remove sarsum
newpage
project sarsum from sar using folderno immedsar sardate where sardate +
>= .strtdate and sardate <= .enddate
compute numrows as rows from sarsum
compute totsars as count folderno from sarsum where folderno exists
compute totimmed as count immedsar from sarsum where immedsar = Y
set var pctimmed real
set var pctnotim real
set var pctimmed to .totimmed / .totsars
set var notimmed to .totsars - .totimmed
set var pctnotim to .notimmed / .totsars
remove temp
*(defining temporary relation for printing)
define
attributes
tmp text 2
relations
temp with tmp
end
*(loading temporary relation with data)
load temp
"XX"
end
newpage
write "Now preparing Immediate SAR case report....." at 10 1
if numrows fails or numrows = 0 then
  newpage
  write "No records exist matching your selection criteria" +
  at 10 1
  write "Please press any key to return to menu" at 16 10
  pause
else
  output printer with immedsar.rpt
  newpage
  print immedsar
  output screen
endif
remove sarsum
remove temp
newpage
clear all variables
return
*( end )

```

## APPENDIX M

### VSLRPTS SOURCE CODE

\$COMMAND

VSL MAIN

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

VESSEL REPORTS MENU and APPLICATION PROGRAMS

Author:     Jon D. Allen, LT, USCG  
             Heidi R. Lang, LT, USN  
             AUGUST 1987

\*\*\*\*\*)

```
set error messages off
set messages off
set escape off
clear all variables
newpage
set var pick8 integer
choose pick8 from vsl_menu in vslrpts.apx
if pick8 eq 0 then
    quit to restvsl.cmd .
endif
if pick8 eq 1 then
    run VESSEL in vslrpts.apx
    quit to restvsl.cmd
endif
if pick8 eq 2 then
    run VSLOWNER in vslrpts.apx
    quit to restvsl.cmd
endif
if pick8 eq 3 then
    run VSLOPER in vslrpts.apx
    quit to restvsl.cmd
endif
if pick8 eq 4 then
    quit to restrpts.cmd
endif
quit to restvsl.cmd
return
$menu
vsl_menu
column SARELTIS --- VESSEL REPORTS
VESSEL SUMMARY LISTING
VESSEL --- OWNERS OF SPECIFIED VESSELS
VESSEL --- OPERATORS OF SPECIFIED VESSELS
RETURN TO REPORTS MENU
*( end )
```

\$COMMAND

VESSEL

\*(\*\*\*\*\*

Program:             Vessel Summary Listing Program

Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a dump of the VESSEL table. Listing entries are selected by vessel type, vessel use, and by an alphabetic search.
Tables Used:	vessel, boattype, boatuse
Temp Tables:	vs1sum, vs1sum1, vs1sum2
Reports Used:	vessel
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will dump all information on vessels "
write "which are selected based on an alphabetic search, vessel "
write "type search, and a vessel use search. "
write "The following is a list a legal codes for vessel type (they "
write "can be modified by changing/adding codes to the BOATYPE table):"
write " "
select all from boattype sorted by vtype
set var legaltyp text
set var typchoic text
set var legaltyp to no
while legaltyp eq no then
    set error messages on
    fillin typchoic using "Please enter in vessel type or [XX] for all +
types: "
    set error messages off
    if typchoic eq XX then
        set var anytype to yes
        set var legaltyp to yes
        break
    else
        set var anytype to no
    endif
    set pointer #1 n1 for boattype
    while n1 eq 0 then
        set var typetest to vtype in #1
        if typchoic eq .typetest then
            set var legaltyp to yes
            break
        endif
        next #1 n1
    endwhile
endwhile
newpage
set var usechoic text
set var legaluse to no
write "The following is a list of legal codes for vessel uses. These "
write "be modified by adding/changing the values in the BOATUSE table."
write " "
select all from boatuse sorted by vuse
set var legaluse text
set var usechoic text
set var legaluse to no
while legaluse eq no then
    set error messages on
    fillin usechoic using "Please enter vessel use or XX for all types: "
    set error messages off
    if usechoic eq XX then
        set var legaluse to yes
        set var anyuse to yes
        break
    endif
endwhile

```

```

else
    set var anyuse to no
endif
set pointer #1 n1 for boatuse
while n1 eq 0 then
    set var usetest to vuse in #1
    if usechoic eq .usetest then
        set var legaluse to yes
        break
    endif
    next #1 n1
endwhile
endwhile
newpage
write "Finally, you will be asked to enter a single letter for both +
the"
write "start and the end of an alphabetic grouping. For example, if "
write "you enter an [e] for the start and an [i] for the end, the "
write "program will only list those vessels whose names begin with the"
write "letters [e] through [i] inclusively. To select the entire +
vessel"
write "database, please enter [a] and [z] in their corresponding +
fields"
set var strtltr text
set var endltr text
set var ltrdiff to 0
set error messages on
while ltrdiff = 0 then
    fillin strtltr using "Please enter starting letter: " at 14 1
    fillin endltr using "Please enter ending letter: " at 16 1
    if endltr lt .strtltr then
        set var ltrdiff to 0
    else
        break
    endif
endwhile
set error messages off
newpage
write "You now have the option to select how you would like the +
report" at 3 1
write "to appear. It can be sorted by vessel name, vessel HIN, " +
at 4 1
write "vessel type, or vessel use." at 5 1
set var choice text
set var legalch to no
while legalch eq no then
    write "1 Sorted by vessel name" at 8 1
    write "2 Sorted by vessel HIN" at 9 1
    write "3 Sorted by vessel type" at 10 1
    write "4 Sorted by vessel use" at 11 1
    set error messages on
    fillin choice using "Please enter your choice: " at 13 1
    set error messages off
    if choice eq 1 or choice eq 2 or choice eq 3 or choice eq 4 then
        set var legalch to yes
        break
    else
        set var legalch to no
    endif
endwhile
remove vslsum1
remove vslsum2
remove vslsum
*(produces vessel listing sorted by vessel name)
if choice eq 1 then
    project vslsum1 from vessel using all sorted by vslname where +
    vslname ge .strtltr and vslname le .endltr
    if anytype eq yes then
        project vslsum2 from vslsum1 using all
    else

```

```

        project vslsum2 from vslsum1 using all where vsltype eq .typchoic
    endif
    if anyuse eq yes then
        project vslsum from vslsum2 using all
    else
        project vslsum from vslsum2 using all where vsluse eq .usechoic
    endif
endif
    *(produces vessel listing sorted by vessel HIM)
if choice eq 2 then
    project vslsum1 from vessel using all sorted by vslhin where +
    vslname ge .strtltr and vslname le .endltr
    if anytype eq yes then
        project vslsum2 from vslsum1 using all
    else
        project vslsum2 from vslsum1 using all where vsltype eq .typchoic
    endif
    if anyuse eq yes then
        project vslsum from vslsum2 using all
    else
        project vslsum from vslsum2 using all where vsluse eq .usechoic
    endif
endif
    *(produces vessel listing sorted by vessel type)
if choice eq 3 then
    project vslsum1 from vessel using all where vslname ge .strtltr and +
    vslname le .endltr
    if anytype eq yes then
        project vslsum2 from vslsum1 using all sorted by vsltype
    else
        project vslsum2 from vslsum1 using all sorted by vsltype where +
        vsltype eq .typchoic
    endif
    if anyuse eq yes then
        project vslsum from vslsum2 using all
    else
        project vslsum from vslsum2 using all where vsluse eq .usechoic
    endif
endif
    *(produces vessel listing sorted by vessel use)
if choice eq 4 then
    project vslsum1 from vessel using all where vslname ge .strtltr and +
    vslname le .endltr
    if anytype eq yes then
        project vslsum2 from vslsum1 using all
    else
        project vslsum2 from vslsum1 using all where vsltype eq .typchoic
    endif
    if anyuse eq yes then
        project vslsum from vslsum2 using all sorted by vsluse
    else
        project vslsum from vslsum2 using all sorted by vsluse where +
        vsluse eq .usechoic
    endif
endif
compute numrows as rows from vslsum
if numrows fails or numrows = 0 then
    write "No records match selection criteria" at 10 10
    write "Please press any key to continue" at 16 10
    pause
else
    output printer with vessel.rpt
    newpage
    print vessel
    output screen
endif
remove vslsum
remove vslsum1
remove vslsum2
newpage

```

```
clear all variables
return
*( end )
```

```
$COMMAND
VSLOWNER
```

```
*(*****)
```

```
Program:          Vessel - Owner Dump Program
Author:           J D Allen and H R Lang
Date Written:     August 1987
Description:      This program performs a listing sorted by
                  vessel name of those vessels which are
                  owned by a specified group of owners. All
                  of the vessels in the VESSEL table may be
                  selected or only a group specified in an
                  alphabetic search.

Tables Used:      owvsl, owners, vessel
Temp Tables:      ownvsls, ownvsls1, ownvsls2
Reports Used:     vslowner
Forms Used:       none
```

```
*****)
```

```
set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will prepare a listing of owners which" at 3 1
write "own by a specified group of vessels. This report can" at 4 1
write "provide a listing of all owners and their vessels by" at 5 1
write "responding [y] to the following question....." at 6 1
write "Do you wish a complete listing of all owners and their" at 9 1
write "vessels contained in the system?" at 10 1
set var allrecs text
set error messages on
fillin allrecs using " " at 10 40
set error messages off
remove ownvsls
remove ownvsls1
remove ownvsls2
newpage
if allrecs contains "y" then
  join owners using ownid with owvsl using idowner forming ownvsls1
  join ownvsls1 using vhinown with vessel using vslhin forming +
  ownvsls2
  project ownvsls from ownvsls2 using ownlname ownfname ownmi owndob +
  ownaddr owncity ownstate ownzip owntelno vslname vslhin sorted by +
  vslname
else
  newpage
  set var strtltr text
  set var endltr text
  set var ltrdiff to 0
  set error messages on
  while ltrdiff = 0 then
    write "Enter starting letter(s) to start search:" at 5 1
    fillin strtltr using " " at 5 45
    write "Enter ending letter(s) to end search:" at 7 1
    fillin endltr using " " at 7 45
    if endltr lt .strtltr then
      set var ltrdiff to 0
    else
      break
  endif
endif
```



```

endwhile
set error messages off
join owners using ownid with owvsl using idowner forming ownvsls1
join ownvsls1 using vhinown with vessel using vslhin forming +
ownvsls2
project ownvsls from ownvsls2 using ownlname ownfname ownmi owndob +
ownaddr owncity ownstate ownzip ownelno vslname vslhin sorted by +
vslname where vslname ge .strtltr and vslname le .endltr
endif
remove ownvsls1
remove ownvsls2
newpage
compute numrows as rows from ownvsls
if numrows fails or numrows = 0 then
write "No records match selection criteria" at 10 10
write "Please press any key to continue" at 16 10
pause
else
output printer with vsllowner.rpt
newpage
print vsllowner
output screen
endif
remove ownvsls
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## VSLOPER

```

*(*****

```

Program:	Vessel - Operator Dump Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a listing sorted by vessel name of those vessels which are operated by a specified group of operators. The entire list of vessels may be printed or a specified group based on an alphabetic search.
Tables Used:	opvsl, operator, vessel
Temp Tables:	opervsls, opvsls1, opvsls2
Reports Used:	vsloper
Forms Used:	none

```

*****

```

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will prepare a listing of operators which" at 3 1
write "operate a specified group of vessels. This report can" at 4 1
write "provide a listing of all operators and their vessels by" at 5 1
write "responding [y] to the following question....." at 6 1
write "Do you wish a complete listing of all operators and their" +
at 9 1
write "vessels contained in the system?" at 10 1
set var allrecs text
set error messages on
fillin allrecs using " " at 10 40
set error messages off
remove opervsls

```

```

remove opvsls1
remove opvsls2
newpage
if allrecs contains "y" then
  join operator using opid with opvsl using idoper forming opvsls1
  join opvsls1 using vhinoper with vessel using vslhin forming opvsls2
  project opervsls from opvsls2 using oplname opfname opmi opdob +
  opaddr opcity opstate opzip optelno vslname vslhin sorted by vslname
else
  newpage
  set var strtltr text
  set var endltr text
  set var ltrdiff to 0
  set error messages on
  while ltrdiff = 0 then
    write "Enter starting letter(s) to start search:" at 5 1
    fillin strtltr using " " at 5 45
    write "Enter ending letter(s) to end search:" at 7 1
    fillin endltr using " " at 7 45
    if endltr lt .strtltr then
      set var ltrdiff to 0
    else
      break
    endif
  endwhile
  set error messages off
  join operator using opid with opvsl using idoper forming opvsls1
  join opvsls1 using vhinoper with vessel using vslhin forming opvsls2
  project opervsls from opvsls2 using oplname opfname opmi opdob +
  opaddr opcity opzip opstate optelno vslname vslhin sorted by +
  vslname where vslname ge .strtltr and vslname le .endltr
endif
compute numrows as rows from opervsls
remove opvsls1
remove opvsls2
newpage
if numrows fails or numrows = 0 then
  write "No records match selection criteria" at 10 10
  write "Please press any key to continue" at 16 10
  pause
else
  output printer with vsloper.rpt
  newpage
  print vsloper
  output screen
endif
remove opvsls
newpage
clear all variables
return
*( end )

```

## APPENDIX N

### PRSRPTS SOURCE CODE

```

$COMMAND
PRS MAIN
*(*****
                                US COAST GUARD GROUP MONTEREY
                                SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
                                INTELLIGENCE SYSTEM (SARELTIS)

                                PERSONNEL REPORTS MENU and APPLICATION PROGRAMS

                                Author:   Jon D. Allen, LT, USCG
                                           Heidi R. Lang, LT, USN
                                           AUGUST 1987

*****)

set error messages off
set messages off
set escape off
clear all variables
newpage
set var pick9 integer
choose pick9 from prs_menu in prsrpts.apx
if pick9 eq 0 then
    quit to restprs.cmd
endif
if pick9 eq 1 then
    run OWNERS in prsrpts.apx
    quit to restprs.cmd
endif
if pick9 eq 2 then
    run OWNVSL in prsrpts.apx
    quit to restprs.cmd
endif
if pick9 eq 3 then
    run OPERATOR in prsrpts.apx
    quit to restprs.cmd
endif
if pick9 eq 4 then
    run OPERVSL in prsrpts.apx
    quit to restprs.cmd
endif
if pick9 eq 5 then
    quit to restrpts.cmd
endif
quit to restprs.cmd
return
$menu
prs_menu
column SARELTIS --- PERSONNEL REPORTS
OWNERS OF VESSELS SUMMARY LISTING
OWNER --- VESSELS WHICH ARE OWNED BY SPECIFIED OWNERS
OPERATORS OF VESSELS SUMMARY LISTING
OPERATORS --- VESSELS WHICH ARE OPERATED BY SPECIFIED OPERATORS
RETURN TO REPORTS MENU
*( end )

```

# \$COMMAND

## OWNERS

\*(\*\*\*\*\*)

Program: Vessel Owners Table Dump  
Author: J D Allen and H R Lang  
Date Written: August 1987  
Description: This program prints a sorted listing of vessel owners contained in the database based on the owner's last name and date of birth.  
  
Tables Used: owners  
Temp Tables: ownsum1, ownsum2  
Reports Used: owners  
Forms Used: none

\*\*\*\*\*)

```
set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will dump all information on owners in the +
database" at 3 1
write "which are selected based on date of birth. If you wish to +
print" at 4 1
write "out the entire list of owners, enter the date [01/01/1900] +
for " at 5 1
write "the starting date and todays date for the ending date." at 6 1
set var datediff to 0
set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 53
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
newpage
write "Since this listing can be very long, you have the option of +
only" at 3 1
write "printing a selected alphabetical grouping of owners. You will +
be" at 4 1
write "asked to enter a single letter for the both the start and end +
of" at 5 1
write "an alphabetic grouping. For example, if you enter in an [e] +
for" at 6 1
write "start and an [i] for the end, the program will provide a +
listing" at 7 1
write "of only those owners whose last names begin with the letters " +
at 8 1
write "[e] through [i]. To select the entire owner database, +
please" at 9 1
write "enter [a] and [z] in their corresponding fields....." +
at 10 1
set var strtltr text
set var endltr text
set var ltrdiff to 0
set error messages on
while ltrdiff = 0 then
    fillin strtltr using "Please enter starting letter: " at 14 1
    fillin endltr using "Please enter ending letter: " at 16 1
    if endltr lt .strtltr then
        set var ltrdiff to 0
    else
        break
```

```

endif
endwhile
set error messages off
remove ownsum1
remove ownsum2
newpage
project ownsum1 from owners using all sorted by ownlname where +
owndob >= .strtdate and owndob <= .enddate
project ownsum2 from ownsum1 using all where ownlname ge .strtltr and +
ownlname le .endltr
compute numrows as rows from ownsum2
newpage
write "Processing of statistical information completed." at 10 1
write "Now preparing report....." at 11 1
if numrows fails or numrows = 0 then
    write "No records match selection criteria" at 10 10
    write "Please press any key to continue" at 16 10
    pause
else
    output printer with owners.rpt
    newpage
    print owners
    newpage
    output screen
endif
remove ownsum1
remove ownsum2
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## OPERATOR

```

*(*****

```

```

Program:      Vessel Operator Listing
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a listing of operators
              of vessels contained in the table OPERATOR.
              They are selected by date of birth and by
              the first letter of the last name. The
              listing is sorted alphabetically before
              being printed.

Tables Used:  operator
Temp Tables:  opsum1, opsum2
Reports Used: operator
Forms Used:   none

```

```

*****

```

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will dump all information on operators " at 3 1
write "which are selected based on date of birth. If you wish to +
print" at 4 1
write "out the entire list of operators, enter the date [01/01/1900] +
for" at 5 1
write "the starting date and todays date for the ending date." at 6 1
set var strtdate date
set var enddate date
set var datediff to 0

```

```

set error messages on
while datediff <= 0 then
    write "Please enter starting date in the form MM/DD/YYYY:" at 8 1
    fillin strtdate using " " at 8 53
    write "Please enter ending date in the form MM/DD/YYYY:" at 10 1
    fillin enddate using " " at 10 53
    set var datediff to .enddate - .strtdate
endwhile
set error messages off
newpage
write "Since this listing can be very long, you have the option of +
only" at 3 1
write "printing a selected grouping of operators. You will be" at 4 1
write "asked to enter a single letter for the both the start and end +
of " at 5 1
write "an alphabetic grouping. For example, if you enter in an [e] +
for" at 6 1
write "start and an [i] for the end, the program will provide a +
listing" at 7 1
write "of only those operators whose last names begin with the +
letters " at 8 1
write "[e] through [i]. To select the entire operator database, +
please" at 9 1
write "enter [a] and [z] in their corresponding fields....." +
at 10 1
set var strtltr text
set var endltr text
set var ltrdiff to 0
set error messages on
while ltrdiff = 0 then
    fillin strtltr using "Please enter starting letter: " at 14 1
    fillin endltr using "Please enter ending letter: " at 16 1
    if endltr lt .strtltr then
        set var ltrdiff to 0
    else
        break
    endif
endwhile
set error messages off
remove opsum1
remove opsum2
newpage
project opsum1 from operator using all sorted by oplname where +
opdob >= .strtdate and opdob <= .enddate
project opsum2 from opsum1 using all where oplname ge .strtltr and +
oplname le .endltr
compute numrows as rows from opsum2
write "Processing of statistical information completed." at 10 1
write "Now preparing report....." at 11 1
if numrows fails or numrows = 0 then
    write "No records match selection criteria" at 10 10
    write "Please press any key to continue" at 16 10
    pause
else
    output printer with operator.rpt
    newpage
    print operator
    output screen
endif
remove opsum1
remove opsum2
newpage
clear all variables
return
*( end )

```

\$COMMAND  
OPERSVLS

\*(\*\*\*\*\*)

Program:	Operator - Vessel Program
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program performs a listing sorted by operator last name of those vessels which are used by specified operators. Operators may be selected by an alphabetic search or may be selected in their entirety.
Tables Used:	opvsl, operator, vessel
Temp Tables:	opvsls, opvsls1, opvsls2
Reports Used:	opervsls
Forms Used:	none

\*\*\*\*\*)

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will prepare a listing of vessels which are" at 3 1
write "operated by a selected group of operators. This report can" +
at 4 1
write "provide a listing of all operators and their vessels by" at 5 1
write "responding [y] to the following question....." at 6 1
write "Do you wish a complete listing of all operators and their" +
at 9 1
write "vessels contained in the system?" at 10 1
set var allrecs text
set error messages on
fillin allrecs using " " at 10 40
set error messages off
remove opervsls
remove opvsls1
remove opvsls2
if allrecs = "y" then
    join operator using opid with opvsl using idoper forming opvsls1
    join opvsls1 using vhinoper with vessel using vslhin forming opvsls2
    project opervsls from opvsls2 using oplname opfname opmi opdob +
    opaddr opcity opstate opzip optelno vslname vslhin sorted by oplname
else
    newpage
    set var strtltr text
    set var endltr text
    set var ltrdiff to 0
    set error messages on
    while ltrdiff = 0 then
        write "Enter starting letter(s) to start search:" at 5 1
        fillin strtltr using " " at 5 45
        write "Enter ending letter(s) to end search:" at 7 1
        fillin endltr using " " at 7 45
        if endltr lt .strtltr then
            set var ltrdiff to 0
        else
            break
        endif
    endwhile
    set error messages off
    join operator using opid with opvsl using idoper forming opvsls1
    join opvsls1 using vhinoper with vessel using vslhin forming opvsls2
    project opervsls from opvsls2 using oplname opfname opmi opdob +
    opaddr opcity opstate opzip optelno vslname vslhin sorted by +
    oplname where oplname ge .strtltr and oplname le .endltr
endif
compute numrows as rows from opervsls
remove opvsls1

```

```

remove opvsls2
newpage
if numrows fails or numrows = 0 then
  write "No records match selection criteria" at 10 10
  write "Please press any key to continue" at 16 10
  pause
else
  output printer with opervsls.rpt
  newpage
  print opervsls
  output screen
endif
remove opervsls
newpage
clear all variables
return
*( end )

```

# \$COMMAND

## OWNVSL

```

*(*****

```

```

Program:      Owner - Vessel Dump Program
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program performs a listing sorted by
              owner last name of those owners which own
              specific vessels. Owners may be selected
              in their entirety or may be selected by
              an alphabetic search.
Tables Used:  owvsl, owners, vessel
Temp Tables:  ownvsls, ownvsls1, ownvsls2
Reports Used: ownvsls
Forms Used:   none

```

```

*****

```

```

set null " "
set error messages off
set messages off
set escape on
newpage
clear all variables
write "This program will prepare a listing of vessels which are" at 3 1
write "owned by a selected group of owners. This report can" at 4 1
write "provide a listing of all owners and their vessels by" at 5 1
write "responding [y] to the following question....." at 6 1
write "Do you wish a complete listing of all owners and their" at 9 1
write "vessels contained in the system?" at 10 1
set var allrecs text
set error messages on
fillin allrecs using " " at 10 40
set error messages off
remove ownvsls
remove ownvsls1
remove ownvsls2
newpage
if allrecs contains "y" then
  join owners using ownid with owvsl using idowner forming ownvsls1
  join ownvsls1 using vhinown with vessel using vslhin forming +
  ownvsls2
  project ownvsls from ownvsls2 using own.name ownfname ownmi owndob +
  ownaddr owncity ownstate ownzip owntelno vslname vslhin sorted by +
  ownlname
else
  newpage
  set var strtltr text

```



```

set var endltr text
set var ltrdiff to 0
set error messages on
while ltrdiff = 0 then
    write "Enter starting letter(s) to begin search" at 5 1
    fillin strtltr using " " at 5 45
    write "Enter ending letter(s) to end search:" at 7 1
    fillin endltr using " " at 7 45
    if endltr lt .strtltr then
        set var ltrdiff to 0
    else
        break
    endif
endwhile
set error messages off
join owners using ownid with ownvsl using idowner forming ownvsls1
join ownvsls1 using vhinown with vessel using vsihin forming +
ownvsls2
project ownvsls from ownvsls2 using ownlname ownfname ownmi owndob +
ownaddr owncity ownstate ownzip owntelno vsiname vsihin sorted by +
ownlname where ownlname ge .strtltr and ownlname le .endltr
endif
compute numrows as rows from ownvsls
if numrows fails or numrows = 0 then
    write "No records match selection criteria" at 10 10
    write "Please press any key to continue" at 16 10
    pause
else
    output printer with ownvsls.rpt
    newpage
    print ownvsls
    output screen
endif
remove ownvsls
remove ownvsls1
remove ownvsls2
newpage
clear all variables
return
*( end )

```

# APPENDIX O

## SQUERY SOURCE CODE

\$COMMAND

QRYMAIN

\*(\*\*\*\*\*

US COAST GUARD GROUP MONTEREY  
SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES  
INTELLIGENCE SYSTEM (SARELTIS)

QUERY MENU and APPLICATION PROGRAMS

Author: Jon D. Allen, LT, USCG  
Heidi R. Lang, LT, USN  
AUGUST 1987

\*\*\*\*\*)

```
set messages off
set escape off
newpage
clear all variables
set var pick10 integer
newpage
choose pick10 from qry_menu in squery.apx
if pick10 eq 0 then
  quit to restqry.cmd
endif
if pick10 eq 1 then
  run quer_vsl in squery.apx
  quit to restqry.cmd
endif
if pick10 eq 2 then
  run quer_per in squery.apx
  quit to restqry.cmd
endif
if pick10 eq 3 then
  quit to restmain.cmd
endif
quit to restqry.cmd
return
$menu
qry_menu
column SARELTIS --- QUERY MENU
VESSEL QUERY
PERSONNEL QUERY
RETURN TO MAIN MENU
*( end )
```

\$COMMAND

QUER\_VSL

\*(\*\*\*\*\*

Program:	Query Vessel
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program searches database for all information concerning a particular vessel.
Tables Used:	vessel, sar, boarding, owner, operator,

Temp Tables:	owvsl, opvsl, vslintel, perintel
Reports Used:	temp, vslint, perint, bohis, sarhis
	vslqprn, boqprn, sarqprn, owqprn, opqprn,
	pintqprn, vintqprn
Forms Used:	vslquery, brdquery, sarquery, ownquery,
	opquery, pintquer, vintquer

\*\*\*\*\*)

```

set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ..... " +
at 10 10
clear all variables
set null " "
set var more to Y
remove temp *(relation for print purposes only)
define
attributes
tmp text 2
relations
tmp with tmp
end
load temp
"XX"
end
while more eq Y then *(main loop)
  set var vvslname text
  set var choice to 0
  while choice lt 1 or choice gt 6 then
    newpage
    write "Search Option Menu" at 5 15
    write "-----" at 6 15
    write "1. Search by HIN" at 8 15
    write "2. Search by Vessel Name" at 9 15
    write "3. Search by Vessel Number" at 10 15
    write "4. Search by Vessel Official Number" at 11 15
    write "5. Search Only Vessel Intelligence File by Vessel Name" +
at 12 15
    write "6. Quit" at 13 15
    write "Enter Choice: " at 15 20
    fillin choice using " " at 15 33
  endwhile
  if choice eq 2 then *(search by vessel name)
    set var chk-name to Y
    while chk-name eq Y then
      newpage
      write "Enter name of desired vessel: " at 10 10
      fillin vvslname using " " at 10 39
      while vvslname exists then
        set pointer #1 el for vessel where vslname eq .vvslname
        newpage
        if el eq 0 then
          sel vslname vslhin vslmake vslmodel vsltype vslllenft from +
          vessel where vslname eq .vvslname
          write " "
          write "End of data for this vessel name"
          write " "
          write "Press any key to continue"
          pause
        else
          write "This vessel name does not exist in the database" +
at 10 10
          write "Press any key to continue" at 15 15
          pause
          set var choice to 0
        endif
        set var chk-name to N
      endwhile
    endwhile
  endif
endwhile

```

```

        break
    endwhile
endwhile
endif
if choice eq 3 then *(search by vessel number)
    set var chk-no to Y
    while chk-no eq Y then
        newpage
        write "Enter number of desired vessel: " at 10 10
        fillin vvsln no using " " at 10 41
        while vvsln no exists then
            set pointer #1 el for vessel where vsln no eq .vvsln no
            newpage
            if el eq 0 then
                set var vvsln name to vsln name in #1
                sel vsln name vsln hin vsln make vsln model vsln type vsln len ft from +
                vessel where vsln no eq .vvsln no
                write " "
                write "End of data for this vessel number"
                write " "
                write "Press any key to continue"
                pause
            else
                write "This vessel number does not exist in the database" +
at 10 10 write "Press any key to continue" at 15 15
                pause
                set var choice to 0
            endif
            set var chk-no to N
            break
        endwhile
    endwhile
endif
if choice eq 4 then *(search by vessel official number)
    set var chkoffno to Y
    while chkoffno eq Y then
        newpage
        write "Enter official number of desired vessel: " at 10 10
        fillin voffno using " " at 10 50
        while voffno exists then
            set pointer #1 el for vessel where vsloffno eq .voffno
            newpage
            if el eq 0 then
                set var vvsln name to vsln name in #1
                sel vsln name vsln hin vsln make vsln model vsln type vsln len ft from +
                vessel where vsloffno eq .voffno
                write " "
                write "End of data for this vessel official number"
                write " "
                write "Press any key to continue"
                pause
            else
                write "This official number does not exist in the database" +
at 10 10 write "Press any key to continue" at 15 15
                pause
                set var choice to 0
            endif
            set var chkoffno to N
            break
        endwhile
    endwhile
endif
if choice ne 5 and choice ne 6 and choice ne 0 then *(search by HIN)
    set var menu to N
    set var chk-hin to Y
    while chk-hin eq Y then
        newpage
        if vvsln name exists then

```

```

set var vlname to .vvslname
set var nameok to N
while nameok eq N then
  newpage
  set pointer #3 e3 for vessel where vslname eq .vlname
  while e3 eq 0 then
    newpage
    set var vvslname to vslname in #3
    set var vvslnhin to vslnhin in #3
    draw hinquery with all at 1
    write "Press [ENTER] to advance to next hin, [PGDN] to +
use displayed data," at 22 5
    write "or [ESC] to return to menu" at 23 5
    edit var vvslnhin return esc enter pgdn
    if #return eq enter then
      next #3 e3
    endif
    if #return eq pgdn then
      set var nameok to Y
      break
    endif
    if #return eq esc then
      set var nameok to Y
      set var menu to Y
      break
    endif
  endwhile
endwhile
if menu eq Y then
  set var choice to 0
  break
endif
else
  set var vvslnhin text
  write "Enter HIN of desired vessel: " at 10 10
  write "(or enter xxx to go back to menu)" at 12 10
  fillin vvslnhin using " " at 10 38
  if vvslnhin exists and vvslnhin eq xxx then
    set var choice to 0
    break
  endif
endif
while vvslnhin exists then
  set pointer #1 e1 for vessel where vslnhin = .vvslnhin
  newpage
  if e1 eq 0 then
    *(vessel exists in database)
    set var vvslnno to v. 'no in #1
    set var vvslnname to vslnname in #1
    set var vvslnmake to vslnmake in #1
    set var vvslnmod to vslnmodel in #1
    set var vvslnyear to vslnyear in #1
    set var vvslnlon to vslnlon in #1
    set var vvslnft to vsllenft in #1
    set var vvslnin to vsllenin in #1
    set var vvslnhp to vslnhp in #1
    set var vvslnuse to vslnuse in #1
    set var vusedscr to vusedesc in boatuse where vuse eq +
.vvslnuse
    set var vvslnstyp to vslnstyp in #1
    set var vtypdscr to vtypedes in boattyp where vtype eq +
.vvslnstyp
    set var vvslnprop to vslnprop in #1
    set var vpropdsc to propdesc in boatprop where proptype eq +
.vvslnprop
    set var vvslnhull to vslnhull in #1
    set var vhulldsc to hmatdesc in hullmat where hmattype eq +
.vvslnhull
    set var vvslnleng to vslnleng in #1
    set var vengdsc to ecompdes in engcomp where ecomptyp eq +

```

```

.vvsleng
set var vvselfuel to vselfuel in #1
set var vfueldes to fcompdes in fuelcomp where fcomptyp eq +
.vvselfuel
set var vconstr to vslconst in #1
set var vcondesc to consdesc in constr where constype eq +
.vconstr
set var vdecad to cmedecad in #1
set var vcmeyear to cmeyear in #1
set var voffno to vsloffno in #1
set var vhome to homeport in #1
set var vcall to vslcall in #1
set var vvalue to vslvalue in #1
set var vsuper to vslsuper in #1
set var vmasts to vslmasts in #1
set var vsailno to sailno in #1
set var vhlcolor to hlcolor in #1
set var vtrcolor to trcolor in #1
set var vslcolor to slcolor in #1
set var vcbcolor to cbcolor in #1
set var vdkcolor to dkcolor in #1
set var vmarks to vslmarks in #1
newpage
draw vslquery with all at 1.
set var vslprn to A
while vslprn ne P and vslprn ne C and vslprn ne M then
  write "Enter P to print vessel data, C to continue or M +
for main menu: " at 23 5
  fillin vslprn using " " at 23 68
  if vslprn eq P then
    output printer
    newpage
    print vslprn
    output screen
  endif
  if vslprn eq M then
    set var menu to Y
    set var chk-hin to N
    break
  endif
endif
endwhile
if menu eq Y then
  set var choice to 0
  break
endif
set pointer #2 e2 for vslintel where intname eq .vvslname
set var count to 1
if e2 eq 0 then
  newpage
  write "US Coast Guard Group Monterey Intelligence History" +
  at 1 10
  write "-----+
-----" at 2 1
else
  newpage
  write "There is no intelligence for this vessel name" +
  at 10 10
  write "Press any key to continue" at 23 10
  pause
  newpage
endif
while e2 eq 0 then
  set var vintdate to intdate in #2
  set var vepic to epiccode in #2
  set var vstolen to stolen in #2
  set var vvrem1 to vremark1 in #2
  set var vvrem2 to vremark2 in #2
  set var vvrem3 to vremark3 in #2
  if count eq 1 then
    draw vintquer with all at 3

```

```

endif
if count eq 2 then
    draw vintquer with all at 9
endif
if count eq 3 then
    draw vintquer with all at 15
    write "Press any key to continue" at 23 10
    pause
    newpage
endif
set var count to .count + 1
if count eq 4 then
    set var count to 1
endif
next #2 e2
endwhile
set pointer #2 e2 for vslintel where intvname eq .vvslname
if e2 eq 0 then
    write "Print vessel intelligence information? (Y)" at 23 10
    fillin vintprn using "(" at 23 49
    if vintprn fails or vintprn eq Y then
        newpage
        write "Preparing report, please stand by ....." +
            at 10 10
        remove vslint
        project vslint from vslintel using all sorted by intdate +
            where intvname eq .vvslname
        output printer
        newpage
        print vintqprn
        output screen
        remove vslint
    endif
endif
set pointer #2 e2 for boarding where bovhin eq .vvslnhin
while e2 eq 0 then
    set var vbodate to bodate in #2
    set var vbotime to botime in #2
    set var vbono to bono in #2
    set var vvslopob to vslopob in #2
    set var vbolat to obslat in #2
    set var vbolong to obslong in #2
    set var vviol54 to viol54 in #2
    set var vviol55 to viol55 in #2
    set var vviol56 to viol56 in #2
    set var vviol57 to viol57 in #2
    set var vviol58 to viol58 in #2
    set var vviol59 to viol59 in #2
    set var vviol60 to viol60 in #2
    set var vviol61 to viol61 in #2
    set var vviol62 to viol62 in #2
    set var vviol63 to viol63 in #2
    set var vviol64 to viol64 in #2
    set var vviol65 to viol65 in #2
    set var vviol66 to viol66 in #2
    set var vviol67 to viol67 in #2
    set var vviol68 to viol68 in #2
    set var vuns69 to uns69 in #2
    set var vuns70 to uns70 in #2
    set var vuns71 to uns71 in #2
    set var vuns72 to uns72 in #2
    set var vuns73 to uns73 in #2
    set var vuns74 to uns74 in #2
    set var vuns75 to uns75 in #2
    set var vuns76 to uns76 in #2
    set var vuns77 to uns77 in #2
    set var vuns78 to uns78 in #2
    set var vuns79 to uns79 in #2
    set var vborem1 to boreml in #2
    set var vborem2 to boreml in #2

```

```

set var vborem3 to borem3 in #2
set var vbname to boname in #2
set var vborate to borate in #2
set var vweapons to weapons in #2
set var valc to uns76 in #2
newpage
write "US Coast Guard Group Monterey Boarding History" +
at 1 10
write "-----" at 2 1
draw brdquery with all at 3
write "Press any key to continue" at 23 10
pause
next #2 e2
endwhile
set pointer #2 e2 for boarding where bovhin eq .vvslnhin
if e2 eq 0 then
write "Print boarding history? (Y)" at 23 10
fillin bohisprn using "(" at 23 34
if bohisprn fails or bohisprn eq Y then
newpage
write "Preparing report, please stand by ...." +
at 10 10
remove bohis
project bohis from boarding using bodate botime bono +
vslpob obslat obslong viol54 viol55 viol56 viol57 viol58 +
viol59 viol60 viol61 viol62 viol63 viol64 viol65 viol66 +
viol67 viol68 uns69 uns70 uns71 uns72 uns73 uns74 uns75 +
uns76 uns77 uns78 uns79 boreml boreml2 boreml3 boname +
borate weapons bovhin sorted by bodate where +
bovhin eq .vvslnhin
output printer
newpage
print boqprn
output screen
remove bohis
endif
endif
if e2 ne 0 then
newpage
write "There are no boarding cases for this vessel" +
at 10 10
write "Press any key to continue" at 20 10
pause
endif
set pointer #2 e2 for sar where sarvhin eq .vvslnhin
set var count to 1
if e2 eq 0 then
newpage
write "US Coast Guard Group Monterey Sar History" at 1 10
write "-----" at 2 1
endif
while e2 eq 0 then
set var vfoldno to folderno in #2
set var vucn to ucn in #2
set var vmucn to mucn in #2
set var vsardate to sardate in #2
set var vsarday to sarday in #2
set var vsartime to sartime in #2
set var vsarnod to sarnod in #2
set var vsarpob to sarpob in #2
set var vsarlat to sarlat in #2
set var vsarlong to sarlong in #2
set var vdistoff to offshore in #2
set var vimmed to immedsar in #2
if count eq 1 then
draw sarquery with all at 3
endif
if count eq 2 then

```



```

        draw sarquery with all at 9
    endif
    if count eq 3 then
        draw sarquery with all at 15
        write "Press any key to continue" at 23 10
        pause
        newpage
    endif
    set var count to .count + 1
    if count eq 4 then
        set var count to 1
    endif
    next #2 e2
endwhile
set pointer #2 e2 for sar where sarvhin eq .vvslnhin
if e2 eq 0 then
    write "Print sar history? (Y)" at 23 10
    fillin sarhsprn using "(" at 23 29
    if sarhsprn fails or sarhsprn eq Y then
        newpage
        write "Preparing report, please stand by ....." +
            at 10 10
        remove sarhis
        project sarhis from sar using folder no ucn much sardate +
        sartime sarnod sarpob sarlat sarlong offshore immedsar +
        sarvhin sorted by sardate where sarvhin eq .vvslnhin
        output printer
        newpage
        print sarqprn
        output screen
        remove sarhis
    endif
endif
if e2 ne 0 then
    newpage
    write "There are no sar cases for this vessel" at 10 10
    write "Press any key to continue" at 20 10
    pause
endif
set pointer #2 e2 for owvsl where vhinown eq .vvslnhin
newpage
while e2 eq 0 then
    set var vowlid to idowner in #2
    set pointer #3 e3 for owners where ownid eq .vowlid
    set var vowlname to ownlname in #3
    set var vowfname to ownfname in #3
    set var vowmi to ownmi in #3
    set var vowaddr to ownaddr in #3
    set var vowcity to owncity in #3
    set var vowst to ownstate in #3
    set var vowzip to ownzip in #3
    set var vowntelno to owntelno in #3
    set var vowdob to owndob in #3
    newpage
    draw ownquery with all
    write "Press any key to continue" at 23 10
    pause
    set pointer #1 e1 for perintel where intlname eq .vowlname
    set var count to 1
    if e1 eq 0 then
        newpage
        write "US Coast Guard Group Monterey Intelligence +
History" at 1 10
        write "-----" +
            at 2 1
    else
        newpage
        write "There is no intelligence for this owner" at 10 10
    endif
    while e1 eq 0 then

```

```

set var vlname to intlname in #1
set var vfname to intfname in #1
set var vmi to intmi in #1
set var vdob to intdob in #1
set var vrem1 to pintrem1 in #1
set var vrem2 to pintrem2 in #1
set var vrem3 to pintrem3 in #1
set var vdate to pintdate in #1
if count eq 1 then
    draw pintquer with all at 3
endif
if count eq 2 then
    draw pintquer with all at 9
endif
if count eq 3 then
    draw pintquer with all at 15
    write "Press any key to continue" " +
    at 23 10
    pause
    newpage
endif
set var count to .count + 1
if count eq 4 then
    set var count to 1
endif
next #1 e1
endwhile
write "Press any key to continue" " +
at 23 10
pause
next #2 e2
endwhile
write "Print owners and owner intelligence? (Y)" at 23 10
fillin owhisprn using "(" at 23 47
if owhisprn fails or owhisprn eq Y then
    newpage
    write "Preparing report, please stand by ....." at 10 10
    set pointer #2 e2 for owvsl where vhinown eq .vvsllhin
    while e2 eq 0 then
        set var vovid to idowner in #2
        set pointer #3 e3 for owners where ownid eq .vovid
        set var vowelname to ownlname in #3
        set var vowelname to ownfname in #3
        set var vovmi to ownmi in #3
        set var vovaddr to ownaddr in #3
        set var vovcity to owncity in #3
        set var vovst to ownstate in #3
        set var vovzip to ownzip in #3
        set var vovtelno to owntelno in #3
        set var vovdob to owndob in #3
        output printer
        newpage
        print owqprn
        output screen
        remove perint
        project perint from perintel using all sorted by +
        pintdate where intlname eq .vowelname
        output printer
        newpage
        print pintqprn
        output screen
    next #2 e2
endwhile
remove perint
endif
set pointer #2 e2 for opvsl where vhinoper eq .vvsllhin
newpage
while e2 eq 0 then
    set var vopid to idoper in #2
    set pointer #3 e3 for operator where opid eq .vopid

```

```

set var voplname to oplname in #3
set var vopfname to opfname in #3
set var vopmi to opmi in #3
set var vopaddr to opaddr in #3
set var vopcity to opcity in #3
set var vopst to opstate in #3
set var vopzip to opzip in #3
set var voptelno to optelno in #3
set var vopdob to opdob in #3
set var vopcrse to opcourse in #3
newpage
draw opquery with all
write "Press any key to continue" at 23 10
pause
set pointer #1 e1 for perintel where intlname eq .voplname
set var count to 1
if e1 eq 0 then
    newpage
    write "US Coast Guard Group Monterey Intelligence +
    History" at 1 10
    write "-----" at 2 1
else
    newpage
    write "There is no intelligence for this operator" +
    at 10 10
endif
while e1 eq 0 then
    set var vlname to intlname in #1
    set var vfname to intfname in #1
    set var vmi to intmi in #1
    set var vdob to intdob in #1
    set var vrem1 to pintrem1 in #1
    set var vrem2 to pintrem2 in #1
    set var vrem3 to pintrem3 in #1
    set var vdate to pintdate in #1
    if count eq 1 then
        draw pintquer with all at 3
    endif
    if count eq 2 then
        draw pintquer with all at 9
    endif
    if count eq 3 then
        draw pintquer with all at 15
        write "Press any key to continue" at 23 10
        pause
        newpage
    endif
    set var count to .count + 1
    if count eq 4 then
        set var count to 1
    endif
    next #1 e1
endwhile
write "Press any key to continue" at 23 10
pause
next #2 e2
endwhile
write "Print operators and operator intelligence? (Y)" +
at 23 10
fillin ophisprn using "(" at 23 53
if ophisprn fails or ophisprn eq Y then
    newpage
    write "Preparing report, please stand by ....." at 10 10
    set pointer #2 e2 for opvsl where vhinoper eq .vvslnhin
    while e2 eq 0 then
        set var vopid to idoper in #2
        set pointer #3 e3 for operator where opid eq .vopid
        set var voplname to oplname in #3
        set var vopfname to opfname in #3

```

```

        set var vopmi to opmi in #3
        set var vopaddr to opaddr in #3
        set var vopcity to opcity in #3
        set var vopst to opstate in #3
        set var vopzip to opzip in #3
        set var voptelno to optelno in #3
        set var vopdob to opdob in #3
        set var vopcrse to opcourse in #3
        output printer
        newpage
        print opqprn
        output screen
        remove perint
        project perint from perintel using all sorted by +
        pintdate where intlname eq .voplname
        output printer
        newpage
        print pintqprn
        output screen
        next #2 e2
    endwhile
    remove perint
endif
newpage
write "End of data for this vessel" at 21 10
set var chk-hin to N
break
else
    newpage
    write "This HIN does not exist in the database" at 10 20
    write "Do you wish to reenter the HIN? (Y)" at 12 20
    fillin correct using "(" at 12 52
    if correct exists and correct eq N then
        set var chk_hin to N
    endif
    break
endif
endwhile
endif
endif
if choice eq 5 then
    set var chk-intl to Y
    while chk-intl eq Y then
        newpage
        write "Enter name of desired vessel: " at 10 10
        fillin vvslname using " " at 10 39
        while vvslname exists then
            set pointer #2 e2 for vslintel where intvname eq .vvslname
            set var count to 1
            if e2 eq 0 then
                newpage
                write "US Coast Guard Group Monterey Intelligence History" +
                    at 1 10
                write "-----"
                -----" at 2 1
            else
                newpage
                write "There is no intelligence for this vessel name" at 10 10
                write "Press any key to continue" at 23 10
                pause
            endif
            while e2 eq 0 then
                set var vintdate to intdate in #2
                set var vepic to epiccode in #2
                set var vstolen to stolen in #2
                set var vvrem1 to vremark1 in #2
                set var vvrem2 to vremark2 in #2
                set var vvrem3 to vremark3 in #2
                if count eq 1 then
                    draw vintquer with all at 3
                endif
            endwhile
        endwhile
    endwhile
endif

```

```

endif
if count eq 2 then
    draw vintquer with all at 9
endif
if count eq 3 then
    draw vintquer with all at 15
    write "Press any key to continue" at 23 10
    pause
    newpage
endif
set var count to .count + 1
if count eq 4 then
    set var count to 1
endif
next #2 e2
endwhile
set pointer #2 e2 for vslintel where intvname eq .vvslname
if e2 eq 0 then
    write "Print vessel intelligence information? (Y)" at 23 10
    fillin vintprn using "(" at 23 49
    if vintprn fails or vintprn eq Y then
        remove vslint
        project vslint from vslintel using all sorted by intdate +
        where intvname eq .vvslname
        output printer
        newpage
        print vintqprn
        output screen
        remove vslint
    endif
endif
write "End of data for this vessel"
set var chk-intl to N
endwhile
endif
if choice eq 6 then
    set var more to N
endif
endwhile *(end of main loop)
remove temp
remove bohls
remove sarhis
remove perint
remove vslint
set null -0-
return
*( end )

```

**\$COMMAND**  
**QUER PER**

\*(\*\*\*\*\*)

Program:	Query Personnel
Author:	H R Lang and J D Allen
Date Written:	August 1987
Description:	This program searches database for all information concerning a particular person, including all vessels owned or operated and all historical information concerning these vessels.
Tables Used:	vessel, sar, boarding, owner, operator, owvsl, opvsl, opown, vslintel, perintel
Temp Tables:	temp, vslint, perint, bohls, sarhis, vslsown, vslsopr, wvsljoin, pvsljoin
Reports Used:	vslqprn, boqprn, sarqprn, perqprn, pintqprn, vintqprn
Forms Used:	vslquery, brdquery, sarquery, perquer1,

# perquer2, pintquer, vintquer

\*\*\*\*\*)

```

set messages off
set escape off
newpage
write "Program loading in progress. Please stand by ..... " +
at 10 10
clear all variables
set null " "
set var more to Y
remove temp *(relation for print purposes only)
define
attributes
tmp text 2
relations
temp with tmp
end
load temp
"xx"
end
while more eq Y then *(main loop)
    set var ownfound to N
    set var oprfound to N
    set var status to N
    newpage
    write "Press [PGDN] after entering initial information to check if" +
    at 1 5
    write "person exists in database. Press [ESC] to quit" at 2 10
    draw perquer1 at 4
    enter var return esc pgdn
    if #return ne esc then
        if vlname exists and vfname exists then
            set pointer #2 e2 for owners where ownlname contains .vlname and +
            ownfname contains .vfname
            newpage
            while e2 eq 0 then
                *(last/first name exist in owners)
                set var vplname to ownlname in #2
                set var vpfname to ownfname in #2
                set var vpermi to ownmi in #2
                set var vperdob to owndob in #2
                set var vperaddr to ownaddr in #2
                set var vpercitey to owncity in #2
                set var vperst to ownstate in #2
                set var vperzip to ownzip in #2
                set var vperitel to owntelno in #2
                newpage
                draw perquer2 with all at 3
                write "Correct owner? (N)" at 21 20
                fillin owfound using "(" at 21 35
                if owfound exists and owfound eq Y then
                    set var vowid integer
                    set var vowid to ownid in #2
                    set var ownfound to Y
                    break
                endif
            next #2 e2
            endwhile
            set var chk-op to Y
            if ownfound eq Y then
                set pointer #2 e2 for opown where ownno eq .vowid
                if e2 eq 0 then
                    set var vopid to opno in #2
                    set var oprfound to Y
                    set var chk-op to N
                else
                    set pointer #3 e3 for operator where oplname = .vlname and +

```

```

opfname = .vfname
*(check if an operator record = owner record)
newpage
while e3 eq 0 then
  *(last/first name exist in operator)
  set var voplname to oplname in #3
  set var vopfname to opfname in #3
  set var vopmi to opmi in #3
  set var vopdob to opdob in #3
  set var vopaddr to opaddr in #3
  set var vopcity to opcity in #3
  set var vopst to opstate in #3
  set var vopzip to opzip in #3
  set var voptelno to optelno in #3
  set var owoptest to T
  if vplname ne .voplname or vpfname ne .vopfname then
    set var owoptest to F
  endif
  if vpermi exists and vopmi exists and vpermi ne .vopmi then
    set var owoptest to F
  endif
  if vperdob exists and vopdob exists and vperdob ne .vopdob +
  then
    set var owoptest to F
  endif
  if vperaddr exists and vopaddr exists and vperaddr ne +
  .vopaddr then
    set var owoptest to F
  endif
  if vpercity exists and vopcity exists and vpercity ne +
  .vopcity then
    set var owoptest to F
  endif
  if vperst exists and vopst exists and vperst ne .vopst then
    set var owoptest to F
  endif
  if vperzip exists and vopzip exists and vperzip ne .vopzip +
  then
    set var owoptest to F
  endif
  if vper tel exists and voptelno exists and vper tel ne +
  .voptelno then
    set var owoptest to F
  endif
  if owoptest eq T then
    set var vopid integer
    set var vopid to opid in #3
    set var chk-op to N
    set var oprfound to Y
    break
  endif
  next #3 e3
endwhile
endif
endif
if chk-op eq Y then
  set pointer #3 e3 for operator where oplname contains .vlname +
  and opfname contains .vfname
  newpage
  while e3 eq 0 then
    *(last/first name exist in operator)
    set var vplname to oplname in #3
    set var vpfname to opfname in #3
    set var vpermi to opmi in #3
    set var vperdob to opdob in #3
    set var vperaddr to opaddr in #3
    set var vpercity to opcity in #3
    set var vperst to opstate in #3
    set var vperzip to opzip in #3
    set var vper tel to optelno in #3

```

```

newpage
draw perquer2 with all at 3
write "Correct operator? (N)" at 22 20
fillin opfound using "(" at 22 38
if opfound exists and opfound eq Y then
    set var vopid integer
    set var vopid to opid in #2
    set var oprfound to Y
    break
endif
next #3 e3
endwhile
endif
if ownfound eq Y or oprfound eq Y then
    newpage
    write "Print owner/operator information? (Y)" at 10 10
    fillin persprn using "(" at 10 44
    if persprn fails or persprn eq Y then
        newpage
        write "Preparing report, please stand by....." at 10 10
        output printer
        newpage
        print perqprn
        output terminal
    endif
endif
if ownfound eq N and oprfound eq N then
    set var vplname to .vlname
endif
set pointer #1 e1 for perintel where intlname contains .vplname
set var count to 1
if e1 eq 0 then
    newpage
    write "US Coast Guard Group Monterey Intelligence History" +
    at 1 10
    write "-----+
-----" at 2 1
else
    newpage
    write "There is no intelligence for this person" at 10 10
    write "Press any key to continue" " at 23 10
    pause
endif
while e1 eq 0 then
    set var vlname to intlname in #1
    set var vfname to intfname in #1
    set var vmi to intmi in #1
    set var vdob to intdob in #1
    set var vrem1 to pintrem1 in #1
    set var vrem2 to pintrem2 in #1
    set var vrem3 to pintrem3 in #1
    set var vdate to pintdate in #1
    if count eq 1 then
        draw pintquer with all at 3
    endif
    if count eq 2 then
        draw pintquer with all at 9
    endif
    if count eq 3 then
        draw pintquer with all at 15
        write "Press any key to continue" " at 23 10
        pause
        newpage
    endif
    set var count to .count + 1
    if count eq 4 then
        set var count to 1
    endif
    next #1 e1
endwhile

```



```

set pointer #1 e1 for perintel where intlname eq .vplname
if e1 eq 0 then
  write "Print personnel intelligence? (Y)" at 23 10
  fillin perintpr using "(" at 23 40
  if perintpr fails or perintpr eq Y then
    newpage
    write "Preparing report, please stand by....." at 10 10
    remove perint
    project perint from perintel using all sorted by pintdate +
    where intlname eq .vplname
    output printer
    newpage
    print pintqprn
    output screen
    remove perint
  endif
endif
*(determine status of person, select vessels owned and operated)
*(W = owner, P = operator, B = both and N = neither)
if ownfound eq Y and oprfound eq Y then
  set var status to B
  remove vslsown
  project vslsown from owvsl using all where idowner eq .vowid
  remove wvsljoin
  join vslsown using vhinown with vessel using vslhin forming +
  wvsljoin where eq
  newpage
  write "This individual owns the following vessels:" at 1 2
  write " "
  sel vslhin vslname from wvsljoin
  write " "
  write "End of data."
  remove vslsopr
  project vslsopr from opvsl using all where idoper eq .vopid
  remove pvsljoin
  join vslsown using vhinown with vessel using vslhin forming +
  pvsljoin where eq
  write " "
  write " "
  write "This individual has operated the following vessels:"
  write " "
  sel vslhin vslname from pvsljoin
  write " "
  write "End of data. Press any key to continue"
  pause
endif
if ownfound eq Y and oprfound eq N then
  set var status to W
  remove vslsown
  project vslsown from owvsl using all where idowner eq .vowid
  remove wvsljoin
  join vslsown using vhinown with vessel using vslhin forming +
  wvsljoin where eq
  newpage
  write "This individual owns the following vessels:" at 1 10
  write " "
  sel vslhin vslname from wvsljoin
  write " "
  write "End of data. Press any key to continue"
  pause
endif
if ownfound eq N and oprfound eq Y then
  set var status to P
  remove vslsopr
  project vslsopr from opvsl using all where idoper eq .vopid
  remove pvsljoin
  join vslsown using vhinown with vessel using vslhin forming +
  pvsljoin where eq
  newpage
  write "This individual has operated the following vessels:" +

```

```

at 1 10
write " "
sel vslhin vslname from pvsljoin
write " "
write "End of data. Press any key to continue"
pause
endif
if status ne N then
  newpage
  write "Do you wish to search for full information concerning +
these vessels? (N)" at 10 5
  fillin searchok using "(" at 10 74
  if searchok exists and searchok eq Y then
    set var done to N
    set var owndone to N
    while done eq N then
      if status eq B and owndone eq N then
        remove vslsown
        project vslsown from owvsl using all where idowner eq .vowid
        set pointer #3 e3 for vslsown
      endif
      if status eq W then
        remove vslsown
        project vslsown from owvsl using all where idowner eq .vowid
        set pointer #3 e3 for vslsown
      endif
      if status eq P then
        remove vslsopr
        project vslsopr from opvsl using all where idoper eq .vopid
        set pointer #3 e3 for vslsopr
      endif
      if status eq B and owndone eq Y then
        remove vslsopr
        project vslsopr from opvsl using all where idoper eq .vopid
        set pointer #3 e3 for vslsopr where vhinoper nea vhinown +
        in vslsown
      endif
      while e3 eq 0 then
        if status eq B and owndone eq N or status eq W then
          set var vslhin to vhinown in #3
        endif
        if status eq B and owndone eq Y or status eq P then
          set var vslhin to vhinoper in #3
        endif
        set pointer #1 e1 for vessel where vslhin eq .vslhin
        set var vslno to vslno in #1
        set var vslname to vslname in #1
        set var vslmake to vslmake in #1
        set var vslmod to vslmodel in #1
        set var vslyear to vslyear in #1
        set var vslton to vsltons in #1
        set var vslft to vslenft in #1
        set var vslin to vsllein in #1
        set var vslhp to vslhp in #1
        set var vsluse to vsluse in #1
        set var vusedscr to vusedesc in boatuse where vuse eq +
        .vsluse
        set var vsltype to vsltype in #1
        set var vtypdscr to vtypedesc in boattype where vtype eq +
        .vsltype
        set var vslprop to vslprop in #1
        set var vpropdsc to propdesc in boatprop where proptype eq +
        .vslprop
        set var vslhull to vslhull in #1
        set var vhulldsc to hmatdesc in hullmat where hmattype eq +
        .vslhull
        set var vsleng to vsleng in #1
        set var vengdesc to ecompdes in engcomp where ecomptyp eq +
        .vsleng
        set var vslfuel to vslfuel in #1

```

```

set var vfueldes to fcompdes in fuelcomp where fcomptyp eq +
.vvslfuel
set var vconstr to vslconst in #1
set var vcondesc to consdesc in constr where constype eq +
.vconstr
set var vdecal to cmedecal in #1
set var vcmeyear to cmeyear in #1
set var voffno to vsloffno in #1
set var vhome to homeport in #1
set var vcall to vsicall in #1
set var vvalue to vslvalue in #1
set var vsuper to vslsuper in #1
set var vmasts to vslmasts in #1
set var vsailno to sailno in #1
set var vhlcolor to hlcolor in #1
set var vtrcolor to trcolor in #1
set var vsicolor to slcolor in #1
set var vcbcolor to cbcolor in #1
set var vdkcolor to dkcolor in #1
set var vmarks to vslmarks in #1
newpage
if status eq B and owndone eq N or status eq W then
    write "This vessel is owned by the designated +
individual. Press any key to continue" at 1 1
endif
if status eq B and owndone eq Y or status eq P then
    write "Subject person has operated this vessel. Press +
any key to continue" at 1 1
endif
draw vslquery with all at 3
pause
set pointer #2 e2 for vslintel where intvname eq .vvslname
set var count to 1
if e2 eq 0 then
    newpage
    write "US Coast Guard Group Monterey Intelligence +
History" at 1 10
    write "-----"
    "-----" at 2 1
else
    newpage
    write "There is no intelligence for this vessel name" +
    at 10 10
    write "Press any key to continue" at 23 10
    pause
endif
newpage
while e2 eq 0 then
    set var vintdate to intdate in #2
    set var vepic to epiccode in #2
    set var vstolen to stolen in #2
    set var vvrem1 to vremark1 in #2
    set var vvrem2 to vremark2 in #2
    set var vvrem3 to vremark3 in #2
    if count eq 1 then
        draw vintquer with all at 3
    endif
    if count eq 2 then
        draw vintquer with all at 9
    endif
    if count eq 3 then
        draw vintquer with all at 15
        write "Press any key to continue" at 23 10
        pause
        newpage
    endif
    set var count to .count + 1
    if count eq 4 then
        set var count to 1
    endif
endif

```

```

next #2 e2
endwhile
if status eq W or status eq B then
  set pointer #3 e3 for vsisown
endif
if status eq P then
  set pointer #3 e3 for vsisopr
endif
if status eq B and owndone eq Y then
  set pointer #3 e3 for vsisopr where vhinoper nea +
  vhinown in vsisown
endif
if e3 eq 0 then
  write "Print vessel information and intelligence? (Y)" +
  at 23 10
  fillin vslprn using "(" at 23 53
  if vslprn fails or vslprn eq Y then
    newpage
    write "Preparing report, please stand by....." +
    at 10 10
    while e3 eq 0 then
      set var vvslnhin to vhinown in #3
      set pointer #1 e1 for vessel where vslnhin eq .vvslnhin
      set var vvslnno to vslnno in #1
      set var vvslnname to vslnname in #1
      set var vvslnmake to vslnmake in #1
      set var vvslnmod to vslnmodel in #1
      set var vvslnyear to vslnyear in #1
      set var vvslnon to vslnons in #1
      set var vvslnft to vsllenft in #1
      set var vvslnin to vsllenin in #1
      set var vvslnhp to vslnhp in #1
      set var vvslnuse to vslnuse in #1
      set var vusedscr to vusedesc in boatuse where vuse +
      eq .vvslnuse
      set var vvslnype to vslnype in #1
      set var vtypdscr to vtypedesc in boattype where +
      vtype eq .vvslnype
      set var vvslnprop to vslnprop in #1
      set var vpropdsc to propdesc in boatprop where +
      proptype eq .vvslnprop
      set var vvslnhull to vslnhull in #1
      set var vhulldsc to hmatdesc in hullmat where +
      hmattype eq .vvslnhull
      set var vvslnleng to vslnleng in #1
      set var vengdsc to ecompdes in engcomp where +
      ecomptyp eq .vvslnleng
      set var vvslnfuel to vslnfuel in #1
      set var vfueldes to fcompdes in fuelcomp where +
      fcomptyp eq .vvslnfuel
      set var vconstr to vslnconst in #1
      set var vcondesc to consdesc in constr where +
      constype eq .vconstr
      set var vdecad to cmedecad in #1
      set var vcmeyear to cmeyear in #1
      set var voffno to vsloffno in #1
      set var vhome to homeport in #1
      set var vcall to vslncall in #1
      set var vvalue to vslnvalue in #1
      set var vsuper to vslnsuper in #1
      set var vmasts to vslnmasts in #1
      set var vsailno to sailno in #1
      set var vhlcolor to hlcolor in #1
      set var vtrcolor to trcolor in #1
      set var vslncolor to slcolor in #1
      set var vcbcolor to cbcolor in #1
      set var vdkcolor to dkcolor in #1
      set var vmarks to vslnmarks in #1
    endwhile
    newpage
    write "Preparing report, please stand by....." +

```



```

next #2 e2
endwhile
set pointer #2 e2 for boarding where bovhin eq .vvs1hin
if e2 eq 0 then
write "Print boarding history? (Y)" at 23 10
fillin bohisprn using "(" at 23 34
if bohisprn fails or bohisprn eq Y then
newpage
write "Preparing report, please stand by....." +
at 10 10
remove bohis
project bohis from boarding using bodate botime bono +
vslpob obslat obslong viol54 viol55 viol56 viol57 +
viol58 viol59 viol60 viol61 viol62 viol63 viol64 +
viol65 viol66 viol67 viol68 uns69 uns70 uns71 uns72 +
uns73 uns74 uns75 uns76 uns77 uns78 uns79 boreml +
borem2 boreml3 boname borate weapons bovhin sorted by +
bodate where bovhin eq .vvs1hin
output printer
newpage
print boqprn
output screen
remove bohis
endif
endif
if e2 ne 0 then
newpage
write "There are no boarding cases for this vessel" +
at 10 10
write "Press any key to continue" at 20 10
pause
endif
set pointer #2 e2 for sar where sarvhin eq .vvs1hin
set var count to 1
if e2 eq 0 then
newpage
write "US Coast Guard Group Monterey Sar History" +
at 1 10
write "-----"
-----" at 2 1
endif
while e2 eq 0 then
set var vfoldno to folderno in #2
set var vucn to ucn in #2
set var vmucn to mucn in #2
set var vsardate to sardate in #2
set var vsarday to sarday in #2
set var vsartime to sartime in #2
set var vsarnod to sarnod in #2
set var vsarpob to sarpob in #2
set var vsarlat to sarlat in #2
set var vsarlong to sarlong in #2
set var vdistoff to offshore in #2
set var vimmed to immedsar in #2
if count eq 1 then
draw sarquery with all at 3
endif
if count eq 2 then
draw sarquery with all at 9
endif
if count eq 3 then
draw sarquery with all at 15
write "Press any key to continue" at 23 10
pause
newpage
endif
set var count to .count + 1
if count eq 4 then
set var count to 1
endif

```

```

        next #2 e2
    endwhile
    set pointer #2 e2 for sar where sarvhin eq .vvslnhin
    if e2 eq 0 then
        write "Print sar history? (Y)" at 23 10
        fillin sarhsprn using "(" at 23 29
        if sarhsprn fails or sarhsprn eq Y then
            newpage
            write "Preparing report, please stand by....." +
            at 10 10
            remove sarhis
            project sarhis from sar using folderno ucn mucn +
            sardate sartime sarnod sarpob sarlat sarlong offshore +
            immedsar sarvhin sorted by sardate where sarvhin eq +
            .vvslnhin
            output printer
            newpage
            print sarqprn
            output screen
            remove sarhis
        endif
    endif
    if e2 ne 0 then
        newpage
        write "There are no sar cases for this vessel" at 10 10
        write "Press any key to continue" at 20 10
        pause
    endif
    next #3 e3
endwhile
if status eq W or status eq P then
    set var done to Y
endif
if status eq B and owndone eq N then
    set var owndone to Y
endif
if status eq B and owndone eq Y then
    set var done to Y
endif
endwhile
remove vslsown
remove vslsopr
remove wvsljoin
remove pvsljoin
endif
else
    newpage
    write "This name does not exist as an owner or an operator" +
    at 10 10
    write "Press any key to continue" at 15 15
    pause
endif
endif
label moreblk
newpage
write "More names to check? (N)" at 10 10
fillin mrname using "(" at 10 31
if mrname fails or mrname eq N then
    set var more to N
else
    clear all variables
    set var more to Y
endif
endwhile *(end of main loop)
remove temp
remove vslsown
remove vslsopr
remove perint
remove vslint

```

```
remove bohis  
remove sarhis  
set null -0-  
return  
*( end )
```



## APPENDIX P

### UTILITY SOURCE CODE

```

$COMMAND
UTLMAIN
*(*****
      US COAST GUARD GROUP MONTEREY
    SEARCH & RESCUE and ENFORCEMENT of LAWS and TREATIES
      INTELLIGENCE SYSTEM (SARELTIS)

    UTILITIES MENU and APPLICATION PROGRAMS

      Author:   Jon D. Allen, LT, USCG
                Heidi R. Lang, LT, USN
                AUGUST 1987

*****)

set error messages off
set messages off
set escape off
clear all variables
newpage
set var pick11 integer
choose pick11 from utl_menu in sutility.apx
if pick11 eq 0 then
  quit to restutly.cmd
endif
if pick11 eq 1 then
  run INITIAL in sutility.apx
  quit to restutly.cmd
endif
if pick11 eq 2 then
  run PACKDBMS in sutility.apx
  quit to restutly.cmd
endif
if pick11 eq 3 then
  run BACKDBMS in sutility.apx
  quit to restutly.cmd
endif
if pick11 eq 4 then
  run RESTDBMS in sutility.apx
  quit to restutly.cmd
endif
if pick11 eq 5 then
  quit to restmain.cmd
endif
quit to restutly.cmd
return
$menu
utl_menu
column SARELTIS --- UTILITIES MENU
INITIALIZE DATABASE
PACK DATABASE
BACKUP DATABASE
RESTORE DATABASE
RETURN TO MAIN MENU
*( end )

```

\$COMMAND

INITIAL

\*(\*\*\*\*\*)

Program:	Initialize SARSYS
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program removes all temporary tables that can be created by the system.
Tables Used:	none
Temp Tables:	all
Reports Used:	none
Forms Used:	none

\*\*\*\*\*)

```
set error messages off
set messages off
set escape off
newpage
remove epicsum
remove stolesum
remove intelsum
remove epictmpl
remove epictmp2
remove epictmp
remove sarsum
remove temp
remove bosum
remove vsisum
remove violsum
remove vsimo
remove summary1
remove summary2
remove summary3
remove summary4
remove summary5
remove summary6
remove summary7
remove frqchart
remove positfrq
remove sarsum
remove bovsisum
remove ownsum1
remove ownsum2
remove opsum1
remove opsum2
remove vsisum
remove vsisum1
remove vsisum2
remove sartime1
remove sartime2
remove sartime3
remove sartime4
remove sartime5
remove sarsum1
remove sarstat
remove intelsum
remove opvsis1
remove opvsis2
remove opervsis
remove ownvsis1
remove ownvsis2
remove ownvsis
newpage
return
*( end )
```

\$COMMAND  
PACKDBMS

\*(\*\*\*\*\*)

```

Program:      Pack Database
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program packs/compresses the database.
Tables Used:  none
Temp Tables:  none
Reports Used: none
Forms Used:   none

```

\*\*\*\*\*)

```

set error messages off
set messages off
set escape off
clear all variables
newpage
write "Before packing the database, please ensure that you have +
made" at 4 1
write "a back up of the database. Ideally, you should back up +
the " at 5 1
write "database just prior to performing the packing operation." at 6 1
set var choice text
write "Do you wish to continue with the packing program? (N)" at 8 1
set error messages on
fillin choice using "/" at 8 51
set error messages off
if choice fails or choice eq n then
    return
else
    write "Packing/Compressing the database will take several +
minutes." at 10 1
    write "Please be patient....." at 12 1
    write "Please press any key to continue" at 16 1
    pause
    newpage
    write "Now packing the database....." at 10 1
    set error var erv
    pack sarsys
    if erv = 0 then
        write "Packing has successfully completed." at 12 1
    else
        write "An error has occurred during the packing." at 12 1
        write "Please refer to the reference manual page 5-25." at 13 1
    endif
    write "Please press any key to continue" at 18 1
endif
clear all variables
return
*( end )

```

\$COMMAND  
BACKDBMS

\*(\*\*\*\*\*)

```

Program:      Backup Database
Author:       J D Allen and H R Lang
Date Written: August 1987
Description:  This program provides instructions for
              backing up the database.
Tables Used:  none
Temp Tables:  none
Reports Used: none

```

Forms Used: none

\*\*\*\*\*)

```
set error messages off
set messages off
set escape off
newpage
write "Backing up of the database should be done at a minimum of once +
per" at 3 1
write "week. To back the database up only requires that you exit +
the " at 4 1
write "database and executing a DOS (Disk Operating System) batch +
program" at 5 1
write "that has been specifically customized to do the backup for +
you." at 6 1
write "To exit the system, you must choose the [EXIT SARSYS] option +
from" at 10 1
write "the master menu. This will exit from RBase 5000 and return +
you to" at 11 1
write "the DOS prompt. At the DOS prompt, enter the following:" +
at 12 1
write "BACKDBMS" +
at 14 1
write "Please follow the instructions/prompts that the computer +
displays" at 16 1
write "with regard to the insertion of formatted disks. Upon +
completion" at 17 1
write "of the program, you will automatically be returned to RBase +
5000." at 18 1
write "Please press any key when you are ready to proceed....." +
at 23 1
pause
newpage
return
*( end )
```

\$COMMAND  
RESTDBMS

\*(\*\*\*\*\*)

Program:	Restore Database
Author:	J D Allen and H R Lang
Date Written:	August 1987
Description:	This program provides instructions for restoring the database from a backup.
Tables Used:	none
Temp Tables:	none
Reports Used:	none
Forms Used:	none

\*\*\*\*\*)

```
set error messages off
set messages off
set escape off
newpage
write "To restore the database only requires that you exit the " +
at 4 1
write "database and execute a DOS (Disk Operating System) batch +
program" at 5 1
write "that has been specifically customized to do the restore for +
you." at 6 1
write "To exit the system, you must choose the [EXIT SARSYS] option +
from" at 10 1
write "the master menu. This will exit from RBase 5000 and return +
```

```

you to" at 11 1
write "the DOS prompt. At the DOS prompt, enter the following:" +
at 12 1
write "                                RESTDBMS                                " +
at 14 1
write "Please follow the instructions/prompts that the computer +
displays" at 16 1
write "with regard to the insertion of backup disks. Upon completion" +
at 17 1
write "of the program, you will automatically be returned to RBase +
5000." at 18 1
write "Please press any key when you are ready to proceed....." +
at 23 1
pause
newpage
return
*( end )

```

## LIST OF REFERENCES

1. Commandant, U. S. Coast Guard Instruction 7100.1A, 11 February 1982.
2. Davis, William S., *Systems Analysis and Design*, Addison-Wesley Publishing Company, 1983.
3. Kroenke, David M., *DATABASE PROCESSING: Fundamentals, Design, Implementation*, Science Research Associates, Inc., 1983.
4. Graham, James M., *The Completed Management Information System for the Monterey Navy Flying Club*, Masters Thesis, Naval Postgraduate School, Monterey, California, March 1987.
5. *R:base 5000 User's Manual*, MicroRim, Inc., 1985.

## BIBLIOGRAPHY

- Ackoff, Russel L., "Management Misinformation Systems", *Management Science*, v. 14, no. 4, December 1967, pp. (B)147-(B)156.
- Bloomfield, Howard V. L., *The Compact History of the United States Coast Guard*, Hawthorne Books, Inc., 1966.
- Bohl, Marilyn, *Information Processing*, Science Research Associates, Inc., 1984.
- Briggs, Charles L., Birkes, Evan G. and Atkins, William, *Managing the Systems Development Process*, Touche Ross and Company, 1980.
- Coast Guard Fact File (1986-1987)*, Community Relations Branch (G-BPA-3), U. S. Coast Guard, July 1986.
- Coast Guard Group Monterey Instruction 5400, 15 November 1984.
- Commandant, U. S. Coast Guard Instruction 7100.1A, 11 February 1982.
- Commandant, U. S. Coast Guard Instruction 16203.1, 29 May 1980.
- Commandant, U. S. Coast Guard Instruction M16750.4, 13 September 1979.
- Davis, William S., *Systems Analysis and Design*, Addison-Wesley Publishing Company, Inc., 1983.
- Department of Transportation, U. S. Coast Guard, *Enforcement of Laws and Treaties FY 82-91*, Operating Program Plan (1979).
- Department of Transportation, U. S. Coast Guard, *Missions of the United States Coast Guard (CG-378-8)*, 1985.
- Dickson, Gary W. and Wetherbe, James C., *The Management of Information Systems*, McGraw-Hill Book Company, 1985.
- Dinerstein, Nelson T., *R:base 5000 for the Programmer*, Scott, Foresman and Company, 1986.
- Evans, Stephan H., *The United States Coast Guard 1790-1915*, The United States Naval Institute, 1949.
- Graham, James M., *The Completed Management Information System for the Monterey Navy Flying Club*, Masters Thesis, Naval Postgraduate School, Monterey, California, March 1987.
- Kent, William, "A Simple Guide to Five Normal Forms in Relational Database Theory", *Communications of the ACM*, vol 26, no. 2, February 1983, pp. 120-125.
- King, David, *Current Practices in Software Development*, Yourdon Press, 1984.
- Kroenke, David, *Database Processing: Fundamentals, Design, Implementation* Science Research Associates, Inc., 1977.

Lutton, Bill and Matson, Jo Anna, *Enforcement Management Information System User's Manual*, National Marine Fishery Service, Washington, D.C.

Mitchell, Thaddeus R. and Bell, Robert S. *Drug Interdiction Operations by the Coast Guard: Database and Analysis*, Center for Naval Analysis, Report CRC 413, December 1979.

Page-Jones, Meilir, *The Practical Guide to Structured Systems Design*, Yourdon Press, 1980.

Prague, Cary N. and Hammitt, James E., *Programming with R:base 5000*, Tab Books, Inc., 1986.

*ReQuest System User Manual*, System Automation Corporation, April 1984.

*R:base 4000 User's Manual and Tutorial*, MicroRim, Inc., 1984.

*R:base 5000 User's Manual*, MicroRim, Inc., 1985.

Simpson, Alan, *Understanding R:base 5000*, SYBEX, 1985.

Yourdon, Edward, *Managing the Structured Techniques*, Yourdon Press, 1976.



## INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Technical Information Center Cameron Station Alexandria, VA 22304-6145	2
2.	Library, Code 0142 Naval Postgraduate School Monterey, CA 93943-5002	2
3.	Curricular Office, Code 37 Department of Computer Technology Naval Postgraduate School Monterey, CA 93943-5000	1
4.	Barry A. Frew, Code 54Fw Department of Administrative Sciences Naval Postgraduate School Monterey, CA 93943-5000	2
5.	Vincent Y. Lum Department of Computer Science Naval Postgraduate School Monterey, CA 93943-5000	1
6.	Chief of Naval Operations Director, Information Systems (OP-945) Navy Department Washington, D. C. 20350-2000	2
7.	RADM W. Merlin Commandant (G-T) U.S. Coast Guard 2100 Second Street SW Washington, D. C. 20590-0000	2
8.	Commandant (G-TPP/HRM) U.S. Coast Guard 2100 Second Street SW Washington, D. C. 20593-0000	2
9.	Commandant (G-PTE-1) U.S. Coast Guard 2100 Second Street SW Washington, D. C. 20590-0000	2

- |     |   |   |
|-----|---|---|
| 10. | Commander<br>Coast Guard Group Monterey<br>100 Lighthouse Avenue<br>Monterey, CA 93940-1497                 | 2 |
| 11. | LT Jon D. Allen<br>U.S. Coast Guard Station Alexandria<br>Telegraph Road<br>Alexandria, Virginia 22310-0000 | 6 |
| 12. | LT Heidi R. Lang<br>100 Conant Drive<br>Buffalo, New York 14223-0000  | 6 |
| 13. | Mr. and Mrs. Gordon G. Allen<br>1555 Dorset Street<br>South Burlington, VT 05402-0000                       | 1 |
| 14. | Mr. and Mrs. Edward P. Lang<br>100 Conant Drive<br>Buffalo, New York 14223-0000                             | 1 |